

2016.0 RANGE ROVER (LG), 414-01

BATTERY, MOUNTING AND CABLES

DESCRIPTION AND OPERATION

WARNINGS:

- This procedure must be carried out in the exact sequence shown. Failure to do so could result in serious personal injury.
- This procedure must only be carried out by authorised personnel.
- Make sure that you also comply with any local legislation regarding working with high voltages, whilst carrying out this procedure.
- Approved personal protection equipment, to include; safety glasses or visor, black rubber gloves meeting the required standards and non-flammable, non-melting clothing, must be worn when instructed to do so.

SAFE TRANSPORTATION ANALYSIS SHEET FOR HIGH VOLTAGE BATTERIES

This form must be filled out in order to assess whether a Land Rover high voltage battery is safe for transportation. The results of the test are to be documented in this assessment form. A copy of the assessment form is to remain with the high voltage battery. For transportation purposes all high voltage batteries must include not only this form, but also the documents specified for hazardous materials. The requirements pertaining to the specified documents are different for each country and the transportation method involved.

Land Rover part number

High voltage battery serial number

STEP 1

Critical safety inspection (Detection of immediate safety concerns):

		Yes	No
1	Are there any active emission of smoke or flames from the high voltage battery?		
2	Are there any active emissions of electric sparks or arcs from the high voltage battery?		

If at least one question is answered **Yes**, contact the relevant emergency services immediately.

STEP 2

Inspection for damage:

		Yes	No
1	Are there any indications that an explosion or a fire has taken place?		
2	Are there any indications of loose components within the high voltage battery?		
3	Are there any signs that electrolyte has leaked out?		
4	Are there any cracks or holes in the high voltage battery housing?		

5	Are there any dents or scratches, that extend beyond what is permitted (depth > 2.0 mm)?		
6	Are any high voltage connections damaged (normally insulated conductors now exposed)?		
7	With the exception of the coolant connections, does any coolant leak out of the high voltage battery housing)?		
If at least one question is answered Yes , the high voltage battery shall be deemed unsafe for transportation and the vehicle must be quarantined accordingly. Contact Technical Support for further assistance.			

STEP 3			
Connect the Land Rover approved diagnostic equipment and carry out a diagnostic check on the high voltage system:			
If communication with the high voltage battery system is NOT possible , the high voltage battery shall be deemed unsafe for transportation and the vehicle must be quarantined accordingly. Contact Technical Support for further assistance.			
		Yes	No
1	Are any concerns present indicating an internal fault is present within the high voltage battery?		
If the question is answered Yes , the high voltage battery shall be deemed unsafe for transportation and the vehicle must be quarantined accordingly. Contact Technical Support for further assistance.			

STEP 4	
Removal of the high voltage battery:	
If at least one question was answered Yes in the previous 3 steps and after consultation with Technical Support; the vehicle must remain quarantined for a minimum of 5 days , before the high voltage battery can be removed from the vehicle.	

STEP 5

WARNING:

This section is only to be completed if all the questions in sections 1 to 3 have been answered **No**.

OK to ship:

Retailer name:

Repair order number:

Vehicle Identification Number:

Vehicle Registration mark:

Authorised Personnel name:

Telephone number:

Date:

Signature: