

2016.0 RANGE ROVER (LG), 307-01

AUTOMATIC TRANSMISSION/TRANSAXLE - VEHICLES WITH: 8HP70 8- SPEED AUTOMATIC TRANSMISSION AWD

SPECIFICATIONS

Maintenance

CAUTION:

Use only Shell L12108 (ZF Lifeguard 8) Automatic transmission fluid.
Use of any other fluids may result in a transmission malfunction or failure.

DESCRIPTION	INTERVALS
Normal maintenance	Filled for life.
Severe duty maintenance	Change the fluid at 48,000 km (30,000 miles) intervals.

Capacities

	LITERS
Transmission	8.5

Lubricants, Fluids, Sealers and Adhesives

DESCRIPTION	SPECIFICATION
Transmission fluid	Shell L12108 (ZF Lifeguard 8)
Sealant	WSS-M4G323-A6
Metal surface cleaner	WSW-M5B392-A
High temperature grease	Molecote FB180

Torque Specifications

NOTE:

*refer to the procedure for correct torque sequence.

DESCRIPTION	NM	LB- FT	LB- IN
Transmission retaining bolts	40	30	-
Transmission mount retaining bolts	63	46	-
*Transmission fluid fill plug	35	26	-
*Transmission control module (TCM) and main control valve body retaining bolts	8	-	71
Torque converter retaining bolts	63	46	-
Transmission fluid cooler tube retaining bolt	22	16	-
Transmission fluid drain plug	8	-	71
*Transmission fluid pan, gasket and filter retaining bolts	10	7	-