

PUBLISHED: 05-JAN-2016

2015.0 RANGE ROVER (LG), 303-03

ENGINE COOLING - TDV8 4.4L DIESEL

SPECIFICATIONS

Fluid



NOTE:

Coolant must be collected into a clean container and can be reused if not contaminated.

DESCRIPTION	SPECIFICATION
Land Rover premium cooling system fluid	Havoline XLC

Capacity

ITEM	LITRES
Vehicles fitted with 2 zone air conditioning (A/C)	7.13
Vehicles fitted with 2 zone A/C and fuel fired booster heater (FFBH)	7.3
Vehicles fitted with 4 zone A/C	8.77
Vehicles fitted with 4 zone A/C and FFBH	8.94

General Specifications

Item	Specification
Cooling system type	Pressurised, thermostatically controlled with remote header tank
Expansion tank	Remote - fitted with a bleed screw and low coolant level sensor
Pressure cap rating	110 kPa (1.1 bar) (16 lbf/in ²)
Thermostat:	
Starts to open	88° C (190° F)
Fully open	96° C (204° F)
Cooling fan	Variable speed electric fans
Direction of rotation	Clockwise when viewed from front of engine
Coolant pump	Centrifugal flow impellor, belt driven from crankshaft

Torque Specifications

ITEM	NM	LB-FT	LB-IN
Coolant pump pulley bolt	23	17	-
Coolant pump bolts	23	17	-
Air intake pipe connector	8	-	71
Charge air cooler hose clamp	3.5	-	40
Coolant expansion tank bolt	2.8	-	25
Charge air cooler hose retaining clamp to fan shroud bolt	7	-	62
Fan shroud studs	7	-	62
A/C pipe to fan shroud	7	-	62
A/C pipe to condenser nut	8	-	71
Transmission oil cooler to fan shroud	7	-	62
Cooling fan shroud to radiator bolt	7	-	62
Dynamic response pressure pipe to engine	10	7	-
Coolant radiator lower retaining bolt	15	11	-
Dynamic response cooler to condenser bolt	7	-	62
Dynamic response cooler to condenser nut	7	-	62
Condenser retainer to radiator bolt	4.5	-	40