

PUBLISHED: 05-JAN-2016

2014.0 RANGE ROVER (LG), 303-03

ENGINE COOLING - V8 N/A 5.0L PETROL/V8 S/C 5.0L PETROL

SPECIFICATIONS

Lubricants

NOTE:

Coolant must be collected into a clean container and can be reused if not contaminated.

DESCRIPTION	SPECIFICATION
Coolant	Havoline Extended Life Coolant (XLC)
Coolant concentration	50%

Capacities

ITEM	VEHICLES WITHOUT SUPERCHARGER	VEHICLES WITH SUPERCHARGER
	LITRES	LITRES
Vehicles fitted with 2 zone Air Conditioning (A/C)	6.83	8.83
Vehicles fitted with 2 zone Air Conditioning (A/C) and Fuel fired booster heater (FFBH)	7	9
Vehicles fitted with 4 zone Air Conditioning (A/C)	8.47	10.47
Vehicles fitted with 4 zone Air Conditioning (A/C) and Fuel fired booster heater (FFBH)	8.64	10.64

Torque Specifications

DESCRIPTION	NM	LB-FT	LB-IN
Coolant expansion tank retaining bolt	9	-	80
Cooling fan assembly retaining nut	65	48	-
Thermostat housing retaining bolts	10	7	-
Coolant pump retaining bolts	12	9	-
Accessory drive belt tensioner bolt	48	35	-
Radiator drain plug	5	-	44
Auxiliary radiator nut and bolt	9	-	80

Auxiliary radiator bolt	5	-	44
Auxiliary radiator nuts	9	-	80
Cooling fan shroud upper half screw	4	-	35
Transmission oil cooler to cooling fan shroud bolt	7	-	62
Cooling fan shroud to radiator bolt	7	-	62
Radiator lower bushing bolt	15	11	-
Condenser core retainer to coolant radiator bolt	4.5	-	40
Refrigerant line to condenser core nut	8	-	71
Coolant bleed screw	3	-	27