

PUBLISHED: 23-AUG-2012

2014.0 RANGE ROVER (LG), 303-04

FUEL CHARGING AND CONTROLS - V8 S/C 5.0L PETROL

SPECIFICATIONS

Torque Specifications

NOTE:

Tighten the fuel rail high pressure fuel pump fuel line unions and fuel rail crossover pipe unions as it is instructed in service manual.

DESCRIPTION	NM	LB-FT	LB-IN
Ignition coil-on-plugs retaining bolts	8	-	71
Fuel rail retaining bolt	Stage 1 - 20 Stage 2 - 30	Stage 1 - 15 Stage 2 - 22	-
Fuel rail crossover pipe unions	21	15	-
Fuel rail crossover pipe retaining bolts	8	-	71
Fuel rail pressure sensor	33	24	-
Fuel rail pressure and temperature sensor	37	27	-
Fuel rail high pressure fuel pump fuel line unions	21	15	-
Fuel rail high pressure fuel pump fuel line M8 bolt	25	18	-
Fuel rail high pressure fuel pump fuel line M6 bolt	12	9	-
Fuel rail high pressure fuel pump fuel line M5 nut	6	-	53
Fuel rail high pressure fuel pump fuel line shield M10 bolt	29	21	-
Fuel rail high pressure fuel pump fuel line shield M6 bolt	12	9	-
Fuel rail high pressure fuel pump torx bolts	12	9	-
Throttle body retaining bolts	17	13	-
Accessory drive belt idler pulley bracket bolts	25	18	-
Fuel pump driver modul (FPDM) bracket to body bolt	10	7	-
FPDM to bracket bolts	3	-	27

