

Database documentation for PlumJob application

Jagiellonian University in Krakow

Kinga Żmuda

Dominik Szymczyk

Martyna Cios

Piotr Szulej

Wojciech Popiel

Krakow 16.06.2025

1. Introduction

This file contains a description of the tables, procedures, functions, and indexes used in the database for the PlumJob application. **IMPORTANT:** Do not modify the “users” and “authorities” tables. The technologies we use enforce a specific structure for these tables, and any changes may cause numerous errors. It is also not recommended to remove the INSERT statements to the “RecruitmentStatus” table, as they are necessary for some procedures and parts of the source code.

2. Tables

2.1 **users**

This table stores the user identifier, password, and whether the account is active.

2.2 **authorities**

This table stores user permissions.

2.3 **UserInfo**

This table stores basic user information such as first name, last name, email, and creation date. This table also stores information necessary for working of user avatar. They are located in columns `profile_picture` and `profile_picture_type`.

2.4 **Ads**

This table contains information related to advertisements, such as who created the ad, its start and end display dates, a link to the offer, an image link, and whether the ad is active.

2.5 **RecruitmentStatus**

This table stores the ID and name of the status.

2.6 **RecruitmentHistory**

This table stores recruitments added by the user. It includes information about the user ID, the position applied for, the company name, start date, recruitment status, description, and whether the recruitment is archived.

2.7 **TagCodes**

This table stores tag IDs and their names. It should remain

separate from “TagUsers” and “TagOffer” to maintain database scalability.

2.8 **TagUsers**

This table contains tags selected by the user.

2.9 **TagOffer**

This table contains tags for individual recruitments, assigned by the user.

2.10 **Template**

This table contains information about templates used in the CV builder. It includes the template name, description, date added, and last modified date.

2.11 **Article**

This table contains information about articles from the Tips section. It includes the article title, creation date, and last modified date.

2.12 **ErrorLogs**

This table contains error codes and their corresponding dates.

2.13 **RecruitmentStatusHistory**

This table contains the history of status changes for individual recruitments. It stores the recruitment ID, old status, new status, and the date of change.

3. Stored Procedures

3.1 **sp_showUserHistory**

This procedure takes the user ID and a flag indicating whether to

return active or inactive users. Based on the selected option, it returns the appropriate users.

3.2 **sp_updateStatus**

This procedure takes the recruitment ID and the new status. It checks whether the completion status of the recruitment changes and adjusts it if needed. Then it adds the appropriate row to the “RecruitmentStatusHistory” table.

3.3 **sp_getUserStatusChanges**

This procedure takes the user ID, start date, and end date of a time range. It then returns the history of recruitment status changes for that user in the given period by joining data from the “RecruitmentStatusHistory” and “RecruitmentHistory” tables.

3.4 **RecruitmentHistory**

This procedure takes the recruitment ID. It is used to simultaneously remove the relevant rows from both the “RecruitmentStatusHistory” and “RecruitmentHistory” tables.

3.5 **sp_addNewRecruitment**

This procedure takes the user ID, recruitment position, company name, recruitment start date, recruitment status, description, and completion status. It then adds these values to the “RecruitmentHistory” table and calls the “sp_updateStatus” procedure.

3.6 **sp_getUserStatusChangesFullPath**

This procedure takes the user ID, selects all changes in recruitment status and counts them. It then returns the amounts from each type to each type (example: from applied to interviewed)

4. Other

4.1 get_accepted

A function that returns the number of recruitments completed with an accepted offer.

4.2 Indexes

The following indexes are created in the database:

ix_auth_username ON authorities (username, authority);

ix_history_users ON RecruitmentHistory (user_id, user_start_date);
ix_tag_users ON TagUsers (user_id, tag_id);
ix_tag_offer ON TagOffer (offer_id, tag_id).

4.3 ER diagram

