

Exercise 4.27.

Suppose we type in the following definitions to the lazy evaluator:

```
(define count 0)

(define (id x)
  (set! count (+ count 1))
  x)
```

Give the missing values in the following sequence of interactions, and explain your answers.¹

```
(define w (id (id 10)))

;;; L-Eval input:
count
;;; L-Eval value:
<response>

;;; L-Eval input:
w
;;; L-Eval value:
<response>

;;; L-Eval input:
count
;;; L-Eval value:
<response>
```

Answer.

Starting the the evaluator we can see the response it prompted:

```
(define w (id (id 10)))

;;; L-Eval input:
count
;;; L-Eval value:
1
```


We know that the lazy evaluator will not evaluate the arguments until the body of a procedure is entered. As you can see, `(id (id 10))` is a procedure application. By lazy evaluation, the evaluator packaged the argument `(id 10)` to produce a thunk and evaluated the body of the compound procedure `id`, that is,

```
((set! count (+ count))
 x)
```

Evaluating this increments the variable `count` to `1` and unchangedly return the argument—the thunk it just packaged.

At this juncture, if we ask value of `w`, the evaluator will force the thunk, namely, evaluate the argument `(id 10)`. This again increments `count` and sets it to be `2` and return `10` to the procedure calls it—the outer `id`. The latter one simply returns whatever it accepted, since the assignment expression has been evaluated the moment we defined `w`.

```
;;; L-Eval input:
w
```

*. Creative Commons  2014, Lawrence X. Amlord (颜世敏, aka 颜序).
Email address: informlarry@gmail.com

1. This exercise demonstrates that the interaction between lazy evaluation and side effects can be very confusing. This is just what you might expect from the discussion in chapter 3.

```
;;; L-Eval value:  
10
```

```
;;; L-Eval input:  
count
```

```
;;; L-Eval value:  
2
```