

MODULE 14

# Networking & Persistence

Retrofit, Coroutines, Room, Secure Storage, and Offline Sync

Phase 03 | Android Development with Kotlin

# What You Will Build in This Module

1

## Networking

Retrofit, kotlinx.serialization, coroutines, interceptors, MockWebServer

2

## Persistence and Security

Room, migrations, DataStore, Keystore encryption, token refresh, pinning

3

## Offline-First

Single source of truth, outbox, WorkManager sync, capstone



## Section 1

# Networking: Retrofit, JSON, and Coroutines

- 1.1 HTTP, REST, and Retrofit Foundations
- 1.2 JSON Serialization with `kotlinx.serialization`
- 1.3 Coroutines for Asynchronous Networking
- 1.4 Interceptors, Error Handling, and Testing the Network Layer

# HTTP, REST, and Retrofit Foundations

- Read an HTTP request and response and name its verb, path, headers, status code, and body
- Configure Retrofit and OkHttp in a Gradle project with the correct permission and base URL
- Declare a typed API interface using Retrofit annotations and suspend functions



# Anatomy of a Mobile API Call

- Verb says intent:
  - GET reads
  - POST creates
  - PUT replaces
  - DELETE removes
- Status code says outcome:
  - 2xx success
  - 4xx client fault
  - 5xx server fault
- Headers carry identity and format:  
Authorization, Content-Type, Accept
- Always HTTPS; the transport protects the user, not your code

## Code Bite

```
GET /v1/accounts HTTP/1.1
Host: api.pncmobile.example
Authorization: Bearer eyJhbGciOi...
Accept: application/json
```

```
HTTP/1.1 200 OK
Content-Type: application/json
Cache-Control: private, max-age=30
```

```
[{"id":"acc_1","name":"Virtual
Wallet","masked_number":"****4821","balance"
:2450.75}]
```



# Retrofit and OkHttp: Division of Labor

OkHttp moves bytes: connections, TLS, timeouts, interceptors, cache

Retrofit turns an annotated interface into OkHttp calls

A converter turns JSON bodies into Kotlin objects and back

One shared client per app, never one per request



# Gradle Setup

- Retrofit 3.0, OkHttp 5.5, kotlin.serialization converter (already included earlier)
- Serialization plugin applied in the module build file
- INTERNET permission is declared, never requested at runtime
- Version catalog keeps versions in one place

## Code Bite

```
plugins {  
    alias(libs.plugins.kotlin.serialization)  
}  
dependencies {  
    implementation(libs.retrofit)  
    implementation(libs.okhttp)  
    implementation(libs.okhttp.logging)  
}
```



# Gradle Permissions

- The INTERNET permission MUST be included in AndroidManifest.xml
- If not, the requests will just silently fail
  - Which may cause errors downstream in your app, of course!

## Code Bite

```
// AndroidManifest.xml
<uses-permission android:name =
    "android.permission.INTERNET" />
```



# Declaring the API Interface

- One annotation per HTTP verb: @GET, @POST, @PUT, @DELETE
- @Path fills the URL, @Query appends parameters, @Body sends JSON
- Mark functions suspend so callers use coroutines
- Return the body type, or Response<T> when you need the status code

## Code Bite

```
interface AccountsApi {  
    @GET("accounts")  
        suspend fun getAccounts():  
        List<AccountDto>  
  
    @GET("accounts/{id}/transactions")  
        suspend fun getTransactions(  
            @Path("id") accountId: String,  
            @Query("limit") limit: Int = 50,  
            @Query("cursor") cursor: String? = null  
        ): TransactionPageDto  
}
```



# Sending Data

- @Path fills the URL, @Query appends parameters, @Body sends JSON
- Mark functions suspend so callers use coroutines
- Return the body type, or Response<T> when you need the status code

## Code Bite

```
interface AccountsApi {  
    . . .  
  
    @POST("transfer")  
    suspend fun transfer(@Body request:  
        TransferRequestDto): Response<Unit>  
  
}
```



# Building the Client and Reaching Localhost

- Base URL must end with a slash
- Emulator reaches your computer at 10.0.2.2, not localhost
- Allow cleartext only in a debug network security config
- Release builds stay HTTPS only

## Code Bite

```
val json = Json { ignoreUnknownKeys = true }

val retrofit = Retrofit.Builder()
    .baseUrl(BuildConfig.API_BASE_URL)
    .client(okHttpClient)
    .addConverterFactory(
        json.asConverterFactory(
            "application/json".toMediaType()
        )
    ).build()

val accountsApi: AccountsApi =
    retrofit.create(AccountsApi::class.java)
```



# Lesson 1.1

## Skill Check ✓

**1. A response returns status 401. Which layer of the app should react first?**

- A) The Room database
- B) The authentication layer, which should attempt a token refresh
- C) The Compose theme
- D) The Gradle build

**2. Why does the emulator need 10.0.2.2 instead of localhost?**

- A) It is faster
- B) localhost on the emulator points to the emulator itself
- C) Android forbids localhost for security
- D) Retrofit rewrites it

**3. Which configuration belongs on OkHttpClient rather than Retrofit?**

- A) @GET paths
- B) Read timeout
- C) Return types
- D) Query parameter names

**4. Where should cleartext HTTP be allowed?**

- A) In the main manifest for all builds
- B) Only in a debug-only network security config
- C) In every build type
- D) Nowhere, ever, including debug



# JSON Serialization with `kotlinx.serialization`

- Explain why network DTOs are separate from domain models
- Represent money and timestamps safely
- Annotate DTOs with `@Serializable` and `@SerialName` and configure `Json` for forward compatibility
- Handle unknown enum values without crashing



# DTO, Entity, Domain: Three Different Shapes

DTO mirrors the server JSON exactly

Domain model mirrors what the app needs

Entity mirrors a database row (later lesson)

Mappers are the only code that knows two shapes at once



# DTO, Entity, Domain: Three Different Shapes (code)

@Serializable

```
data class AccountDto(  
    val id: String,  
    val name: String,  
    @SerializedName("masked_number") val maskedNumber: String,  
    @SerializedName("balance_cents") val balanceCents: Long  
)
```

```
data class Account(  
    val id: String,  
    val name: String,  
    val maskedNumber: String,  
    val balance: Money  
)
```

```
fun AccountDto.toDomain() = Account(id, name, maskedNumber, Money(balanceCents))
```



# Json Configuration

- Defaults make fields optional in the payload
- ignoreUnknownKeys lets the server add fields safely

## Code Bite

```
val appJson = Json {  
    ignoreUnknownKeys = true  
    explicitNulls = false  
    coerceInputValues = true  
    encodeDefaults = false  
}
```



# Annotations for Json Encoding

- `@Serializable` generates the serializer at compile time
- `@SerializedName` maps snake\_case JSON to camelCase Kotlin

## Code Bite

```
@Serializable
data class TransferRequestDto(
    @SerializedName("from_account")
    val fromAccountId: String,
    @SerializedName("to_account")
    val toAccountId: String,
    @SerializedName("amount_cents")
    val amountCents: Long,
    val memo: String? = null
)
```



# Money Done Safely

- Never use Double for currency
  - $0.1 + 0.2$  is not  $0.3$
- Safe (accurate) options include:
  - Integer minor units (cents)
  - BigDecimal strings
- It can be useful to wrap either of those options in a class

## Code Bite

```
class Money(val cents: Long) {  
  
    operator fun plus(o: Money) =  
        Money(cents + o.cents)  
  
    fun format(  
        locale: Locale = Locale.getDefault()  
    ): String =  
        NumberFormat  
            .getCurrencyInstance(locale)  
            .format(cents / 100.0)  
  
}
```



# Money and Time Done Safely

- Parse ISO-8601 timestamps to Instant with a custom serializer
- Format for display only at the UI edge, using the user's locale

## Code Bite

```
object InstantSerializer:  
    KSerializer<Instant> {  
    override val descriptor =  
        PrimitiveSerialDescriptor("Instant",  
            PrimitiveKind.STRING)  
    override fun serialize(encoder: Encoder,  
        value: Instant) =  
        encoder.encodeString(value.toString())  
    override fun deserialize(  
        decoder: Decoder  
    ): Instant =  
        Instant.parse(decoder.decodeString())  
}
```



# Enums, Sealed Types, and Unknown Values

A new server enum value must not crash an old app

`coerceInputValues` maps unknown enums to the declared default

Add an explicit UNKNOWN case and render it gracefully

Polymorphic payloads use a sealed class with a discriminator



# Enums, Sealed Types, and Unknown Values (code)

```
@Serializable
```

```
enum class TxType {  
    @SerializedName("debit") DEBIT,  
    @SerializedName("credit") CREDIT,  
    @SerializedName("hold") HOLD,  
    UNKNOWN  
}
```

```
@Serializable
```

```
data class TransactionDto(  
    val id: String,  
    @SerializedName("amount_cents") val amountCents: Long,  
    val type: TxType = TxType.UNKNOWN,  
    @Serializable(with = InstantSerializer::class) val posted: Instant  
)
```



# Lesson 1.2

## Skill Check ✓

### 1. Why not let Composables read DTOs directly?

- A) DTOs are slower
- B) Wire format changes would ripple through the UI
- C) Compose cannot display DTOs
- D) DTOs cannot be null

### 2. What does `ignoreUnknownKeys = true` protect against?

- A) Missing required fields
- B) New fields added by the server
- C) Slow networks
- D) Expired tokens

### 3. Which type is safest for currency amounts?

- A) Float
- B) Double
- C) Long cents or BigDecimal
- D) String concatenation

### 4. How do you survive a new enum value from the server?

- A) Catch the exception in the Composable
- B) Declare an UNKNOWN default and enable `coerceInputValues`
- C) Delete the enum
- D) Ask the server team never to change it

