



MODULE 8

Data & API Integration

Phase 02 | iOS Development with Swift

Module 8 Roadmap

PART 1

Networking Fundamentals

- REST & HTTP
- URLSession & Async/Await
- JSON & Codable
- Error Handling

PART 2

Auth, Security & Persistence

- Authentication Workflows
- Secure Token Handling
- Local Persistence Overview
- Core Data Fundamentals I

PART 3

Core Data & Caching

- Core Data Fundamentals II
- Caching Strategies
- The Full Data Layer
- Capstone Lab



RESTful API Fundamentals & HTTP

- HTTP Verbs & Status Codes
- REST Conventions
- Reading API Documentation



HTTP Verbs & Status Codes

GET

Retrieve data, no side effects

`GET /accounts`

POST

Create something, or trigger an action

`POST /transfers`

PUT / PATCH

Update an existing resource

`PATCH /accounts/{id}`

DELETE

Remove a resource

`DELETE /payees/{id}`

Status Code Families

2xx

Success

4xx

Client error - you sent something wrong

5xx

Server error - not your fault, but you must handle it



Reading API Documentation



Base URL

The root the whole API is hosted under - changes per environment (recall Module 5's Dev/Staging/Prod schemes)



Endpoint & path parameters

The specific resource, e.g. `/accounts/{accountId}/transactions`



Headers

Metadata about the request - Authorization, Content-Type, Accept



Request / response body shape

The JSON contract both sides agree to - this is what Codable models in Lesson 3 will mirror exactly



Lesson 1 - RESTful API Fundamentals & HTTP

Skill Check ✓

- Which HTTP verb would you use to submit a new money transfer, and which to simply view account balances?
- A response comes back with status 404. Which status code family is that, and what does it generally mean?
- Name the four things you need from an API doc page before you can write a single line of networking code.



URLSession & Async/Await

- URLSession Fundamentals
- Swift Concurrency: async/await
- Your First Real Network Call



URLSession

- URLSession is Apple's native networking framework
 - It is built into the Foundation library
 - It is available for iOS, macOS, watchOS, and tvOS
- It provides an API for interacting with web servers via HTTP and HTTPS
- URLSession allows apps to download data, upload files and data, and fetch assets
- It works completely asynchronously
- URLSession (the architecture) is an entire cooperative ecosystem consisting of five parts:
 - URLSession (the coordinator) manages and kicks off network operations
 - URLSessionConfiguration (the settings) configures timeouts, cookie policies, caching, etc.
 - URLRequest (the request) represents the network request package - URL, HTTP method, headers, etc.
 - URLSessionTask (the action) is the worker created by the session to run the request
 - URLResponse (the metadata) contains the server's response details such as headers and status codes



Types of Network Tasks

- When you configure a session, you create specific tasks depending on your objective
- **Data Tasks** are best for sending or receiving short pieces of information
 - e.g. interacting with a RESTful API
 - Format is usually JSON
- **Download Tasks** are designed to pull large files (like videos, images, or PDFs) directly into the device's storage instead of caching them in memory
 - These tasks can pause and resume safely if a connection drops
- **Upload Tasks** are handcrafted to stream or push local data and files onto a server



Creating the URL

- The URL initializer function returns an `Optional<URL>`
 - It must be unwrapped for use in a request
- If your code has the url string as a literal string that you can guarantee is well-formed then you could force unwrap it
- If not, then one of the safe unwrapping patterns should be used
 - e.g. if the user is entering the URL or you are retrieving it from a data store

Code Bite

```
let url = URL(string:
    "https://api-dev.pncmobile.com/accounts")!

guard let url = URL(string: urlStr) else {
    return
}
```



Creating the URLRequest

- URLRequest is a structure that stores all the settings for an HTTP request
- It is created by passing a URL object into its initializer
- The httpMethod property should be set to a valid HTTP method
- HTTP Headers can be specified using the setValue() method

Code Bite

```
var request = URLRequest(url: url)

request.httpMethod = "GET"

request.setValue("Bearer \(token)",
    forHTTPHeaderField: "Authorization")
```



Encoding Data for POST, PUT, or PATCH

- The URLRequest's httpBody property contains data that will be sent to the server
- The most common format is JSON
- Swift's JSONEncoder will convert a dictionary into the proper format

Code Bite

```
request.httpMethod = "POST"
request.setValue("application/json",
    forHTTPHeaderField: "Content-Type")

let bodyData = try JSONEncoder()
    .encode(["name": "Alice"])

request.httpBody = bodyData
```



Sending the Request

- The `URLSession.shared` static property contains the singleton `URLSession` object
- Its `data()` method is an async method used to fetch data from a given URL
- It is marked *async* and *throws* so you must call it using *try await* inside an asynchronous context
- It returns a tuple containing the raw binary data response and a `URLResponse` object

Code Bite

```
let (data, response) = try await
    URLSession.shared.data(for: request)

guard let httpResponse = response as?
    HTTPURLResponse,
    (200...299).contains(httpResponse
        .statusCode) else {
    throw NetworkError.badResponse
}
```



A Complete Request

```
let url = URL(string: "https://api-dev.pncmobile.com/accounts")!
var request = URLRequest(url: url)
request.httpMethod = "GET"
request.setValue("Bearer \$(token)", forHTTPHeaderField: "Authorization")

let (data, response) = try await URLSession.shared.data(for: request)

guard let httpResponse = response as? HTTPURLResponse,
      (200...299).contains(httpResponse.statusCode) else {
    throw NetworkError.badResponse
}

// 'data' is now the raw response bytes - ready for Codable from Lesson 3
```



Swift Concurrency: traditional style

// Old style - completion handlers

```
func fetchAccounts(completion: @escaping ([Account]?, Error?) -> Void) {  
    URLSession.shared.dataTask(with: url) { data, _, error in  
        if let error { completion(nil, error); return }  
        guard let data else { completion(nil, NetworkError.noData); return }  
        let accounts = try? JSONDecoder().decode([Account].self, from: data)  
        completion(accounts, nil)  
    }.resume()  
}
```

// Nests badly once a second dependent call is needed



Swift Concurrency: async/await

```
// Modern style - async/await  
func fetchAccounts() async throws -> [Account] {  
    let (data, _) = try await URLSession.shared.data(for: request)  
    return try JSONDecoder().decode([Account].self, from: data)  
}  
// Reads top-to-bottom like synchronous code. Errors propagate with 'throws'.
```



Lesson 2 - URLSession & Async/Await

Skill Check ✓

- What problem does async/await solve that completion-handler-based networking code has?
- What does the 'await' keyword actually do at the call site?
- Why check response as? HTTPURLResponse and its statusCode before trusting the returned data?



JSON Parsing with Codable

- Codable & Automatic Synthesis
- CodingKeys & Snake Case
- Nested & Optional Fields



Codable: Automatic JSON ↔ Swift Conversion

- Create your Swift model to conform to the Codable protocol
 - This combines two other protocols: Encodable and Decodable
- Note that snake_case in JSON becomes camelCase in Swift with zero extra code
 - When using .convertFromSnakeCase

Code Bite

```
// JSON Response
{
  "id": "a1b2c3",
  "name": "Everyday Checking",
  "masked_number": ".... 4471",
  "balance": 4281.16
}

// Swift Model
struct Account: Codable {
    let id: String
    let name: String
    let maskedNumber: String
    let balance: Decimal
}
```



keyDecodingStrategy

- JSONDecoders have a pluggable decoding strategy
- The convertFromSnakeCase strategy handles snake_case -> camelCase automatically for the WHOLE payload

Code Bite

```
let decoder = JSONDecoder()
decoder.keyDecodingStrategy =
    .convertFromSnakeCase

let accounts = try
    decoder.decode([Account].self, from: data)
```



Custom CodingKeys

- Manual mapping - only needed when a key can't be auto-converted
- Simply add the nested enum and the encoders/decoders will take the mappings into account
 - It must be called CodingKeys
 - It must conform to CodingKey and have a String base type

Code Bite

```
struct Account: Codable {  
    let id: String  
    let name: String  
    let maskedNumber: String  
  
    enum CodingKeys: String, CodingKey {  
        case id, name  
        case maskedNumber = "acct_num_masked"  
        // irregular key name  
    }  
}
```



Nested & Optional Fields

```
struct Account: Codable {  
    let id: String  
    let name: String  
    let balance: Decimal  
    let institution: Institution    // nested object  
    let nickname: String?          // optional - may be absent or nil  
}
```

```
struct Institution: Codable {  
    let name: String  
    let routingNumber: String  
}
```

```
// Decoding fails LOUDLY (throws) if a required field is missing -  
// that's a feature, not a bug: better a caught error than silent wrong data.
```



Lesson 3 - JSON Parsing with Codable

Skill Check ✓

- What does `.keyDecodingStrategy = .convertFromSnakeCase` eliminate the need for, in most cases?
- When would you still need a manual `CodingKeys` enum even with `convertFromSnakeCase` enabled?
- Why is it a feature, not a bug, that decoding throws when a required field is missing?



Error Handling & the Generic Fetch Pattern

- Custom NetworkError Types
- A Reusable Generic Fetch Function



Custom NetworkError Types

- Our network code needs to be more specific about error conditions
- Preview: .unauthorized deserves its own case rather than folding into badResponse
 - This lets you trigger an automatic token refresh - a generic error can't carry that meaning

Code Bite

```
enum NetworkError: Error {  
    case invalidURL  
    case noConnection  
    case badResponse(statusCode: Int)  
    case decodingFailed(underlying: Error)  
    case encodingFailed(underlying: Error)  
    case unauthorized  
}
```



Writing Reusable Code

- Repository code we've seen so far has a lot of boilerplate code in each method
- New repository classes for other entities would duplicate that boilerplate
- It is straightforward to encapsulate that boilerplate code in generic methods
- Create a generic base class for all remote repositories and include the boilerplate code
- We can take advantage of this re-write to add more thorough error handling



Generic Repository Base Class

```
class RemoteRepositoryBase<Item: Codable> {  
    func fetchAll(_ urlString: String) async throws -> [Item] {  
        . . .  
    }  
  
    func fetchOne(_ urlString: String) async throws -> Item {  
        . . .  
    }  
  
    func post(_ urlString: String, send item: Item) async throws -> Item { . . . }  
    func put(_ urlString: String, send item: Item) async throws { . . . }  
    func del(_ urlString: String) async throws { . . . }  
}
```



fetchAll() method

```
func fetchAll(_ urlString: String) async throws -> [Item] {  
  
    guard let url = URL(string: urlString) else {  
        throw NetworkError.invalidURL  
    }  
  
    var request = URLRequest(url: url)  
    request.setValue("Bearer \(TokenStore.current)", forHTTPHeaderField: "Authorization")  
  
    let (data, response) = try await URLSession.shared.data(for: request)  
  
    guard let http = response as? HTTPURLResponse else {  
        throw NetworkError.badResponse(statusCode: -1)  
    }  
}
```



fetchAll() method - continued

```
guard (200...299).contains(http.statusCode) else {  
    if http.statusCode == 401 { throw NetworkError.unauthorized }  
    throw NetworkError.badResponse(statusCode: http.statusCode)  
}
```

```
do {  
    let decoder = JSONDecoder()  
    decoder.keyDecodingStrategy = .convertFromSnakeCase  
    return try decoder.decode(Array<Item>.self, from: data)  
} catch {  
    throw NetworkError.decodingFailed(underlying: error)  
}
```

```
}
```



Using the Generic Boilerplate Methods

- Every repository implementation should now inherit from the generic base class
- The inherited boilerplate methods are available to assist in implementing the protocol methods

Code Bite

```
class RemoteProductRepository:
    RemoteRepositoryBase<Product>,
    RepositoryProtocol<Product> {

    func getAll() async throws -> [Product] {
        let urlString = "\(urlBase)/products"
        return try await fetchAll(urlString)
    }

    . . .

}
```



Lesson 4 - Error Handling & the Generic Fetch Pattern

Skill Check ✓

- Why define distinct `NetworkError` cases instead of throwing a single generic error?
- In `fetch<T: Decodable>`, what does the generic parameter `T` let one function do that a non-generic version couldn't?

