

NEURAL DATA ANALYSIS

ALEXANDER ECKER, PHILIPP BERENS,
MATTHIAS BETHGE

COMPUTATIONAL VISION AND
NEUROSCIENCE GROUP

QUESTIONS SO FAR?

Preprocessing for spikes from electrophysiological recordings



Other recording techniques?

INFERRING SPIKES FROM CALCIUM TRACES




CALCIUM IMAGING




- Calcium indicator: Dye (e.g. OGB1)
- Binds to intracellular calcium and changes fluorescence
- Fluorescence measured by two-photon imaging



CALCIUM AND SPIKES




A SIMPLIFIED CALCIUM IMAGING MODEL




SIMULATED PATTERNS

Simulated firing patterns and calcium signals:

— Firing rate
— Calcium signal




INVERTING THE FORWARD MODEL




ALGORITHM

1. Low pass filter trace (Butterworth/Gaussian)
2. Iterative local averaging procedure (for details see paper) to remove noise below a threshold without affecting AP transients
3. Deconvolution with exponential kernel
 - Finding the time constant?
 - Reconstruction of low pass-filtered trace
 - Negative rates?




RESULTS


Reconstruction by deconvolution:



RESULTS



A MORE COMPLEX MODEL



$$F_t = \alpha [Ca^{2+}]_t + \beta + \epsilon_t$$

$$[Ca^{2+}]_{t+1} = \frac{1 - \Delta}{\tau} [Ca^{2+}]_t + n_t \quad n_t \in N_0$$

$$n_t \sim \text{Poisson}(\lambda \Delta)$$

Spike train

Bin width

Fluorescence

$$\hat{n} = \arg \max P[n|F]$$

Expected rate

$$\hat{n} = \arg \max_{\text{Intracellular calcium}} \sum_{t=1}^T \left[-\frac{1}{2\sigma^2} (F_t - \alpha C_t - \beta)^2 + n_t \ln \lambda \Delta - \ln n_t! \right]$$

MAP Estimate

Because of Poisson prior!

Vogelstein et al. 2009/2010


APPROXIMATE SOLUTION

$$\hat{n} = \arg \max P[n|F]$$
$$\hat{n} = \arg \max \sum_{t=1}^T -\frac{1}{2\sigma} (F_t - \alpha C_t - \beta)^2 + n_t \lambda \Delta$$


With exponential prior
 $n_t \geq 0$

- Convex in spike train
- Interior-point methods because of threshold
- Iterate
 1. Solve for spike train, fix parameters
 2. Solve for parameters, fix spike train

RESULT



SUPERVISED LEARNING



- Learn function from calcium snippets to spike rates
- Flexible model
- See next week: Theis, Berens et al. 2015


OTHER IDEAS

- **GLMs with calcium as input**
- **STA/STC**
- **Classifier that classifies snippets of calcium trace as spike or not spike**
- **...**

COMPETITION

1. You get a set of 10 cells for which
 - Calcium trace
 - Spike ratehas been simultaneously recorded*.
2. You implement an algorithm to infer rates from calcium signals and learn it's parameters on the ten cells you have.
3. You submit your m file and we evaluate it on another set of 45 cells.
4. The winning team gets a 10 Euro voucher

* Data courtesy of
M. Froudarakis (BCM)



DETAILS

1. Data format

- Galvo trace
- Spike trace
- Fps (frame per second): Temporal resolution of both traces

2. Don't use preimplemented algorithms

3. Evaluation

- `corr(spiketrace, ispiketrace)`
- mean across testset
- Baseline with the most simple algorithm: ~0.32 (0.00-0.54)
- Due date: 14 of July!