



SQLite

sql database engine

tutorialspoint
SIMPLY EASY LEARNING

www.tutorialspoint.com



<https://www.facebook.com/tutorialspointindia>



<https://twitter.com/tutorialspoint>

About the Tutorial

SQLite is a software library that implements a self-contained, serverless, zero-configuration, transactional SQL database engine. SQLite is the most widely deployed SQL database engine in the world. The source code for SQLite is in the public domain.

This tutorial will give you a quick start with SQLite and make you comfortable with SQLite programming.

Audience

This tutorial has been prepared for beginners to help them understand the basic-to-advanced concepts related to SQLite Database Engine.

Prerequisites

Before you start practicing various types of examples given in this reference, **we assume that you are already aware about what is a database, especially RDBMS and what is a computer programming language.**

Disclaimer & Copyright

© Copyright 2017 by Tutorials Point (I) Pvt. Ltd.

All the content and graphics published in this e-book are the property of Tutorials Point (I) Pvt. Ltd. The user of this e-book is prohibited to reuse, retain, copy, distribute or republish any contents or a part of contents of this e-book in any manner without written consent of the publisher.

We strive to update the contents of our website and tutorials as timely and as precisely as possible, however, the contents may contain inaccuracies or errors. Tutorials Point (I) Pvt. Ltd. provides no guarantee regarding the accuracy, timeliness or completeness of our website or its contents including this tutorial. If you discover any errors on our website or in this tutorial, please notify us at contact@tutorialspoint.com.

Table of Contents

About the Tutorial	i
Audience.....	i
Prerequisites.....	i
Disclaimer & Copyright	i
Table of Contents	ii
 SQLITE BASICS.....	 1
1. SQLite – Overview.....	2
What is SQLite?	2
Why SQLite?	2
SQLite – A Brief History	3
SQLite Limitations.....	3
SQLite Commands	3
2. SQLite – Installation	5
Install SQLite on Windows	5
Install SQLite on Linux	5
Install SQLite on Mac OS X.....	6
3. SQLite – Commands	7
4. SQLite – Syntax	11
5. SQLite – Data Type.....	18
SQLite Storage Classes.....	18
SQLite Affinity Type	18
SQLite Affinity and Type Names	19
6. SQLite – CREATE Database	21
The .dump Command	22
7. SQLite – ATTACH Database	23
8. SQLite – DETACH Database	24
9. SQLite – CREATE Table	25
10. SQLite – DROP Table	27
11. SQLite – INSERT Query	28
12. SQLite – SELECT Query	31
13. SQLite – Operators.....	34
What is an Operator in SQLite?	34
SQLite Arithmetic Operators	34
SQLite Comparison Operators.....	35
SQLite Logical Operators	38
SQLite Bitwise Operators.....	42

14. SQLite – Expressions	44
SQLite - Boolean Expression	44
SQLite - Numeric Expression	45
SQLite - Date Expression.....	45
15. SQLite – WHERE Clause	46
16. SQLite – AND & OR Operators.....	50
The AND Operator	50
The OR Operator	51
17. SQLite – UPDATE Query	53
18. SQLite – DELETE Query	55
19. SQLite – LIKE Clause	57
20. SQLite – GLOB Clause	60
21. SQLite – LIMIT Clause	63
22. SQLite – ORDER BY Clause.....	65
23. SQLite – GROUP BY Clause	67
24. SQLite – HAVING Clause	70
25. SQLite – DISTINCT Keyword	72
ADVANCED SQLITE	74
26. SQLite – PRAGMA	75
auto_vacuum Pragma.....	75
cache_size Pragma	76
case_sensitive_like Pragma	76
count_changes Pragma	76
database_list Pragma	76
encoding Pragma	76
freelist_count Pragma	77
index_info Pragma.....	77
index_list Pragma	77
journal_mode Pragma	77
max_page_count Pragma.....	78
page_count Pragma.....	78
page_size Pragma.....	78
parser_trace Pragma	78
recursive_triggers Pragma.....	79
schema_version Pragma.....	79
secure_delete Pragma.....	79
sql_trace Pragma	79
synchronous Pragma	80
temp_store Pragma.....	80

temp_store_directory Pragma	80
user_version Pragma	81
writable_schema Pragma	81
27. SQLite – Constraints	82
NOT NULL Constraint	82
DEFAULT Constraint	83
UNIQUE Constraint	83
PRIMARY KEY Constraint	84
CHECK Constraint	84
Dropping Constraint	85
28. SQLite – JOINS	86
The CROSS JOIN	87
The INNER JOIN	88
The OUTER JOIN	89
29. SQLite – UNION Clause	90
The UNION ALL Clause	92
30. SQLite – NULL Values	94
31. SQLite – ALIAS Syntax	97
32. SQLite – Triggers	100
Listing Triggers	102
Dropping Triggers	103
33. SQLite – Indexes	104
The CREATE INDEX Command	104
The DROP INDEX Command	106
34. SQLite – INDEXED BY Clause	107
35. SQLite – ALTER TABLE Command	109
36. SQLite – TRUNCATE TABLE Command	111
37. SQLite – Views	112
Creating Views	112
Dropping Views	113
38. SQLite – Transactions	114
Properties of Transactions	114
Transaction Control	114
39. SQLite – Subqueries	117
Subqueries with SELECT Statement	117
Subqueries with INSERT Statement	118
Subqueries with UPDATE Statement	119
Subqueries with DELETE Statement	120
40. SQLite – AUTOINCREMENT	121

41. SQLite – Injection	123
Preventing SQL Injection	123
42. SQLite – EXPLAIN	125
43. SQLite – VACUUM	127
Manual VACUUM	127
Auto-VACCUM	127
44. SQLite – Date & Time	129
Time Strings	129
Modifiers	130
Formatters	130
45. SQLite – Useful Functions.....	133
SQLite COUNT Function	134
SQLite MAX Function	135
SQLite MIN Function.....	135
SQLite AVG Function	135
SQLite SUM Function.....	136
SQLite RANDOM Function	136
SQLite ABS Function	136
SQLite UPPER Function	136
SQLite LOWER Function.....	137
SQLite LENGTH Function	137
SQLite sqlite_version Function	138
SQLITE INTERFACES.....	139
46. SQLite – C/C++	140
C/C++ Interface APIs	140
Connect to Database	141
Create a Table.....	142
INSERT Operation	143
SELECT Operation	145
UPDATE Operation	147
DELETE Operation.....	149
47. SQLite – Java	152
Installation.....	152
Connect to Database	152
Create a Table.....	153
INSERT Operation	154
SELECT Operation	155
UPDATE Operation	157
DELETE Operation.....	159
48. SQLite – PHP	162
Installation	162
PHP Interface APIs	162
Connect to Database	163
Create a Table.....	164

INSERT Operation	165
SELECT Operation	166
UPDATE Operation	168
DELETE Operation.....	169
49. SQLite – Perl	172
Installation	172
DBI Interface APIs	172
Connect to Database	174
Create a Table.....	175
INSERT Operation	176
SELECT Operation	177
UPDATE Operation	179
DELETE Operation.....	180
50. SQLite – Python	183
Installation	183
Python sqlite3 module APIs.....	183
Connect to Database	186
Create a Table.....	186
INSERT Operation	187
SELECT Operation	188
UPDATE Operation	189
DELETE Operation.....	190

SQLite Basics

1. SQLite – Overview

SQL tutorial 3

This chapter helps you understand what is SQLite, how it differs from SQL, why it is needed and the way in which it handles the applications Database.

SQLite is a software library that implements a self-contained, serverless, zero-configuration, transactional SQL database engine. SQLite is one of the fastest-growing database engines around, but that's growth in terms of popularity, not anything to do with its size. The source code for SQLite is in the public domain.

What is SQLite?

SQLite is an in-process library that implements a self-contained, serverless, zero-configuration, transactional SQL database engine. It is a database, which is zero-configured, which means like other databases you do not need to configure it in your system.

SQLite engine is not a standalone process like other databases, you can link it statically or dynamically as per your requirement with your application. SQLite accesses its storage files directly.

Why SQLite?

SQLite DBMS

MS access . MySQL DB
, Oracle
DB .

- SQLite does not require a separate server process or system to operate (serverless).
- SQLite comes with zero-configuration, which means no setup or administration needed.
- A complete SQLite database is stored in a single cross-platform disk file.
- SQLite is very small and light weight, less than 400KiB fully configured or less than 250KiB with optional features omitted.
- SQLite is self-contained, which means no external dependencies.
oracle Java SE Development Kit .
- SQLite transactions are fully ACID-compliant, allowing safe access from multiple processes or threads.
Atomicity, Consistency, Isolation, Durability
- SQLite supports most of the query language features found in SQL92 (SQL2) standard.
- SQLite is written in ANSI-C and provides simple and easy-to-use API.
- SQLite is available on UNIX (Linux, Mac OS-X, Android, iOS) and Windows (Win32, WinCE, WinRT).

UnQLite is an embedded NoSQL (Key/Value store and Document - store) database engine. Unlike most other NoSQL databases, UnQLite does not have a separate server process. UnQLite reads and writes directly to ordinary disk files. A complete database with multiple collections, is contained in a single disk file. The database file format is cross - platform.

SQLite – A Brief History

- 2000 - D. Richard Hipp designed SQLite for the purpose of no administration required for operating a program.
- 2000 - In August, SQLite 1.0 released with GNU Database Manager.
- 2011 - Hipp announced to add UNQL interface to SQLite DB and to develop UNQLite (Document oriented database).

SQLite Limitations

There are few unsupported features of SQL92 in SQLite which are listed in the following table.

Feature	Description
RIGHT OUTER JOIN	Only LEFT OUTER JOIN is implemented.
FULL OUTER JOIN	Only LEFT OUTER JOIN is implemented.
ALTER TABLE	The RENAME TABLE and ADD COLUMN variants of the ALTER TABLE command are supported. The DROP COLUMN, ALTER COLUMN, ADD CONSTRAINT are not supported.
Trigger support	FOR EACH ROW triggers are supported but not FOR EACH STATEMENT triggers.
VIEWS	VIEWS in SQLite are read-only. You may not execute a DELETE, INSERT, or UPDATE statement on a view.
GRANT and REVOKE	The only access permissions that can be applied are the normal file access permissions of the underlying operating system.

SQLite Commands

The standard SQLite commands are SQL, SQLite, and SQL. They are CREATE, SELECT, INSERT, UPDATE, DELETE and DROP. These commands can be classified into groups based on their operational nature.

DDL - Data Definition Language

Command	Description
CREATE	Creates a new table, a view of a table, or other object in database.
ALTER	Modifies an existing database object, such as a table.

DROP	Deletes an entire table, a view of a table or other object in the database.
-------------	-----------------------------------------------------------------------------

DML - Data Manipulation Language

Command	Description
INSERT	Creates a record
UPDATE	Modifies records
DELETE	Deletes records

DQL - Data Query Language

Command	Description
SELECT	Retrieves certain records from one or more tables

TCL (transaction control language): BEGIN, COMMIT, ROLLBACK
DCL(data control language): GRANT, REVOKE

2. SQLite – Installation

SQLite is famous for its great feature zero-configuration, which means no complex setup or administration is needed. This chapter shows how to install SQLite on Windows, Linux and Mac OS.

sqlite - tools - win32 - x86 - *.zip

Install SQLite on Windows

Step 1: Go to [SQLite download page](#), and download precompiled binaries from Windows section.

Step 2: Download sqlite-shell-win32-*.zip and sqlite-dll-win32-*.zip zipped files.

Step 3: Create a folder C:\>sqlite and unzip above two zipped files in this folder, which will give you sqlite3.def, sqlite3.dll and sqlite3.exe files.

Step 4: Add C:\>sqlite in your PATH environment variable and finally go to the command prompt and issue sqlite3 command, which should display the following result.

```
C:\>sqlite3
SQLite version 3.7.15.2 2013-01-09 11:53:05
Enter ".help" for instructions
Enter SQL statements terminated with a ";"
sqlite>
```

```
1. https://github.com/joongyang/Lecture - Materials - for - SQLite/tree/master/
test
2. testDB.db
3. 가
( 가 db )
( ) C:\Users\joong\Desktop\sqlite> sqlite3
4. 3 가 sqlite
5. .quit sqlite
```

If you do not see the above result, then it means you do not have SQLite installed on your Linux machine. Following are the steps to install SQLite:

Step 1: Go to [SQLite download page](#) and download sqlite-autoconf-*.tar.gz from source code section.

Step 2: Run the following command.

```
$tar xvfz sqlite-autoconf-3071502.tar.gz
$cd sqlite-autoconf-3071502
$./configure --prefix=/usr/local
$make
$make install
```

The above command will end with SQLite installation on your Linux machine, which you can verify as explained above.

Install SQLite on Mac OS X

Though the latest version of Mac OS X comes pre-installed with SQLite, but if you do not have installation available then just follow these steps:

Step 1: Go to [SQLite download page](#), and download sqlite-autoconf-*.tar.gz from source code section.

Step 2: Run the following command.

```
$tar xvfz sqlite-autoconf-3071502.tar.gz
$cd sqlite-autoconf-3071502
$./configure --prefix=/usr/local
$make
$make install
```

The above procedure will end with SQLite installation on your Mac OS X machine, which you can verify by issuing the following command:

```
$sqlite3
SQLite version 3.7.15.2 2013-01-09 11:53:05
Enter ".help" for instructions
Enter SQL statements terminated with a ";"
sqlite>
```

Finally, you have SQLite command prompt where you can issue SQLite commands for your exercises.

3. SQLite – Commands

SQLite	.	(SQLite	.	SQLite	SQL
.)	가	.	SQLite	.	SQL
.	3	SQLite	,	4	SQL	.

Let's start with typing a simple **sqlite3** command at command prompt which will provide you with SQLite command prompt where you will issue various SQLite commands.

```
$sqlite3
SQLite version 3.3.6
Enter ".help" for instructions
sqlite>
```

For a listing of the available dot commands, you can enter ".help" any time. For example:

```
sqlite>.help
```

The above command will display a list of various important SQLite dot commands, which are listed in the following table.

Command	Description
.backup ?DB? FILE	Backup DB (default "main") to FILE
.bail ON OFF	Stop after hitting an error. Default OFF
.databases	List names and files of attached databases
.dump ?TABLE?	Dump the database in an SQL text format. If TABLE specified, only dump tables matching LIKE pattern TABLE
.echo ON OFF	Turn command echo on or off
.exit	Exit SQLite prompt
.explain ON OFF	Turn output mode suitable for EXPLAIN on or off. With no args, it turns EXPLAIN on
.header(s) ON OFF	Turn display of headers on or off
.help	Show this message

.import FILE TABLE	Import data from FILE into TABLE
.indices ?TABLE?	Show names of all indices. If TABLE specified, only show indices for tables matching LIKE pattern TABLE
.load FILE ?ENTRY?	Load an extension library
.log FILE off	Turn logging on or off. FILE can be stderr/stdout
.mode MODE	<p>Set output mode where MODE is one of:</p> <ul style="list-style-type: none"> • <u>csv</u> Comma-separated values • <u>column</u> Left-aligned columns • <u>html</u> HTML <table> code • <u>insert</u> SQL insert statements for TABLE • line One value per line • list Values delimited by .separator string • <u>tabs</u> Tab-separated values • tcl TCL list elements
.nullvalue STRING	Print STRING in place of NULL values
.output FILENAME	Send output to FILENAME
.output stdout	Send output to the screen
.print STRING...	Print literal STRING
.prompt MAIN CONTINUE	Replace the standard prompts
.quit	Exit SQLite prompt

.read FILENAME	Execute SQL in FILENAME
.schema ?TABLE?	Show the CREATE statements. If TABLE specified, only show tables matching LIKE pattern TABLE
.separator STRING	Change separator used by output mode and .import
.show	Show the current values for various settings
.stats ON OFF	Turn stats on or off
.tables ?PATTERN?	List names of tables matching a LIKE pattern
.timeout MS	Try opening locked tables for MS milliseconds
.width NUM NUM	Set column widths for "column" mode
.timer ON OFF	Turn the CPU timer measurement on or off

Let's try **.show** command to see default setting for your SQLite command prompt.

<pre> sqlite>.show echo: off explain: off headers: off mode: column nullvalue: "" output: stdout separator: " " width: sqlite> </pre>	<pre> sqlite> .echo on sqlite> .show sqlite> .echo off sqlite> .show </pre>
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------

Make sure there is no space in between sqlite> prompt and dot command, otherwise it will not work.


```
( ) testDB.db 가 SQLite
.
testDB.db
$ sqlite3 testDB.db
SQLite가 .databases, .tables, .schema, .mode SQLite
sqlite>.mode column
```

**** Sqlite (optional)**

```
home> sqlite3 testDB.db "select * from employees;"
home> sqlite3 -column -csv testDB.db "select * from department;"
home> sqlite3 - - help

output redirection

home> sqlite3 -column -header -csv testDB.db "select * from employees;" > employees.csv
```

```
1 Paul 32 California 20000.0
( ) testDB testDB.sql backup
.output, .dump, .read

2. testDB.sql
3. testDB.sql
4. testDB.db
5. testDB.sql testDB.db
6. testDB.db
```

The sqlite_master Table

The master table holds the key information about your database tables and it is called **sqlite_master**. You can see its schema as follows:

```
sqlite>.schema sqlite_master
```

This will produce the following result.

```
CREATE TABLE sqlite_master (
  type text,
  name text,
  tbl_name text,
  rootpage integer,
```

```
( ) scott.db
scott.db .) . (
1)
2)
3) . csv
4) csv excel
5) scott.db backup
```

4. SQLite – Syntax

SQLite is followed by a unique set of rules and guidelines called Syntax. This chapter lists all the basic SQLite Syntax.

Case Sensitivity

Important point to be noted is that **SQLite is case insensitive**, but there are some commands, which are case sensitive like **GLOB** and **glob** have different meaning in SQLite statements.

Comments

SQLite comments are extra notes, which you can add in your SQLite code to increase its readability and they can appear anywhere; whitespace can occur, including inside expressions and in the middle of other SQL statements but they cannot be nested.

SQL comments begin with two consecutive "--" characters (ASCII 0x2d) and extend up to and including the next newline character (ASCII 0x0a) or until the end of input, whichever comes first.

You can also use C-style comments, which begin with "/*" and extend up to and including the next "*/" character pair or until the end of input, whichever comes first. C-style comments can span multiple lines.

```
sqlite>.help -- This is a single line comment
```

SQL Statements

All the SQLite statements start with any of the keywords like SELECT, INSERT, UPDATE, DELETE, ALTER, DROP, etc., and **all the statements end with a semicolon (;).**

SQLite ANALYZE Statement

```
ANALYZE;  
  
or  
  
ANALYZE database_name;  
  
or  
  
ANALYZE database_name.table_name;
```

SQLite AND/OR Clause

```
SELECT column1, column2....columnN  
FROM   table_name  
WHERE  CONDITION-1 {AND|OR} CONDITION-2;
```

SQLite ALTER TABLE Statement

```
ALTER TABLE table_name ADD COLUMN column_def...;
```

SQLite ALTER TABLE Statement (Rename)

```
ALTER TABLE table_name RENAME TO new_table_name;
```

SQLite ATTACH DATABASE Statement

```
ATTACH DATABASE 'DatabaseName' As 'Alias-Name';
```

SQLite BEGIN TRANSACTION Statement

```
BEGIN;  
or  
BEGIN EXCLUSIVE TRANSACTION;
```

SQLite BETWEEN Clause

```
SELECT column1, column2....columnN  
FROM table_name  
WHERE column_name BETWEEN val-1 AND val-2;
```

SQLite COMMIT Statement

```
COMMIT;
```

SQLite CREATE INDEX Statement

```
CREATE INDEX index_name  
ON table_name ( column_name COLLATE NOCASE );
```

SQLite CREATE UNIQUE INDEX Statement

```
CREATE UNIQUE INDEX index_name  
ON table_name ( column1, column2,...columnN);
```

SQLite CREATE TABLE Statement

```
CREATE TABLE table_name(  
    column1 datatype,  
    column2 datatype,
```

```

    column3 datatype,
    .....
    columnN datatype,
    PRIMARY KEY( one or more columns )
);

```

SQLite CREATE TRIGGER Statement

```

CREATE TRIGGER database_name.trigger_name
BEFORE INSERT ON table_name FOR EACH ROW
BEGIN
    stmt1;
    stmt2;
    ....
END;

```

SQLite CREATE VIEW Statement

```

CREATE VIEW database_name.view_name AS
SELECT statement....;

```

SQLite CREATE VIRTUAL TABLE Statement

```

CREATE VIRTUAL TABLE database_name.table_name USING weblog( access.log );
or
CREATE VIRTUAL TABLE database_name.table_name USING fts3( );

```

SQLite COMMIT TRANSACTION Statement

```

COMMIT;

```

SQLite COUNT Clause

```

SELECT COUNT(column_name)
FROM   table_name
WHERE  CONDITION;

```

SQLite DELETE Statement

```
DELETE FROM table_name
WHERE {CONDITION};
```

SQLite DETACH DATABASE Statement

```
DETACH DATABASE 'Alias-Name';
```

SQLite DISTINCT Clause

```
SELECT DISTINCT column1, column2....columnN
FROM table_name;
```

SQLite DROP INDEX Statement

```
DROP INDEX database_name.index_name;
```

SQLite DROP TABLE Statement

```
DROP TABLE database_name.table_name;
```

SQLite DROP VIEW Statement

```
DROP INDEX database_name.view_name;
```

SQLite DROP TRIGGER Statement

```
DROP INDEX database_name.trigger_name;
```

TRIGGER

SQLite EXISTS Clause

```
SELECT column1, column2....columnN
FROM table_name
WHERE column_name EXISTS (SELECT * FROM table_name );
```

SQLite EXPLAIN Statement

```
EXPLAIN INSERT statement...;
or
EXPLAIN QUERY PLAN SELECT statement...;
```

SQLite GLOB Clause

```
SELECT column1, column2....columnN
```

```
FROM    table_name  
WHERE   column_name GLOB { PATTERN };
```

SQLite GROUP BY Clause

```
SELECT SUM(column_name)  
FROM    table_name  
WHERE   CONDITION  
GROUP BY column_name;
```

SQLite HAVING Clause

```
SELECT SUM(column_name)  
FROM    table_name  
WHERE   CONDITION  
GROUP BY column_name  
HAVING (arithmetic function condition);
```

SQLite INSERT INTO Statement

```
INSERT INTO table_name( column1, column2....columnN)  
VALUES ( value1, value2....valueN);
```

SQLite IN Clause

```
SELECT column1, column2....columnN  
FROM    table_name  
WHERE   column_name IN (val-1, val-2,...val-N);
```

SQLite Like Clause

```
SELECT column1, column2....columnN  
FROM    table_name  
WHERE   column_name LIKE { PATTERN };
```

SQLite NOT IN Clause

```
SELECT column1, column2....columnN  
FROM    table_name
```

```
WHERE column_name NOT IN (val-1, val-2,...val-N);
```

SQLite ORDER BY Clause

```
SELECT column1, column2....columnN
FROM table_name
WHERE CONDITION
ORDER BY column_name {ASC|DESC};
```

SQLite PRAGMA Statement

```
PRAGMA pragma_name;
```

For example:

```
PRAGMA page_size;
PRAGMA cache_size = 1024;
PRAGMA table_info(table_name);
```

SQLite RDBMS SQL 가
DBMS (

SQLite RELEASE SAVEPOINT Statement

```
RELEASE savepoint_name;
```

SQLite REINDEX Statement

```
REINDEX collation_name;
REINDEX database_name.index_name;
REINDEX database_name.table_name;
```

SQLite ROLLBACK Statement

```
ROLLBACK;
or
ROLLBACK TO SAVEPOINT savepoint_name;
```

SQLite SAVEPOINT Statement

```
SAVEPOINT savepoint_name;
```

SQLite SELECT Statement

```
SELECT column1, column2....columnN  
FROM   table_name;
```

SQLite UPDATE Statement

```
UPDATE table_name  
SET column1 = value1, column2 = value2....columnN=valueN  
[ WHERE CONDITION ];
```

SQLite VACUUM Statement

```
VACUUM;
```

SQLite WHERE Clause

```
SELECT column1, column2....columnN  
FROM   table_name  
WHERE  CONDITION;
```


5. SQLite – Data Type

RDBMS (type) type) class) RDBMS	SQLite .	:	DBMS SQLite	(affinity (storage
---------------------------------------------	-------------	---	----------------	-----------------------

SQLite Storage Classes

SQLite DB 5가
가 .

Each value stored in an SQLite database has one of the following storage classes:

Storage Class	Description
NULL	The value is a NULL value.
INTEGER	The value is a signed integer, stored in 1, 2, 3, 4, 6, or 8 bytes depending on the magnitude of the value.
REAL	The value is a floating point value, stored as an 8-byte IEEE floating point number.
TEXT	The value is a text string, stored using the database encoding (UTF-8, UTF-16BE or UTF-16LE)
BLOB	The value is a blob of data, stored exactly as it was input.

binary large object
→

(field) (affinity type))	sqlite DBMS (storage class) 가 .
SQLite . DBMS	

column in an SQLite database is assigned one of the following type affinities.

Affinity	Description
TEXT	This column stores all data using storage classes NULL, TEXT or BLOB.
NUMERIC	This column may contain values using all five storage classes.
INTEGER	Behaves the same as a column with NUMERIC affinity, with an exception in a CAST expression.

REAL	Behaves like a column with NUMERIC affinity except that it forces integer values into floating point representation.
NONE	A column with affinity NONE does not prefer one storage class over another and no attempt is made to coerce data from one storage class into another.

SQLite Affinity and Type Names

Following table lists down various data type names which can be used while creating SQLite3 tables with the corresponding applied affinity.

Data Type	Affinity
<ul style="list-style-type: none"> INT INTEGER TINYINT SMALLINT MEDIUMINT BIGINT UNSIGNED BIG INT INT2 INT8 	<p>SQL</p> <p>SQL</p> <p>SQLite storage class</p>
<ul style="list-style-type: none"> CHARACTER(20) CHAR(20) VARCHAR(255) VARYING CHARACTER(255) NCHAR(55) NATIVE CHARACTER(70) NVARCHAR(100) TEXT CLOB 	<p>TEXT</p> <p>char, nchar</p> <p>char ascii 1 2</p> <p>nchar 2 가 nchar</p> <p>nchar, nvarchar</p>
<ul style="list-style-type: none"> BLOB no datatype specified 	
<ul style="list-style-type: none"> REAL 	REAL

character large object block

<ul style="list-style-type: none"> • DOUBLE • DOUBLE PRECISION • FLOAT 	
<ul style="list-style-type: none"> • NUMERIC • DECIMAL(10,5) • BOOLEAN • DATE • DATETIME 	NUMERIC

Boolean Datatype

SQLite does not have a separate Boolean storage class. Instead, Boolean values are stored as integers 0 (false) and 1 (true).

Date and Time Datatype

SQLite does not have a separate storage class for dates and times. It is capable of storing dates and times in a variety of formats.

RDBMS SQL DATE, DATETIME, SQLite

Storage Class	Date Format
TEXT	A date in a format like "YYYY-MM-DD HH:MM:SS.SSS" ISO
REAL	The number of days since <u>noon in Greenwich on November 24, 4714 B.C.</u>
INTEGER	The number of seconds since <u>1970-01-01 00:00:00 UTC</u> unix epoch

You can choose to store dates and times in any of these formats and freely convert between formats using the built-in date and time functions.

BC 4713 7980 Julian Period
 Julian Period가 BC
 4713 11 24 (julian date)

6. SQLite – CREATE Database

In SQLite, **sqlite3** command is used to create a new SQLite database. You do not need to have any special privilege to create a database.

Syntax

Basic syntax of sqlite3 command is as follows:

```
$sqlite3 DatabaseName.db
```

Always, database name should be unique within the RDBMS.

Example

If you want to create a new database <testDB.db>, then SQLITE3 statement would be as follows:

```
$sqlite3 testDB.db
SQLite version 3.7.15.2 2013-01-09 11:53:05
Enter ".help" for instructions
Enter SQL statements terminated with a ";"
sqlite>
```

The above command will create a file **testDB.db** in the current directory. This file will be used as database by SQLite engine. If you have noticed while creating database, sqlite3 command will provide a **sqlite>** prompt after creating a database file successfully.

Once a database is created, you can verify it in the list of databases using the following SQLite **.databases** command.

```
sqlite>.databases
seq  name          file
---  -
0    main           /home/sqlite/testDB.db
```

You will use SQLite **.quit** command to come out of the sqlite prompt as follows:

```
sqlite>.quit
$
```

The .dump Command

You can use **.dump** dot command to export complete database in a text file using the following SQLite command at the command prompt.

```
$sqlite3 testDB.db .dump > testDB.sql
```

The above command will convert the entire contents of **testDB.db** database into SQLite statements and dump it into ASCII text file **testDB.sql**. You can perform restoration from the generated testDB.sql in a simple way as follows:

```
$sqlite3 testDB.db < testDB.sql
```

At this moment your database is empty, so you can try above two procedures once you have few tables and data in your database. For now, let's proceed to the next chapter.

```
SQLite          sqlite3.exe          가          .
          . SQLite          .dump
.

sqlite> .output dump_filename.sql
sqlite> .dump
sqlite> .output stdout
```

```
( )          .

1. scott.db          scott.db          .
2. HR.db          HR.db          .
```

7. SQLite – ATTACH Database

Consider a case when you have multiple databases available and you want to use any one of them at a time. SQLite **ATTACH DATABASE** statement is used to select a particular database, and after this command, all SQLite statements will be executed under the attached database.

Syntax

Following is the basic syntax of SQLite ATTACH DATABASE statement.

```
ATTACH DATABASE 'DatabaseName' As 'Alias-Name';
```

The above command will also create a database in case the database is already not created, otherwise it will just attach database file name with logical database 'Alias-Name'.

Example

If you want to attach an existing database **testDB.db**, then ATTACH DATABASE statement would be as follows:

```
sqlite> ATTACH DATABASE 'testDB.db' as 'TEST';
```

Use SQLite **.database** command to display attached database.

```
sqlite> .database
seq  name          file
---  -
0    main           /home/sqlite/testDB.db
2    test           /home/sqlite/testDB.db
```

The database names **main** and **temp** are reserved for the primary database and database to hold temporary tables and other temporary data objects. Both of these database names exist for every database connection and should not be used for attachment, otherwise you will get the following warning message.

```
sqlite> ATTACH DATABASE 'testDB.db' as 'TEMP';
Error: database TEMP is already in use
sqlite> ATTACH DATABASE 'testDB.db' as 'main';
Error: database TEMP is already in use
```

```
( ) attach DB schema . alias가 'main',
'temp' DB schema .
```

8. SQLite – DETACH Database

SQLite **DETACH DATABASE** statement is used to detach and dissociate a named database from a database connection which was previously attached using **ATTACH** statement. If the same database file has been attached with multiple aliases, then **DETACH** command will disconnect only the given name and rest of the attachment will still continue. You cannot detach the **main** or **temp** databases.

If the database is an in-memory or temporary database, the database will be destroyed and the contents will be lost.

Syntax

Following is the basic syntax of SQLite **DETACH DATABASE 'Alias-Name'** statement.

```
DETACH DATABASE 'Alias-Name';
```

Here, 'Alias-Name' is the same alias, which you had used while attaching the database using **ATTACH** statement.

Example

Consider you have a database, which you created in the previous chapter and attached it with 'test' and 'currentDB' as we can see using **.database** command.

```
sqlite>.databases
```

seq	name	file
0	main	/home/sqlite/testDB.db
2	test	/home/sqlite/testDB.db
3	currentDB	/home/sqlite/testDB.db

db
(alias) attach
.

main db detach
?

Let's try to detach 'currentDB' from testDB.db using the following command.

```
sqlite> DETACH DATABASE 'currentDB';
```

Now, if you will check the current attachment, you will find that testDB.db is still connected with 'test' and 'main'.

(1) chinook.db, hr.db, school.db, scott.db (connection)
, DB schema
diagram .
(2) SQL
.
SELECT * FROM ;
DB DB
.
(3) DB .

9. SQLite – CREATE Table

DB testDB.db DB
testDB.db testDB.db .dump backup
(backup testDB.sql .) testDB.db

DB testDB.db
1. sqlite db db가
main
\$ sqlite3 testDB.db
2. sqlite DB attach DB가
sqlite> attach database 'testDB.db' as 'test'

Syntax

Following is the basic syntax of **CREATE TABLE statement**.

```
CREATE TABLE database_name.table_name(
    column1 datatype PRIMARY KEY(one or more columns),
    column2 datatype,
    column3 datatype,
    .....
    columnN datatype,
);
```

RDB

27 storage class, affinity type, SQL
data type . create table
SQL data type
SQLite가

CREATE TABLE is the keyword telling the database system to create a new table. The unique name or identifier for the table follows the CREATE TABLE statement. Optionally, you can specify *database_name* along with *table_name*.

Example

schema diagram
testDB schema diagram

```
sqlite> CREATE TABLE COMPANY(
    ID INT PRIMARY KEY NOT NULL,
    NAME TEXT NOT NULL,
    AGE INT NOT NULL,
    ADDRESS CHAR(50),
    SALARY REAL
);
```

(constraint)?

(constraint)?

Let us create one more table, which we will use in our exercises in subsequent chapters.

```
sqlite> CREATE TABLE DEPARTMENT(
    ID INT PRIMARY KEY NOT NULL,
    DEPT CHAR(50) NOT NULL,
    EMP_ID INT NOT NULL
);
```

emp_id int not null references company(id)

You can verify if your table has been created successfully using SQLite command **.tables** command, which will be used to list down all the tables in an attached database.

```
sqlite>.tables
COMPANY      DEPARTMENT
```

Here, you can see the COMPANY table twice because its showing COMPANY table for main database and test.COMPANY table for 'test' alias created for your testDB.db. You can get complete information about a table using the following SQLite **.schema** command.

```
sqlite>.schema COMPANY
CREATE TABLE COMPANY(
  ID INT PRIMARY KEY     NOT NULL,
  NAME           TEXT     NOT NULL,
  AGE            INT       NOT NULL,
  ADDRESS        CHAR(50),
  SALARY         REAL
);
```

drop table

```
create table company(
id int not null
, name text not null
, age int not null
, address char(50)
, salary real
, constraint com_pk primary key (id)
);
create table department(
id int not null
, dept char(50) not null
, emp_id int not null
, constraint dept_pk primary key(id)
, constraint dept_com_fk foreign key(emp_id) references company(id)
);
```

sqlite

```
sqlite> pragma foreign_keys;
sqlite> pragma foreign_keys=on;
sqlite> pragma foreign_keys=off;
```

10. SQLite – DROP Table

SQLite **DROP TABLE** statement is used to remove a table definition and all associated data, indexes, triggers, constraints, and permission specifications for that table.

You have to be careful while using this command because once a table is deleted then all the information available in the table would also be lost forever.

Syntax

Following is the basic syntax of DROP TABLE statement. You can optionally specify the database name along with table name as follows:

```
DROP TABLE database_name.table_name;
```

Example

Let us first verify COMPANY table and then we will delete it from the database.

```
sqlite>.tables
COMPANY      test.COMPANY
```

This means COMPANY table is available in the database, so let us drop it as follows:

```
sqlite>DROP TABLE COMPANY;
sqlite>
```

Now, if you try **.TABLES** command, then you will not find COMPANY table anymore.

```
sqlite>.tables
sqlite>
```

It shows nothing which means the table from your database has been dropped successfully.

() scott.db .

1. scott.db schema diagram
scott.db schema daigram

2. scott.db Schema diagram scott_twin.db . scott.db unicode

11. SQLite – INSERT Query

SQLite **INSERT INTO** Statement is used to add new rows of data into a table in the database.

Syntax

DB .

Following are the two basic syntaxes of INSERT INTO statement.

```
INSERT INTO TABLE_NAME [(column1, column2, column3,...columnN)]  
VALUES (value1, value2, value3,...valueN);
```

Here, column1, column2, ... columnN are the names of the columns in the table into which you want to insert data.

You may not need to specify the column(s) name in the SQLite query if you are adding values for all the columns of the table. However, make sure the same order as the columns in the table. The SQLite INSERT follows:

create table

```
INSERT INTO TABLE_NAME VALUES (value1,value2,value3,...valueN);
```

Example

Consider you already have created COMPANY table in your testDB.db as follows:

```
sqlite> CREATE TABLE COMPANY(  
    ID INT PRIMARY KEY     NOT NULL,  
    NAME           TEXT     NOT NULL,  
    AGE            INT       NOT NULL,  
    ADDRESS        CHAR(50),  
    SALARY         REAL  
);
```

Now, the following statements would create six records in COMPANY table.

```
INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
VALUES (1, 'Paul', 32, 'California', 20000.00 );

INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
VALUES (2, 'Allen', 25, 'Texas', 15000.00 );

INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
VALUES (3, 'Teddy', 23, 'Norway', 20000.00 );

INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
VALUES (4, 'Mark', 25, 'Rich-Mond ', 65000.00 );

INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
VALUES (5, 'David', 27, 'Texas', 85000.00 );

INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
VALUES (6, 'Kim', 22, 'South-Hall', 45000.00 );
```

You can create a record in COMPANY table using the second syntax as follows:

```
INSERT INTO COMPANY VALUES (7, 'James', 24, 'Houston', 10000.00 );
```

All the above statements would create the following records in COMPANY table. In the next chapter, you will learn how to display all these records from a table.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Populate One Table Using Another Table

You can populate data into a table through select statement over another table provided another table has a set of fields, which are required to populate the first table. Here is the syntax:

insert into , select
select select

```
INSERT INTO first_table_name [(column1, column2, ... columnN)]
SELECT column1, column2, ...columnN
FROM second_table_name
[WHERE condition];
```

() testDB.db schema diagram 가
mytestDB.db department .
가 . (.)

id	dept	emp_id
1	IT Billing	1
2	Engineerin	2
3	Finance	7

() chinook.db schema diagram 가 mychinook database .

가 가 "PSY 8th 4x2=8" MPEG audio
file K - pop 가 .
, , , 가 .

I LUV IT, 18900, 5510424,
New Faces, 19000, 7689012,

() mychinook.db SQL .

1. chinook.db 가 " 가 "
2. chinook.db 가 가?
3. (trot) 가?
4. 가 " 가 "

12. SQLite – SELECT Query

SQLite **SELECT** statement is used to fetch the data from a SQLite database table which returns data in the form of a result table. These result tables are also called **result sets**.

Syntax

Following is the basic syntax of SQLite SELECT statement.

```
SELECT column1, column2, columnN FROM table_name;
```

select . from , select
. select from .

```
SELECT * FROM table_name;
```

Example

Consider COMPANY table with the following records:

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following is an example to fetch and display all these records using SELECT statement. Here, the first three commands have been used to set a properly formatted output.

```
sqlite>.header on
sqlite>.mode column
sqlite> SELECT * FROM COMPANY;
```

Finally, you will get the following result.

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

If you want to fetch only selected fields of COMPANY table, then use the following query:

```
sqlite> SELECT ID, NAME, SALARY FROM COMPANY;
```

The above query will produce the following result.

ID	NAME	SALARY
1	Paul	20000.0
2	Allen	15000.0
3	Teddy	20000.0
4	Mark	65000.0
5	David	85000.0
6	Kim	45000.0
7	James	10000.0

Setting Output Column Width

```
sqlite> .mode column
sqlite> .width 10
```

```
sqlite> .width 10, 20, 10
sqlite> SELECT * FROM COMPANY;
```

The above **.width** command sets the first column width to 10, the second column width to 20 and the third column width to 10. Finally, the above SELECT statement will give the following result.

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Schema Information

meta data
SQLite가
DML

DQL

As all the **dot commands** are available at SQLite prompt, hence while programming with SQLite, you will use the following SELECT statement with **sqlite_master** table to list down all the tables created in your database.

```
sqlite> SELECT tbl_name FROM sqlite_master WHERE type = 'table';
```

Assuming you have only COMPANY table in your testDB.db, this will produce the following result.

```
tbl_name
-----
COMPANY
```

You can list down **complete information about COMPANY table** as follows:

```
sqlite> SELECT sql FROM sqlite_master WHERE type = 'table' AND tbl_name = 'COMPANY';
```

() department

() 1. northwind.db schema diagram
. Schema diagram

가

meta data

2. scott.db, schoo.db, chinook.db schema diagram

() sqlite_master

13. SQLite – Operators

What is an Operator in SQLite?

An operator is a reserved word or a character used primarily in an SQLite expression WHERE clause to perform operation(s), such as comparisons and arithmetic operations.

Operators are used to specify conditions in an SQLite statement and to serve as conjunctions for multiple conditions in a statement.

- Arithmetic operators
- Comparison operators
- Logical operators
- Bitwise operators

(expression) (), , , ,
, , . SQL
select (select), where ,
having 가 (condition) .

SQLite Arithmetic Operators

Assume variable **a** holds 10 and variable **b** holds 20, then SQLite arithmetic operators will be used as follows:

Operator	Description	Example
+	Addition - Adds values on either side of the operator	a + b will give 30
-	Subtraction - Subtracts the right hand operand from the left hand operand	a - b will give -10
*	Multiplication - Multiplies values on either side of the operator	a * b will give 200
/	Division - Divides the left hand operand by the right hand operand	b / a will give 2
%	Modulus - Divides the left hand operand by the right hand operand and returns the remainder	b % a will give 0

SQLite - Arithmetic Operators Example

Following are some simple examples showing the usage of SQLite Arithmetic Operators.

```
sqlite> .mode line ← mode
sqlite> select 10 + 20;
```

10 + 20 = 30

sqlite> select 10 - 20;

10 - 20 = -10

sqlite> select 10 * 20;

10 * 20 = 200

sqlite> select 10 / 5;

10 / 5 = 2

/

select 2./3;
select 2/3;

sqlite> select 12 % 5;

12 % 5 = 2

%

가

SQLite Comparison Operators

Assume variable **a** holds 10 and variable **b** holds 20, then SQLite comparison operators will be used as follows:

Operator	Description	Example
==	Checks if the values of two operands are equal or not, if yes then the condition becomes true.	(a == b) is not true.
=	Checks if the values of two operands are equal or not, if yes then the condition becomes true.	(a = b) is not true.
!=	Checks if the values of two operands are equal or not, if the values are not equal, then the condition becomes true.	(a != b) is true.
<>	Checks if the values of two operands are equal or not, if the values are not equal, then the condition becomes true.	(a <> b) is true.
>	Checks if the values of the left operand is greater than the value of the right operand, if yes then the condition becomes true.	(a > b) is not true.
<	Checks if the values of the left operand is less than the value of the right operand, if yes then the condition becomes true.	(a < b) is true.

>=	Checks if the value of the left operand is greater than or equal to the value of the right operand, if yes then the condition becomes true.	(a >= b) is not true.
<=	Checks if the value of the left operand is less than or equal to the value of the right operand, if yes then the condition becomes true.	(a <= b) is true.
!<	Checks if the value of the left operand is not less than the value of the right operand, if yes then the condition becomes true.	(a !< b) is false.
!>	Checks if the value of the left operand is not greater than the value of the right operand, if yes then the condition becomes true.	(a !> b) is true.

SQLite - Comparison Operators Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

```

select      : from
              where
              가
select      (
) , where

```

sqlite> SELECT * FROM COMPANY WHERE SALARY > 50000;				
ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

```
( ) select name, salary, salary + 100 from company where salary > 50000;
```

Following SELECT statement lists down all the records having SALARY equal to 20,000.00.

```
sqlite> SELECT * FROM COMPANY WHERE SALARY = 20000;
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
3	Teddy	23	Norway	20000.0

Following SELECT statement lists down all the records having SALARY not equal to 20,000.00.

```
sqlite> SELECT * FROM COMPANY WHERE SALARY != 20000;
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
2	Allen	25	Texas	15000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following SELECT statement lists down all the records having SALARY not equal to 20,000.00.

```
sqlite> SELECT * FROM COMPANY WHERE SALARY <> 20000;
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
2	Allen	25	Texas	15000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following SELECT statement lists down all the records having SALARY greater than or equal to 65,000.00.

```
sqlite> SELECT * FROM COMPANY WHERE SALARY >= 65000;
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

SQLite Logical Operators

Here is a list of all the logical operators available in SQLite.

Operator	Description
AND	The AND operator allows the existence of multiple conditions in a SQL statement's WHERE clause.
BETWEEN	The BETWEEN operator is used to search for values that are within a set of values, given the minimum value and the maximum value.
EXISTS	The EXISTS operator is used to search for the presence of a row in a specified table that meets a certain criteria.
IN	The IN operator is used to compare a value to a list of literal values that have been specified.
NOT IN	The negation of IN operator is used to compare a value to a list of literal values that have been specified.
LIKE	The LIKE operator is used to compare a value to similar values using wildcard operators.
GLOB	The GLOB operator is used to compare a value to similar values using wildcard operators. Also, GLOB is case sensitive, unlike LIKE.
NOT	The NOT operator reverses the meaning of the logical operator with which it is used. Example, NOT EXISTS , NOT BETWEEN , NOT IN , etc. This is a negate operator.
OR	The OR operator is used to combine multiple conditions in an SQL statement's WHERE clause.
IS NULL	The NULL operator is used to compare a value with a NULL value.
IS	The IS operator work like =
IS NOT	The IS operator work like !=
 	Adds two different strings and make a new one.
UNIQUE	The UNIQUE operator searches every row of a specified table for uniqueness (no duplicates).

SQLite - Logical Operators Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following are simple examples showing the usage of SQLite Logical Operators. Following SELECT statement lists down all the records where AGE is greater than or equal to 25 and salary is greater than or equal to 65000.00.

```
sqlite> SELECT * FROM COMPANY WHERE AGE >= 25 AND SALARY >= 65000;
```

ID	NAME	AGE	ADDRESS	SALARY
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

Following SELECT statement lists down all the records where AGE is greater than or equal to 25 **OR** salary is greater than or equal to 65000.00.

```
sqlite> SELECT * FROM COMPANY WHERE AGE >= 25 OR SALARY >= 65000;
```

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

Following SELECT statement lists down all the records where AGE is not NULL, which means all the records because none of the record has AGE equal to NULL.

```
sqlite> SELECT * FROM COMPANY WHERE AGE IS NOT NULL;
```

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0

3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following SELECT statement lists down all the records where NAME starts with 'Ki', does not matter what comes after 'Ki'.

```
sqlite> SELECT * FROM COMPANY WHERE NAME LIKE 'Ki%';
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
6	Kim	22	South-Hall	45000.0

Following SELECT statement lists down all the records where NAME starts with 'Ki', does not matter what comes after 'Ki'.

```
sqlite> SELECT * FROM COMPANY WHERE NAME GLOB 'Ki*';
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
6	Kim	22	South-Hall	45000.0

Following SELECT statement lists down all the records where AGE value is either 25 or 27.

```
sqlite> SELECT * FROM COMPANY WHERE AGE IN ( 25, 27 );
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
2	Allen	25	Texas	15000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

Following SELECT statement lists down all the records where AGE value is neither 25 nor 27.

```
sqlite> SELECT * FROM COMPANY WHERE AGE NOT IN ( 25, 27 );
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
3	Teddy	23	Norway	20000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following SELECT statement lists down all the records where AGE value is in BETWEEN 25 AND 27.

```
sqlite> SELECT * FROM COMPANY WHERE AGE BETWEEN 25 AND 27;
```

ID	NAME	AGE	ADDRESS	SALARY
2	Allen	25	Texas	15000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

Following SELECT statement makes use of SQL sub-query where sub-query finds all the records with AGE field having SALARY > 65000 and later WHERE clause is being used along with EXISTS operator to list down all the records where AGE from the outside query exists in the result returned by the sub-query.

```
sqlite> SELECT AGE FROM COMPANY
```

```
WHERE EXISTS (SELECT AGE FROM COMPANY WHERE SALARY > 65000);
```

AGE

```
-----
32
25
23
25
27
22
24
```

Following SELECT statement makes use of SQL sub-query where subquery finds all the records with AGE field having SALARY > 65000 and later WHERE clause is being used along with > operator to list down all the records where AGE from the outside query is greater than the age in the result returned by the sub-query.

```
sqlite> SELECT * FROM COMPANY
```

```
WHERE AGE > (SELECT AGE FROM COMPANY WHERE SALARY > 65000);
```

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	California	20000.0

SQLite Bitwise Operators

Bitwise operator works on bits and performs bit-by-bit operation. Following is the truth table for **&** and **|**.

p	q	p & q	p q
0	0	0	0
0	1	0	1
1	1	1	1
1	0	0	1

Assume if **A** = 60 and **B** = 13, then in binary format, they will be as follows:

A = 0011 1100

B = 0000 1101

A&B = 0000 1100

A|B = 0011 1101

~A = 1100 0011

The Bitwise operators supported by SQLite language are listed in the following table. Assume variable **A** holds 60 and variable **B** holds 13, then:

Operator	Description	Example
&	Binary AND Operator copies a bit to the result, if it exists in both operands.	(A & B) will give 12 which is 0000 1100
 	Binary OR Operator copies a bit, if it exists in either operand.	(A B) will give 61 which is 0011 1101
~	Binary Ones Complement Operator is unary and has the effect of 'flipping' bits.	(~A) will give -61 which is 1100 0011 in 2's complement form due to a signed binary number
<<	Binary Left Shift Operator. The left operands value is moved left by the number of bits specified by the right operand.	A << 2 will give 240 which is 1111 0000

>>	Binary Right Shift Operator. The left operands value is moved right by the number of bits specified by the right operand.	A >> 2 will give 15 which is 0000 1111
----	---------------------------------------------------------------------------------------------------------------------------	----------------------------------------

SQLite - Bitwise Operators Example

Following are simple examples showing the usage of SQLite Bitwise Operators.

```

sqlite> .mode line
sqlite> select 60 | 13;
60 | 13 = 61

sqlite> select 60 & 13;
60 & 13 = 12

sqlite> select 60 ^ 13;
10 * 20 = 200

sqlite> select (~60);
(~60) = -61

sqlite> select (60 << 2);
(60 << 2) = 240

sqlite> select (60 >> 2);
(60 >> 2) = 15

```

14. SQLite – Expressions

An expression is a combination of one or more values, operators, and SQL functions that evaluate to a value.

SQL Expressions are like formulas and they are written in query language. You can also use to query the database for a specific set of data.

Syntax

Consider the basic syntax of the SELECT statement as follows:

```
SELECT column1, column2, columnN
FROM table_name
WHERE [CONDITION | EXPRESSION];
```

Following are the different types of SQLite expressions.

SQLite - Boolean Expression

SQLite Boolean Expressions fetch the data on the basis of matching single value. Following is the syntax:

```
SELECT column1, column2, columnN
FROM table_name
WHERE SINGLE VALUE MATCHING EXPRESSION;
```

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following is a simple example showing the usage of SQLite Boolean Expressions.

```
sqlite> SELECT * FROM COMPANY WHERE SALARY = 10000;
ID          NAME      AGE      ADDRESS      SALARY
-----
```

testDB.db

testDB.db

가

```
select age+1, salary * 1.1 from company;
```

가

```
select age+1 as age, salary * 1.1 as salary from company;
```

```
SELECT numerical_expression as OPERATION_NAME
[FROM table_name WHERE CONDITION] ;
```

Here, numerical_expression is used for mathematical expression or any formula. Following is a simple example showing the usage of SQLite Numeric Expression.

```
sqlite> SELECT (15 + 6) AS ADDITION
ADDITION = 21
```

```
select (15+6) as addition from company;
```

There are several built-in functions such as **avg()**, **sum()**, **count()**, etc., to perform what is known as **aggregate data calculations** against a table or a specific table column.

```
sqlite> SELECT COUNT(*) AS "RECORDS" FROM COMPANY;
RECORDS = 7
```

SQLite - Date Expression

Date Expression returns the current system date and time values. These expressions are used in various data manipulations.

```
sqlite> SELECT CURRENT_TIMESTAMP;
CURRENT_TIMESTAMP = 2013-03-17 10:43:35
```

```
select current_date;
select current_time;
```

15. SQLite – WHERE Clause

The SQLite **WHERE** clause is used to specify a condition while fetching the data from one table or multiple tables.

If the given condition is satisfied, means true, then it returns the specific value from the table. You will have to use WHERE clause to filter the records and fetch only the necessary records.

The WHERE clause not only is used in SELECT statement, but it is also used in UPDATE, DELETE statement, etc., which will be covered in subsequent chapters.

Syntax

Following is the basic syntax of SQLite SELECT statement with WHERE clause.

```
SELECT column1, column2, columnN
FROM table_name
WHERE [condition]
```

가 (boolean expression)

```
select : from ,
where ,
가 .
select (
, where .
```

1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following is a simple example showing the usage of SQLite Logical Operators. Following SELECT statement lists down all the records where AGE is greater than or equal to 25 **AND** salary is greater than or equal to 65000.00.

```
sqlite> SELECT * FROM COMPANY WHERE AGE >= 25 AND SALARY >= 65000;
```

ID	NAME	AGE	ADDRESS	SALARY
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

Following SELECT statement lists down all the records where AGE is greater than or equal to 25 **OR** salary is greater than or equal to 65000.00.

```
sqlite> SELECT * FROM COMPANY WHERE AGE >= 25 OR SALARY >= 65000;
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

Following SELECT statement lists down all the records where AGE is not NULL, which means all the records because none of the record has AGE equal to NULL.

```
sqlite> SELECT * FROM COMPANY WHERE AGE IS NOT NULL;
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following SELECT statement lists down all the records where NAME starts with 'Ki', does not matter what comes after 'Ki'.

```
sqlite> SELECT * FROM COMPANY WHERE NAME LIKE 'Ki%';
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
6	Kim	22	South-Hall	45000.0

%, _

) '_park%'

Following SELECT statement lists down all the records where NAME starts with 'Ki', does not matter what comes after 'Ki'.

```
sqlite> SELECT * FROM COMPANY WHERE NAME GLOB 'Ki*';
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
6	Kim	22	South-Hall	45000.0

*, ?, []

) '?at*Letter[0 - 9]'

Following SELECT statement lists down all the records where AGE value is either 25 or 27.

```
sqlite> SELECT * FROM COMPANY WHERE AGE IN ( 25, 27 );
```

ID	NAME	AGE	ADDRESS	SALARY
2	Allen	25	Texas	15000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

Following SELECT statement lists down all the records where AGE value is neither 25 nor 27.

```
sqlite> SELECT * FROM COMPANY WHERE AGE NOT IN ( 25, 27 );
```

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	California	20000.0
3	Teddy	23	Norway	20000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following SELECT statement lists down all the records where AGE value is in BETWEEN 25 AND 27.

```
sqlite> SELECT * FROM COMPANY WHERE AGE BETWEEN 25 AND 27;
```

ID	NAME	AGE	ADDRESS	SALARY
2	Allen	25	Texas	15000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

Following SELECT statement makes use of SQL sub-query where sub-query finds all the

select (query) , select select
 . select (subquery) (inner query)
 . (main query) (outer
 query)

```
sqlite> SELECT AGE FROM COMPANY
```

```
WHERE EXISTS (SELECT AGE FROM COMPANY WHERE SALARY > 65000);
```

AGE

AGE
32
25
23
25
27

exists , select
 . exists FALSE,
 TRUE
 If the subquery returns at least one row, the result is true.
 Otherwise, the EXISTS operator returns false or NULL.

22

24

Following SELECT statement makes use of SQL sub-query, where sub-query finds all the records with AGE field having SALARY > 65000 and later WHERE clause is being used along with > operator to list down all the records where AGE from the outside query is greater than the age in the result returned by the sub-query.

```
sqlite> SELECT * FROM COMPANY
```

```
WHERE AGE > (SELECT AGE FROM COMPANY WHERE SALARY > 65000);
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0

16. SQLite – AND & OR Operators

The SQLite **AND** & **OR** operators are used to compile multiple conditions to narrow down the selected data in an SQLite statement. These two operators are called **conjunctive operators**.

These operators provide a means to make multiple comparisons with different operators in the same SQLite statement.

The AND Operator

The **AND** operator allows the existence of multiple conditions in a SQLite statement's WHERE clause. While using AND operator, complete condition will be assumed true when all the conditions are true. For example, [condition1] AND [condition2] will be true only when both condition1 and condition2 are true.

Syntax

Following is the basic syntax of AND operator with WHERE clause.

```
SELECT column1, column2, columnN
FROM table_name
WHERE [condition1] AND [condition2]...AND [conditionN];
```

You can combine **N** number of conditions using AND operator. For an action to be taken by the SQLite statement, whether it be a transaction or query, all conditions separated by the AND must be TRUE.

Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following SELECT statement lists down all the records where AGE is greater than or equal to 25 **AND** salary is greater than or equal to 65000.00.

```
sqlite> SELECT * FROM COMPANY WHERE AGE >= 25 AND SALARY >= 65000;
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

The OR Operator

The OR operator is also used to combine multiple conditions in a SQLite statement's WHERE clause. While using OR operator, complete condition will be assumed true when at least any of the conditions is true. For example, [condition1] OR [condition2] will be true if either condition1 or condition2 is true.

Syntax

Following is the basic syntax of OR operator with WHERE clause.

```
SELECT column1, column2, columnN
FROM table_name
WHERE [condition1] OR [condition2]...OR [conditionN]
```

You can combine **N** number of conditions using OR operator. For an action to be taken by the SQLite statement, whether it be a transaction or query, only any **ONE** of the conditions separated by the OR must be TRUE.

Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following SELECT statement lists down all the records where AGE is greater than or equal to 25 **OR** salary is greater than or equal to 65000.00.

```
sqlite> SELECT * FROM COMPANY WHERE AGE >= 25 OR SALARY >= 65000;
```

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

() scott.db

1. scott.db schema diagram DB
2. 가 7521, 7654, 7844 ()
3. emp mgr 가 mgr null
4. 가 1500 , ,
5. scott , ,
6. emp hiredate 'yyyy - mm - dd'
7. emp deptno job
8. 10
9. 가 2000 3000 , ,
- 10.
11. '1987 - 01 - 01' '1987 - 12 - 31'

() HR.db SQL

1. (job) (job_id)가 9 , , job_id
2. job_id가 9
3. Programmer , , job_id
4. Jennifer Whalen
5. Jennifer Whalen 가
6. Jennifer Whalen 가 가 가?
7. Jennifer Whalen 가?
8. 1990
- 9.
10. Seattle 가?
11. Seattle
12. Seattle 가

17. SQLite – UPDATE Query

DB insert, update, delete
DB가
, 가,
(log)
가

Following is the basic syntax of UPDATE query with WHERE clause.

```
UPDATE table_name
SET column1 = value1, column2 = value2..., columnN = valueN
WHERE [condition];
```

You can combine **N** number of conditions using AND or OR operators.

Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following is an example, which will update ADDRESS for a customer whose ID is 6.

```
sqlite> UPDATE COMPANY SET ADDRESS = 'Texas' WHERE ID = 6;
```

Now, COMPANY table will have the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

6	Kim	22	Texas	45000.0
7	James	24	Houston	10000.0

If you want to modify all ADDRESS and SALARY column values in COMPANY table, you do not need to use WHERE clause and UPDATE query will be as follows:

```
sqlite> UPDATE COMPANY SET ADDRESS = 'Texas', SALARY = 20000.00;
```

Now, COMPANY table will have the following records.

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	Texas	20000.0
2	Allen	25	Texas	20000.0
3	Teddy	23	Texas	20000.0
4	Mark	25	Texas	20000.0
5	David	27	Texas	20000.0
6	Kim	22	Texas	20000.0

select . create table ... as select SQL .

create table test.company_copy as select * from test.company;

() scott.db scott attach SQL .

1. emp dept emp01, dept01 .
 emp01 dept01 .
 2. 10 30 .
 3. 가 3000 10% .
 4. 가 10000 5000 .
 5. scott 20 MANAGER . (...)
 6. scott , 50 , 4000 .
 7. 10 .
 8. 10% .
 9. emp01 .

() HR.db SQL .

1. Kimberly Grant가 가?
 2. Kimberly Grant가 Alexander Hunold가 IT
 SQL 가?

18. SQLite – DELETE Query

SQLite **DELETE** Query is used to delete the existing records from a table. You can use WHERE clause with DELETE query to delete the selected rows, otherwise all the records would be deleted.

Syntax

Following is the basic syntax of DELETE query with WHERE clause.

```
DELETE FROM table_name  
WHERE [condition];
```

You can combine **N** number of conditions using AND or OR operators.

Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following is an example, which will DELETE a customer whose ID is 7.

```
sqlite> DELETE FROM COMPANY WHERE ID = 7;
```

Now COMPANY table will have the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0

If you want to DELETE all the records from COMPANY table, you do not need to use WHERE clause with DELETE query, which will be as follows:

```
sqlite> DELETE FROM COMPANY;
```

Now, COMPANY table does not have any record as all the records have been deleted by DELETE statement.

```
( ) scott.db scott attach SQL
.
1. emp emp01 , emp01
.
2. 10 . (
.
. 가
.)
3. emp01 .
```

```
( ) chinook.db mychinook.db .
1. K - pop 가?
( 가 .)
```

```
delete where
. delete where 가 select
.
```

19. SQLite – LIKE Clause

SQLite **LIKE** operator is used to match text values against a pattern using wildcards. If the search expression can be matched to the pattern expression, the LIKE operator will return true, which is 1. There are two wildcards used in conjunction with the LIKE operator:

- The percent sign (%) **like**
- The underscore (_) **.**

The percent sign represents zero, one, or multiple numbers or characters. The underscore represents a single number or character. These symbols can be used in combinations.

Syntax

Following is the basic syntax of % and _.

```
SELECT FROM table_name
WHERE column LIKE 'XXXX%'

or

SELECT FROM table_name
WHERE column LIKE '%XXXX%'

or

SELECT FROM table_name
WHERE column LIKE 'XXXX_'

or

SELECT FROM table_name
WHERE column LIKE '_XXXX'

or

SELECT FROM table_name
WHERE column LIKE '_XXXX_'
```


You can combine **N** number of conditions using AND or OR operators. Here, **XXXX** could be any numeric or string value.

like

SQLite
DBMS

Statement	Description
WHERE SALARY LIKE '200%'	Finds any values that start with 200
WHERE SALARY LIKE '%200%'	Finds any values that have 200 in any position
WHERE SALARY LIKE '_00%'	Finds any values that have 00 in the second and third positions
WHERE SALARY LIKE '2_%_ %'	Finds any values that start with 2 and are at least 3 characters in length
WHERE SALARY LIKE '%2'	Finds any values that end with 2
WHERE SALARY LIKE '_2%3'	Finds any values that has a 2 in the second position and ends with a 3
WHERE SALARY LIKE '2___3'	Finds any values in a five-digit number that starts with 2 and ends with 3

Let us take a real example, consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23		
4	Mark	25		
5	David	27		
6	Kim	22		
7	James	24		

Following is an example, which will display all the records from COMPANY table where AGE starts with 2.

```
sqlite> SELECT * FROM COMPANY WHERE AGE LIKE '2%';
```

This will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following is an example, which will display all the records from COMPANY table where ADDRESS will have a hyphen (-) inside the text.

```
sqlite> SELECT * FROM COMPANY WHERE ADDRESS LIKE '%-%';
```

This will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
4	Mark	25	Rich-Mond	65000.0
6	Kim	22	South-Hall	45000.0

20. SQLite – GLOB Clause

DBMS가 glob	.	like
oracle	.	(regular expression)
regexp_like(,)	.	
가	.	text mining

SQLite **GLOB** operator is used to match only text values against a pattern using wildcards.

If the search expression can be matched to the pattern expression, the GLOB operator will return true, which is 1. Unlike LIKE operator, GLOB is case sensitive and it follows syntax of UNIX for specifying THE following wildcards.

- The asterisk sign (*)
- The question mark (?)

sqlite like glob :

glob

glob 가

*:

?:

[abcd]: a, b, c, d

[a - t]: a t

[^abcd]: a, b, c, d,

() select ... where filename glob '*[_.,:;! ? - () { } < >]OK';

or

```
SELECT FROM table_name
WHERE column GLOB '*XXXX*'
```

or

```
SELECT FROM table_name
WHERE column GLOB 'XXXX?'
```

or

```
SELECT FROM table_name
WHERE column GLOB '?XXXX'
```

or

```
SELECT FROM table_name
WHERE column GLOB '?XXXX?'
```

or

```
SELECT FROM table_name
WHERE column GLOB '????'
```

You can combine **N** number of conditions using AND or OR operators. Here, XXXX could be any numeric or string value.

Example

Following table lists a number of examples showing WHERE part having different LIKE clause with '*' and '?' operators.

Statement	Description
WHERE SALARY GLOB '200*'	Finds any values that start with 200
WHERE SALARY GLOB '*200*'	Finds any values that have 200 in any position
WHERE SALARY GLOB '?00*'	Finds any values that have 00 in the second and third positions
WHERE SALARY GLOB '2??'	Finds any values that start with 2 and are at least 3 characters in length
WHERE SALARY GLOB '*2'	Finds any values that end with 2
WHERE SALARY GLOB '?2*3'	Finds any values that have a 2 in the second position and end with a 3
WHERE SALARY GLOB '2???3'	Finds any values in a five-digit number that start with 2 and end with 3

Let us take a real example, consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0

7	James	24	Houston	10000.0
---	-------	----	---------	---------

Following is an example, which will display all the records from COMPANY table, where AGE starts with 2.

```
sqlite> SELECT * FROM COMPANY WHERE AGE GLOB '2*';
```

This will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following is an example, which will display all the records from COMPANY table where ADDRESS will have a hyphen (-) inside the text.

```
sqlite> SELECT * FROM COMPANY WHERE ADDRESS GLOB '*-*';
```

This will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
4	Mark	25	Rich-Mond	65000.0
6	Kim	22	South-Hall	45000.0

()	scott.db	SQL	.
1.	J	.	.	.
2.	1	csv	EXCEL	.
3.	K가	.	.	.
4.	K	.	.	.
5.	A가	.	.	.

()	chinookdb	SQL	.
1.
2.	(media type)가 MPEG - 4	id	.	.
3.	Man	.	.	.
4.	Man	.	.	.
5.	2 - 4	가 ere	.	.
6.	가	.	.	.
7.	가	.	.	.

21. SQLite – LIMIT Clause

limit select .

Syntax

Following is the basic syntax of SELECT statement with LIMIT clause.

```
SELECT column1, column2, columnN
FROM table_name
LIMIT [no of rows]
```

Following is the syntax of LIMIT clause when it is used along with OFFSET clause.

```
SELECT column1, column2, columnN
FROM table_name
LIMIT [no of rows] OFFSET [row num]
```

SQLite engine will return rows starting from the next row to the given OFFSET as shown below in the last example.

Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following is an example, which limits the row in the table according to the number of rows you want to fetch from table.

```
sqlite> SELECT * FROM COMPANY LIMIT 6;
```

This will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0

However in certain situations, you may need to pick up a set of records from a particular offset. Here is an example, which picks up 3 records starting from the 3rd position.

```
sqlite> SELECT * FROM COMPANY LIMIT 3 OFFSET 2;
```

This will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

22. SQLite – ORDER BY Clause

order by

. select 가 .

SQLite **ORDER BY** clause is used to sort the data in an ascending or descending order, based on one or more columns.

Syntax

Following is the basic syntax of ORDER BY clause.

```
SELECT column-list  
FROM table_name  
[WHERE condition]  
[ORDER BY column1, column2, .. columnN] [ASC | DESC];
```

select

You can use more than one column in the ORDER BY clause. **Make sure whatever column you are using to sort, that column should be available in the column-list.**

Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following is an example, which will sort the result in descending order by SALARY.

```
sqlite> SELECT * FROM COMPANY ORDER BY SALARY ASC;
```


This will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
7	James	24	Houston	10000.0
2	Allen	25	Texas	15000.0
1	Paul	32	California	20000.0
3	Teddy	23	Norway	20000.0
6	Kim	22	South-Hall	45000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

Following is an example, which will sort the result in descending order by NAME and SALARY.

```
sqlite> SELECT * FROM COMPANY ORDER BY NAME, SALARY ASC;
```

This will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
2	Allen	25	Texas	15000.0
5	David	27	Texas	85000.0
7	James	24	Houston	10000.0
6	Kim	22	South-Hall	45000.0
4	Mark	25	Rich-Mond	65000.0
1	Paul	32	California	20000.0
3	Teddy	23	Norway	20000.0

Following is an example, which will sort the result in descending order by NAME.

```
sqlite> SELECT * FROM COMPANY ORDER BY NAME DESC;
```

This will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
3	Teddy	23	Norway	20000.0
1	Paul	32	California	20000.0
4	Mark	25	Rich-Mond	65000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0
5	David	27	Texas	85000.0
2	Allen	25	Texas	15000.0

```
( ) chinook.db SQL .
1. , ,
2. .
```

23. SQLite – GROUP BY Clause

GROUP BY

```
select
    (aggregate function) sum(), avg(), count(), max(), min(),
    group_concat(),
    group_concat()
group by
group by where , order by
```

```
SELECT column-list
FROM table_name
WHERE [ conditions ]
GROUP BY column1, column2....columnN
ORDER BY column1, column2....columnN
```

You can use more than one column in the GROUP BY clause. Make sure whatever column you are using to group, that column should be available in the column-list.

Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

If you want to know the total amount of salary on each customer, then GROUP BY query will be as follows:

```
sqlite> SELECT NAME, SUM(SALARY) FROM COMPANY GROUP BY NAME;
```

This will produce following result.

NAME	SUM(SALARY)
-----	-----
Allen	15000.0
David	85000.0
James	10000.0
Kim	45000.0
Mark	65000.0
Paul	20000.0
Teddy	20000.0

Now, let us create three more records in COMPANY table using the following INSERT statements.

```
INSERT INTO COMPANY VALUES (8, 'Paul', 24, 'Houston', 20000.00 );
INSERT INTO COMPANY VALUES (9, 'James', 44, 'Norway', 5000.00 );
INSERT INTO COMPANY VALUES (10, 'James', 45, 'Texas', 5000.00 );
```

Now, our table has the following records with duplicate names.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0
8	Paul	24	Houston	20000.0
9	James	44	Norway	5000.0
10	James	45	Texas	5000.0

Again, let us use the same statement to group-by all the records using NAME column as follows:

```
sqlite> SELECT NAME, SUM(SALARY) FROM COMPANY GROUP BY NAME ORDER BY NAME;
```

This will produce the following result.

NAME	SUM(SALARY)
-----	-----
Allen	15000
David	85000
James	20000
Kim	45000
Mark	65000
Paul	40000
Teddy	20000

Let us use ORDER BY clause along with GROUP BY clause as follows:

```
sqlite> SELECT NAME, SUM(SALARY)
        FROM COMPANY GROUP BY NAME ORDER BY NAME DESC;
```

This will produce the following result.

NAME	SUM(SALARY)
-----	-----
Teddy	20000
Paul	40000
Mark	65000
Kim	45000
James	20000
David	85000
Allen	15000

```
( ) scott.db select .
1. .
2. .
3. (job) 가 가?
4. 가?
5. ?
6. 가?
7. , , .
8. 가 가
. ( ?)
```

```
( ) chinook.db
1. track , track , 가 , 가
.
```

```
( ) northwind.sql northwind.db
. ($ sqlite3 northwind.db < northwind.sql)
1. , , ,
```

24. SQLite – HAVING Clause

having group by . group by
 having
 . having group by
 . order by order by .

The WHERE clause places conditions on the selected columns, whereas the HAVING clause places conditions on groups created by GROUP BY clause.

Syntax

Following is the position of HAVING clause in a SELECT query.

```
SELECT
FROM
WHERE
GROUP BY
HAVING
ORDER BY
```

HAVING clause must follow GROUP BY clause in a query and must also precede ORDER BY clause, if used. Following is the syntax of the SELECT statement, including HAVING clause.

```
SELECT column1, column2
FROM table1, table2
WHERE [ conditions ]
GROUP BY column1, column2
HAVING [ conditions ]
ORDER BY column1, column2
```

from 2
join .

Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

70

8	Paul	24	Houston	20000.0
9	James	44	Norway	5000.0
10	James	45	Texas	5000.0

Following is the example, which will display the record for which the name count is less than 2.

```
sqlite > SELECT * FROM COMPANY GROUP BY name HAVING count(name) < 2;
```

This will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
2	Allen	25	Texas	15000
5	David	27	Texas	85000
6	Kim	22	South-Hall	45000
4	Mark	25	Rich-Mond	65000
3	Teddy	23	Norway	20000

Following is the example, which will display the record for which the name count is greater than 2.

```
sqlite > SELECT * FROM COMPANY GROUP BY name HAVING count(name) > 2;
```

This will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
10	James	45	Texas	5000

```
( ) scott.db
1. 가 2000
7. 가 2900
```

```
( ) chinook.db
1. 5 가
2. 100 track track
```

25. SQLite – DISTINCT Keyword

SQLite **DISTINCT** keyword is used in conjunction with SELECT statement to eliminate all the duplicate records and fetch only the unique records.

There may be a situation when you have multiple duplicate records in a table. While fetching such records, it makes more sense to fetch only unique records instead of fetching duplicate records.

Syntax

Following is the basic syntax of DISTINCT keyword to eliminate duplicate records.

```
SELECT DISTINCT column1, column2,.....columnN
FROM table_name
WHERE [condition]
```

Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0
8	Paul	24	Houston	20000.0
9	James	44	Norway	5000.0
10	James	45	Texas	5000.0

First, let us see how the following SELECT query returns duplicate salary records.

```
sqlite> SELECT name FROM COMPANY;
```

This will produce the following result.

```
NAME
-----
Paul
Allen
Teddy
Mark
David
Kim
James
Paul
James
James
```

Now, let us use **DISTINCT** keyword with the above SELECT query and see the result.

```
sqlite> SELECT DISTINCT name FROM COMPANY;
```

This will produce the following result, where there is no duplicate entry.

```
NAME
-----
Paul
Allen
Teddy
Mark
David
Kim
James
```

```
( ) scott.db
```

```
1.
2.      ?      .      ?
      ?      가      ?
```

```
( ) northwind.db
```

```
1.
2.      .
```


Advanced SQLite

26. SQLite – PRAGMA

SQLite **PRAGMA** command is a special command to be used to control various environmental variables and state flags within the SQLite environment. A PRAGMA value can be read and it can also be set based on the requirements.

Syntax

To query the current PRAGMA value, just provide the name of the pragma.

```
PRAGMA pragma_name;
```

To set a new value for PRAGMA, use the following syntax.

```
PRAGMA pragma_name = value;
```

The set mode can be either the name or the integer equivalent but the returned value will always be an integer.

auto_vacuum Pragma

The **auto_vacuum** pragma gets or sets the auto-vacuum mode. Following is the simple syntax.

```
PRAGMA [database.]auto_vacuum;  
PRAGMA [database.]auto_vacuum = mode;
```

Where **mode** can be any of the following:

Pragma Value	Description
0 or NONE	Auto-vacuum is disabled. This is the default mode which means that a database file will never shrink in size unless it is manually vacuumed using the VACUUM command.
1 or FULL	Auto-vacuum is enabled and fully automatic which allows a database file to shrink as data is removed from the database.
2 or INCREMENTAL	Auto-vacuum is enabled but must be manually activated. In this mode, the reference data is maintained, but free pages are simply put on the free list. These pages can be recovered using the incremental_vacuum pragma any time.

--	--

cache_size Pragma

The **cache_size** pragma can get or temporarily set the maximum size of the in-memory page cache. Following is the simple syntax.

```
PRAGMA [database.]cache_size;  
PRAGMA [database.]cache_size = pages;
```

The **pages** value represents the number of pages in the cache. The built-in page cache has a default size of 2,000 pages and a minimum size of 10 pages.

case_sensitive_like Pragma

The **case_sensitive_like** pragma controls the case-sensitivity of the built-in LIKE expression. By default, this pragma is false which means that the built-in LIKE operator ignores the letter case. Following is the simple syntax.

```
PRAGMA case_sensitive_like = [true|false];
```

There is no way to query for the current state of this pragma.

count_changes Pragma

count_changes pragma gets or sets the return value of data manipulation statements such as INSERT, UPDATE and DELETE. Following is the simple syntax.

```
PRAGMA count_changes;  
PRAGMA count_changes = [true|false];
```

By default, this pragma is false and these statements do not return anything. If set to true, each of the mentioned statement will return a one-column, one-row table consisting of a single integer value, indicating impacted rows by the operation.

database_list Pragma

The **database_list** pragma will be used to list down all the databases attached. Following is the simple syntax.

```
PRAGMA database_list;
```

This pragma will return a three-column table with one row per open or attached database giving database sequence number, its name and the file associated.

encoding Pragma

The **encoding** pragma controls how strings are encoded and stored in a database file. Following is the simple syntax.

```
PRAGMA encoding;
```

```
PRAGMA encoding = format;
```

The format value can be one of **UTF-8**, **UTF-16le**, or **UTF-16be**.

freelist_count Pragma

The **freelist_count** pragma returns a single integer indicating how many database pages are currently marked as free and available. Following is the simple syntax.

```
PRAGMA [database.]freelist_count;
```

The format value can be one of **UTF-8**, **UTF-16le**, or **UTF-16be**.

index_info Pragma

The **index_info** pragma returns information about a database index. Following is the simple syntax.

```
PRAGMA [database.]index_info( index_name );
```

The result set will contain one row for each column contained in the index giving column sequence, column index within table and column name.

index_list Pragma

index_list pragma lists all of the indexes associated with a table. Following is the simple syntax.

```
PRAGMA [database.]index_list( table_name );
```

The result set will contain one row for each index giving index sequence, index name and flag indicating whether the index is unique or not.

journal_mode Pragma

The **journal_mode** pragma gets or sets the journal mode which controls how the journal file is stored and processed. Following is the simple syntax.

```
PRAGMA journal_mode;
PRAGMA journal_mode = mode;
PRAGMA database.journal_mode;
PRAGMA database.journal_mode = mode;
```

There are five supported journal modes as listed in the following table.

Pragma Value	Description
DELETE	This is the default mode. Here at the conclusion of a transaction, the journal file is deleted.

TRUNCATE	The journal file is truncated to a length of zero bytes.
PERSIST	The journal file is left in place, but the header is overwritten to indicate the journal is no longer valid.
MEMORY	The journal record is held in memory, rather than on disk.
OFF	No journal record is kept.

max_page_count Pragma

The **max_page_count** pragma gets or sets the maximum allowed page count for a database. Following is the simple syntax.

```
PRAGMA [database.]max_page_count;
PRAGMA [database.]max_page_count = max_page;
```

The default value is 1,073,741,823 which is one giga-page, which means if the default is 1 KB page size, this allows databases to grow up to one terabyte.

page_count Pragma

The **page_count** pragma returns the current number of pages in the database. Following is the simple syntax.

```
PRAGMA [database.]page_count;
```

The size of the database file should be `page_count * page_size`.

page_size Pragma

The **page_size** pragma gets or sets the size of the database pages. Following is the simple syntax.

```
PRAGMA [database.]page_size;
PRAGMA [database.]page_size = bytes;
```

By default, the allowed sizes are 512, 1024, 2048, 4096, 8192, 16384, and 32768 bytes. The only way to alter the page size on an existing database is to set the page size and then immediately **VACUUM** the database.

parser_trace Pragma

The **parser_trace** pragma controls printing the debugging state as it parses SQL commands. Following is the simple syntax.

```
PRAGMA parser_trace = [true|false];
```

By default, it is set to false but when enabled by setting it to true, the SQL parser will print its state as it parses SQL commands.

recursive_triggers Pragma

The **recursive_triggers** pragma gets or sets the recursive trigger functionality. If recursive triggers are not enabled, a trigger action will not fire another trigger. Following is the simple syntax.

```
PRAGMA recursive_triggers;  
PRAGMA recursive_triggers = [true|false];
```

schema_version Pragma

The **schema_version** pragma gets or sets the schema version value that is stored in the database header. Following is the simple syntax.

```
PRAGMA [database.]schema_version;  
PRAGMA [database.]schema_version = number;
```

This is a 32-bit signed integer value that keeps track of schema changes. Whenever a schema-altering command is executed (like, CREATE... or DROP...), this value is incremented.

secure_delete Pragma

The **secure_delete** pragma is used to control how the content is deleted from the database. Following is the simple syntax.

```
PRAGMA secure_delete;  
PRAGMA secure_delete = [true|false];  
PRAGMA database.secure_delete;  
PRAGMA database.secure_delete = [true|false];
```

The default value for the secure delete flag is normally off, but this can be changed with the SQLITE_SECURE_DELETE build option.

sql_trace Pragma

The **sql_trace** pragma is used to dump SQL trace results to the screen. Following is the simple syntax.

```
PRAGMA sql_trace;  
PRAGMA sql_trace = [true|false];
```

SQLite must be compiled with the SQLITE_DEBUG directive for this pragma to be included.

synchronous Pragma

The **synchronous** pragma gets or sets the current disk synchronization mode, which controls how aggressively SQLite will write data all the way out to physical storage. Following is the simple syntax.

```
PRAGMA [database.]synchronous;
PRAGMA [database.]synchronous = mode;
```

SQLite supports the following synchronization modes as listed in the table.

Pragma Value	Description
0 or OFF	No syncs at all
1 or NORMAL	Sync after each sequence of critical disk operations
2 or FULL	Sync after each critical disk operation

temp_store Pragma

The **temp_store** pragma gets or sets the storage mode used by temporary database files. Following is the simple syntax.

```
PRAGMA temp_store;
PRAGMA temp_store = mode;
```

SQLite supports the following storage modes.

Pragma Value	Description
0 or DEFAULT	Use compile-time default. Normally FILE.
1 or FILE	Use file-based storage.
2 or MEMORY	Use memory-based storage.

temp_store_directory Pragma

The **temp_store_directory** pragma gets or sets the location used for temporary database files. Following is the simple syntax.

```
PRAGMA temp_store_directory;
PRAGMA temp_store_directory = 'directory_path';
```

user_version Pragma

The **user_version** pragma gets or sets the user-defined version value that is stored in the database header. Following is the simple syntax.

```
PRAGMA [database.]user_version;  
PRAGMA [database.]user_version = number;
```

This is a 32-bit signed integer value, which can be set by the developer for version tracking purpose.

writable_schema Pragma

The **writable_schema** pragma gets or sets the ability to modify system tables. Following is the simple syntax.

```
PRAGMA writable_schema;  
PRAGMA writable_schema = [true|false];
```

If this pragma is set, tables that start with `sqlite_` can be created and modified, including the `sqlite_master` table. Be careful while using pragma because it can lead to complete database corruption.

27. SQLite – Constraints

가 (constraint) . 가 schema
diagram
SQLite 가 .

to one column, whereas table level constraints are applied to the whole table.

Following are commonly used constraints available in SQLite.

- **NOT NULL Constraint:** Ensures that a column cannot have NULL value.
- **DEFAULT Constraint:** Provides a default value for a column when none is specified. Foreign Key constraint???
- **UNIQUE Constraint:** Ensures that all values in a column are different.
- **PRIMARY Key:** Uniquely identifies each row/record in a database table.
- **CHECK Constraint:** Ensures that all values in a column satisfies certain conditions.

NOT NULL Constraint

By default, a column can hold NULL values. If you do not want a column to have a NULL value, then you need to define such constraint on this column specifying that NULL is now not allowed for that column.

A NULL is not the same as no data, rather, it represents unknown data.

Example

For example, the following SQLite statement creates a new table called COMPANY and adds five columns, three of which, ID and NAME and AGE, specifies not to accept NULLs.

```
CREATE TABLE COMPANY(  
  ID INT PRIMARY KEY NOT NULL,  
  NAME TEXT NOT NULL,  
  AGE INT NOT NULL,  
  ADDRESS CHAR(50),  
  SALARY REAL  
);
```

not null

. (SQLite)

DEFAULT Constraint

The DEFAULT constraint provides a default value to a column when the INSERT INTO statement does not provide a specific value.

Example

For example, the following SQLite statement creates a new table called COMPANY and adds five columns. Here, SALARY column is set to 5000.00 by default, thus in case INSERT INTO statement does not provide a value for this column, then by default, this column would be set to 5000.00.

```
CREATE TABLE COMPANY(
  ID INT PRIMARY KEY     NOT NULL,
  NAME           TEXT     NOT NULL,
  AGE            INT       NOT NULL,
  ADDRESS        CHAR(50),
  SALARY         REAL      DEFAULT 5000.00
);
```

default . (SQLite)

UNIQUE Constraint

The UNIQUE Constraint prevents two records from having identical values in a particular column. In the COMPANY table, for example, you might want to prevent two or more people from having an identical age.

Example

For example, the following SQLite statement creates a new table called COMPANY and adds five columns. Here, AGE column is set to NOT NULL and UNIQUE, thus in case INSERT INTO statement does not provide a value for this column, then by default, this column would be set to 5000.00.

```
CREATE TABLE COMPANY(
  ID INT PRIMARY KEY     NOT NULL,
  NAME           TEXT     NOT NULL,
  AGE            INT       NOT NULL UNIQUE,
  ADDRESS        CHAR(50),
  SALARY         REAL      DEFAULT 5000.00
);
```

unique , .
constraint age_uk unique(age)

PRIMARY KEY Constraint

The PRIMARY KEY constraint uniquely identifies each record in a database table. There can be more UNIQUE columns, but only one primary key in a table. Primary keys are important when designing the database tables. Primary keys are unique IDs.

We use them to refer to table rows. Primary keys become foreign keys in other tables, when creating relations among tables. Due to a 'longstanding coding oversight', primary keys can be NULL in SQLite. This is not the case with other databases.

A primary key is a field in a table which uniquely identifies each rows/records in a database table. Primary keys must contain unique values. A primary key column cannot have NULL values.

A table can have only one primary key, which may consist of single or multiple fields. When multiple fields are used as a primary key, they are called a **composite key**.

sqlite primary key not null
 . DBMS 가 . primary key
 unique + not null .

Example

You already have seen various examples above where we have created COMPANY table with ID as a primary key.

```
CREATE TABLE COMPANY(
  ID INT PRIMARY KEY NOT NULL,
  NAME TEXT NOT NULL,
  AGE INT NOT NULL,
  ADDRESS CHAR(50),
  SALARY REAL
);
```

primary key

constraint company_pk primary key(id)

CHECK Constraint

CHECK Constraint enables a condition to check the value being entered into a record. If the condition evaluates to false, the record violates the constraint and isn't entered into the table.

Example

For example, the following SQLite creates a new table called COMPANY and adds five columns. Here, we add a CHECK with SALARY column, so that you cannot have any SALARY Zero.

```
CREATE TABLE COMPANY3(
  ID INT PRIMARY KEY NOT NULL,
  NAME TEXT NOT NULL,
  AGE INT NOT NULL,
  ADDRESS CHAR(50),
```

constraint company_salary_ck check (salary > 0)

```
SALARY      REAL      CHECK(SALARY > 0)
);
```

Dropping Constraint

SQLite supports a limited subset of ALTER TABLE. The ALTER TABLE command in SQLite allows the user to rename a table or add a new column to an existing table. It is not possible to rename a column, remove a column, or add or remove constraints from a table.

DBMS alter table
SQLite alter table
alter table
add constraint ;
alter table
drop constraint ;

foreign key . foreign key
foreign key
foreign key primary
key . foreign key (reference)
constraint tbla_tblb_fk foreign key (_) references _
(_ _)

() northwind DB schema diagram

28. SQLite – JOINS

(normalization) join , SQL 2 (

SQLite **Joins** clause is used to combine records from two or more tables in a database. A JOIN is a means for combining fields from two tables by using values common to each.

SQL defines three major types of joins –

- The CROSS JOIN
- The INNER JOIN
- The OUTER JOIN

schema diagram

Before we proceed, let's consider two tables COMPANY and DEPARTMENT. We already have seen INSERT statements to populate COMPANY table. So just let's assume the list of records available in COMPANY table –

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Another table is DEPARTMENT with the following definition –

```
CREATE TABLE DEPARTMENT(  
    ID INT PRIMARY KEY NOT NULL,  
    DEPT CHAR(50) NOT NULL,  
    EMP_ID INT NOT NULL  
);
```

Here is the list of INSERT statements to populate DEPARTMENT table –

```
INSERT INTO DEPARTMENT (ID, DEPT, EMP_ID)  
VALUES (1, 'IT Billing', 1 );  
  
INSERT INTO DEPARTMENT (ID, DEPT, EMP_ID)  
VALUES (2, 'Engineering', 2 );
```

```
INSERT INTO DEPARTMENT (ID, DEPT, EMP_ID)
VALUES (3, 'Finance', 7 );
```

Finally, we have the following list of records available in DEPARTMENT table –

ID	DEPT	EMP_ID
1	IT Billing	1
2	Engineering	2
3	Finance	7

The CROSS JOIN

CROSS JOIN matches every row in the input tables have \times columns. Because CROSS JOIN care must be taken to only use them when appropriate.

cross join .

Cartesian product . cross join

Following is the syntax of CROSS JOIN –

```
SELECT ... FROM table1 CROSS JOIN table2 ...
```

Based on the above tables, you can write a CROSS JOIN as follows –

```
sqlite> SELECT EMP_ID, NAME, DEPT FROM COMPANY CROSS JOIN DEPARTMENT;
```

The above query will produce

EMP_ID	NAME	DEPT
1	Paul	IT Billing
2	Paul	Engineering
7	Paul	Finance
1	Allen	IT Billing
2	Allen	Engineering
7	Allen	Finance
1	Teddy	IT Billing
2	Teddy	Engineering
7	Teddy	Finance
1	Mark	IT Billing
2	Mark	Engineering
7	Mark	Finance
1	David	IT Billing

가

2	David	Engineering
7	David	Finance
1	Kim	IT Billing
2	Kim	Engineering
7	Kim	Finance
1	James	IT Billing
2	James	Engineering
7	James	Finance

The INNER JOIN

INNER JOIN creates a result set (a join) between two tables (table1 and table2) based upon the join-predicate. The join-predicate specifies the columns to be compared. Each row of table2 is compared with each row of table1 to find all pairs of rows which satisfy the join-predicate. When the join-predicate is satisfied, the column values for each matched pair of rows of A and B are combined into a result row.

An INNER JOIN is the most common and default type of join. You can use the **INNER** keyword optionally.

Following is the syntax of INNER JOIN –

```
SELECT ... FROM table1 [INNER] JOIN table2 ON conditional_expression ...
```

To avoid redundancy and keep the phrasing shorter, the join-predicate can be declared with a **USING** expression. This expression specifies the columns to be compared.

```
SELECT ... FROM table1 JOIN table2 USING ( column1 ,... ) ...
```

A NATURAL JOIN is similar to a **JOIN...USING**, only it automatically tests for equality between the values of every column that exists in both tables –

```
SELECT ... FROM table1 NATURAL JOIN table2...
```

Based on the above tables, you can write an INNER JOIN as follows –

```
sqlite> SELECT EMP_ID, NAME, DEPT FROM COMPANY INNER JOIN DEPARTMENT
        ON COMPANY.ID = DEPARTMENT.EMP_ID;
```

The above query will produce the following result –

EMP_ID	NAME	DEPT
1	Paul	IT Billing
2	Allen	Engineering
7	James	Finance

The OUTER JOIN

OUTER JOIN is an extension of the INNER JOIN.

OUTER JOINS: LEFT, RIGHT, FULL

OUTER JOINS have a condition that is used to filter the results.

USING, or NATURAL key words can be used to specify the primary JOIN is calculated.

both tables, pad them out with NULLs.

Following is the syntax of the OUTER JOIN:

inner join

outer join

outer join full outer join, left outer join, right outer join

가 가

가

full outer join 가

```
SELECT ... FROM table1 LEFT OUTER JOIN table2 ON conditional_expression ...
```

To avoid redundancy and keep the phrasing shorter, OUTER JOIN conditions can be declared with a USING expression. This expression specifies a list of one or more columns.

```
SELECT ... FROM table1 LEFT OUTER JOIN table2 USING ( column1 ,... ) ...
```

Based on the above tables, you can write an inner join as follows –

```
sqlite> SELECT EMP_ID, NAME, DEPT FROM COMPANY LEFT OUTER JOIN DEPARTMENT
ON COMPANY.ID = DEPARTMENT.EMP_ID;
```

The above query will produce the following result –

EMP_ID	NAME	DEPT
1	Paul	IT Billing
2	Allen	Engineerin

```
SELECT c.EMP_ID, c.NAME, d.DEPT
FROM COMPANY as c LEFT OUTER JOIN DEPARTMENT as d
ON c.ID = d.EMP_ID;
```

() scott.db

1. 'SCOTT' 가?
2. ACCOUNTING
3. (self join)
4. (self join) KING
5. (self join) 가
6. (self join)
7. (self join)
8. (self join)
- 9.

() chinook.db

1. "Movies" playlist track ,
2. 5 ,
3. track id, ,
4. 가 50 (invoice) (track id, track , 가)

() northwind.db

29. SQLite – UNION Clause

SQL , sqlite . select
" " , select
(union), (intersect),
(except) . select
select (,
) 가 .

Syntax

Following is the basic syntax of **UNION**.

```
SELECT column1 [, column2 ]  
FROM table1 [, table2 ]  
[WHERE condition]
```

UNION

```
SELECT column1 [, column2 ]  
FROM table1 [, table2 ]  
[WHERE condition]
```

select

intersect, except가 가 ,

Here the given condition could be any given expression based on your requirement.

Example

Consider the following two tables, (a) COMPANY table as follows:

```
sqlite> select * from COMPANY;
```

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

(b) Another table is DEPARTMENT as follows:

ID	DEPT	EMP_ID
-----	-----	-----
1	IT Billing	1
2	Engineering	2
3	Finance	7
4	Engineering	3
5	Finance	4
6	Engineering	5
7	Finance	6

Now let us join these two tables using SELECT statement along with UNION clause as follows:

```
sqlite> SELECT EMP_ID, NAME, DEPT FROM COMPANY INNER JOIN DEPARTMENT
        ON COMPANY.ID = DEPARTMENT.EMP_ID
UNION
        SELECT EMP_ID, NAME, DEPT FROM COMPANY LEFT OUTER JOIN DEPARTMENT
        ON COMPANY.ID = DEPARTMENT.EMP_ID;
```

This will produce the following result:

EMP_ID	NAME	DEPT
-----	-----	-----
1	Paul	IT Billing
2	Allen	Engineering
3	Teddy	Engineering
4	Mark	Finance
5	David	Engineering
6	Kim	Finance
7	James	Finance

The UNION ALL Clause

The UNION ALL operator is used to combine the results of two SELECT statements including duplicate rows.

The same rules that apply to UNION apply to the UNION ALL operator as well.

Syntax

Following is the basic syntax of **UNION ALL**.

```
SELECT column1 [, column2 ]
FROM table1 [, table2 ]
[WHERE condition]
```

UNION ALL

.

...

```
SELECT column1 [, column2 ]
FROM table1 [, table2 ]
[WHERE condition]
```

Here the given condition could be any given expression based on your requirement.

Example

Now, let us join the above-mentioned two tables in our SELECT statement as follows:

```
sqlite> SELECT EMP_ID, NAME, DEPT FROM COMPANY INNER JOIN DEPARTMENT
        ON COMPANY.ID = DEPARTMENT.EMP_ID
UNION ALL
        SELECT EMP_ID, NAME, DEPT FROM COMPANY LEFT OUTER JOIN DEPARTMENT
        ON COMPANY.ID = DEPARTMENT.EMP_ID;
```

This will produce the following result:

EMP_ID	NAME	DEPT
1	Paul	IT Billing
2	Allen	Engineering
3	Teddy	Engineering
4	Mark	Finance
5	David	Engineering
6	Kim	Finance
7	James	Finance
1	Paul	IT Billing

2	Allen	Engineering
3	Teddy	Engineering
4	Mark	Finance
5	David	Engineering
6	Kim	Finance
7	James	Finance

() 1. scott.db .

() chinook.db .

1. track id .
2. id .
3. playlist track id .
4. .

30. SQLite – NULL Values

SQLite **NULL** is the term used to represent a missing value. A NULL value in a table is a value in a field that appears to be blank.

A field with a NULL value is a field with no value. It is very important to understand that a NULL value is different than a zero value or a field that contains spaces.

Syntax

Following is the basic syntax of using **NULL** while creating a table.

```
SQLite> CREATE TABLE COMPANY(  
    ID INT PRIMARY KEY     NOT NULL,  
    NAME           TEXT     NOT NULL,  
    AGE            INT       NOT NULL,  
    ADDRESS        CHAR(50),  
    SALARY         REAL  
);
```

Here, **NOT NULL** signifies that the column should always accept an explicit value of the given data type. There are two columns where we did not use NOT NULL which means these columns could be NULL.

A field with a NULL value is one that has been left blank during record creation.

Example

The NULL value can cause problems when selecting data, because when comparing an unknown value to any other value, the result is always unknown and not included in the final results. Consider the following table, COMPANY with the following records:

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Let us use UPDATE statement to set a few nullable values as NULL as follows:

```
sqlite> UPDATE COMPANY SET ADDRESS = NULL, SALARY = NULL where ID IN(6,7);
```

Now, COMPANY table will have the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22		
7	James	24		

Next, let us see the usage of **IS NOT NULL** operator to list down all the records where SALARY is not NULL.

```
sqlite> SELECT ID, NAME, AGE, ADDRESS, SALARY
        FROM COMPANY
        WHERE SALARY IS NOT NULL;
```

The above SQLite statement will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

Following is the usage of **IS NULL** operator, which will list down all the records where SALARY is NULL.

```
sqlite> SELECT ID, NAME, AGE, ADDRESS, SALARY
        FROM COMPANY
        WHERE SALARY IS NULL;
```

The above SQLite statement will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
6	Kim	22		
7	James	24		

31. SQLite – ALIAS Syntax

You can rename a table or a column temporarily by giving another name, which is known as **ALIAS**. The use of table aliases means to rename a table in a particular SQLite statement. Renaming is a temporary change and the actual table name does not change in the database.

The column aliases are used to rename a table's columns for the purpose of a particular SQLite query.

Syntax

Following is the basic syntax of table alias.

```
SELECT column1, column2....  
FROM table_name AS alias_name  
WHERE [condition];
```

Following is the basic syntax of column alias.

```
SELECT column_name AS alias_name  
FROM table_name  
WHERE [condition];
```

Example

Consider the following two tables, (a) COMPANY table is as follows:

```
sqlite> select * from COMPANY;
```

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

(b) Another table is DEPARTMENT as follows:

ID	DEPT	EMP_ID
1	IT Billing	1
2	Engineering	2
3	Finance	7
4	Engineering	3
5	Finance	4
6	Engineering	5
7	Finance	6

Now, following is the usage of **TABLE ALIAS** where we use C and D as aliases for COMPANY and DEPARTMENT tables respectively:

```
sqlite> SELECT C.ID, C.NAME, C.AGE, D.DEPT
FROM COMPANY AS C, DEPARTMENT AS D
WHERE C.ID = D.EMP_ID;
```

select c.id, c.name, c.age, d.dept
from company as c inner join
department as d on (c.id = d.emp_id)

The above SQLite statement will produce the following result.

ID	NAME	AGE	DEPT
1	Paul	32	IT Billing
2	Allen	25	Engineerin
3	Teddy	23	Engineerin
4	Mark	25	Finance
5	David	27	Engineerin
6	Kim	22	Finance
7	James	24	Finance

Consider an example for the usage of **COLUMN ALIAS** where COMPANY_ID is an alias of ID column and COMPANY_NAME is an alias of name column.

```
sqlite> SELECT C.ID AS COMPANY_ID, C.NAME AS COMPANY_NAME, C.AGE, D.DEPT
FROM COMPANY AS C, DEPARTMENT AS D
WHERE C.ID = D.EMP_ID;
```

select c.id as company_id
, c.name as company_name
, c.age
, d.dept
from company as c inner join department as d on c.id = d.emp_id;

The above SQLite statement will produce the following result.

COMPANY_ID	COMPANY_NAME	AGE	DEPT
-----	-----	-----	-----
1	Paul	32	IT Billing
2	Allen	25	Engineerin
3	Teddy	23	Engineerin
4	Mark	25	Finance
5	David	27	Engineerin
6	Kim	22	Finance
7	James	24	Finance

32. SQLite – Triggers

SQLite Triggers are database callback functions, which are automatically performed/invoked when a specified database event occurs. Following are the important points about SQLite triggers:

- SQLite trigger may be specified to fire whenever a DELETE, INSERT or UPDATE of a particular database table occurs or whenever an UPDATE occurs on one or more specified columns of a table.
- At this time, SQLite supports only FOR EACH ROW triggers, not FOR EACH STATEMENT triggers. Hence, explicitly specifying FOR EACH ROW is optional.
- Both the WHEN clause and the trigger actions may access elements of the row being inserted, deleted, or updated using references of the form **NEW.column-name** and **OLD.column-name**, where column-name is the name of a column from the table that the trigger is associated with.
- If a WHEN clause is supplied, the SQL statements specified are only executed for rows for which the WHEN clause is true. If no WHEN clause is supplied, the SQL statements are executed for all rows.
- The BEFORE or AFTER keyword determines when the trigger actions will be executed relative to the insertion, modification, or removal of the associated row.
- Triggers are automatically dropped when the table that they are associated with is dropped.
- The table to be modified must exist in the same database as the table or view to which the trigger is attached and one must use just **tablename** not **database.tablename**.
- A special SQL function RAISE() may be used within a trigger-program to raise an exception.

Syntax

Following is the basic syntax of creating a **trigger**.

```
CREATE TRIGGER trigger_name [BEFORE|AFTER] event_name
ON table_name for each row
BEGIN
    -- Trigger logic goes here....
END;
```

Here, **event_name** could be *INSERT*, *DELETE*, and *UPDATE* database operation on the mentioned table **table_name**. You can optionally specify FOR EACH ROW after table name.

Following is the syntax for creating a trigger on an UPDATE operation on one or more specified columns of a table.

```
CREATE TRIGGER trigger_name [BEFORE|AFTER] UPDATE OF column_name
ON table_name
BEGIN
    -- Trigger logic goes here....
END;
```

Example

Let us consider a case where we want to **keep audit trail for every record being inserted in COMPANY table**, which we create newly as follows (Drop COMPANY table if you already have it).

```
sqlite> CREATE TABLE COMPANY(
    ID INT PRIMARY KEY     NOT NULL,
    NAME           TEXT     NOT NULL,
    AGE            INT       NOT NULL,
    ADDRESS        CHAR(50),
    SALARY         REAL
);
```

To keep audit trail, we will create a new table called AUDIT where the log messages will be inserted, whenever there is an entry in COMPANY table for a new record.

```
sqlite> CREATE TABLE AUDIT( id integer primary key autoincrement,
    EMP_ID INT NOT NULL,
    ENTRY_DATE TEXT NOT NULL
);
```

Here, ID is the AUDIT record ID, and EMP_ID is the ID which will come from COMPANY table and DATE will keep timestamp when the record will be created in COMPANY table. Now let's create a trigger on COMPANY table as follows:

```
sqlite> CREATE TRIGGER audit_log AFTER INSERT
ON COMPANY
BEGIN
    INSERT INTO AUDIT(EMP_ID, ENTRY_DATE) VALUES (new.ID, datetime('now'));
END;
```

current_timestamp

```
dbvisualizer      trigger      가
. SQL      ;      ;      - - / /
```

Now, we will start actual work. Let's start inserting record in COMPANY table which should result in creating an audit log record in AUDIT table. Create one record in COMPANY table as follows:

```
sqlite> INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
VALUES (1, 'Paul', 32, 'California', 20000.00 );
```

This will create one record in COMPANY table, which is as follows:

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0

Same time, one record will be created in AUDIT table. This record is the result of a trigger, which we have created on INSERT operation in COMPANY table. Similarly, you can create your triggers on UPDATE and DELETE operations based on your requirements.

EMP_ID	ENTRY_DATE
-----	-----
1	2013-04-05 06:26:00

Listing Triggers

```
dbvisualizer free version fuction, procedure, trigger
.
select * from sql_master where type='trigger';
```

The above SQLite statement will list down only one entry as follows:

name

audit_log

If you want to list down triggers on a particular table, then use AND clause with table name as follows:

```
sqlite> SELECT name FROM sqlite_master
WHERE type = 'trigger' AND tbl_name = 'COMPANY';
```

The above SQLite statement will also list down only one entry as follows:

name

audit_log

Dropping Triggers

Following is the DROP command, which can be used to drop an existing trigger.

```
sqlite> DROP TRIGGER trigger_name;
```

```
(      ) scott.db      emp
      가      log      .
emp      not null      가      .
action      'insert', 'update', 'delete'      .

id, action, old_empid, old_ename, old_mgr, old_sal, old_comm, old_deptno,
new_ename, new_mgr, new_sal, new_comm, new_deptno

1. insert, update, delete      log
trigger      .
```

33. SQLite – Indexes

with UPDATE and INSERT statements. Indexes can be created or dropped with no effect on the data in the table. Indexes can be created on one or more columns. The index is in an ascending or descending order.

Indexes can also be unique, similar to the UNIQUE constraint, in that the index prevents duplicate entries in the column or combination of columns on which there's an index.

The CREATE INDEX Command

Following is the basic syntax of **CREATE INDEX**.

```
CREATE INDEX index_name ON table_name;
```

Single-Column Indexes

A single-column index is one that is created based on only one table column. The basic syntax is as follows:

```
CREATE INDEX index_name  
ON table_name (column_name);
```

Unique Indexes

Unique indexes are used not only for performance, but also for data integrity. A unique index does not allow any duplicate values to be inserted into the table. The basic syntax is as follows:

```
CREATE UNIQUE INDEX index_name  
on table_name (column_name);
```

unique
index

Composite Indexes

A composite index is an index on two or more columns of a table. The basic syntax is as follows:

```
CREATE INDEX index_name
on table_name (column1, column2);
```

where

Whether to create a single-column index or a composite index, take into consideration the column(s) that you may use very frequently in a query's WHERE clause as filter conditions.

Should there be only one column used, a single-column index should be the choice. Should there be two or more columns that are frequently used in the WHERE clause as filters, the composite index would be the best choice.

Implicit Indexes

Implicit indexes are indexes that are automatically created by the database server when an object is created. Indexes are automatically created for primary key constraints and unique constraints.

Example

Following is an example where we will create an index in COMPANY table for salary column:

```
sqlite> CREATE INDEX salary_index ON COMPANY (salary);
```

Now, let's list down all the indices available in COMPANY table using **.indices** command as follows:

```
sqlite> .indices COMPANY
```

This will produce the following result, where sqlite_autoindex_COMPANY_1 is an implicit index which got created when the table itself was created.

```
salary_index
sqlite_autoindex_COMPANY_1
```

You can list down all the indexes database wide as follows:

```
sqlite> SELECT * FROM sqlite_master WHERE type = 'index';
```

() chinook.db, northwind.db, hr.db
primary key, foreign key index가 index
가 . index .

The DROP INDEX Command

An index can be dropped using SQLite **DROP** command. Care should be taken when dropping an index because performance may be slowed or improved.

The basic syntax is as follows:

```
DROP INDEX index_name;
```

You can use the following statement to delete a previously created index.

```
sqlite> DROP INDEX salary_index;
```

When Should Indexes Be Avoided?

Although indexes are intended to enhance the performance of a database, there are times when they should be avoided. The following guidelines indicate when the use of an index should be reconsidered.

Indexes should not be used in –

- Small tables.
- Tables that have frequent, large batch update or insert operations.
- Columns that contain a high number of NULL values.
- Columns that are frequently manipulated.

```
pragma index_list(
);

pragma index_info(
);

( ) index_list, index_info, table_info, ... pragma , pragma

attach
```

34. SQLite – INDEXED BY Clause

The "INDEXED BY index-name" clause specifies that the named index must be used in order to look up values on the preceding table.

If index-name does not exist or cannot be used for the query, then the preparation of the SQLite statement fails.

The "NOT INDEXED" clause specifies that no index shall be used when accessing the preceding table, including implied indices created by UNIQUE and PRIMARY KEY constraints.

However, the INTEGER PRIMARY KEY can still be used to look up entries even when "NOT INDEXED" is specified.

Syntax

Following is the syntax for INDEXED BY clause and it can be used with DELETE, UPDATE or SELECT statement.

```
SELECT|DELETE|UPDATE column1, column2...  
INDEXED BY (index_name)  
table_name  
WHERE (CONDITION);
```

Example

Consider table COMPANY. We will create an index and use it for performing INDEXED BY operation.

```
sqlite> CREATE INDEX salary_index ON COMPANY(salary);  
sqlite>
```

Now selecting the data from table COMPANY you can use INDEXED BY clause as follows:

```
sqlite> SELECT * FROM COMPANY INDEXED BY salary_index WHERE salary > 5000;
```

This will produce the following result.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
7	James	24	Houston	10000.0
2	Allen	25	Texas	15000.0
1	Paul	32	California	20000.0
3	Teddy	23	Norway	20000.0
6	Kim	22	South-Hall	45000.0

4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0

35. SQLite – ALTER TABLE Command

가 DBMS 가/ / , 가/
/ , alter table .
sqlite alter table , 가 .

There is no other operation supported by ALTER TABLE command in SQLite except renaming a table and adding a column in an existing table.

Syntax

Following is the basic syntax of **ALTER TABLE** to RENAME an existing table.

```
ALTER TABLE database_name.table_name RENAME TO new_table_name;
```

Following is the basic syntax of **ALTER TABLE** to add a new column in an existing table.

```
ALTER TABLE database_name.table_name ADD COLUMN column_def...;
```

Example

Consider the COMPANY table with the following records.

add column
drop column
modify column (oracle)
alter column (sql server)

add constraint
drop constraint

5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Now, let's try to rename this table using ALTER TABLE statement as follows:

```
sqlite> ALTER TABLE COMPANY RENAME TO OLD_COMPANY;
```

The above SQLite statement will rename COMPANY table to OLD_COMPANY. Now, let's try to add a new column in OLD_COMPANY table as follows:

```
sqlite> ALTER TABLE OLD_COMPANY ADD COLUMN SEX char(1);
```

COMPANY table is now changed and following will be the output from SELECT statement.

ID	NAME	AGE	ADDRESS	SALARY	SEX
1	Paul	32	California	20000.0	
2	Allen	25	Texas	15000.0	
3	Teddy	23	Norway	20000.0	
4	Mark	25	Rich-Mond	65000.0	
5	David	27	Texas	85000.0	
6	Kim	22	South-Hall	45000.0	
7	James	24	Houston	10000.0	

It should be noted that newly added column is filled with NULL values.

```
(
가
) chinook.db customers email unique
. sqlite alter table 가
가 .

1. customers 가 가
. ( customers create table
.)

2. insert into select * from customers; customers

3. customers .
4. customers .
```

36. SQLite – TRUNCATE TABLE Command

DBMS truncate table ;
SQLite
. truncate table where delete
delete .

SQLite **DELETE** command to delete complete data from an existing table, though it is recommended to use DROP TABLE command to drop the complete table and re-create it once again.

Syntax

Following is the basic syntax of DELETE command.

```
sqlite> DELETE FROM table_name; truncate table ;
```

Following is the basic syntax of DROP TABLE.

```
sqlite> DROP TABLE table_name;
```

If you are using DELETE TABLE command to delete all the records, it is recommended to use **VACUUM** command to clear unused space.

Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following is the example to truncate the above table:

```
SQLite> DELETE FROM COMPANY;
```

```
SQLite> VACUUM;
```

DBMS SQLite
DBMS

```
( ) testDB.db backup
```

```
1. testDB.db
```

```
2. testDB.db company
```

```
3. testDB.db
```

```
4. testDB.db vacuum
```


```
5. testDB.db
```

```
( ) vacuum attach . sqlite
```

```
DB
```

```
( ) vacuum
```

37. SQLite – Views



- Summarize data from various tables, which can be used to generate reports.

SQLite views are read-only and thus you may not be able to execute a DELETE, INSERT, or UPDATE statement on a view. However, you can create a trigger on a view that fires on an attempt to DELETE, INSERT, or UPDATE a view and do what you need in the body of the trigger.

Creating Views

SQLite views are created using the **CREATE VIEW** statement. SQLite views can be created from a single table, multiple tables, or another view.

Following is the basic CREATE VIEW syntax.

```
CREATE [TEMP | TEMPORARY] VIEW view_name AS
SELECT column1, column2.....
FROM table_name
WHERE [condition];
```

You can include multiple tables in your SELECT statement in a similar way as you use them in a normal SQL SELECT query. If the optional TEMP or TEMPORARY keyword is present, the view will be created in the temp database.

Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0

3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following is an example to create a view from COMPANY table. This view will be used to have only a few columns from COMPANY table.

```
sqlite> CREATE VIEW COMPANY_VIEW AS
SELECT ID, NAME, AGE
FROM COMPANY;
```

You can now query COMPANY_VIEW in a similar way as you query an actual table. Following is an example:

```
sqlite> SELECT * FROM COMPANY_VIEW;
```

This will produce the following result.

ID	NAME	AGE
1	Paul	32
2	Allen	25
3	Teddy	23
4	Mark	25
5	David	27
6	Kim	22
7	James	24

Dropping Views

To drop a view, simply use the DROP VIEW statement with the **view_name**. The basic DROP VIEW syntax is as follows:

```
sqlite> DROP VIEW view_name;
```

The following command will delete COMPANY_VIEW view, which we created in the last section.

```
sqlite> DROP VIEW COMPANY_VIEW;
```

```
( ) , , select
select
(1) chinook.db
(2) scott.db
(3) Northwind.db 가 10가 view view
```


38. SQLite – Transactions

chinook.db

가?

1. 50 1, 2, 3 track 가 1.00 1 .

1) invoices invoice 가 . (insert into)

2) invoice_items 3 가 . (insert into 2)

4 insert into

가?

2. 50 2, 3 .

1) invoice_items 2, 3 . (delete)

2) invoices Total . (update)

가?

SQL (transaction)

SQL

. (all - or -

nothing)

Transactions have the following four standard properties, usually referred to by the acronym ACID.

- **Atomicity:** Ensures that a transaction is either completed successfully or not at all. If a transaction fails, all previous operations are rolled back to their former state.
- **Consistency:** Ensures that a transaction brings the database from one valid state to another, without violating any constraints.
- **Isolation:** Ensures that concurrent transactions do not interfere with each other. Each transaction appears to execute in isolation.
- **Durability:** Ensures that the changes made by a transaction are permanent, even in the case of a system failure.

Transaction Control **TCL**

Following are the commands used to control transactions:

- **BEGIN TRANSACTION:** To start a transaction.
- **COMMIT:** To save the changes, alternatively you can use END TRANSACTION command.
- **ROLLBACK:** To roll back the changes.

Transactional control commands are only used with DML commands INSERT, UPDATE, and DELETE. They cannot be used while creating tables or dropping them because these operations are automatically committed in the database.

BEGIN TRANSACTION Command

Transactions can be started using BEGIN TRANSACTION or simply BEGIN command. Such transactions usually persist until the next COMMIT or ROLLBACK command is encountered. However, a transaction will also ROLLBACK if the database is closed or if an error occurs. Following is the simple syntax to start a transaction.

```
BEGIN;

or

BEGIN TRANSACTION;
```

COMMIT Command

COMMIT command is the transactional command used to save changes invoked by a transaction to the database.

COMMIT command saves all transactions to the database since the last COMMIT or ROLLBACK command.

Following is the syntax for COMMIT command.

```
COMMIT;

or

END TRANSACTION;
```

ROLLBACK Command

ROLLBACK command is the transactional command used to undo transactions that have not already been saved to the database.

ROLLBACK command can only be used to undo transactions since the last COMMIT or ROLLBACK command was issued.

Following is the syntax for ROLLBACK command.

```
ROLLBACK;
```

Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0

3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Now, let's start a transaction and delete records from the table having age = 25. Then, use ROLLBACK command to undo all the changes.

```
sqlite> BEGIN;
sqlite> DELETE FROM COMPANY WHERE AGE = 25;
sqlite> ROLLBACK;
```

Now, if you check COMPANY table, it still has the following records:

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Let's start another transaction and delete records from the table having age = 25 and finally we use COMMIT command to commit all the changes.

```
sqlite> BEGIN;
sqlite> DELETE FROM COMPANY WHERE AGE = 25;
sqlite> COMMIT;
```

If you now check COMPANY table still has the following records:

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0

() chinook.db
가?

1. 50 1, 2, 3, 4, 5 가 1.00 1 .

2. 50 . .

39. SQLite – Subqueries

select, insert, update, delete
subquery, inner query, nested query)
, main query)

select (,
가 (,
가 .

=, <, >, >=, <=, in 가 가 .

2 2

in, not in, exists . exists
1 True False가 .

- Subqueries must be enclosed within parentheses.
- A subquery can have only one column in the SELECT clause, unless multiple columns are in the main query for the subquery to compare its selected columns.
- An ORDER BY cannot be used in a subquery, although the main query can use an ORDER BY. The GROUP BY can be used to perform the same function as the ORDER BY in a subquery.
- Subqueries that return more than one row can only be used with multiple value operators, such as the IN operator.
- BETWEEN operator cannot be used with a subquery; however, BETWEEN can be used within the subquery.

Subqueries with SELECT Statement

between () and ()

Subqueries are most frequently used with the SELECT statement. The basic syntax is as follows:

```
SELECT column_name [, column_name ]
FROM table1 [, table2 ]
WHERE column_name OPERATOR
      (SELECT column_name [, column_name ]
      FROM table1 [, table2 ]
      [WHERE])
```

Example

Consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Now, let us check the following sub-query with SELECT statement.

```
sqlite> SELECT *
        FROM COMPANY
        WHERE ID IN (SELECT ID
                    FROM COMPANY
                    WHERE SALARY > 45000) ;
```

This will produce the following result.

```
(
1. scott.db      JONES      가?
2. chinookdb     1
3. chinook.db    400
4. hr.db         Neena Kochhar  가
```

Subqueries with INSERT Statement

Subqueries can also be used with INSERT statements. The INSERT statement uses the data returned from the subquery to insert into another table. The selected data in the subquery can be modified with any of the character, date, or number functions.

The basic syntax is as follows:

```
INSERT INTO table_name [ (column1 [, column2 ]) ]
        SELECT [ *|column1 [, column2 ]
        FROM table1 [, table2 ]
        [ WHERE VALUE OPERATOR ]
```

가

118

Example

Consider a table COMPANY_BKP with similar structure as COMPANY table and can be created using the same CREATE TABLE using COMPANY_BKP as the table name. To copy the complete COMPANY table into COMPANY_BKP, following is the syntax:

```
sqlite> INSERT INTO COMPANY_BKP
```

```
SELECT * FROM COMPANY
WHERE ID IN (SELECT ID
            FROM COMPANY) ;
```

가

Subqueries with UPDATE Statement

The subquery can be used in conjunction with the UPDATE statement. Either single or multiple columns in a table can be updated when using a subquery with the UPDATE statement.

The basic syntax is as follows:

```
UPDATE table
SET column_name = new_value
[ WHERE OPERATOR [ VALUE ]
  (SELECT COLUMN_NAME
   FROM TABLE_NAME)
[ WHERE) ]
```

Example

Assuming, we have COMPANY_BKP table available which is a backup of COMPANY table.

Following example updates SALARY by 0.50 times in COMPANY table for all the customers, whose AGE is greater than or equal to 27.

```
sqlite> UPDATE COMPANY
      SET SALARY = SALARY * 0.50
      WHERE AGE IN (SELECT AGE FROM COMPANY_BKP
                   WHERE AGE >= 27 );
```

가 27

50%

where

.

where age >= 27

()

1. (scott.db) sales

10%

.

.)

rollback

4

Mark

25

Rich-Mond

65000.0

from	subquery가	.	subquery	alias
.				
select ... from () as where ... ;				
5	David	27	Texas	42500.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Subqueries with DELETE Statement

Subquery can be used in conjunction with the DELETE statement like with any other statements mentioned above.

The basic syntax is as follows:

```
DELETE FROM TABLE_NAME
[ WHERE OPERATOR [ VALUE ]
  (SELECT COLUMN_NAME
   FROM TABLE_NAME)
[ WHERE) ]
```

Example

Assuming, we have COMPANY_BKP table available which is a backup of COMPANY table.

Following example deletes records from COMPANY table for age is greater than or equal to 27.

```
sqlite> DELETE FROM COMPANY
        WHERE AGE IN (SELECT AGE FROM COMPANY_BKP
                     WHERE AGE > 27 );
```

27

== >

where age > = 27

This will impact two rows and finally COMPANY table will have the following records.

() chinook.db	.
1. track	.
2. .	.
3. playlist track	.
4. .	.
5. playlist 가 track	.
() 89 28	가
.	.
가	.
.	.

() scott.db	가?
가? ((correlated subquery)	,
.	가
.	.)
.	.
select empno, ename, job, deptno from emp e	
where exists (select * from emp where mgr = e.empno);	
.	.
select ename, sal, deptno from emp e	
where sal > (select avg(sal) from emp where deptno = e.deptno);	

40. SQLite – AUTOINCREMENT

SQLite **AUTOINCREMENT** is a keyword used for auto incrementing a value of a field in the table. We can auto increment a field value by using **AUTOINCREMENT** keyword when creating a table with specific column name to auto increment it.

The keyword **AUTOINCREMENT** can be used with **INTEGER** field only.

Syntax

The basic usage of **AUTOINCREMENT** keyword is as follows:

```
CREATE TABLE table_name(  
    column1 INTEGER AUTOINCREMENT,  
    column2 datatype,  
    column3 datatype,  
    .....  
    columnN datatype,  
);
```

Example

Consider COMPANY table to be created as follows:

```
sqlite> CREATE TABLE COMPANY(  
    ID INTEGER PRIMARY KEY AUTOINCREMENT,  
    NAME          TEXT          NOT NULL,  
    AGE           INT           NOT NULL,  
    ADDRESS       CHAR(50),  
    SALARY        REAL  
);
```

Now, insert the following records into table COMPANY:

```
INSERT INTO COMPANY (NAME,AGE,ADDRESS,SALARY)  
VALUES ( 'Paul', 32, 'California', 20000.00 );  
  
INSERT INTO COMPANY (NAME,AGE,ADDRESS,SALARY)  
VALUES ( 'Allen', 25, 'Texas', 15000.00 );  
  
INSERT INTO COMPANY (NAME,AGE,ADDRESS,SALARY)
```



```
VALUES ( 'Teddy', 23, 'Norway', 20000.00 );

INSERT INTO COMPANY (NAME,AGE,ADDRESS,SALARY)
VALUES ( 'Mark', 25, 'Rich-Mond ', 65000.00 );

INSERT INTO COMPANY (NAME,AGE,ADDRESS,SALARY)
VALUES ( 'David', 27, 'Texas', 85000.00 );

INSERT INTO COMPANY (NAME,AGE,ADDRESS,SALARY)
VALUES ( 'Kim', 22, 'South-Hall', 45000.00 );

INSERT INTO COMPANY (NAME,AGE,ADDRESS,SALARY)
VALUES ( 'James', 24, 'Houston', 10000.00 );
```

This will insert 7 tuples into the table COMPANY and COMPANY will have the following records:

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

41. SQLite – Injection

If you take user input through a webpage and insert it into a SQLite database there's a chance that you have left yourself wide open for a security issue known as SQL Injection. In this chapter, you will learn how to help prevent this from happening and help you secure your scripts and SQLite statements.

Injection usually occurs when you ask a user for input, like their name, and instead of a name they give you a SQLite statement that you will unknowingly run on your database.

Never trust user provided data, process this data only after validation; as a rule, this is done by pattern matching. In the following example, the username is restricted to alphanumerical chars plus underscore and to a length between 8 and 20 chars - modify these rules as needed.

```
if (preg_match("/^\w{8,20}$/", $_GET['username'], $matches)){
    $db = new SQLiteDatabase('filename');
    $result = @$db->query("SELECT * FROM users WHERE username=$matches[0]");
}else{
    echo "username not accepted";
}
```

To demonstrate the problem, consider this excerpt:

```
$name = "Qadir"; DELETE FROM users;";
@$db->query("SELECT * FROM users WHERE username='{$name}'");
```

The function call is supposed to retrieve a record from the users table where the name column matches the name specified by the user. Under normal circumstances, **\$name** would only contain alphanumeric characters and perhaps spaces, such as the string ilia. However in this case, by appending an entirely new query to \$name, the call to the database turns into a disaster: the injected DELETE query removes all records from users.

There are databases interfaces which do not permit query stacking or executing multiple queries in a single function call. If you try to stack queries, the call fails but SQLite and PostgreSQL, happily perform stacked queries, executing all of the queries provided in one string and creating a serious security problem.

Preventing SQL Injection

You can handle all escape characters smartly in scripting languages like PERL and PHP. Programming language PHP provides the function **string sqlite_escape_string()** to escape input characters that are special to SQLite.

```
if (get_magic_quotes_gpc())
{
    $name = sqlite_escape_string($name);
}
$result = @$db->query("SELECT * FROM users WHERE username='{ $name}'");
```

Although the encoding makes it safe to insert the data, it will render simple text comparisons and **LIKE** clauses in your queries unusable for the columns that contain the binary data.

Note: **addslashes()** should NOT be used to quote your strings for SQLite queries; it will lead to strange results when retrieving your data.

42. SQLite – EXPLAIN

SQLite statement can be preceded by the keyword "EXPLAIN" or by the phrase "EXPLAIN QUERY PLAN" used for describing the details of a table.

Either modification causes the SQLite statement to behave as a query and to return information about how the SQLite statement would have operated if the EXPLAIN keyword or phrase had been omitted.

- The output from EXPLAIN and EXPLAIN QUERY PLAN is intended for interactive analysis and troubleshooting only.
- The details of the output format are subject to change from one release of SQLite to the next.
- Applications should not use EXPLAIN or EXPLAIN QUERY PLAN since their exact behavior is variable and only partially documented.

Syntax

Syntax for **EXPLAIN** is as follows:

```
EXPLAIN [SQLite Query]
```

Syntax for **EXPLAIN QUERY PLAN** is as follows:

```
EXPLAIN QUERY PLAN [SQLite Query]
```

Example

Consider COMPANY table with the following records:

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Now, let us check the following sub-query with SELECT statement:

```
sqlite> EXPLAIN SELECT * FROM COMPANY WHERE Salary >= 20000;
```

This will produce the following result:

addr	opcode	p1	p2	p3
-----	-----	-----	-----	-----
0	Goto	0	19	
1	Integer	0	0	
2	OpenRead	0	8	
3	SetNumColu	0	5	
4	Rewind	0	17	
5	Column	0	4	
6	RealAffini	0	0	
7	Integer	20000	0	
8	Lt	357	16	collseq(BI
9	Rowid	0	0	
10	Column	0	1	
11	Column	0	2	
12	Column	0	3	
13	Column	0	4	
14	RealAffini	0	0	
15	Callback	5	0	
16	Next	0	5	
17	Close	0	0	
18	Halt	0	0	
19	Transactio	0	0	
20	VerifyCook	0	38	
21	Goto	0	1	
22	Noop	0	0	

Now, let us check the following **Explain Query Plan** with SELECT statement:

SQLite> EXPLAIN QUERY PLAN SELECT * FROM COMPANY WHERE Salary >= 20000;		
order	from	detail
-----	-----	-----
0	0	TABLE COMPANY

43. SQLite – VACUUM

VACUUM command cleans the main database by copying its contents to a temporary database file and reloading the original database file from the copy. This eliminates free pages, aligns table data to be contiguous, and otherwise cleans up the database file structure.

VACUUM command may change the ROWID of entries in tables that do not have an explicit INTEGER PRIMARY KEY. The VACUUM command only works on the main database. It is not possible to VACUUM an attached database file.

VACUUM command will fail if there is an active transaction. VACUUM command is a no-op for in-memory databases. As the VACUUM command rebuilds the database file from scratch, VACUUM can also be used to modify many database-specific configuration parameters.

Manual VACUUM

Following is a simple syntax to issue a VACUUM command for the whole database from command prompt:

```
$sqlite3 database_name "VACUUM;"
```

You can run VACUUM from SQLite prompt as well as follows:

```
sqlite> VACUUM;
```

You can also run VACUUM on a particular table as follows:

```
sqlite> VACUUM table_name;
```

Auto-VACUUM

SQLite Auto-VACUUM does not do the same as VACUUM rather it only moves free pages to the end of the database thereby reducing the database size. By doing so it can significantly fragment the database while VACUUM ensures defragmentation. Hence, Auto-VACUUM just keeps the database small.

You can enable/disable SQLite auto-vacuuming by the following pragmas running at SQLite prompt:

```
sqlite> PRAGMA auto_vacuum = NONE;  -- 0 means disable auto vacuum
sqlite> PRAGMA auto_vacuum = FULL;  -- 1 means enable full auto vacuum
sqlite> PRAGMA auto_vacuum = INCREMENTAL;  -- 2 means enable incremental vacuum
```

You can run the following command from the command prompt to check the auto-vacuum setting:

```
$sqlite3 database_name "PRAGMA auto_vacuum;"
```

44. SQLite – Date & Time

ISO

Sr. No.	Function	Example
1	date(timestring, modifiers...)	This returns the date in this format: YYYY-MM-DD
2	time(timestring, modifiers...)	This returns the time as HH:MM:SS
3	datetime(timestring, modifiers...)	This returns YYYY-MM-DD HH:MM:SS
4	julianday(timestring, modifiers...)	This returns the number of days since noon in Greenwich on November 24, 4714 B.C.
	strftime(formatstring, timestring)	This returns the date formatted according to the format string specified as the first argument formatted as per formatters explained below.

All the above five date and time functions take a time string as an argument. The time string is followed by zero or more modifiers. The strftime() function also takes a format string as its first argument. Following section will give you detail on different types of time strings and modifiers.

Time Strings

A time string can be in any of the following formats:

Sr. No.	Time String	Example
1	YYYY-MM-DD	2010-12-30
2	YYYY-MM-DD HH:MM	2010-12-30 12:10
3	YYYY-MM-DD HH:MM:SS.SSS	2010-12-30 12:10:04.100
4	MM-DD-YYYY HH:MM	30-12-2010 12:10
5	HH:MM	12:10
6	YYYY-MM-DDTHH:MM	2010-12-30 12:10

7	HH:MM:SS	12:10:01
8	YYYYMMDD HHMMSS	20101230 121001
9	<code>now</code>	2013-05-07

You can use the "T" as a literal character separating the date and the time.

Modifiers

The time string can be followed by zero or more modifiers that will alter date and/or time returned by any of the above five functions. Modifiers are applied from the left to right.

Following modifiers are available in SQLite:

- NNN days
- NNN hours
- NNN minutes
- NNN.NNNN seconds
- NNN months
- NNN years
- start of month
- start of year
- start of day
- weekday N
- unixepoch
- localtime
- utc

modifier 1 . 2 . NNN
 , - 5 days , 5 , 5 days 5

00:00:00

0, 1, ...

...

Formatters

SQLite provides a very handy function **strftime()** to format any date and time. You can use the following substitutions to format your date and time.

Substitution	Description
%d	Day of month, 01-31
%f	Fractional seconds, SS.SSS
%H	Hour, 00-23

%j	Day of year, 001-366
%J	Julian day number, DDDD.DDDD
%m	Month, 00-12
%M	Minute, 00-59
%s	Seconds since 1970-01-01 ← unixepoch, unixtimestamp
%S	Seconds, 00-59
%w	Day of week, 0-6 (0 is Sunday)
%W	Week of year, 01-53
%Y	Year, YYYY
%%	% symbol

Examples

Let's try various examples now using SQLite prompt. Following command computes the current date.

```
sqlite> SELECT date('now');
2013-05-07
```

time('now'), date('now'), datetime('now')
current_time, current_date, current_timestamp
UTC
(local time)

Following command computes the

```
sqlite> SELECT date('now','start of month','+1 month','-1 day');
2013-05-31
```

Following command computes the date and time for a given UNIX timestamp 1092941466.

```
sqlite> SELECT datetime(1092941466, 'unixepoch');
2004-08-19 18:51:06
```

Following command computes the date and time for a given UNIX timestamp 1092941466 and compensates for your local timezone.

```
sqlite> SELECT datetime(1092941466, 'unixepoch', 'localtime');
2004-08-19 13:51:06
```

Following command computes the current UNIX timestamp.

```
sqlite> SELECT strftime('%s','now');
1393348134
```

() select , select where , insert, update
. scott.db .
1. .
2. .

() chinook.db

- 1.
2. 2013 11 12 2
3. 2013 11 12 2

of Independence.

```
sqlite> SELECT julianday('now') - julianday('1776-07-04');  
86798.7094695023
```

Following command computes the number of seconds since a particular moment in 2004.

```
sqlite> SELECT strftime('%s', 'now') - strftime('%s', '2004-01-01 02:34:56');  
295001572
```

julianday(), strftime('%s', timestring)가
julianday()가

2013-10-01

, strftime('%m', timestring), strftime('%d',
timestring) cast(as decimal)

3

select strftime('%Y', invoicedate) as year, sum(total) from invoice
where cast(strftime('%m', invoicedate) as integer) = 3
group by year;

cf. integer, decimal, float, real, text etc.

05:00:00

```
sqlite> SELECT time('12:00', 'utc');  
19:00:00
```

select datetime('now'), datetime('now', 'localtime'), datetime('now', 'utc');

'now' utc . 'localtime' modifier utc
가 , 'utc' modifier 가
utc . 'utc' modifier

45. SQLite – Useful Functions

SQLite has many built-in functions to perform processing on string or numeric data. Following is the list of few useful SQLite built-in functions and all are case in-sensitive which means you can use these functions either in lower-case form or in upper-case or in mixed form. For more details, you can check official documentation for SQLite.

Sr. No.	Function & Description
1	SQLite COUNT Function The SQLite COUNT aggregate function is used to count the number of rows in a database table.
2	SQLite MAX Function The SQLite MAX aggregate function allows us to select the highest (maximum) value for a certain column.
3	SQLite MIN Function The SQLite MIN aggregate function allows us to select the lowest (minimum) value for a certain column.
4	SQLite AVG Function The SQLite AVG aggregate function selects the average value for certain table column.
5	SQLite SUM Function The SQLite SUM aggregate function allows selecting the total for a numeric column.
6	SQLite RANDOM Function The SQLite RANDOM function returns a pseudo-random integer between -9223372036854775808 and +9223372036854775807.

7	SQLite ABS Function The SQLite ABS function returns the absolute value of the numeric argument.
8	SQLite UPPER Function The SQLite UPPER function converts a string into upper-case letters.
9	SQLite LOWER Function The SQLite LOWER function converts a string into lower-case letters.
10	SQLite LENGTH Function The SQLite LENGTH function returns the length of a string.
11	SQLite sqlite_version Function The SQLite sqlite_version function returns the version of the SQLite library.

Before we start giving examples on the above-mentioned functions, consider COMPANY table with the following records.

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	-----	-----	-----
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

SQLite COUNT Function

SQLite COUNT aggregate function is used to count the number of rows in a database table. Following is an example:

```
sqlite> SELECT count(*) FROM COMPANY;
```

The above SQLite SQL statement will produce the following result:

```
count(*)
-----
7
```

SQLite MAX Function

SQLite MAX aggregate function allows us to select the highest (maximum) value for a certain column. Following is an example:

```
sqlite> SELECT max(salary) FROM COMPANY;
```

The above SQLite SQL statement will produce the following result.

```
max(salary)
-----
85000.0
```

SQLite MIN Function

SQLite MIN aggregate function allows us to select the lowest (minimum) value for a certain column. Following is an example:

```
sqlite> SELECT min(salary) FROM COMPANY;
```

The above SQLite SQL statement will produce the following result.

```
min(salary)
-----
10000.0
```

SQLite AVG Function

SQLite AVG aggregate function selects the average value for a certain table column. Following is an example:

```
sqlite> SELECT avg(salary) FROM COMPANY;
```

The above SQLite SQL statement will produce the following result.

```
avg(salary)
-----
37142.8571428572
```

SQLite SUM Function

SQLite SUM aggregate function allows selecting the total for a numeric column. Following is an example:

```
sqlite> SELECT sum(salary) FROM COMPANY;
```

The above SQLite SQL statement will produce the following result.

```
sum(salary)
-----
260000.0
```

SQLite RANDOM Function

SQLite RANDOM function returns a pseudo-random integer between -9223372036854775808 and +9223372036854775807. Following is an example:

```
sqlite> SELECT random() AS Random;
```

The above SQLite SQL statement will produce the following result.

```
Random
-----
5876796417670984050
```

SQLite ABS Function

SQLite ABS function returns the absolute value of the numeric argument. Following is an example:

```
sqlite> SELECT abs(5), abs(-15), abs(NULL), abs(0), abs("ABC");
```

The above SQLite SQL statement will produce the following result.

abs(5)	abs(-15)	abs(NULL)	abs(0)	abs("ABC")
-----	-----	-----	-----	-----
5	15		0	0.0

SQLite UPPER Function

SQLite UPPER function converts a string into upper-case letters. Following is an example:

```
sqlite> SELECT upper(name) FROM COMPANY;
```

The above SQLite SQL statement will produce the following result.

```
upper(name)
-----
PAUL
ALLEN
TEDDY
MARK
DAVID
KIM
JAMES
```

SQLite LOWER Function

SQLite LOWER function converts a string into lower-case letters. Following is an example:

```
sqlite> SELECT lower(name) FROM COMPANY;
```

The above SQLite SQL statement will produce the following result.

```
lower(name)
-----
paul
allen
teddy
mark
david
kim
james
```

SQLite LENGTH Function

SQLite LENGTH function returns the length of a string. Following is an example:

```
sqlite> SELECT name, length(name) FROM COMPANY;
```

The above SQLite SQL statement will produce the following result.

NAME	length(name)
-----	-----
Paul	4
Allen	5

Teddy	5
Mark	4
David	5
Kim	3
James	5

SQLite sqlite_version Function

SQLite sqlite_version function returns the version of the SQLite library. Following is an example:

```
sqlite> SELECT sqlite_version() AS 'SQLite Version';
```

The above SQLite SQL statement will produce the following result.

```
SQLite Version
-----
3.6.20
```

SQLite Interfaces

46. SQLite – C/C++

In this chapter, you will learn how to use SQLite in C/C++ programs.

Installation

Before you start using SQLite in our C/C++ programs, you need to make sure that you have SQLite library set up on the machine. You can check SQLite Installation chapter to understand the installation process.

C/C++ Interface APIs

Following are important C/C++ SQLite interface routines, which can suffice your requirement to work with SQLite database from your C/C++ program. If you are looking for a more sophisticated application, then you can look into SQLite official documentation.

Sr. No.	API & Description
1	<p>sqlite3_open(const char *filename, sqlite3 **ppDb)</p> <p>This routine opens a connection to an SQLite database file and returns a database connection object to be used by other SQLite routines.</p> <p>If the <i>filename</i> argument is NULL or ':memory:', sqlite3_open() will create an in-memory database in RAM that lasts only for the duration of the session.</p> <p>If the filename is not NULL, sqlite3_open() attempts to open the database file by using its value. If no file by that name exists, sqlite3_open() will open a new database file by that name.</p>
2	<p>sqlite3_exec(sqlite3*, const char *sql, sqlite_callback, void *data, char **errmsg)</p> <p>This routine provides a quick, easy way to execute SQL commands provided by sql argument, which can consist of more than one SQL command.</p> <p>Here, the first argument <i>sqlite3</i> is an open database object, <i>sqlite_callback</i> is a callback for which <i>data</i> is the 1st argument and errmsg will be returned to capture any error raised by the routine.</p> <p>The sqlite3_exec() routine parses and executes every command given in the sql argument until it reaches the end of the string or encounters an error.</p>

3	<p>sqlite3_close(sqlite3*)</p> <p>This routine closes a database connection previously opened by a call to sqlite3_open(). All prepared statements associated with the connection should be finalized prior to closing the connection.</p> <p>If any queries remain that have not been finalized, sqlite3_close() will return SQLITE_BUSY with the error message Unable to close due to unfinalized statements.</p>
---	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Connect to Database

Following C code segment shows how to connect to an existing database. If the database does not exist, then it will be created and finally a database object will be returned.

```
#include <stdio.h>
#include <sqlite3.h>

int main(int argc, char* argv[])
{
    sqlite3 *db;
    char *zErrMsg = 0;
    int rc;

    rc = sqlite3_open("test.db", &db);

    if( rc ){
        fprintf(stderr, "Can't open database: %s\n", sqlite3_errmsg(db));
        return(0);
    }else{
        fprintf(stderr, "Opened database successfully\n");
    }
    sqlite3_close(db);
}
```

Now, let's compile and run the above program to create our database **test.db** in the current directory. You can change your path as per your requirement.

```
$gcc test.c -l sqlite3
$./a.out
Opened database successfully
```

If you are going to use C++ source code, then you can compile your code as follows:

```
$g++ test.c -l sqlite3
```

Here, we are linking our program with sqlite3 library to provide required functions to C program. This will create a database file test.db in your directory and you will have the following result.

```
-rwxr-xr-x. 1 root root 7383 May  8 02:06 a.out
-rw-r--r--. 1 root root  323 May  8 02:05 test.c
-rw-r--r--. 1 root root    0 May  8 02:06 test.db
```

Create a Table

Following C code segment will be used to create a table in the previously created database.

```
#include <stdio.h>
#include <stdlib.h>
#include <sqlite3.h>

static int callback(void *NotUsed, int argc, char **argv, char **azColName){
    int i;
    for(i=0; i<argc; i++){
        printf("%s = %s\n", azColName[i], argv[i] ? argv[i] : "NULL");
    }
    printf("\n");
    return 0;
}

int main(int argc, char* argv[])
{
    sqlite3 *db;
    char *zErrMsg = 0;
    int rc;
    char *sql;

    /* Open database */
    rc = sqlite3_open("test.db", &db);
    if( rc ){
        fprintf(stderr, "Can't open database: %s\n", sqlite3_errmsg(db));
```

```

        return(0);
    }else{
        fprintf(stdout, "Opened database successfully\n");
    }

    /* Create SQL statement */
    sql = "CREATE TABLE COMPANY(" \
        "ID INT PRIMARY KEY     NOT NULL," \
        "NAME           TEXT     NOT NULL," \
        "AGE             INT      NOT NULL," \
        "ADDRESS          CHAR(50)," \
        "SALARY           REAL );";

    /* Execute SQL statement */
    rc = sqlite3_exec(db, sql, callback, 0, &zErrMsg);
    if( rc != SQLITE_OK ){
        fprintf(stderr, "SQL error: %s\n", zErrMsg);
        sqlite3_free(zErrMsg);
    }else{
        fprintf(stdout, "Table created successfully\n");
    }
    sqlite3_close(db);
    return 0;
}

```

When the above program is compiled and executed, it will create COMPANY table in your test.db and the final listing of the file will be as follows:

```

-rwxr-xr-x. 1 root root 9567 May  8 02:31 a.out
-rw-r--r--. 1 root root 1207 May  8 02:31 test.c
-rw-r--r--. 1 root root 3072 May  8 02:31 test.db

```

INSERT Operation

Following C code segment shows how you can create records in COMPANY table created in the above example:

```

#include <stdio.h>
#include <stdlib.h>
#include <sqlite3.h>

```

```

static int callback(void *NotUsed, int argc, char **argv, char **azColName){
    int i;
    for(i=0; i<argc; i++){
        printf("%s = %s\n", azColName[i], argv[i] ? argv[i] : "NULL");
    }
    printf("\n");
    return 0;
}

int main(int argc, char* argv[])
{
    sqlite3 *db;
    char *zErrMsg = 0;
    int rc;
    char *sql;

    /* Open database */
    rc = sqlite3_open("test.db", &db);
    if( rc ){
        fprintf(stderr, "Can't open database: %s\n", sqlite3_errmsg(db));
        return(0);
    }else{
        fprintf(stderr, "Opened database successfully\n");
    }

    /* Create SQL statement */
    sql = "INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY) " \
        "VALUES (1, 'Paul', 32, 'California', 20000.00 );" \
        "INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY) " \
        "VALUES (2, 'Allen', 25, 'Texas', 15000.00 );" \
        "INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)" \
        "VALUES (3, 'Teddy', 23, 'Norway', 20000.00 );" \
        "INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)" \
        "VALUES (4, 'Mark', 25, 'Rich-Mond ', 65000.00 );";

    /* Execute SQL statement */
    rc = sqlite3_exec(db, sql, callback, 0, &zErrMsg);
    if( rc != SQLITE_OK ){

```

```

        fprintf(stderr, "SQL error: %s\n", zErrMsg);
        sqlite3_free(zErrMsg);
    }else{
        fprintf(stdout, "Records created successfully\n");
    }
    sqlite3_close(db);
    return 0;
}

```

When the above program is compiled and executed, it will create the given records in COMPANY table and will display the following two lines:

```

Opened database successfully
Records created successfully

```

SELECT Operation

Before proceeding with actual example to fetch records, let us look at some detail about the callback function, which we are using in our examples. This callback provides a way to obtain results from SELECT statements. It has the following declaration:

```

typedef int (*sqlite3_callback)(
void*,      /* Data provided in the 4th argument of sqlite3_exec() */
int,        /* The number of columns in row */
char**,     /* An array of strings representing fields in the row */
char**      /* An array of strings representing column names */
);

```

If the above callback is provided in `sqlite3_exec()` routine as the third argument, SQLite will call this callback function for each record processed in each SELECT statement executed within the SQL argument.

Following C code segment shows how you can fetch and display records from the COMPANY table created in the above example.

```

#include <stdio.h>
#include <stdlib.h>
#include <sqlite3.h>

static int callback(void *data, int argc, char **argv, char **azColName){
    int i;
    fprintf(stderr, "%s: ", (const char*)data);
    for(i=0; i<argc; i++){
        printf("%s = %s\n", azColName[i], argv[i] ? argv[i] : "NULL");
    }
}

```



```

    }
    printf("\n");
    return 0;
}

int main(int argc, char* argv[])
{
    sqlite3 *db;
    char *zErrMsg = 0;
    int rc;
    char *sql;
    const char* data = "Callback function called";

    /* Open database */
    rc = sqlite3_open("test.db", &db);
    if( rc ){
        fprintf(stderr, "Can't open database: %s\n", sqlite3_errmsg(db));
        return(0);
    }else{
        fprintf(stderr, "Opened database successfully\n");
    }
    /* Create SQL statement */
    sql = "SELECT * from COMPANY";

    /* Execute SQL statement */
    rc = sqlite3_exec(db, sql, callback, (void*)data, &zErrMsg);
    if( rc != SQLITE_OK ){
        fprintf(stderr, "SQL error: %s\n", zErrMsg);
        sqlite3_free(zErrMsg);
    }else{
        fprintf(stdout, "Operation done successfully\n");
    }
    sqlite3_close(db);
    return 0;
}

```

When the above program is compiled and executed, it will produce the following result.

```

Opened database successfully
Callback function called: ID = 1

```

```

NAME = Paul
AGE = 32
ADDRESS = California
SALARY = 20000.0

Callback function called: ID = 2
NAME = Allen
AGE = 25
ADDRESS = Texas
SALARY = 15000.0

Callback function called: ID = 3
NAME = Teddy
AGE = 23
ADDRESS = Norway
SALARY = 20000.0

Callback function called: ID = 4
NAME = Mark
AGE = 25
ADDRESS = Rich-Mond
SALARY = 65000.0

Operation done successfully

```

UPDATE Operation

Following C code segment shows how we can use UPDATE statement to update any record and then fetch and display updated records from the COMPANY table.

```

#include <stdio.h>
#include <stdlib.h>
#include <sqlite3.h>

static int callback(void *data, int argc, char **argv, char **azColName){
    int i;
    fprintf(stderr, "%s: ", (const char*)data);
    for(i=0; i<argc; i++){
        printf("%s = %s\n", azColName[i], argv[i] ? argv[i] : "NULL");
    }
}

```

```

    }
    printf("\n");
    return 0;
}

int main(int argc, char* argv[])
{
    sqlite3 *db;
    char *zErrMsg = 0;
    int rc;
    char *sql;
    const char* data = "Callback function called";

    /* Open database */
    rc = sqlite3_open("test.db", &db);
    if( rc ){
        fprintf(stderr, "Can't open database: %s\n", sqlite3_errmsg(db));
        return(0);
    }else{
        fprintf(stderr, "Opened database successfully\n");
    }

    /* Create merged SQL statement */
    sql = "UPDATE COMPANY set SALARY = 25000.00 where ID=1; " \
        "SELECT * from COMPANY";

    /* Execute SQL statement */
    rc = sqlite3_exec(db, sql, callback, (void*)data, &zErrMsg);
    if( rc != SQLITE_OK ){
        fprintf(stderr, "SQL error: %s\n", zErrMsg);
        sqlite3_free(zErrMsg);
    }else{
        fprintf(stdout, "Operation done successfully\n");
    }
    sqlite3_close(db);
    return 0;
}

```

When the above program is compiled and executed, it will produce the following result.

```
Opened database successfully
Callback function called: ID = 1
NAME = Paul
AGE = 32
ADDRESS = California
SALARY = 25000.0

Callback function called: ID = 2
NAME = Allen
AGE = 25
ADDRESS = Texas
SALARY = 15000.0

Callback function called: ID = 3
NAME = Teddy
AGE = 23
ADDRESS = Norway
SALARY = 20000.0

Callback function called: ID = 4
NAME = Mark
AGE = 25
ADDRESS = Rich-Mond
SALARY = 65000.0

Operation done successfully
```

DELETE Operation

Following C code segment shows how you can use DELETE statement to delete any record and then fetch and display the remaining records from the COMPANY table.

```
#include <stdio.h>
#include <stdlib.h>
#include <sqlite3.h>
```

```

static int callback(void *data, int argc, char **argv, char **azColName){
    int i;
    fprintf(stderr, "%s: ", (const char*)data);
    for(i=0; i<argc; i++){
        printf("%s = %s\n", azColName[i], argv[i] ? argv[i] : "NULL");
    }
    printf("\n");
    return 0;
}

int main(int argc, char* argv[])
{
    sqlite3 *db;
    char *zErrMsg = 0;
    int rc;
    char *sql;
    const char* data = "Callback function called";

    /* Open database */
    rc = sqlite3_open("test.db", &db);
    if( rc ){
        fprintf(stderr, "Can't open database: %s\n", sqlite3_errmsg(db));
        return(0);
    }else{
        fprintf(stderr, "Opened database successfully\n");
    }

    /* Create merged SQL statement */
    sql = "DELETE from COMPANY where ID=2; " \
        "SELECT * from COMPANY";

    /* Execute SQL statement */
    rc = sqlite3_exec(db, sql, callback, (void*)data, &zErrMsg);
    if( rc != SQLITE_OK ){
        fprintf(stderr, "SQL error: %s\n", zErrMsg);
        sqlite3_free(zErrMsg);
    }
}

```

```
}else{  
    fprintf(stdout, "Operation done successfully\n");  
}  
sqlite3_close(db);  
return 0;  
}
```

When the above program is compiled and executed, it will produce the following result.

```
Opened database successfully  
Callback function called: ID = 1  
NAME = Paul  
AGE = 32  
ADDRESS = California  
SALARY = 20000.0  
  
Callback function called: ID = 3  
NAME = Teddy  
AGE = 23  
ADDRESS = Norway  
SALARY = 20000.0  
  
Callback function called: ID = 4  
NAME = Mark  
AGE = 25  
ADDRESS = Rich-Mond  
SALARY = 65000.0  
  
Operation done successfully
```

47. SQLite – Java

In this chapter, you will learn how to use SQLite in Java programs.

Installation

Before you start using SQLite in your Java programs, you need to make sure that you have SQLite JDBC Driver and Java set up on the machine. You can check Java tutorial for Java installation on your machine. Now, let us check how to set up SQLite JDBC driver.

Step 1: Download latest version of `sqlite-jdbc-(VERSION).jar` from [sqlite-jdbc](#) repository.

Step 2: Add downloaded jar file `sqlite-jdbc-(VERSION).jar` in your class path, or you can use it along with `-classpath` option as explained in the following examples.

Following section assumes you have little knowledge about Java JDBC concepts. If you don't, then it is suggested to spent half an hour with [JDBC Tutorial](#) to become comfortable with the concepts explained below.

Connect to Database

Following Java programs show how to connect to an existing database. If the database does not exist, then it will be created and finally a database object will be returned.

```
import java.sql.*;
public class SQLiteJDBC
{
    public static void main( String args[] )
    {
        Connection c = null;
        try {
            Class.forName("org.sqlite.JDBC");
            c = DriverManager.getConnection("jdbc:sqlite:test.db");
        } catch ( Exception e ) {
            System.err.println( e.getClass().getName() + ": " + e.getMessage() );
            System.exit(0);
        }
        System.out.println("Opened database successfully");
    }
}
```

Now, let's compile and run the above program to create our database **test.db** in the current directory. You can change your path as per your requirement. We are assuming the current version of JDBC driver *sqlite-jdbc-3.7.2.jar* is available in the current path.

```
$javac SQLiteJDBC.java
$java -classpath ".:sqlite-jdbc-3.7.2.jar" SQLiteJDBC
Open database successfully
```

If you are going to use Windows machine, then you can compile and run your code as follows:

```
$javac SQLiteJDBC.java
$java -classpath ".;sqlite-jdbc-3.7.2.jar" SQLiteJDBC
Opened database successfully
```

Create a Table

Following Java program will be used to create a table in the previously created database.

```
import java.sql.*;

public class SQLiteJDBC
{
    public static void main( String args[] )
    {
        Connection c = null;
        Statement stmt = null;
        try {
            Class.forName("org.sqlite.JDBC");
            c = DriverManager.getConnection("jdbc:sqlite:test.db");
            System.out.println("Opened database successfully");

            stmt = c.createStatement();
            String sql = "CREATE TABLE COMPANY " +
                "(ID INT PRIMARY KEY     NOT NULL," +
                " NAME           TEXT     NOT NULL, " +
                " AGE            INT       NOT NULL, " +
                " ADDRESS        CHAR(50), " +
                " SALARY          REAL)";
            stmt.executeUpdate(sql);
            stmt.close();
        }
        catch (Exception e) {
            System.out.println(e);
        }
    }
}
```



```

        c.close();
    } catch ( Exception e ) {
        System.err.println( e.getClass().getName() + ": " + e.getMessage() );
        System.exit(0);
    }
    System.out.println("Table created successfully");
}
}

```

When the above program is compiled and executed, it will create COMPANY table in your **test.db** and final listing of the file will be as follows:

```

-rw-r--r--. 1 root root 3201128 Jan 22 19:04 sqlite-jdbc-3.7.2.jar
-rw-r--r--. 1 root root    1506 May  8 05:43 SQLiteJDBC.class
-rw-r--r--. 1 root root     832 May  8 05:42 SQLiteJDBC.java
-rw-r--r--. 1 root root    3072 May  8 05:43 test.db

```

INSERT Operation

Following Java program shows how to create records in the COMPANY table created in above example.

```

import java.sql.*;

public class SQLiteJDBC
{
    public static void main( String args[] )
    {
        Connection c = null;
        Statement stmt = null;
        try {
            Class.forName("org.sqlite.JDBC");
            c = DriverManager.getConnection("jdbc:sqlite:test.db");
            c.setAutoCommit(false);
            System.out.println("Opened database successfully");

            stmt = c.createStatement();
            String sql = "INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY) " +
                "VALUES (1, 'Paul', 32, 'California', 20000.00 );";
            stmt.executeUpdate(sql);

```

```

        sql = "INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY) " +
              "VALUES (2, 'Allen', 25, 'Texas', 15000.00 );";
        stmt.executeUpdate(sql);

        sql = "INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY) " +
              "VALUES (3, 'Teddy', 23, 'Norway', 20000.00 );";
        stmt.executeUpdate(sql);

        sql = "INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY) " +
              "VALUES (4, 'Mark', 25, 'Rich-Mond ', 65000.00 );";
        stmt.executeUpdate(sql);

        stmt.close();
        c.commit();
        c.close();
    } catch ( Exception e ) {
        System.err.println( e.getClass().getName() + ": " + e.getMessage() );
        System.exit(0);
    }
    System.out.println("Records created successfully");
}
}

```

When the above program is compiled and executed, it will create the given records in the COMPANY table and will display the following two lines.

```

Opened database successfully
Records created successfully

```

SELECT Operation

Following Java program shows how to fetch and display records from the COMPANY table created in the above example.

```

import java.sql.*;

public class SQLiteJDBC
{
    public static void main( String args[] )

```

```

{
    Connection c = null;
    Statement stmt = null;
    try {
        Class.forName("org.sqlite.JDBC");
        c = DriverManager.getConnection("jdbc:sqlite:test.db");
        c.setAutoCommit(false);
        System.out.println("Opened database successfully");

        stmt = c.createStatement();
        ResultSet rs = stmt.executeQuery( "SELECT * FROM COMPANY;" );
        while ( rs.next() ) {
            int id = rs.getInt("id");
            String name = rs.getString("name");
            int age = rs.getInt("age");
            String address = rs.getString("address");
            float salary = rs.getFloat("salary");
            System.out.println( "ID = " + id );
            System.out.println( "NAME = " + name );
            System.out.println( "AGE = " + age );
            System.out.println( "ADDRESS = " + address );
            System.out.println( "SALARY = " + salary );
            System.out.println();
        }
        rs.close();
        stmt.close();
        c.close();
    } catch ( Exception e ) {
        System.err.println( e.getClass().getName() + ": " + e.getMessage() );
        System.exit(0);
    }
    System.out.println("Operation done successfully");
}
}

```

When the above program is compiled and executed, it will produce the following result.

```
Opened database successfully
```

```
ID = 1
NAME = Paul
AGE = 32
ADDRESS = California
SALARY = 20000.0

ID = 2
NAME = Allen
AGE = 25
ADDRESS = Texas
SALARY = 15000.0

ID = 3
NAME = Teddy
AGE = 23
ADDRESS = Norway
SALARY = 20000.0

ID = 4
NAME = Mark
AGE = 25
ADDRESS = Rich-Mond
SALARY = 65000.0

Operation done successfully
```

UPDATE Operation

Following Java code shows how to use UPDATE statement to update any record and then fetch and display the updated records from the COMPANY table.

```
import java.sql.*;

public class SQLiteJDBC
{
    public static void main( String args[] )
    {
        Connection c = null;
        Statement stmt = null;
```

```

try {
    Class.forName("org.sqlite.JDBC");
    c = DriverManager.getConnection("jdbc:sqlite:test.db");
    c.setAutoCommit(false);
    System.out.println("Opened database successfully");

    stmt = c.createStatement();
    String sql = "UPDATE COMPANY set SALARY = 25000.00 where ID=1;";
    stmt.executeUpdate(sql);
    c.commit();

    ResultSet rs = stmt.executeQuery( "SELECT * FROM COMPANY;" );
    while ( rs.next() ) {
        int id = rs.getInt("id");
        String name = rs.getString("name");
        int age = rs.getInt("age");
        String address = rs.getString("address");
        float salary = rs.getFloat("salary");
        System.out.println( "ID = " + id );
        System.out.println( "NAME = " + name );
        System.out.println( "AGE = " + age );
        System.out.println( "ADDRESS = " + address );
        System.out.println( "SALARY = " + salary );
        System.out.println();
    }
    rs.close();
    stmt.close();
    c.close();
} catch ( Exception e ) {
    System.err.println( e.getClass().getName() + ": " + e.getMessage() );
    System.exit(0);
}
System.out.println("Operation done successfully");
}
}

```

When the above program is compiled and executed, it will produce the following result.

```

Opened database successfully
ID = 1

```

```
NAME = Paul
AGE = 32
ADDRESS = California
SALARY = 25000.0

ID = 2
NAME = Allen
AGE = 25
ADDRESS = Texas
SALARY = 15000.0

ID = 3
NAME = Teddy
AGE = 23
ADDRESS = Norway
SALARY = 20000.0

ID = 4
NAME = Mark
AGE = 25
ADDRESS = Rich-Mond
SALARY = 65000.0

Operation done successfully
```

DELETE Operation

Following Java code shows how to use DELETE statement to delete any record and then fetch and display the remaining records from the COMPANY table.

```
import java.sql.*;

public class SQLiteJDBC
{
    public static void main( String args[] )
    {
        Connection c = null;
        Statement stmt = null;
        try {
```

```

Class.forName("org.sqlite.JDBC");
c = DriverManager.getConnection("jdbc:sqlite:test.db");
c.setAutoCommit(false);
System.out.println("Opened database successfully");

stmt = c.createStatement();
String sql = "DELETE from COMPANY where ID=2;";
stmt.executeUpdate(sql);
c.commit();

ResultSet rs = stmt.executeQuery( "SELECT * FROM COMPANY;" );
while ( rs.next() ) {
    int id = rs.getInt("id");
    String name = rs.getString("name");
    int age = rs.getInt("age");
    String address = rs.getString("address");
    float salary = rs.getFloat("salary");
    System.out.println( "ID = " + id );
    System.out.println( "NAME = " + name );
    System.out.println( "AGE = " + age );
    System.out.println( "ADDRESS = " + address );
    System.out.println( "SALARY = " + salary );
    System.out.println();
}
rs.close();
stmt.close();
c.close();
} catch ( Exception e ) {
    System.err.println( e.getClass().getName() + ": " + e.getMessage() );
    System.exit(0);
}
System.out.println("Operation done successfully");
}
}

```

When the above program is compiled and executed, it will produce the following result.

```

Opened database successfully
ID = 1
NAME = Paul

```

AGE = 32

ADDRESS = California

SALARY = 25000.0

ID = 3

NAME = Teddy

AGE = 23

ADDRESS = Norway

SALARY = 20000.0

ID = 4

NAME = Mark

AGE = 25

ADDRESS = Rich-Mond

SALARY = 65000.0

Operation done successfully

48. SQLite – PHP

In this chapter, you will learn how to use SQLite in PHP programs.

Installation

SQLite3 extension is enabled by default as of PHP 5.3.0. It's possible to disable it by using **-without-sqlite3** at compile time.

Windows users must enable **php_sqlite3.dll** in order to use this extension. This DLL is included with Windows distributions of PHP as of PHP 5.3.0.

For detailed installation instructions, kindly check our PHP tutorial and its official website.

PHP Interface APIs

Following are important PHP routines which can suffice your requirement to work with SQLite database from your PHP program. If you are looking for a more sophisticated application, then you can look into PHP official documentation.

Sr. No.	API & Description
1	<p>public void SQLite3::open (filename, flags, encryption_key)</p> <p>Opens SQLite 3 Database. If the build includes encryption, then it will attempt to use the key.</p> <p>If the <i>filename</i> is given as ':memory:', SQLite3::open() will create an in-memory database in RAM that lasts only for the duration of the session.</p> <p>If the filename is actual device file name, SQLite3::open() attempts to open the database file by using its value. If no file by that name exists, then a new database file by that name gets created.</p> <p>Optional flags used to determine how to open the SQLite database. By default, open uses SQLITE3_OPEN_READWRITE SQLITE3_OPEN_CREATE.</p>
2	<p>public bool SQLite3::exec (string \$query)</p> <p>This routine provides a quick, easy way to execute SQL commands provided by sql argument, which can consist of more than one SQL command. This routine is used to execute a result-less query against a given database.</p>
3	<p>public SQLite3Result SQLite3::query (string \$query)</p>

	This routine executes an SQL query, returning an SQLite3Result object if the query returns results.
4	public int SQLite3::lastErrorCode (void) This routine returns the numeric result code of the most recent failed SQLite request.
5	public string SQLite3::lastErrorMsg (void) This routine returns English text describing the most recent failed SQLite request.
6	public int SQLite3::changes (void) This routine returns the number of database rows that were updated, inserted, or deleted by the most recent SQL statement.
7	public bool SQLite3::close (void) This routine closes a database connection previously opened by a call to SQLite3::open().
8	public string SQLite3::escapeString (string \$value) This routine returns a string that has been properly escaped for safe inclusion in an SQL statement.

Connect to Database

Following PHP code shows how to connect to an existing database. If database does not exist, then it will be created and finally a database object will be returned.

```
<?php
class MyDB extends SQLite3
{
    function __construct()
    {
        $this->open('test.db');
    }
}
```

```

$db = new MyDB();
if(!$db){
    echo $db->lastErrorMsg();
} else {
    echo "Opened database successfully\n";
}
?>

```

Now, let's run the above program to create our database **test.db** in the current directory. You can change your path as per your requirement. If the database is successfully created, then it will display the following message:

```
Open database successfully
```

Create a Table

Following PHP program will be used to create a table in the previously created database.

```

<?php
class MyDB extends SQLite3
{
    function __construct()
    {
        $this->open('test.db');
    }
}
$db = new MyDB();
if(!$db){
    echo $db->lastErrorMsg();
} else {
    echo "Opened database successfully\n";
}

$sql = <<<<EOF
CREATE TABLE COMPANY
(ID INT PRIMARY KEY     NOT NULL,
NAME           TEXT     NOT NULL,
AGE           INT       NOT NULL,
ADDRESS       CHAR(50),
SALARY        REAL);
EOF;

```

```

$ret = $db->exec($sql);
if(!$ret){
    echo $db->lastErrorMsg();
} else {
    echo "Table created successfully\n";
}
$db->close();
?>

```

When the above program is executed, it will create the COMPANY table in your **test.db** and it will display the following messages:

```

Opened database successfully
Table created successfully

```

INSERT Operation

Following PHP program shows how to create records in the COMPANY table created in the above example.

```

<?php
class MyDB extends SQLite3
{
    function __construct()
    {
        $this->open('test.db');
    }
}
$db = new MyDB();
if(!$db){
    echo $db->lastErrorMsg();
} else {
    echo "Opened database successfully\n";
}

$sql = <<<<EOF
INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
VALUES (1, 'Paul', 32, 'California', 20000.00 );

INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)

```

```

VALUES (2, 'Allen', 25, 'Texas', 15000.00 );

INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
VALUES (3, 'Teddy', 23, 'Norway', 20000.00 );

INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
VALUES (4, 'Mark', 25, 'Rich-Mond ', 65000.00 );
EOF;

$ret = $db->exec($sql);
if(!$ret){
    echo $db->lastErrorMsg();
} else {
    echo "Records created successfully\n";
}
$db->close();
?>

```

When the above program is executed, it will create the given records in the COMPANY table and will display the following two lines.

```

Opened database successfully
Records created successfully

```

SELECT Operation

Following PHP program shows how to fetch and display records from the COMPANY table created in the above example.

```

<?php
class MyDB extends SQLite3
{
    function __construct()
    {
        $this->open('test.db');
    }
}
$db = new MyDB();
if(!$db){
    echo $db->lastErrorMsg();
} else {

```

```

        echo "Opened database successfully\n";
    }

    $sql = <<<EOF
        SELECT * from COMPANY;
    EOF;

    $ret = $db->query($sql);
    while($row = $ret->fetchArray(SQLITE3_ASSOC) ){
        echo "ID = ". $row['ID'] . "\n";
        echo "NAME = ". $row['NAME'] . "\n";
        echo "ADDRESS = ". $row['ADDRESS'] . "\n";
        echo "SALARY = ". $row['SALARY'] . "\n\n";
    }
    echo "Operation done successfully\n";
    $db->close();
?>

```

When the above program is executed, it will produce the following result.

```

Opened database successfully
ID = 1
NAME = Paul
ADDRESS = California
SALARY = 20000

ID = 2
NAME = Allen
ADDRESS = Texas
SALARY = 15000

ID = 3
NAME = Teddy
ADDRESS = Norway
SALARY = 20000

ID = 4
NAME = Mark
ADDRESS = Rich-Mond

```

```
SALARY = 65000
```

```
Operation done successfully
```

UPDATE Operation

Following PHP code shows how to use UPDATE statement to update any record and then fetch and display the updated records from the COMPANY table.

```
<?php
class MyDB extends SQLite3
{
    function __construct()
    {
        $this->open('test.db');
    }
}
$db = new MyDB();
if(!$db){
    echo $db->lastErrorMsg();
} else {
    echo "Opened database successfully\n";
}

$sql =<<<EOF
    UPDATE COMPANY set SALARY = 25000.00 where ID=1;
EOF;

$ret = $db->exec($sql);
if(!$ret){
    echo $db->lastErrorMsg();
} else {
    echo $db->changes(), " Record updated successfully\n";
}

$sql =<<<EOF
    SELECT * from COMPANY;
EOF;

$ret = $db->query($sql);
while($row = $ret->fetchArray(SQLITE3_ASSOC) ){
```

```
        echo "ID = ". $row['ID'] . "\n";
        echo "NAME = ". $row['NAME'] . "\n";
        echo "ADDRESS = ". $row['ADDRESS'] . "\n";
        echo "SALARY = ". $row['SALARY'] . "\n\n";
    }
    echo "Operation done successfully\n";
    $db->close();
?>
```

When the above program is executed, it will produce the following result.

```
Opened database successfully
1 Record updated successfully
ID = 1
NAME = Paul
ADDRESS = California
SALARY = 25000

ID = 2
NAME = Allen
ADDRESS = Texas
SALARY = 15000

ID = 3
NAME = Teddy
ADDRESS = Norway
SALARY = 20000

ID = 4
NAME = Mark
ADDRESS = Rich-Mond
SALARY = 65000

Operation done successfully
```

DELETE Operation

Following PHP code shows how to use DELETE statement to delete any record and then fetch and display the remaining records from the COMPANY table.


```

<?php
class MyDB extends SQLite3
{
    function __construct()
    {
        $this->open('test.db');
    }
}
$db = new MyDB();
if(!$db){
    echo $db->lastErrorMsg();
} else {
    echo "Opened database successfully\n";
}
$sql = <<<EOF
    DELETE from COMPANY where ID=2;
EOF;
$ret = $db->exec($sql);
if(!$ret){
    echo $db->lastErrorMsg();
} else {
    echo $db->changes(), " Record deleted successfully\n";
}

$sql = <<<EOF
    SELECT * from COMPANY;
EOF;
$ret = $db->query($sql);
while($row = $ret->fetchArray(SQLITE3_ASSOC) ){
    echo "ID = ". $row['ID'] . "\n";
    echo "NAME = ". $row['NAME'] . "\n";
    echo "ADDRESS = ". $row['ADDRESS'] . "\n";
    echo "SALARY = ". $row['SALARY'] . "\n\n";
}
echo "Operation done successfully\n";
$db->close();

```

```
?>
```

When the above program is executed, it will produce the following result.

```
Opened database successfully
1 Record deleted successfully
ID = 1
NAME = Paul
ADDRESS = California
SALARY = 25000

ID = 3
NAME = Teddy
ADDRESS = Norway
SALARY = 20000

ID = 4
NAME = Mark
ADDRESS = Rich-Mond
SALARY = 65000

Operation done successfully
```

49. SQLite – Perl

In this chapter, you will learn how to use SQLite in Perl programs.

Installation

SQLite3 can be integrated with Perl using Perl DBI module, which is a database access module for the Perl programming language. It defines a set of methods, variables, and conventions that provide a standard database interface.

Following are simple steps to install DBI module on your Linux/UNIX machine:

```
$ wget http://search.cpan.org/CPAN/authors/id/T/TI/TIMB/DBI-1.625.tar.gz
$ tar xvfz DBI-1.625.tar.gz
$ cd DBI-1.625
$ perl Makefile.PL
$ make
$ make install
```

If you need to install SQLite driver for DBI, then it can be installed as follows:

```
$ wget http://search.cpan.org/CPAN/authors/id/M/MS/MSERGEANT/DBD-SQLite-1.11.tar.gz
$ tar xvfz DBD-SQLite-1.11.tar.gz
$ cd DBD-SQLite-1.11
$ perl Makefile.PL
$ make
$ make install
```

DBI Interface APIs

Following are important DBI routines, which can suffice your requirement to work with SQLite database from your Perl program. If you are looking for a more sophisticated application, then you can look into Perl DBI official documentation.

Sr. No.	API & Description
1	<p>DBI->connect(\$data_source, "", "", \%attr)</p> <p>Establishes a database connection, or session, to the requested \$data_source. Returns a database handle object if the connection succeeds.</p> <p>Datasource has the form like: DBI:SQLite:dbname='test.db' where SQLite is SQLite driver name and test.db is the name of SQLite database file. If the filename is given as ':memory:', it will create an in-memory database in RAM that lasts only for the duration of the session.</p> <p>If the filename is actual device file name, then it attempts to open the database file by using its value. If no file by that name exists, then a new database file by that name gets created.</p> <p>You keep second and third parameter as blank strings and the last parameter is to pass various attributes as shown in the following example.</p>
2	<p>\$dbh->do(\$sql)</p> <p>This routine prepares and executes a single SQL statement. Returns the number of rows affected or undef on error. A return value of -1 means the number of rows is not known, not applicable, or not available. Here, \$dbh is a handle returned by DBI->connect() call.</p>
3	<p>\$dbh->prepare(\$sql)</p> <p>This routine prepares a statement for later execution by the database engine and returns a reference to a statement handle object.</p>
4	<p>\$sth->execute()</p> <p>This routine performs whatever processing is necessary to execute the prepared statement. An undef is returned if an error occurs. A successful execute always returns true regardless of the number of rows affected. Here, \$sth is a statement handle returned by \$dbh->prepare(\$sql) call.</p>
5	<p>\$sth->fetchrow_array()</p> <p>This routine fetches the next row of data and returns it as a list containing the field values. Null fields are returned as undef values in the list.</p>

6	\$DBI::err This is equivalent to <code>\$h->err</code> , where <code>\$h</code> is any of the handle types like <code>\$dbh</code> , <code>\$sth</code> , or <code>\$drh</code> . This returns native database engine error code from the last driver method called.
7	\$DBI::errstr This is equivalent to <code>\$h->errstr</code> , where <code>\$h</code> is any of the handle types like <code>\$dbh</code> , <code>\$sth</code> , or <code>\$drh</code> . This returns the native database engine error message from the last DBI method called.
8	\$dbh->disconnect() This routine closes a database connection previously opened by a call to <code>DBI->connect()</code> .

Connect to Database

Following Perl code shows how to connect to an existing database. If the database does not exist, then it will be created and finally a database object will be returned.

```
#!/usr/bin/perl

use DBI;
use strict;

my $driver    = "SQLite";
my $database  = "test.db";
my $dsn       = "DBI:$driver:dbname=$database";
my $userid    = "";
my $password  = "";
my $dbh       = DBI->connect($dsn, $userid, $password, { RaiseError => 1 })
                  or die $DBI::errstr;

print "Opened database successfully\n";
```

Now, let's run the above program to create our database `test.db` in the current directory. You can change your path as per your requirement. Keep the above code in `sqlite.pl` file and execute it as shown below. If the database is successfully created, then it will display the following message:

```
$ chmod +x sqlite.pl
$ ./sqlite.pl
Open database successfully
```

Create a Table

Following Perl program is used to create a table in the previously created database.

```
#!/usr/bin/perl

use DBI;
use strict;

my $driver    = "SQLite";
my $database  = "test.db";
my $dsn       = "DBI:$driver:dbname=$database";
my $userid    = "";
my $password  = "";
my $dbh       = DBI->connect($dsn, $userid, $password, { RaiseError => 1 })
                or die $DBI::errstr;

print "Opened database successfully\n";

my $stmt = qq(CREATE TABLE COMPANY
              (ID INT PRIMARY KEY     NOT NULL,
               NAME           TEXT     NOT NULL,
               AGE            INT      NOT NULL,
               ADDRESS        CHAR(50),
               SALARY         REAL));
my $rv = $dbh->do($stmt);
if($rv < 0){
    print $DBI::errstr;
} else {
    print "Table created successfully\n";
}
$dbh->disconnect();
```

When the above program is executed, it will create COMPANY table in your test.db and it will display the following messages:

```
Opened database successfully
Table created successfully
```

Note: In case you see the following error in any of the operation:

```
DBD::SQLite::st execute failed: not an error(21) at dbdimp.c line 398
```

In such case, open **dbdimp.c** file available in DBD-SQLite installation and find out **sqlite3_prepare()** function and change its third argument to **-1** instead of **0**. Finally, install DBD::SQLite using **make** and do **make install** to resolve the problem.

INSERT Operation

Following Perl program shows how to create records in the COMPANY table created in the above example.

```
#!/usr/bin/perl

use DBI;
use strict;

my $driver   = "SQLite";
my $database = "test.db";
my $dsn = "DBI:$driver:dbname=$database";
my $userid = "";
my $password = "";
my $dbh = DBI->connect($dsn, $userid, $password, { RaiseError => 1 })
    or die $DBI::errstr;
print "Opened database successfully\n";

my $stmt = qq(INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
    VALUES (1, 'Paul', 32, 'California', 20000.00 ));
my $rv = $dbh->do($stmt) or die $DBI::errstr;

$stmt = qq(INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
    VALUES (2, 'Allen', 25, 'Texas', 15000.00 ));
$rv = $dbh->do($stmt) or die $DBI::errstr;

$stmt = qq(INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
```

```

VALUES (3, 'Teddy', 23, 'Norway', 20000.00 ));
$rv = $dbh->do($stmt) or die $DBI::errstr;

$stmt = qq(INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY)
VALUES (4, 'Mark', 25, 'Rich-Mond ', 65000.00 ));
$rv = $dbh->do($stmt) or die $DBI::errstr;

print "Records created successfully\n";
$dbh->disconnect();

```

When the above program is executed, it will create the given records in the COMPANY table and it will display the following two lines:

```

Opened database successfully
Records created successfully

```

SELECT Operation

Following Perl program shows how to fetch and display records from the COMPANY table created in the above example.

```

#!/usr/bin/perl

use DBI;
use strict;

my $driver  = "SQLite";
my $database = "test.db";
my $dsn = "DBI:$driver:dbname=$database";
my $userid = "";
my $password = "";
my $dbh = DBI->connect($dsn, $userid, $password, { RaiseError => 1 })
                or die $DBI::errstr;
print "Opened database successfully\n";

my $stmt = qq(SELECT id, name, address, salary  from COMPANY);
my $sth = $dbh->prepare( $stmt );
my $rv = $sth->execute() or die $DBI::errstr;
if($rv < 0){
    print $DBI::errstr;
}

```



```
}  
while(my @row = $sth->fetchrow_array()) {  
    print "ID = ". $row[0] . "\n";  
    print "NAME = ". $row[1] . "\n";  
    print "ADDRESS = ". $row[2] . "\n";  
    print "SALARY = ". $row[3] . "\n\n";  
}  
print "Operation done successfully\n";  
$dbh->disconnect();
```

When the above program is executed, it will produce the following result.

```
Opened database successfully  
ID = 1  
NAME = Paul  
ADDRESS = California  
SALARY = 20000  
  
ID = 2  
NAME = Allen  
ADDRESS = Texas  
SALARY = 15000  
  
ID = 3  
NAME = Teddy  
ADDRESS = Norway  
SALARY = 20000  
  
ID = 4  
NAME = Mark  
ADDRESS = Rich-Mond  
SALARY = 65000  
  
Operation done successfully
```

UPDATE Operation

Following Perl code shows how to use UPDATE statement to update any record and then fetch and display the updated records from the COMPANY table.

```
#!/usr/bin/perl

use DBI;
use strict;

my $driver    = "SQLite";
my $database  = "test.db";
my $dsn       = "DBI:$driver:dbname=$database";
my $userid    = "";
my $password  = "";
my $dbh       = DBI->connect($dsn, $userid, $password, { RaiseError => 1 })
                or die $DBI::errstr;
print "Opened database successfully\n";

my $stmt = qq(UPDATE COMPANY set SALARY = 25000.00 where ID=1;);
my $rv = $dbh->do($stmt) or die $DBI::errstr;
if( $rv < 0 ){
    print $DBI::errstr;
}else{
    print "Total number of rows updated : $rv\n";
}
$stmt = qq(SELECT id, name, address, salary  from COMPANY;);
my $sth = $dbh->prepare( $stmt );
$rv = $sth->execute() or die $DBI::errstr;
if($rv < 0){
    print $DBI::errstr;
}
while(my @row = $sth->fetchrow_array()) {
    print "ID = ". $row[0] . "\n";
    print "NAME = ". $row[1] . "\n";
    print "ADDRESS = ". $row[2] . "\n";
    print "SALARY = ". $row[3] . "\n\n";
}
}
```

```
print "Operation done successfully\n";  
$dbh->disconnect();
```

When the above program is executed, it will produce the following result.

```
Opened database successfully  
Total number of rows updated : 1  
ID = 1  
NAME = Paul  
ADDRESS = California  
SALARY = 25000  
  
ID = 2  
NAME = Allen  
ADDRESS = Texas  
SALARY = 15000  
  
ID = 3  
NAME = Teddy  
ADDRESS = Norway  
SALARY = 20000  
  
ID = 4  
NAME = Mark  
ADDRESS = Rich-Mond  
SALARY = 65000  
  
Operation done successfully
```

DELETE Operation

Following Perl code shows how to use DELETE statement to delete any record and then fetch and display the remaining records from the COMPANY table.

```
#!/usr/bin/perl  
  
use DBI;  
use strict;
```

```

my $driver    = "SQLite";
my $database  = "test.db";
my $dsn       = "DBI:$driver:dbname=$database";
my $userid    = "";
my $password  = "";
my $dbh       = DBI->connect($dsn, $userid, $password, { RaiseError => 1 })
                or die $DBI::errstr;
print "Opened database successfully\n";

my $stmt      = qq(DELETE from COMPANY where ID=2;);
my $rv        = $dbh->do($stmt) or die $DBI::errstr;
if( $rv < 0 ){
    print $DBI::errstr;
}else{
    print "Total number of rows deleted : $rv\n";
}
$stmt = qq(SELECT id, name, address, salary  from COMPANY;);
my $sth       = $dbh->prepare( $stmt );
$rv = $sth->execute() or die $DBI::errstr;
if($rv < 0){
    print $DBI::errstr;
}
while(my @row = $sth->fetchrow_array()) {
    print "ID = ". $row[0] . "\n";
    print "NAME = ". $row[1] . "\n";
    print "ADDRESS = ". $row[2] . "\n";
    print "SALARY = ". $row[3] . "\n\n";
}
print "Operation done successfully\n";
$dbh->disconnect();

```

When the above program is executed, it will produce the following result.

```
Opened database successfully
Total number of rows deleted : 1
ID = 1
NAME = Paul
ADDRESS = California
SALARY = 25000

ID = 3
NAME = Teddy
ADDRESS = Norway
SALARY = 20000

ID = 4
NAME = Mark
ADDRESS = Rich-Mond
SALARY = 65000

Operation done successfully
```

50. SQLite – Python

In this chapter, you will learn how to use SQLite in Python programs.

Installation

SQLite3 can be integrated with Python using `sqlite3` module, which was written by Gerhard Haring. It provides an SQL interface compliant with the DB-API 2.0 specification described by PEP 249. You do not need to install this module separately because it is shipped by default along with Python version 2.5.x onwards.

To use `sqlite3` module, you must first create a connection object that represents the database and then optionally you can create a cursor object, which will help you in executing all the SQL statements.

Python `sqlite3` module APIs

Following are important `sqlite3` module routines, which can suffice your requirement to work with SQLite database from your Python program. If you are looking for a more sophisticated application, then you can look into Python `sqlite3` module's official documentation.

Sr. No.	API & Description
1	<p><code>sqlite3.connect(database [,timeout ,other optional arguments])</code></p> <p>This API opens a connection to the SQLite database file. You can use "<code>:memory:</code>" to open a database connection to a database that resides in RAM instead of on disk. If database is opened successfully, it returns a connection object.</p> <p>When a database is accessed by multiple connections, and one of the processes modifies the database, the SQLite database is locked until that transaction is committed. The timeout parameter specifies how long the connection should wait for the lock to go away until raising an exception. The default for the timeout parameter is 5.0 (five seconds).</p> <p>If the given database name does not exist, then this call will create the database. You can specify filename with the required path as well if you want to create a database anywhere else except in the current directory.</p>

2	<p>connection.cursor([cursorClass])</p> <p>This routine creates a cursor which will be used throughout of your database programming with Python. This method accepts a single optional parameter cursorClass. If supplied, this must be a custom cursor class that extends sqlite3.Cursor.</p>
3	<p>cursor.execute(sql [, optional parameters])</p> <p>This routine executes an SQL statement. The SQL statement may be parameterized (i.e., placeholders instead of SQL literals). The sqlite3 module supports two kinds of placeholders: question marks and named placeholders (named style).</p> <p>For example: cursor.execute("insert into people values (?, ?)", (who, age))</p>
4	<p>connection.execute(sql [, optional parameters])</p> <p>This routine is a shortcut of the above execute method provided by the cursor object and it creates an intermediate cursor object by calling the cursor method, then calls the cursor's execute method with the parameters given.</p>
5	<p>cursor.executemany(sql, seq_of_parameters)</p> <p>This routine executes an SQL command against all parameter sequences or mappings found in the sequence sql.</p>
6	<p>connection.executemany(sql[, parameters])</p> <p>This routine is a shortcut that creates an intermediate cursor object by calling the cursor method, then calls the cursor's executemany method with the parameters given.</p>
7	<p>cursor.executescript(sql_script)</p> <p>This routine executes multiple SQL statements at once provided in the form of script. It issues a COMMIT statement first, then executes the SQL script it gets as a parameter. All the SQL statements should be separated by a semicolon (;).</p>

8	<p>connection.executescript(sql_script)</p> <p>This routine is a shortcut that creates an intermediate cursor object by calling the cursor method, then calls the cursor's executescript method with the parameters given.</p>
9	<p>connection.total_changes()</p> <p>This routine returns the total number of database rows that have been modified, inserted, or deleted since the database connection was opened.</p>
10	<p>connection.commit()</p> <p>This method commits the current transaction. If you don't call this method, anything you did since the last call to commit() is not visible from other database connections.</p>
11	<p>connection.rollback()</p> <p>This method rolls back any changes to the database since the last call to commit().</p>
12	<p>connection.close()</p> <p>This method closes the database connection. Note that this does not automatically call commit(). If you just close your database connection without calling commit() first, your changes will be lost!</p>
13	<p>cursor.fetchone()</p> <p>This method fetches the next row of a query result set, returning a single sequence, or None when no more data is available.</p>
14	<p>cursor.fetchmany([size=cursor.arraysize])</p> <p>This routine fetches the next set of rows of a query result, returning a list. An empty list is returned when no more rows are available. The method tries to fetch as many rows as indicated by the size parameter.</p>
15	<p>cursor.fetchall()</p> <p>This routine fetches all (remaining) rows of a query result, returning a list. An empty list is returned when no rows are available.</p>

Connect to Database

Following Python code shows how to connect to an existing database. If the database does not exist, then it will be created and finally a database object will be returned.

```
#!/usr/bin/python

import sqlite3

conn = sqlite3.connect('test.db')

print "Opened database successfully";
```

Here, you can also supply database name as the special name **:memory:** to create a database in RAM. Now, let's run the above program to create our database **test.db** in the current directory. You can change your path as per your requirement. Keep the above code in **sqlite.py file** and execute it as shown below. If the database is successfully created, then it will display the following message.

```
$chmod +x sqlite.py
$./sqlite.py
Open database successfully
```

Create a Table

Following Python program will be used to create a table in the previously created database.

```
#!/usr/bin/python

import sqlite3

conn = sqlite3.connect('test.db')
print "Opened database successfully";

conn.execute('''CREATE TABLE COMPANY
              (ID INT PRIMARY KEY     NOT NULL,
               NAME           TEXT     NOT NULL,
               AGE            INT      NOT NULL,
               ADDRESS        CHAR(50),
               SALARY         REAL);''')
print "Table created successfully";
conn.close()
```

When the above program is executed, it will create the COMPANY table in your **test.db** and it will display the following messages:

```
Opened database successfully
Table created successfully
```

INSERT Operation

Following Python program shows how to create records in the COMPANY table created in the above example.

```
#!/usr/bin/python

import sqlite3

conn = sqlite3.connect('test.db')
print "Opened database successfully";

conn.execute("INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY) \
VALUES (1, 'Paul', 32, 'California', 20000.00 );");

conn.execute("INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY) \
VALUES (2, 'Allen', 25, 'Texas', 15000.00 );");

conn.execute("INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY) \
VALUES (3, 'Teddy', 23, 'Norway', 20000.00 );");

conn.execute("INSERT INTO COMPANY (ID,NAME,AGE,ADDRESS,SALARY) \
VALUES (4, 'Mark', 25, 'Rich-Mond ', 65000.00 );");

conn.commit()
print "Records created successfully";
conn.close()
```

When the above program is executed, it will create the given records in the COMPANY table and it will display the following two lines:

```
Opened database successfully
Records created successfully
```

SELECT Operation

Following Python program shows how to fetch and display records from the COMPANY table created in the above example.

```
#!/usr/bin/python

import sqlite3

conn = sqlite3.connect('test.db')
print "Opened database successfully";

cursor = conn.execute("SELECT id, name, address, salary  from COMPANY")
for row in cursor:
    print "ID = ", row[0]
    print "NAME = ", row[1]
    print "ADDRESS = ", row[2]
    print "SALARY = ", row[3], "\n"

print "Operation done successfully";
conn.close()
```

When the above program is executed, it will produce the following result.

```
Opened database successfully
ID =  1
NAME =  Paul
ADDRESS =  California
SALARY =  20000.0

ID =  2
NAME =  Allen
ADDRESS =  Texas
SALARY =  15000.0

ID =  3
NAME =  Teddy
ADDRESS =  Norway
SALARY =  20000.0
```

```
ID = 4
NAME = Mark
ADDRESS = Rich-Mond
SALARY = 65000.0

Operation done successfully
```

UPDATE Operation

Following Python code shows how to use UPDATE statement to update any record and then fetch and display the updated records from the COMPANY table.

```
#!/usr/bin/python

import sqlite3

conn = sqlite3.connect('test.db')
print "Opened database successfully";

conn.execute("UPDATE COMPANY set SALARY = 25000.00 where ID=1")
conn.commit
print "Total number of rows updated :", conn.total_changes

cursor = conn.execute("SELECT id, name, address, salary from COMPANY")
for row in cursor:
    print "ID = ", row[0]
    print "NAME = ", row[1]
    print "ADDRESS = ", row[2]
    print "SALARY = ", row[3], "\n"

print "Operation done successfully";
conn.close()
```

When the above program is executed, it will produce the following result.

```
Opened database successfully
Total number of rows updated : 1
ID = 1
NAME = Paul
```

```
ADDRESS = California
```

```
SALARY = 25000.0
```

```
ID = 2
```

```
NAME = Allen
```

```
ADDRESS = Texas
```

```
SALARY = 15000.0
```

```
ID = 3
```

```
NAME = Teddy
```

```
ADDRESS = Norway
```

```
SALARY = 20000.0
```

```
ID = 4
```

```
NAME = Mark
```

```
ADDRESS = Rich-Mond
```

```
SALARY = 65000.0
```

```
Operation done successfully
```

DELETE Operation

Following Python code shows how to use DELETE statement to delete any record and then fetch and display the remaining records from the COMPANY table.

```
#!/usr/bin/python

import sqlite3

conn = sqlite3.connect('test.db')
print "Opened database successfully";

conn.execute("DELETE from COMPANY where ID=2;")
conn.commit
print "Total number of rows deleted :", conn.total_changes

cursor = conn.execute("SELECT id, name, address, salary from COMPANY")
for row in cursor:
    print "ID = ", row[0]
```

```
print "NAME = ", row[1]
print "ADDRESS = ", row[2]
print "SALARY = ", row[3], "\n"

print "Operation done successfully";
conn.close()
```

When the above program is executed, it will produce the following result.

```
Opened database successfully
Total number of rows deleted : 1
ID = 1
NAME = Paul
ADDRESS = California
SALARY = 20000.0

ID = 3
NAME = Teddy
ADDRESS = Norway
SALARY = 20000.0

ID = 4
NAME = Mark
ADDRESS = Rich-Mond
SALARY = 65000.0

Operation done successfully
```