

Node.js Backend Engineering Handbook

A Practical Guide for Building Maintainable, Scalable, Production-Ready APIs

Introduction

This handbook is intended for backend engineers working with Node.js APIs.

The goal is not simply to teach how to write code.

The goal is to teach how to build systems that:

- Work correctly
- Scale gracefully
- Are easy to maintain
- Can be debugged in production
- Can be understood by future engineers

Throughout this handbook you'll notice recurring principles.

These principles matter more than any framework or library.

The First Principle

Many engineers think:

"My job is to write APIs."

A backend engineer's real responsibility is:

Build reliable systems that expose business capabilities through APIs.


The API is merely the interface.

The real work is:


- Business logic
- Data consistency
- Reliability
- Security
- Performance
- Scalability

How a Request Travels Through the System

Before discussing code, understand the journey of a request.



Response:



Every layer has a specific responsibility.

Most backend problems occur when responsibilities are mixed.

PART 1: BACKEND ARCHITECTURE

Understanding Layers

Think of a company.

A customer walks into a bank.

The receptionist greets the customer.

The manager makes business decisions.

The clerk interacts with records and databases.

Your backend follows the same model.

Real World	Application
Receptionist	Controller
Manager	Service
Clerk	Repository
Records Room	Database

Controller Layer

What Is A Controller?

A controller is the entry point into your application.

Its job is to translate HTTP requests into service calls.

Think of a controller as a receptionist.

A receptionist does not decide whether a loan should be approved.

A receptionist simply directs the request to the correct department.

Controllers should do the same.

Responsibilities

Controllers should:

- Read request body
- Read request params
- Read query parameters
- Call services
- Return HTTP responses

- Pass errors to middleware
-


What Does NOT Belong In Controllers?

Controllers should never:

- Query databases
 - Start transactions
 - Implement business rules
 - Contain complex calculations
 - Coordinate workflows
-

Common Mistake

Many developers start here:



It works initially.

Six months later it becomes impossible to maintain.

Golden Rule

Keep Controllers Thin.

Controllers should coordinate requests, not implement business logic.

A good controller often stays under 20–30 lines.

Why This Matters

Thin controllers:

- Easier to test
- Easier to understand
- Easier to maintain
- Easier to scale

Service Layer

What Is A Service?

Services contain business logic.

This is the most important layer in most backend applications.

If controllers are receptionists, services are managers.

Managers make decisions.

Services do the same.

Responsibilities

Services are responsible for:

- Business validation
 - Workflow orchestration
 - Transactions
 - Business rules
 - External service coordination
-

Example

Requirement:

"When a user registers:

1. Create User
2. Create Wallet
3. Create Profile
4. Send Welcome Email"

This is a business workflow.

The service owns it.

Workflow Orchestration

A term you'll hear often is:

"Workflow Orchestration"

This simply means:

Coordinating multiple operations to achieve a business outcome.

Example:

```
Create User
↓
Create Wallet
↓
Create Profile
↓
Send Email
↓
Create Audit Log
```

The service layer decides:

- What happens
- In what order
- Under what conditions

Repositories should never make these decisions.

Business Validation

There are two kinds of validation.

Schema Validation

Examples:

- Email format
- Password length
- Required fields

Usually performed before reaching services.

Business Validation

Examples:

- Email already exists
- Product out of stock
- User account disabled
- Wallet balance insufficient

Business validation requires external information.

Often a database lookup.

Therefore:

If validation requires a database lookup, it belongs in the Service Layer.

Golden Rule

Services Know Business.

Whenever you're unsure where logic belongs, ask:

"Is this a business decision?"

If yes, it belongs in a service.

Repository Layer

What Is A Repository?

Repositories communicate with storage systems.

They translate application requests into database operations.

Think of repositories as clerks retrieving and storing records.

They should not make decisions.

They simply execute requests.

Responsibilities

Repositories should:

- Read data
- Insert data
- Update data
- Delete data

Nothing more.

What Does NOT Belong Here?

Repositories should not:

- Send emails
 - Perform authorization
 - Implement workflows
 - Implement business rules
-

Common Mistake

Bad Repository:

Create User
Create Wallet
Send Email
Audit Log

This repository now knows too much.

It becomes tightly coupled.

Golden Rule

Repositories Know Data.

Keep repositories simple.

The simpler repositories are, the easier databases become to change.

Architecture Principle

If you remember only one thing from this chapter:

Keep Controllers Thin, Services Smart, and Repositories Dumb.

This principle alone can keep a codebase maintainable long after it grows from 10 APIs to hundreds of APIs.

Transactions

What Is A Transaction?

A transaction ensures:

Either everything succeeds.

Or nothing succeeds.

Imagine a user registration process.

Create User
Create Wallet
Create Profile

User creation succeeds.

Wallet creation succeeds.

Profile creation fails.

Without transactions:

User Exists
Wallet Exists
Profile Missing

Database is now inconsistent.

With a transaction:

BEGIN

Create User

Create Wallet

Create Profile

COMMIT

Failure:

ROLLBACK

Everything is undone.

Where Should Transactions Live?

A common junior mistake is placing transactions inside repositories.

Transactions belong in services.

Reason:

Repositories manage individual operations.

Services manage business workflows.

Transactions protect workflows.

Therefore:

Transactions belong where the workflow lives.

That place is the Service Layer.

PART 2: API ENGINEERING

What Is An API?

An API (Application Programming Interface) is a contract between two systems.

Think of a restaurant.

The customer does not enter the kitchen.

The customer places an order through a menu.

The menu is the API.

The kitchen is your backend system.

The customer does not need to know:

- Which database you're using
- Which framework you're using
- How data is stored

The customer only cares about the contract.

Golden Rule

Clients should never have to guess how your API works.

APIs should be:

- Predictable
 - Consistent
 - Well documented
-

REST API Design

Most Node.js APIs follow REST principles.

Good APIs are boring.

The more predictable they are, the easier they are to consume.

Naming Endpoints

Good:

GET /users
GET /users/:id

POST /users

PUT /users/:id

DELETE /users/:id

Bad:

/getUsers
/createUser
/deleteUser

Why?

HTTP methods already describe the action.

The endpoint should describe the resource.

Golden Rule

Use nouns in URLs. Use verbs in HTTP methods.

HTTP Status Codes

Status codes communicate the result of a request.

Many developers misuse them.

Common Status Codes

200 OK

Request succeeded.

201 Created

New resource created successfully.

Example:

POST /users

400 Bad Request

Client sent invalid data.

401 Unauthorized

Authentication required.

403 Forbidden

Authenticated but lacks permission.

404 Not Found

Requested resource doesn't exist.

409 Conflict

Resource already exists.

Example:

Email already registered

422 Unprocessable Entity

Validation failed.

500 Internal Server Error

Unexpected server error.

Common Mistake

Returning:

200 OK

for everything.

This destroys API clarity.

Golden Rule

Status codes are part of your API contract.

Treat them seriously.

API Validation

Never trust incoming requests.

Every request should be considered untrusted.

Why Validation Exists

Without validation:

Age = "banana"

Email = "abc"

Price = -1000

could reach your business logic.

Validation prevents bad data from entering your system.

Two Types Of Validation

Schema Validation

Checks:

- Required fields
- Data types
- Length
- Format

Examples:

Valid email

Password length

Positive number

Business Validation

Checks business rules.

Examples:

Email already exists

Product out of stock

Wallet balance insufficient

Golden Rule

Schema validation protects your application. Business validation protects your business.

Authentication vs Authorization

Many developers confuse these.

Authentication

Question:

Who are you?

Examples:

- JWT
- OAuth
- Session

Authentication verifies identity.

Authorization

Question:

What are you allowed to do?

Example:

Admin can delete users

Customer cannot delete users

Authorization verifies permissions.

Easy Way To Remember

Authentication = Identity

Authorization = Permission

Golden Rule

Authenticate first. Authorize second.

Never reverse the order.

JWT Best Practices

JWT is commonly used in Node.js APIs.

What To Store

Good:

userId

role

Bad:

address

phone

entire user object

Why?

JWT travels with every request.

Large tokens:

- Increase bandwidth
 - Increase latency
 - Become difficult to manage
-

Golden Rule

JWTs should identify users, not describe users.

API Versioning

Applications evolve.

APIs must evolve safely.

Example

Version 1:

`/api/v1/users`

Version 2:

`/api/v2/users`

Why?

Old clients continue working.

New clients can adopt improvements.

Golden Rule

Never break existing consumers without a migration strategy.

API Documentation

Imagine joining a project with 200 APIs and no documentation.

Every endpoint becomes a guessing game.

Good documentation should explain:

- Endpoint
 - Request body
 - Query params
 - Response
 - Errors
 - Authentication requirements
-

Popular Tools

- Swagger
 - OpenAPI
-

Golden Rule

An undocumented API is a future support ticket.

Error Handling

Errors are normal.

Systems fail.

Networks fail.

Databases fail.

External APIs fail.

Good systems expect failure.

Bad Approach

```
catch(error){  
  console.log(error)  
}
```

Error disappears.

Problem remains.

Better Approach

- Log error
 - Add context
 - Return meaningful response
 - Propagate when appropriate
-

Centralized Error Handling

Instead of handling errors everywhere:

Controller
Controller
Controller
Controller

Use:

Global Error Middleware

Benefits:

- Consistency
 - Less code duplication
 - Easier maintenance
-

Golden Rule

Every error should either be handled or propagated. Never silently ignore it.

Logging

One day production will fail.

The question is:

Can you understand why?

Logs answer that question.

What To Log

Good:

- Request ID
 - User ID
 - Endpoint
 - Error details
 - Execution time
-

What NOT To Log

Never log:

- Passwords
 - JWT Tokens
 - OTPs
 - Card Numbers
 - Sensitive personal information
-

Log Levels

ERROR

Application failure.

WARN

Unexpected but recoverable.

INFO

Normal application activity.

DEBUG

Detailed development information.

Golden Rule

If production breaks at 2 AM, your logs should tell you why.

PART 3: NODE.JS ENGINEERING

Understanding Node.js

A common misconception:

"Node.js is fast because it is multi-threaded."

Not true.

Node.js is primarily:

- Single-threaded
 - Event-driven
 - Non-blocking
-

Why Node Performs Well

Node spends most of its time waiting.

Waiting for:

- Databases
- APIs
- File systems
- Networks

Instead of blocking:

Node continues processing other requests.

Golden Rule

Node is fast because it avoids waiting, not because it does more work.

Promises

A Promise represents future completion.

Think of ordering food.

You place an order.

You don't have the food yet.

But you have a promise that it will arrive.

Promise States

Pending

↓

Fulfilled

or

Rejected

Async / Await

Async/Await is cleaner syntax over Promises.

Sequential Execution

Example:

Fetch User

↓

Fetch Orders

↓
Fetch Payments

Each step waits.

Use when:

- Order matters
 - Dependencies exist
-

Parallel Execution

Example:

Fetch User
Fetch Orders
Fetch Payments

All start together.

Use:

Promise.all()

Golden Rule

Sequential when dependent. Parallel when independent.

Common Async Mistake #1

Using async inside forEach.

Example:

```
users.forEach(async user => ...)
```

Problem:

forEach does not wait.

Execution becomes unpredictable.

Use:

for...of

or

Promise.all()

Golden Rule

Never use async with forEach.

Experienced Node developers avoid it completely.

Common Async Mistake #2

Massive Promise.all

Example:

100,000 users

↓

Promise.all()

Problems:

- Memory spikes
 - Database overload
 - API throttling
 - Rate limit failures
-

Use batching instead.

Golden Rule

Just because you can run 100,000 promises simultaneously doesn't mean you should.

Promise.all vs Promise.allSettled

Promise.all:

If one promise fails:

Everything fails.

Promise.allSettled:

Waits for all promises.

Returns:

- Successes
- Failures

Useful for:

- Notifications
 - Reports
 - Background jobs
-

Golden Rule

Use `Promise.all` when every operation must succeed. Use `allSettled` when partial success is acceptable.

PART 4: DATABASE ENGINEERING

Why Databases Matter

Many backend engineers spend most of their time writing application code.

However, most production performance problems originate from the database layer.

A poorly designed query can make the fastest API slow.

A missing index can make a simple request take seconds.

A bad schema can create years of technical debt.

Golden Rule

Most performance problems are data problems before they are code problems.

Understanding the Database Layer

Think of the database as the system of record.

Your application may restart.

Your servers may scale.

Your cache may be cleared.

The database remains the source of truth.

Responsibilities of the Database

Store:

- Users
- Orders
- Products
- Payments
- Audit records

Reliably and consistently.

Database Design

Good database design makes future changes easier.

Bad database design creates permanent complexity.

Goals of Good Design

- Consistency
 - Maintainability
 - Query Performance
 - Data Integrity
-

Common Relationships

One-to-One

Example:

User
↓
Profile

One user has one profile.

One-to-Many

Example:

User
↓
Orders

One user can have many orders.

Many-to-Many

Example:

Users
↔
Roles

Users can have multiple roles.

Roles can belong to multiple users.

Golden Rule

Model relationships clearly. Confusing relationships create confusing applications.

Query Optimization

Not all queries are equal.

Bad:

```
SELECT *  
FROM users;
```

Better:

```
SELECT id, email  
FROM users;
```

Why?

Fetching unnecessary data:

- Uses memory
 - Uses network bandwidth
 - Slows queries
-

Golden Rule

Fetch only what you need.

Database Indexes

An index is similar to a book's table of contents.

Imagine finding a word in a 1000-page book.

Without an index:

You read page by page.

With an index:

You jump directly to the location.

Databases work similarly.

Example

Searching users by email:

WHERE email = ?

Without index:

Full table scan.

With index:

Direct lookup.

Common Index Candidates

- email
 - user_id
 - status
 - created_at
 - foreign keys
-

Warning

Indexes improve reads.

Indexes slightly slow writes.

More indexes are not always better.

Golden Rule

Index fields that are searched often, not fields that simply exist.

N+1 Query Problem

One of the most common backend mistakes.

Example:

Fetch 100 users.

Then fetch orders for each user.

1 query
+
100 queries
=
101 queries

This is called an N+1 problem.

Better:

Use joins or eager loading.

1 query

instead of 101.

Golden Rule

If a query count grows with the amount of data, investigate it.

Transactions

We discussed transactions earlier.

Now let's understand why they matter.

Real Example

Bank Transfer

Move:

₹1000

From:

Account A

To:

Account B

Process:

Deduct ₹1000 from A

Add ₹1000 to B

Imagine:

Deduction succeeds.

Addition fails.

Money disappears.

Transactions prevent this.

Either:

Both succeed

or

Both fail

Golden Rule

If partial completion creates inconsistency, use a transaction.

PART 5: PERFORMANCE & SCALABILITY

What Is Performance?

Performance means:

How fast a system responds.

Examples:

- API latency
 - Query speed
 - Response time
-

What Is Scalability?

Scalability means:

How well a system handles growth.

Example:

100 users

↓

10,000 users

↓

1,000,000 users

Can the system continue operating effectively?

Important Distinction

Performance:

Fast today.

Scalability:

Fast tomorrow.

Golden Rule

Performance solves today's problems. Scalability solves tomorrow's problems.

Caching

Databases are expensive.

Repeatedly asking the database the same question wastes resources.

Caching solves this.

What Is Caching?

Store frequently accessed data in faster storage.

Commonly:

Redis

Without Cache

Request
↓
API
↓
Database

Every request hits the database.

With Cache

Request
↓
API
↓
Redis
↓
Database

Most requests never reach the database.

Cache Aside Pattern

Most common caching strategy.

Step 1

Check cache.

Step 2

If found:

Return result.

Step 3

If missing:

Query database.

Step 4

Store result in cache.

Step 5

Return response.

Good Cache Candidates

- Product catalogs
 - Country lists
 - Feature flags
 - Configuration data
 - Lookup tables
-

Poor Cache Candidates

- Payment balances
 - Real-time financial data
 - Highly volatile information
-

Cache Invalidation

The hardest part of caching.

Example:

Database:

Price = 100

Cache:

Price = 90

Application now serves incorrect information.

When data changes:

Invalidate cache.

Golden Rule

Cache reads. Invalidate on writes.

Rate Limiting

Every public API needs protection.

Without limits:

One user can consume all resources.

Example:

1,000,000 requests

Result:

- CPU exhaustion
 - Memory pressure
 - Database overload
-

What Rate Limiting Does

Defines usage boundaries.

Example:

100 requests/minute

Beyond that:

429 Too Many Requests

Common Strategies

Fixed Window

Simple.

Count requests per time period.

Sliding Window

More accurate.

Tracks activity continuously.

Token Bucket

Most commonly used.

Allows bursts while enforcing limits.

Where Should Rate Limiting Live?

Best placement:

Internet
↓
WAF
↓
Load Balancer
↓
API Gateway
↓
Application

Earlier is always better.

Blocking requests before they reach application servers saves resources.

Golden Rule

The best request is the one you never have to process.

Load Balancers

Eventually one server becomes insufficient.

Load balancers solve this problem.

Without Load Balancer

Client
↓
Node Server

Single point of failure.

With Load Balancer

Load Balancer
↓
Node1
Node2
Node3

Traffic distributed.

Benefits

Scalability

Add more servers.

Availability

One server fails.

Application remains available.

Health Checks

Unhealthy servers removed automatically.

SSL Termination

Load balancer handles HTTPS.

Application servers remain simpler.

Golden Rule

Always assume your application will eventually run on multiple servers.

Horizontal Scaling

One server:

4 CPU
16 GB RAM

Eventually becomes insufficient.

Two choices:

Vertical Scaling

Increase server size.

Example:

4 CPU
↓
16 CPU

Horizontal Scaling

Add more servers.

Example:

1 server
↓
10 servers

Most large systems prefer horizontal scaling.

Requirements For Horizontal Scaling

Applications should be:

- Stateless
 - Session-independent
 - Cache-aware
-

Golden Rule

Design as if another server could be added tomorrow.

Performance Optimization Mindset

Many engineers optimize too early.

Bad Approach

Optimize everything.

Good Approach

Measure first.

Optimize second.

Questions:

- Is database slow?
 - Is network slow?
 - Is CPU overloaded?
 - Is cache missing?
-

Golden Rule

Never optimize what you haven't measured.

PART 6: PRODUCTION ENGINEERING

The Difference Between Development and Production

Many engineers spend most of their time writing features.

Production engineering is about keeping those features running reliably.

A feature that works on your machine but fails in production has little value.

Development Mindset

Focus:

- Functionality

- Feature delivery
-

Production Mindset

Focus:

- Reliability
 - Availability
 - Observability
 - Recovery
-

Golden Rule

Building software is only half the job. Operating it is the other half.

Logging

Sooner or later, something will fail.

The question is:

Can you understand what happened?

Logs answer that question.

Why Logging Exists

Imagine a customer reports:

Payment failed.

Questions immediately arise:

- Which user?
- Which order?
- Which payment provider?
- What error occurred?
- How often is this happening?

Without logs:

You are guessing.

With logs:

You are investigating.

Good Logs

A good log should provide context.

Example:

Request ID
User ID
Endpoint
Duration
Status
Error Details

Bad Logs

Something failed

This tells you nothing.

Log Levels

ERROR

Something failed.

Requires investigation.

WARN

Unexpected situation.

System continues functioning.

INFO

Normal application activity.

DEBUG

Detailed information used during troubleshooting.

What Should Never Be Logged

Never log:

- Passwords
 - OTPs
 - JWT tokens
 - API secrets
 - Credit card details
 - Sensitive personal data
-

Golden Rule

If production breaks at 2 AM, your logs should tell you why.

Monitoring

Logs tell you what happened.

Monitoring tells you when something is wrong.

Why Monitoring Matters

Imagine:

Error Rate = 35%

Customers know.

Management knows.

Social media knows.

Your monitoring system should know first.

Key Metrics

Monitor:

Response Time

How quickly requests complete.

Error Rate

Percentage of failed requests.

Throughput

Requests per second.

CPU Usage

Server workload.

Memory Usage

Application memory consumption.

Database Performance

Slow queries.

Connection usage.

Golden Rule

If you're not measuring it, you're managing it blindly.

Observability

Observability helps explain system behavior.

Traditionally described using three pillars.

Pillar 1: Logs

What happened?

Pillar 2: Metrics

How often did it happen?

Pillar 3: Traces

Where exactly did it happen?

Example:

```
Request
↓
API
↓
Service
↓
Database
↓
External API
```

Tracing helps identify the slow component.

Golden Rule

Logs explain incidents. Metrics detect incidents. Traces diagnose incidents.

Error Handling

Errors are normal.

Expect them.

Design for them.

Common Sources Of Failure

- Database unavailable
 - Third-party API unavailable
 - Timeout
 - Invalid request
 - Network issue
-

Common Mistake

Ignoring errors.

Example:

```
try
catch
do nothing
```

Problem hidden.

Issue unresolved.

Better Approach

- Capture error
 - Add context
 - Log error
 - Return proper response
 - Propagate when necessary
-

Centralized Error Handling

Instead of:

Controller A
Controller B
Controller C

all handling errors differently,

Use:

Global Error Middleware

Benefits:

- Consistency
 - Maintainability
 - Less duplication
-

Golden Rule

Every error should either be handled or propagated. Never silently ignore it.

Environment Variables

Applications require configuration.

Examples:

- Database URL
- JWT Secret
- API Keys
- Redis Host

Bad Practice

Hardcoding values.

Example:

```
password = admin123
```

Better Practice

Use environment variables.

Example:

```
DB_HOST
```

```
DB_PASSWORD
```

```
JWT_SECRET
```

Benefits:

- Security
 - Flexibility
 - Easier deployments
-

Golden Rule

Code should be portable. Configuration should be external.

Security Fundamentals

Security is not a feature.

Security is a requirement.

Principle Of Least Privilege

Every component should have only the permissions it needs.

Example:

Application needs:

Read Orders
Create Orders

Application does NOT need:

Drop Database

Golden Rule

Grant access based on necessity, not convenience.

Input Validation

Never trust user input.

Every request should be considered hostile until validated.

Examples:

- SQL Injection
 - NoSQL Injection
 - Malformed payloads
-

Validation protects your application.

Password Storage

Never store passwords directly.

Never.

Use:

- bcrypt
 - argon2
-

Reason:

If database leaks:

Passwords remain protected.

Golden Rule

If passwords are readable, security has already failed.

HTTPS

HTTPS encrypts communication.

Without HTTPS:

Anyone between client and server can inspect traffic.

Always use HTTPS in production.

CORS

Cross-Origin Resource Sharing controls which domains can access your APIs.

Bad:

Allow Everyone

Better:

Allow only trusted origins.

Golden Rule

Access should be explicitly allowed, not implicitly trusted.

Secrets Management

Applications use secrets.

Examples:

- Database credentials
 - API tokens
 - Encryption keys
-

Never:

- Commit secrets to Git
 - Share secrets through chat
 - Store secrets in source code
-

Golden Rule

Treat secrets like passwords.

Deployment Fundamentals

Deployment is the process of releasing software.

Typical Flow

Developer

↓

Git

↓

CI/CD

↓

Build
↓
Deploy
↓
Production

Goal:

Reliable and repeatable releases.

Golden Rule

Deployments should be boring. Exciting deployments usually mean problems.

CI/CD

CI:

Continuous Integration

CD:

Continuous Delivery / Deployment

Benefits:

- Automated testing
 - Consistent builds
 - Faster releases
 - Reduced human error
-

Typical Pipeline

Code
↓
Lint
↓
Test
↓
Build
↓
Deploy

Golden Rule

If a process is repeated frequently, automate it.

Docker

Docker packages:

- Application
- Dependencies
- Runtime

into a container.

Why Docker Exists

Without Docker:

Works on my machine

becomes common.

Docker ensures consistency.

Development and production behave similarly.

Golden Rule

Containers reduce environment-related surprises.

Kubernetes

As applications grow:

Managing containers manually becomes difficult.

Kubernetes helps manage:

- Scaling
 - Recovery
 - Deployment
 - Networking
 - Service Discovery
-

Example:

Server crashes.

Kubernetes automatically starts a replacement.

Golden Rule

Humans should not manually manage hundreds of containers.

Incident Response

Production incidents happen.

Even at world-class companies.

Good teams focus on:

- Detection
 - Containment
 - Recovery
 - Prevention
-

Bad teams focus on:

- Blame
-

Golden Rule

Fix systems, not people.

Production Readiness Checklist

Before deployment ask:

Functionality

- Does it work?
-

Validation

- Is input validated?
-

Error Handling

- Are errors handled correctly?
-

Logging

- Can issues be debugged?
-

Security

- Are secrets protected?
-

Performance

- Any obvious bottlenecks?
-

Database

- Are indexes required?
-

Monitoring

- Can failures be detected?
-

Testing

- Are critical flows covered?
-

Documentation

- Can another engineer understand it?
-

Final Production Principle

Many engineers measure success by feature delivery.

Production engineers measure success differently.

Success is:

Reliable
Predictable
Maintainable
Observable
Recoverable

A system that survives growth, failures, traffic spikes, deployments, and human mistakes is a successful system.

Golden Rule

A backend engineer builds features. A senior backend engineer builds systems that continue working after the feature is deployed.

PART 7: ENGINEERING PRACTICES & SENIOR ENGINEER PRINCIPLES

Introduction

Most engineers learn how to write code.

Fewer engineers learn how to maintain code.

Even fewer learn how to design systems that remain maintainable for years.

This chapter focuses on the habits and principles that separate junior, mid-level, and senior engineers.

Writing Code For Humans

A common misconception:

Code is written for computers.

Wrong.

Computers execute code.

Humans maintain it.

Most code is read far more often than it is written.

Example

Imagine revisiting code you wrote 18 months ago.

If it takes 30 minutes to understand, that code has already failed one of its jobs.

Golden Rule

Code is a communication tool before it is an execution tool.

Readability Over Cleverness

Many developers try to impress others with clever code.

Experienced engineers optimize for clarity.

Bad:

Complex one-liner
Nested ternaries
Multiple hidden side effects

Good:

Simple variables
Clear naming
Explicit logic

Golden Rule

The best code is usually the code that requires the least explanation.

Naming Things

One of the hardest problems in software engineering.

Good naming dramatically improves maintainability.

Bad Names

data

temp

value

obj

response2

Good Names

customerProfile

paymentStatus

invoiceAmount

userRepository

Names should reveal intent.

Golden Rule

If a variable requires a comment to explain its purpose, it probably needs a better name.

Code Reviews

Code reviews are not merely for finding bugs.

They improve:

- Quality
 - Consistency
 - Knowledge sharing
 - Architecture alignment
-

What To Review

Correctness

Does it work?

Security

Any vulnerabilities?

Performance

Any obvious bottlenecks?

Maintainability

Can another engineer understand it?

Testing

Are important paths covered?

Architecture

Is logic placed in the correct layer?

Golden Rule

Review the design, not just the syntax.

Testing Strategy

Many teams misunderstand testing.


Goal:

Not to increase coverage numbers.

Goal:

Increase confidence.

Testing Pyramid



Unit Tests

Test:

Individual functions.

Examples:

- Price calculation
 - Validation rules
 - Business logic
-

Advantages:

- Fast
 - Reliable
 - Easy to run
-

Integration Tests

Test interaction between components.

Examples:

- Service + Database
 - Service + Redis
 - Service + External API
-

Advantages:

- More realistic
 - Catch integration issues
-

End-To-End Tests

Test complete user workflows.

Examples:

Register User
Create Order
Process Payment
Generate Invoice

Advantages:

Highest confidence.

Disadvantages:

Slowest tests.

Golden Rule

Test critical business workflows, not implementation details.

Technical Debt

Every shortcut creates debt.

Sometimes debt is acceptable.

Ignoring debt is not.

Example:

You skip validation to meet a deadline.

That shortcut becomes future work.

Debt becomes dangerous when:

- Nobody tracks it
 - Nobody prioritizes it
 - Nobody understands it
-

Golden Rule

Technical debt is like financial debt. Small amounts are manageable. Uncontrolled debt becomes crippling.

Refactoring

Refactoring means improving code without changing behavior.

Reasons to Refactor

- Improve readability
 - Reduce duplication
 - Improve maintainability
 - Simplify architecture
-

Bad Reason

Refactor because you are bored.

Good Reason

Refactor because future changes are becoming difficult.

Golden Rule

Refactoring should improve clarity, not satisfy personal preferences.

DRY Principle

DRY:

Don't Repeat Yourself.

Bad:

Same business rule copied into:

- Controller A
 - Controller B
 - Controller C
-

Problem:

Future changes require updating multiple locations.

Good:

Single source of truth.

Warning

Many developers over-apply DRY.

Not all duplication is harmful.

Golden Rule

Duplicate knowledge is dangerous. Duplicate code is sometimes acceptable.

KISS Principle

KISS:

Keep It Simple, Stupid.

Engineers often create solutions for problems that do not exist.

Bad:

5 abstractions
8 interfaces
3 design patterns

for a simple CRUD endpoint.

Good:

Simple code.

Simple architecture.

Simple maintenance.

Golden Rule

Simple systems are easier to understand, test, debug, and scale.

YAGNI Principle

YAGNI:

You Aren't Gonna Need It.

Example:

Building:

Microservices
Event Bus
Kafka
CQRS

for a system with 10 users.

Build for current requirements.

Design for future growth.

Do not build future growth today.

Golden Rule

Future-proofing often becomes future complexity.

Maintainability

Many engineers focus on performance.

Few focus on maintainability.

Reality:

Most systems spend years being maintained.

They spend weeks being developed.

Questions:

Can another engineer understand this?

Can another engineer modify this safely?

Can another engineer debug this quickly?

Golden Rule

Maintainability is a feature.

Common Backend Anti-Patterns

Fat Controllers

Controller contains:

- Validation
- Business Logic
- Database Queries
- Email Logic

Everything.

Problem:

Impossible to scale.

Difficult to test.

Solution:

Move logic into services.

Business Logic In Repositories

Repositories deciding business behavior.

Problem:

Responsibilities become mixed.

Solution:

Keep business logic in services.

Missing Transactions

Multiple writes.

No rollback strategy.

Problem:

Data inconsistency.

Solution:

Protect workflows with transactions.

Missing Validation

Trusting user input.

Problem:

Security and data integrity issues.

Solution:

Validate everything.

No Logging

Problem occurs.

No evidence exists.

Solution:

Add structured logs.

Massive Promise.all

Launching thousands of operations simultaneously.

Problem:

Memory spikes.

Database overload.

Solution:

Use batching.

Senior Engineer Thinking

Junior engineers often ask:

How do I build this?

Senior engineers ask:

What happens when this fails?

Junior engineers think:

Feature.

Senior engineers think:

System.

Junior engineers optimize:

Code.

Senior engineers optimize:

Architecture.

Junior engineers ask:

Can this work?

Senior engineers ask:

Can this survive growth?

Decision Framework

Before implementing anything, ask:

Correctness

Does it work?

Security

Can it be abused?

Reliability

Can it fail safely?

Maintainability

Can another engineer understand it?

Performance

Will it perform adequately?

Scalability

Will it handle growth?

Golden Rule

Always optimize in this order:

1. Correctness
2. Security
3. Reliability
4. Maintainability
5. Performance
6. Scalability

Most production incidents happen because the first four were ignored.

The Layering Principle

If you remember only one architecture principle from this handbook, remember this:

Controllers

Know HTTP.

Services

Know Business.

Repositories

Know Data.

Database

Stores Truth.

When responsibilities remain separated:

- Testing becomes easier
 - Refactoring becomes safer
 - Scaling becomes simpler
 - Debugging becomes faster
-

Golden Rule

Keep Controllers Thin, Services Smart, and Repositories Dumb.

This principle alone can keep a codebase healthy even after it grows from a handful of APIs to hundreds of services and millions of users.

Final Thoughts

Frameworks change.

Libraries change.

Databases evolve.

Cloud providers evolve.

The engineering principles in this handbook remain largely the same.

The best backend engineers are not the ones who memorize the most tools.

They are the ones who consistently make good engineering decisions.

The Senior Backend Engineer's Checklist

Before shipping any feature, ask:

- ✓ Is validation implemented?
 - ✓ Are business rules in services?
 - ✓ Are repositories focused on data access?
 - ✓ Are transactions protecting critical workflows?
 - ✓ Is error handling consistent?
 - ✓ Are logs sufficient for debugging?
 - ✓ Is monitoring available?
 - ✓ Is security considered?
 - ✓ Are indexes required?
 - ✓ Is caching appropriate?
 - ✓ Are tests covering critical paths?
 - ✓ Can another engineer understand this code six months from now?
-

The Final Principle

A junior engineer writes code that works.

A mid-level engineer writes code that others can maintain.

A senior engineer designs systems that continue to work, continue to scale, and continue to be maintainable long after the original author has left the project.

Build systems, not just features.