Student Name
Github root directory: (insert link here)

Date Submitted: 10/1/2018

Task 01:

Youtube Link:

https://youtu.be/wpKVRQnxOE8

40 MHz = 25 ns delay. The number of clock cycles for a 0.425s delay is 0.425s/25ns = 17000000. since SysctlDelay(x) takes 3*x cycles; 17000000/3 = 5666667.

in the first picture the clock cycle counter is reset to 0 (note: the value shown is not reset until the next clock cycle, thus the value shown is not the actual value which is 0)



The total count of 17000006 informs us that based on the 40MHz clock the delay is roughly 0.425s.

Modified Code:

```
#include <stdint.h>
#include <stdbool.h>
#include "inc/hw_memmap.h"
#include "inc/hw_types.h"
#include "driverlib/sysctl.h"
```

Grading scheme: 30% Coding, 30% Documentation, 40% Execution/Video.

```
#include "driverlib/gpio.h"

int main(void)
{
    uint8_t ui8PinData=2;
    SysCtlClockSet(SYSCTL_SYSDIV_5|SYSCTL_USE_PLL|SYSCTL_XTAL_16MHZ|SYSCTL_OSC_MAIN);
    SysCtlPeripheralEnable(SYSCTL_PERIPH_GPIOF);
    GPIOPinTypeGPIOOutput(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3);

    while(1)
    {
        GPIOPinWrite(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3, ui8PinData);
        //40 MHz = 25 ns delay so 0.425/25ns = 17000000. since SysctlDelay(x) takes
3*x cycles 17000000/3 = 5666667.
       // this will give a delay of 0.425s
        SysCtlDelay(5666667);
      GPIOPinWrite(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3, 0x00);
        SysCtlDelay(5666667);
        if(ui8PinData==8) {ui8PinData=2;} else {ui8PinData=ui8PinData*2;}
    }
}
```

Task 02:

Youtube Link:
https://youtu.be/Ul0688uy7O8

Modified Code:

```
#include "inc/hw_memmap.h"
#include "inc/hw_types.h"
#include "driverlib/sysctl.h"
#include "driverlib/gpio.h"

int main(void)
{
    uint8_t ui8PinData=2;
    SysCtlClockSet(SYSCTL_SYSDIV_5|SYSCTL_USE_PLL|SYSCTL_XTAL_16MHZ|SYSCTL_OSC_MAIN);
    SysCtlPeripheralEnable(SYSCTL_PERIPH_GPIOF);
    GPIOPinTypeGPIOOutput(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3);

    while(1)
    {
        GPIOPinWrite(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3, ui8PinData);
        //40 MHz = 25 ns delay so 0.425/25ns = 17000000. since SysctlDelay(x) takes
3*x cycles 17000000/3 = 5666667.
       // this will give a delay of 0.425s
        SysCtlDelay(5666667);
      GPIOPinWrite(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3, 0x00);
        SysCtlDelay(5666667);
        //for the sequence R, G, B, RG, RB, GB, RGB, R, G, ...
        // R = 2, B = 4, G = 8. thus a mapping from blink to the next is made based
on the change in value
```

```
        if(ui8PinData==2 | ui8PinData==4 | ui8PinData== 6) {ui8PinData=ui8PinData+6;}
// R->G, B->RG, RB->GB: add 6 to current value
        else if (ui8PinData==8 | ui8PinData==10) {ui8PinData=ui8PinData-4;}
// G-> B, RG-> RB: subtract 4 from current value
        else if (ui8PinData==12) {ui8PinData=ui8PinData+2;}
// if GB add 2 to get to RGB
        else {ui8PinData=2;}
// if RGB or any other non specified value occurs, go to R

    }
}
```