HEURISTIC ANALYSIS

Problems Definition & Result Matrix:
- Air Cargo Action Schema:
```
Action(Load(c, p, a),
        PRECOND: At(c, a) ∧ At(p, a) ∧ Cargo(c) ∧ Plane(p) ∧ Airport(a)
        EFFECT: ¬ At(c, a) ∧ In(c, p))
Action(Unload(c, p, a),
        PRECOND: In(c, p) ∧ At(p, a) ∧ Cargo(c) ∧ Plane(p) ∧ Airport(a)
        EFFECT: At(c, a) ∧ ¬ In(c, p))
Action(Fly(p, from, to),
        PRECOND: At(p, from) ∧ Plane(p) ∧ Airport(from) ∧ Airport(to)
        EFFECT: ¬ At(p, from) ∧ At(p, to))
```
- Problem 1 initial state and goal:
```
Init(At(C1, SFO) ∧ At(C2, JFK)
        ∧ At(P1, SFO) ∧ At(P2, JFK)
        ∧ Cargo(C1) ∧ Cargo(C2)
        ∧ Plane(P1) ∧ Plane(P2)
        ∧ Airport(JFK) ∧ Airport(SFO))
Goal(At(C1, JFK) ∧ At(C2, SFO))
```
Optimal Plan:
Load(C1, P1, SFO)
Load(C2, P2, JFK)
Fly(P2, JFK, SFO)
Unload(C2, P2, SFO)
Fly(P1, SFO, JFK)
Unload(C1, P1, JFK)

Search Method	Optimality	Plane Length	Time Elapsed	New nodes	# Node Expand	Goal Tests
breadth_first_search	Yes	6	0.052	180	43	56
depth_first_graph_search	No	6	1.36	5960	1458	1459
greedy_best_first_graph_search h_1	Yes	6	0.01	28	7	9

- *Problem 2 initial state and goal:*

```
Init(At(C1, SFO) ∧ At(C2, JFK) ∧ At(C3, ATL)
        ∧ At(P1, SFO) ∧ At(P2, JFK) ∧ At(P3, ATL)
        ∧ Cargo(C1) ∧ Cargo(C2) ∧ Cargo(C3)
        ∧ Plane(P1) ∧ Plane(P2) ∧ Plane(P3)
        ∧ Airport(JFK) ∧ Airport(SFO) ∧ Airport(ATL))
Goal(At(C1, JFK) ∧ At(C2, SFO) ∧ At(C3, SFO))
```

Search Method	Optimality	Plane Length	Time Elapsed	# Node Expand

```
```

- *Problem 3 initial state and goal:*

```
Init(At(C1, SFO) ∧ At(C2, JFK) ∧ At(C3, ATL) ∧ At(C4, ORD)
        ∧ At(P1, SFO) ∧ At(P2, JFK)
        ∧ Cargo(C1) ∧ Cargo(C2) ∧ Cargo(C3) ∧ Cargo(C4)
        ∧ Plane(P1) ∧ Plane(P2)
        ∧ Airport(JFK) ∧ Airport(SFO) ∧ Airport(ATL) ∧ Airport(ORD))
Goal(At(C1, JFK) ∧ At(C3, JFK) ∧ At(C2, SFO) ∧ At(C4, SFO))
```

Search Method	Optimality	Plane Length	Time Elapsed	# Node Expand