

LAB3 - Cryptography

Session Requirements :

- For Microsoft Windows users, if you haven't done before:
 - Please install VirtualBox or VMware on your PC
 - Please install Ubuntu 16.04 (LTS) or a later version
- Please find below some links for downloading virtual machines:

<https://www.virtualbox.org>

<https://www.osboxes.org/vmware-images/>

<https://www.osboxes.org/virtualbox-images/>

<https://virtual-machine.org/download-list>

- Windows VMs:

<https://developer.microsoft.com/en-us/microsoft-edge/tools/vms/>

- All the questions must be answered and included in the report.
- You have to clearly write your names on a cover page
- Make a Zip file contains all files generated in Task 4, keeping the same file names, and a PDF report for all Tasks, including all commands used. Only PDF format is accepted (3 points penalty for other formats)
- Each group (composed of 3 persons at most) must submit a report.

Content

| | | |
|------|--|---|
| I. | Task 1: Hash function ----- | 2 |
| II. | Task 2: Symmetric Encryption ----- | 3 |
| III. | Task 3: Asymmetric Encryption ----- | 3 |
| IV. | Task 4: Asymmetric/Symmetric Encryption, Digital Signature ----- | 4 |
| V. | Job Aids ----- | 5 |

Security Services, Algorithms with toolkit OpenSSL

Activity objective:

The learning objective of this lab is to get familiar with the toolkit OpenSSL. In this lab, we will use ***openssl*** commands and libraries.

OpenSSL is an open-source implementation of the SSL and TLS protocols. It provides:

- a. The core library, written in the C programming language, implements basic cryptographic functions and provides various utility functions, and produce a secured applications Client/Server using SSL/TLS
- b. We use line command OpenSSL to:
 1. Generate RSA, DSA keys (signing)
 2. Generate X509 certificate
 3. Calculate fingerprint (MD5, SHA.....)
 4. Encrypt and decrypt files (RSA, DES, 3DES ...)
 5. Testing Client/Server SSL/TLS
 6. Signing and crypt emails (S/MIME)

Lab Environment

In this lab, we will use ***openssl*** commands and libraries. You should first install openssl package, you will use ***apt-get install openssl***.

- To see the manuals, you can type ***man openssl***

The OpenSSL is an entry point for many functions. You call it following the pattern:

```
$ openssl <command> <option>
```

Task 1: Hash function

In this task, we will play with various one-way hash algorithms. You will use the following ***openssl dgst*** command to generate the hash value for a file.

- a. Create a text file **Plain.txt** contain: **security lab**
- b. Generate the hash values H1 for this file using SHA1 hash algorithm.
- c. Modify **s** into **S (capital letter)** for the word **security** in the file Plain.txt; generate the hash values H2 for the modified file using SHA1 hash algorithm.
- d. Please observe whether H1 and H2 are similar or not.

Task 2: Symmetric Encryption

In this task, you will use the command line **openssl enc** for encrypt and decrypt messages, for more information about this command you can type:

openssl enc -h


- a. Encrypt Plain.txt was created in previous task with **des-cbc** algorithm, and save the file encrypted as Cipher.txt, use **-k** option to enter the password and you can use the **-base64** option to encode binary to text.
- b. Decrypt the file Cipher.txt and save the new file as NewPlain.txt, compare the new file with Plain.txt, use : **diff Plain.txt NewPlain.txt -q**

Task 3: Asymmetric Encryption

The objective of this task is to encrypt a message with a public key, and just the creator of this key will can decrypt the message.

- a. Generate RSA keys with length of 2048 bits; **privMyName.key** is a name of the private key
- b. Extract public key from **privMyName.key**; **pubMyName.key** is a name of the public key.
- c. Encrypt the file Plain.txt with the public key, save the file encrypted as CipherRSA.txt.
- d. Decrypt the file CipherRSA.txt and save the new file as New2Plain.txt, compare the new file with Plain.txt, use : **diff Plain.txt NewPlain.txt -q**

Task 4: Asymmetric/Symmetric Encryption, Digital signature



- Explain the above scenario.
- Generate the symmetric key **sym.key** with length of **128 bits**; use the `rand` command and encode the key in **hex**.
- Realize the above scenario by exchanging a safe way the symmetric key with your colleague.
 - Create **Plaintext.txt** contain : My Security LAB: My Name is **<your_name>**
 - Generate RSA keys with length of 2048 bits: **privA.key**, **pubA.key**, **privB.key** and **pubB.key** (you can use keys generated in Task 3 but you have to modify the file names).
 - Exchange the public keys (use sftp or USB Flash)
 - Encrypt **PlaintextM.txt** using symmetric algorithm (**-aes-128-cbc**) : **Ciphertext.txt** (use the key generated in this task), you will use the options **-kfile** for password and **-base64**
 - Encrypt the symmetric key using asymmetric algorithm (generate an encrypted file: **secret.key**)
 - Generate the hash value of symmetric key using SHA1 (**sym.sha1**)
 - Sign **sym.sha1**, generate a file **sym.sig**
 - Send the necessary files to your colleague that allows decrypting your message, and verify your signature (**you have to use the same options for decrypting as encrypting**),

explain the different steps to decrypt and verify the digital signature.

d. What are the different security services assured by this scenario?

Job Aids

\$diff file1.txt file2.txt -q: compares the contents of the two files

```
$sftp username@remote_hostname_or_IP
ls (list remote files)
lls ( list local files)
cd (change directory / remote)
lcd (change directory / local)
get remoteFile
put localfile
exit
```

```
$openssl genrsa -out <file_rsa.priv> <size>
$ openssl rsa -in <file_rsa.priv> -des3 -out <file.pem>
$ openssl rsa -in <_rsa.priv> -pubout -out <file_rsa.pub> :
$ openssl enc <-algo> -in <Plain.txt> -out <Cipher.enc> : encrypt
$ openssl enc <-algo> -in <Cipher> -d -out <Plain> : decrypt
$ openssl dgst <-algo> -out <out_file> <in_file>
$ openssl rand -out <key> <number_bytes> -hex
$ openssl rsautl -encrypt -pubin -inkey <rsa.pub> -in <Plain.txt> -out
  <Cipher.enc>
$ openssl rsautl -decrypt -inkey <rsa.priv> -in <Cipher.enc> -out <file.txt>
$ openssl rsautl -sign -inkey <rsa.priv> -in <file.txt> -out <file.sig>
$ openssl rsautl -verify -pubin -inkey <rsa.pub> -in file.sig
```