

An assessment of structural enthalpy and crystallization pathways of $\text{Mg}_{65}\text{Zn}_{30}\text{Ca}_5$ bulk metallic glass and amorphous films

Scott Gleason, David Miskovic, Kevin Laws, Michael Ferry

UNSW Australia
School of Material Science and Engineering

April 10, 2017

ABSTRACT

The structural nature and thermal stability of amorphous alloys is highly dependent on the method by which they are produced, i.e. their relaxation rate upon cooling. Both bulk samples and metallic glass films of $\text{Mg}_{65}\text{Zn}_{30}\text{Ca}_5$ were produced by copper mold casting and direct current (DC) magnetron sputtering onto aluminium substrates, respectively. Comparisons between structural enthalpy, crystallization pathways, relaxation and crystallization kinetics of the bulk samples and films were examined by elevated temperature XRD and DSC. Compared with equivalent experiments on the bulk alloy, results for the thin films show distinct differences in structural enthalpy and deviations from the expected crystalline phase evolution, displaying minor peak shifts, failure of some phases to evolve, and variations in the evolution rates.

TABLE OF CONTENTS

ABSTRACT	i
TABLE OF CONTENTS	1
1 INTRODUCTION	1
2 METHOD	1
2.1 Master alloy	1
2.2 DC magnetron sputtering	1
2.3 DSC characterization	2
2.4 XRD characterization	2
3 RESULTS	2
4 DISCUSSION	2
5 CONCLUSIONS	2
6 ACKNOWLEDGEMENTS	2
7 REFERENCES	2

1 INTRODUCTION

The structural nature and thermal stability of amorphous alloys is highly dependent on the method by which they are produced, i.e. their relaxation rate upon cooling. Both bulk samples and metallic glass films of $\text{Mg}_{65}\text{Zn}_{30}\text{Ca}_5$ were produced by copper mold casting and direct current (DC) magnetron sputtering onto aluminium substrates, respectively. Comparisons between structural enthalpy, crystallization pathways, relaxation and crystallization kinetics of the bulk samples and films were examined by elevated temperature XRD and DSC. Compared with equivalent experiments on the bulk alloy, results for the thin films show distinct differences in structural enthalpy and deviations from the expected crystalline phase evolution, displaying minor peak shifts, failure of some phases to evolve, and variations in the evolution rates.

Key sources ^{Zhang Zhang Zhang 2012} [1, 2] [3]

2 METHOD

2.1 Master alloy

The master alloy of $\text{Mg}_{65}\text{Zn}_{30}\text{Ca}_5$ was produced using high-purity elements of Mg (99.85 wt%), Zn (99.995 wt%), and Ca (99.8 wt%). The alloy was prepared by induction melting in boron nitride coated graphite crucibles, purged with Ar (99.997 vol.% purity) five times, and protected with a circulating Ar atmosphere. Alloy homogeneity was ensured through heating and cooling through a cycle 700°C, 385°C, 650°C, 385°C, 650°C to a casting temperature of 500 °C and 450°C for for injection and gravity casting respectively. Bulk amorphous $\text{Mg}_{65}\text{Zn}_{30}\text{Ca}_5$ plate with a thickness of $XX\mu\text{m}$ was produced by copper mold injection casting. The 25.4mm diameter targets were prepared from a cylindrical copper mold gravity casting sectioned to thicknesses of 3.25mm.

2.2 DC magnetron sputtering

Films were produced from an in-house DC magnetron sputtering facility with Ar working gas (99.997 vol.% purity). The power was 15W, typical voltage of 290 – 350V, nominal chamber temperature of 25 °C, pressure 1 bar, Ar flow 3.01 standard cubic centimetres per minute (SCCM).

2.3 DSC characterization

DSC

2.4 XRD characterization

XRD heated in 5 degree increments at 20 k/min. scans of xx over a range of 30 - 60 2 theta allows 20 minute scans.

3 RESULTS

deposition were for 35 minutes, and saw an average temperature rise of 3 – 4 °C during the deposition. Nominal film thickness was about 2.5 μm giving a deposition rate of 1.2nm/s.

4 DISCUSSION

5 CONCLUSIONS


6 ACKNOWLEDGEMENTS

Yu Wang for his assistance with XRD experimentation and Rietveld refinement.


7 REFERENCES

- hang2013 [1] Y. N. Zhang, G. J. Rocher, B. Briccoli, D. Kevorkov, X. B. Liu, Z. Altounian, and M. Medraj. Crystallization characteristics of the Mg-rich metallic glasses in the Ca-Mg-Zn system. *Journal of Alloys and Compounds*, 552:88–97, 2013.
- hang2012 [2] Yi-Nan Zhang, Dmytro Kevorkov, Xue Dong Liu, Florent Bridier, Patrice Chartrand, and Mamoun Medraj. Homogeneity range and crystal structure of the Ca₂Mg₅Zn₁₃ compound. *Journal of Alloys and Compounds*, 523:75–82, 2012.

- [3] Yi-Nan Zhang, Dmytro Kevorkov, Florent Bridier, and Mamoun Medraj. Experimental study of the Ca-Mg-Zn system using diffusion couples and key alloys. *Science and Technology of Advanced Materials*, 12(2):025003, 2011.




(a)




(b)

Figure 1: (a) Stacked X-ray diffraction (XRD) patterns from the incremental heating of bulk $\text{Mg}_{65}\text{Zn}_{30}\text{Ca}_5$. (b) Cascading XRD patterns from the incremental heating of bulk $\text{Mg}_{65}\text{Zn}_{30}\text{Ca}_5$.



(a)



(b)

Figure 2: (a) Stacked XRD patterns from the incremental heating of film $\text{Mg}_{65}\text{Zn}_{30}\text{Ca}_5$. (b) Cascading XRD patterns from the incremental heating of film $\text{Mg}_{65}\text{Zn}_{30}\text{Ca}_5$.




Figure 3: XRD pattern for $\text{Mg}_{65}\text{Zn}_{30}\text{Ca}_5$ heated through several crystallization peaks identified from DSC

DHeating