

Лабораторная работа 1.4

Транзакция 1	Транзакция 2
READ UNCOMMITTED	
<i>Потерянные изменения</i>	
SELECT price FROM medicaments WHERE id_medicament = 14;	
SET TRANSACTION ISOLATION LEVEL READ UNCOMMITTED; BEGIN;	
	SET TRANSACTION ISOLATION LEVEL READ UNCOMMITTED; BEGIN;
UPDATE medicaments SET price = price + 100 WHERE id_medicament = 14;	
	UPDATE medicaments SET price = price + 100 WHERE id_medicament = 14;
COMMIT;	
	COMMIT;
SELECT price FROM medicaments WHERE id_medicament = 14;	
<i>Грязное чтение</i>	
SET TRANSACTION ISOLATION LEVEL READ UNCOMMITTED; BEGIN;	
	SET TRANSACTION ISOLATION LEVEL READ UNCOMMITTED; BEGIN;
SELECT price FROM medicaments WHERE id_medicament = 14;	
	UPDATE medicaments SET price = price + 100 WHERE id_medicament = 14;
SELECT price FROM medicaments WHERE id_medicament = 14;	
	ROLLBACK;
SELECT price FROM medicaments WHERE id_medicament = 14;	
COMMIT;	
	COMMIT;
READ COMMITTED	

<i>Грязное чтение</i>	
SET TRANSACTION ISOLATION LEVEL READ COMMITTED; BEGIN;	
	SET TRANSACTION ISOLATION LEVEL READ COMMITTED; BEGIN;
SELECT price FROM medicaments WHERE id_medicament = 14;	
	UPDATE medicaments SET price = price + 100 WHERE id_medicament = 14;
SELECT price FROM medicaments WHERE id_medicament = 14;	
	ROLLBACK;
SELECT price FROM medicaments WHERE id_medicament = 14;	
COMMIT;	
	COMMIT;
<i>Неповторяемое чтение</i>	
SET TRANSACTION ISOLATION LEVEL READ COMMITTED; BEGIN;	
	SET TRANSACTION ISOLATION LEVEL READ COMMITTED; BEGIN;
SELECT price FROM medicaments WHERE id_medicament = 14;	
	UPDATE medicaments SET price = price + 100 WHERE id_medicament = 14;
	COMMIT;
SELECT price FROM medicaments WHERE id_medicament = 14;	
COMMIT;	
REPEATABLE READ	
<i>Неповторяемое чтение</i>	
SET TRANSACTION ISOLATION LEVEL REPEATABLE READ; BEGIN;	
	SET TRANSACTION ISOLATION LEVEL REPEATABLE READ; BEGIN;

SELECT price FROM medicaments WHERE id_medicament = 14;	
	UPDATE medicaments SET price = price + 100 WHERE id_medicament = 14;
	COMMIT;
SELECT price FROM medicaments WHERE id_medicament = 14;	
COMMIT;	
<i>Фантомное чтение</i>	
SET TRANSACTION ISOLATION LEVEL REPEATABLE READ; BEGIN;	
	SET TRANSACTION ISOLATION LEVEL REPEATABLE READ; BEGIN;
SELECT COUNT(id_order) AS count FROM orders JOIN customers ON orders.customer = customers.id_customer WHERE name = 'Аптека Шексна';	
	DELETE FROM orders WHERE id_order = 3;
	COMMIT;
SELECT COUNT(id_order) AS count FROM orders JOIN customers ON orders.customer = customers.id_customer WHERE name = 'Аптека Шексна';	
COMMIT;	
SERIALIZABLE	
<i>Фантомное чтение</i>	
SET TRANSACTION ISOLATION LEVEL REPEATABLE READ; BEGIN;	
	SET TRANSACTION ISOLATION LEVEL REPEATABLE READ; BEGIN;
SELECT COUNT(id_order) AS count FROM orders	

JOIN customers ON orders.customer = customers.id_customer WHERE name = 'Аптека Шексна';	
	DELETE FROM orders WHERE id_order = 3;
	COMMIT;
SELECT COUNT(id_order) AS count FROM orders JOIN customers ON orders.customer = customers.id_customer WHERE name = 'Аптека Шексна';	
COMMIT;	
READ COMMITTED	
<i>Фантомное чтение</i>	
SET TRANSACTION ISOLATION LEVEL REPEATABLE READ; BEGIN;	
	SET TRANSACTION ISOLATION LEVEL REPEATABLE READ; BEGIN;
SELECT COUNT(id_order) AS count FROM orders JOIN customers ON orders.customer = customers.id_customer WHERE name = 'Аптека Шексна';	
	DELETE FROM orders WHERE id_order = 3;
	COMMIT;
SELECT COUNT(id_order) AS count FROM orders JOIN customers ON orders.customer = customers.id_customer WHERE name = 'Аптека Шексна';	
COMMIT;	