Приложение В (обязательное) Конфигурация оборудования

Конфигурация маршрутизатора

```
Building configuration...
Current configuration: 5278 bytes
version 12.4
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
hostname Router
enable secret 5 $1$mERr$ZX9nCVjjxd165vnoOu0jg.
ip dhcp excluded-address 192.168.120.100
ip dhcp excluded-address 192.168.117.1
ip dhcp pool Telephony
network 192.168.117.0 255.255.255.0
default-router 192.168.117.1
option 150 ip 192.168.117.1
ip cef
no ipv6 cef
ip ftp username Admin
ip ftp password Admin
ip name-server 192.168.120.100
spanning-tree mode pvst!
```

Подп.

Дата

Лист

№ докум.

Лист

```
interface FastEthernet0/0
no ip address
duplex auto
speed auto
interface FastEthernet0/0.210
encapsulation dot1Q 210
ip address 192.168.110.1 255.255.255.0
interface FastEthernet0/0.211
encapsulation dot1Q 211
ip address 192.168.111.1 255.255.255.0
ip helper-address 192.168.120.100
interface FastEthernet0/0.212
encapsulation dot1Q 212
ip address 192.168.112.1 255.255.255.0
ip helper-address 192.168.120.100
interface FastEthernet0/0.213
encapsulation dot1Q 213
ip address 192.168.113.1 255.255.255.0
ip helper-address 192.168.120.100
interface FastEthernet0/0.214
encapsulation dot1Q 214
ip address 192.168.114.1 255.255.255.0
ip helper-address 192.168.120.100
interface FastEthernet0/0.215
encapsulation dot1Q 215
ip address 192.168.115.1 255.255.255.0
ip helper-address 192.168.120.100
interface FastEthernet0/0.216
encapsulation dot1Q 216
ip address 192.168.116.1 255.255.255.0
ip helper-address 192.168.120.100
interface FastEthernet0/0.217
encapsulation dot1Q 217
ip address 192.168.117.1 255.255.255.0
ip helper-address 192.168.120.100
interface FastEthernet0/0.219
encapsulation dot1Q 219
ip address 192.168.119.1 255.255.255.0
interface FastEthernet0/0.220
encapsulation dot1Q 220
ip address 192.168.120.1 255.255.255.0
interface FastEthernet0/1
no ip address
duplex auto
speed auto
shutdown
```

```
interface Vlan1
no ip address
shutdown
ip classless
ip flow-export version 9
telephony-service
max-ephones 26
max-dn 26
ip source-address 192.168.116.100 port 2000
auto assign 1 to 26
ephone-dn 1
number 101
ephone-dn 2
number 102
ephone-dn 3
number 103
ephone-dn 4
number 104
ephone-dn 5
number 105
ephone-dn 6
number 106
ephone-dn 7
number 107
ephone-dn 8
number 108
ephone-dn 9
number 109
ephone-dn 10
number 110
ephone-dn 11
number 111
ephone-dn 12
number 112
ephone-dn 13
```

```
number 113
ephone-dn 14
number 114
ephone-dn 15
number 115
ephone-dn 16
number 116
ephone-dn 17
number 117
ephone-dn 18
number 118
ephone-dn 19
number 119
ephone-dn 20
number 120
ephone-dn 21
number 121
ephone-dn 22
number 122
ephone-dn 23
number 123
ephone-dn 24
number 124
ephone-dn 25
number 125
ephone-dn 26
number 126
ephone 1
device-security-mode none
mac-address 0050.0F43.7638
type 7960
button 1:4
ephone 2
device-security-mode none
mac-address 00D0.BCAA.28CC
type 7960
button 1:12
ephone 3
device-security-mode none
mac-address 000C.8573.C085
type 7960
button 1:18
```

```
ephone 4
device-security-mode none
mac-address 00E0.B002.DA05
type 7960
button 1:16
ephone 5
device-security-mode none
mac-address 0030.F2E8.8779
type 7960
button 1:14
ephone 6
device-security-mode none
mac-address 0001.C745.4B92
type 7960
button 1:23
ephone 7
device-security-mode none
mac-address 00D0.FF6D.6C03
type 7960
button 1:6
ephone 8
device-security-mode none
mac-address 00E0.F744.5835
type 7960
button 1:19
ephone 9
device-security-mode none
mac-address 00D0.D3C9.D070
type 7960
button 1:3
ephone 10
device-security-mode none
mac-address 0004.9A99.5D86
type 7960
button 1:11
ephone 11
device-security-mode none
mac-address 0009.7C37.884E
type 7960
button 1:10
ephone 12
device-security-mode none
mac-address 00E0.B019.38D7
type 7960
button 1:7
ephone 13
device-security-mode none
mac-address 0004.9A23.7996
type 7960
button 1:25
```

```
ephone 14
device-security-mode none
mac-address 0002.1770.CA8B
type 7960
button 1:22
ephone 15
device-security-mode none
mac-address 00D0.FFA3.714B
type 7960
button 1:8
ephone 16
device-security-mode none
mac-address 0060.70B9.E696
type 7960
button 1:17
ephone 17
device-security-mode none
mac-address 00E0.A328.B19B
type 7960
button 1:24
ephone 18
device-security-mode none
mac-address 00E0.8F27.C6C1
type 7960
button 1:2
ephone 19
device-security-mode none
mac-address 00D0.BAD6.7E0E
type 7960
button 1:13
ephone 20
device-security-mode none
mac-address 0002.1655.CC37
type 7960
button 1:1
ephone 21
device-security-mode none
mac-address 0002.16DA.A876
type 7960
button 1:5
ephone 22
device-security-mode none
mac-address 0000.0CC3.C1A5
type 7960
button 1:21
ephone 23
device-security-mode none
mac-address 0001.C946.6DB4
type 7960
```

```
button 1:20
ephone 24
device-security-mode none
mac-address 00E0.B069.0A50
type 7960
button 1:26
ephone 25
device-security-mode none
mac-address 0006.2A06.9435
type 7960
button 1:9
ephone 26
device-security-mode none
mac-address 000C.85CA.DE4C
type 7960
button 1:15
line con 0
exec-timeout 60 0
password Polina
login
line aux 0
line vty 04
login
end
```

Изм	Лист	№ докум.	Подп.	Дата

Конфигурация коммутатора Switch0

```
Building configuration...
Current configuration: 3118 bytes
version 12.2
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
hostname Switch
enable secret 5 $1$mERr$ZX9nCVjjxd165vnoOu0jg.
vtp mode transparent
spanning-tree mode pvst
spanning-tree extend system-id
vlan 210
name Useless
vlan 211
name Wireless
vlan 212
name R
vlan 213
name O
vlan 214
name Y
vlan 215
name G
vlan 216
name B
vlan 217
name N
vlan 218
name Trunk
vlan 219
name Admin
vlan 220
name Server
interface FastEthernet0/1
```

```
switchport access vlan 212
switchport mode access
interface FastEthernet0/2
switchport access vlan 212
switchport mode access
interface FastEthernet0/3
switchport access vlan 212
switchport mode access
interface FastEthernet0/4
switchport access vlan 212
switchport mode access
interface FastEthernet0/5
switchport access vlan 212
switchport mode access
interface FastEthernet0/6
switchport access vlan 212
switchport mode access
interface FastEthernet0/7
switchport access vlan 212
switchport mode access
interface FastEthernet0/8
switchport access vlan 212
switchport mode access
interface FastEthernet0/9
switchport access vlan 212
switchport mode access
interface FastEthernet0/10
switchport access vlan 212
switchport mode access
interface FastEthernet0/11
switchport access vlan 212
switchport mode access
interface FastEthernet0/12
switchport access vlan 212
switchport mode access
interface FastEthernet0/13
switchport access vlan 212
switchport mode access
interface FastEthernet0/14
switchport access vlan 212
switchport mode access
interface FastEthernet0/15
switchport access vlan 210
switchport mode access
switchport voice vlan 217
```

```
interface FastEthernet0/16
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/17
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/18
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/19
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/20
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/21
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/22
switchport trunk native vlan 218
switchport mode trunk
interface FastEthernet0/23
switchport access vlan 211
switchport mode access
interface FastEthernet0/24
switchport access vlan 210
switchport mode access
interface GigabitEthernet0/1
switchport access vlan 210
switchport mode access
interface GigabitEthernet0/2
switchport access vlan 210
switchport mode access
interface Vlan1
no ip address
shutdown
interface Vlan219
description LAN
mac-address 00d0.ffa4.8001
ip address 192.168.119.101 255.255.255.0
```

```
ip default-gateway 192.168.112.1
line con 0
password Polina
login
exec-timeout 60 0
line vty 0 4
login
line vty 5 15
login
end
```

Изм	Лист	Nogoram	Подп	Лата

```
Конфигурация коммутатора Switch1
Building configuration...
Current configuration: 3218 bytes
version 12.2
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
hostname Switch
ip ftp username Admin
ip ftp password Admin
enable secret 5 $1$mERr$ZX9nCVjjxd165vnoOu0jg.
vtp mode transparent
spanning-tree mode pvst
spanning-tree extend system-id
vlan 210
name Useless
vlan 211
name Wireless
vlan 212
name R
vlan 213
name O
vlan 214
name Y
vlan 215
name G
vlan 216
name B
vlan 217
name N
vlan 218
name Trunk
vlan 219
name Admin
vlan 220
name Server
```

```
interface FastEthernet0/1
switchport access vlan 213
switchport mode access
interface FastEthernet0/2
switchport access vlan 213
switchport mode access
interface FastEthernet0/3
switchport access vlan 213
switchport mode access
interface FastEthernet0/4
switchport access vlan 213
switchport mode access
interface FastEthernet0/5
switchport access vlan 213
switchport mode access
interface FastEthernet0/6
switchport access vlan 213
switchport mode access
interface FastEthernet0/7
switchport access vlan 213
switchport mode access
interface FastEthernet0/8
switchport access vlan 213
switchport mode access
interface FastEthernet0/9
switchport access vlan 213
switchport mode access
interface FastEthernet0/10
switchport access vlan 213
switchport mode access
interface FastEthernet0/11
switchport access vlan 213
switchport mode access
interface FastEthernet0/12
switchport access vlan 213
switchport mode access
interface FastEthernet0/13
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/14
switchport access vlan 210
switchport mode access
switchport voice vlan 217
```

```
interface FastEthernet0/15
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/16
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/17
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/18
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/19
switchport trunk native vlan 218
switchport mode trunk
interface FastEthernet0/20
switchport access vlan 220
switchport trunk native vlan 218
switchport mode access
interface FastEthernet0/21
switchport trunk native vlan 218
switchport mode trunk
interface FastEthernet0/22
switchport trunk native vlan 218
switchport mode trunk
interface FastEthernet0/23
switchport trunk native vlan 218
switchport mode trunk
interface FastEthernet0/24
switchport access vlan 210
switchport trunk native vlan 218
switchport mode access
interface GigabitEthernet0/1
switchport access vlan 210
switchport mode access
interface GigabitEthernet0/2
switchport access vlan 210
switchport mode access
interface Vlan1
no ip address
shutdown
interface Vlan219
```

```
description LAN
mac-address 0001.6372.b501
ip address 192.168.119.102 255.255.255.0
!
ip default-gateway 192.168.113.1
!
!
!!
line con 0
password Polina
login
exec-timeout 60 0
!
line vty 0 4
login
line vty 5 15
login
!
!
!
!
!
! end
```

Изм	Лист	№ докум.	Подп.	Дата

```
Конфигурация коммутатора Switch2
Building configuration...
Current configuration: 3040 bytes
version 12.2
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
hostname Switch
enable secret 5 $1$mERr$ZX9nCVjjxd165vnoOu0jg.
vtp mode transparent
spanning-tree mode pvst
spanning-tree extend system-id
vlan 210
name Useless
vlan 211
name Wireless
vlan 212
name R
vlan 213
name O
vlan 214
name Y
vlan 215
name G
vlan 216
name B
vlan 217
name N
vlan 218
name Trunk
vlan 219
name Admin
vlan 220
name Server
interface FastEthernet0/1
```

```
switchport access vlan 215
switchport mode access
interface FastEthernet0/2
switchport access vlan 215
switchport mode access
interface FastEthernet0/3
switchport access vlan 215
switchport mode access
interface FastEthernet0/4
switchport access vlan 215
switchport mode access
interface FastEthernet0/5
switchport access vlan 215
switchport mode access
interface FastEthernet0/6
switchport access vlan 215
switchport mode access
interface FastEthernet0/7
switchport access vlan 215
switchport mode access
interface FastEthernet0/8
switchport access vlan 215
switchport mode access
interface FastEthernet0/9
switchport access vlan 215
switchport mode access
interface FastEthernet0/10
switchport access vlan 215
switchport mode access
interface FastEthernet0/11
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/12
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/13
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/14
switchport access vlan 210
switchport mode access
switchport voice vlan 217
```

```
interface FastEthernet0/15
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/16
switchport trunk native vlan 218
switchport mode trunk
interface FastEthernet0/17
switchport access vlan 211
interface FastEthernet0/18
switchport access vlan 210
switchport mode access
interface FastEthernet0/19
switchport access vlan 210
switchport mode access
interface FastEthernet0/20
switchport access vlan 210
switchport mode access
interface FastEthernet0/21
switchport access vlan 210
switchport mode access
interface FastEthernet0/22
switchport access vlan 210
switchport mode access
interface FastEthernet0/23
switchport access vlan 210
switchport mode access
interface FastEthernet0/24
switchport access vlan 210
switchport mode access
interface GigabitEthernet0/1
switchport access vlan 210
switchport mode access
interface GigabitEthernet0/2
switchport access vlan 210
switchport mode access
interface Vlan1
no ip address
shutdown
interface Vlan219
description LAN
mac-address 0003.e4a3.cc01
ip address 192.168.119.104 255.255.255.0
ip default-gateway 192.168.115.1
```

line con 0 password Polina login exec-timeout 60 0 line vty 0 4 login line vty 5 15 login end Лист БГУИР 961401.001 105 Лист № докум. Подп. Дата

Конфигурация коммутатора Switch3

```
Building configuration...
Current configuration: 3018 bytes
version 12.2
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
hostname Switch
enable secret 5 $1$mERr$ZX9nCVjjxd165vnoOu0jg.
vtp mode transparent
spanning-tree mode pvst
spanning-tree extend system-id
vlan 210
name Useless
vlan 211
name Wireless
vlan 212
name R
vlan 213
name O
vlan 214
name Y
vlan 215
name G
vlan 216
name B
vlan 217
name N
vlan 218
name Trunk
vlan 219
name Admin
vlan 220
name Server
interface FastEthernet0/1
```

```
switchport access vlan 214
switchport mode access
interface FastEthernet0/2
switchport access vlan 214
switchport mode access
interface FastEthernet0/3
switchport access vlan 214
switchport mode access
interface FastEthernet0/4
switchport access vlan 214
switchport mode access
interface FastEthernet0/5
switchport access vlan 214
switchport mode access
interface FastEthernet0/6
switchport access vlan 214
switchport mode access
interface FastEthernet0/7
switchport access vlan 214
switchport mode access
interface FastEthernet0/8
switchport access vlan 214
switchport mode access
interface FastEthernet0/9
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/10
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/11
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/12
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/13
switchport trunk native vlan 218
switchport mode trunk
interface FastEthernet0/14
switchport trunk native vlan 218
switchport mode trunk
```

```
interface FastEthernet0/15
switchport access vlan 211
interface FastEthernet0/16
switchport access vlan 210
switchport mode access
interface FastEthernet0/17
switchport access vlan 210
switchport mode access
interface FastEthernet0/18
switchport access vlan 210
switchport mode access
interface FastEthernet0/19
switchport access vlan 210
switchport mode access
interface FastEthernet0/20
switchport access vlan 210
switchport mode access
interface FastEthernet0/21
switchport access vlan 210
switchport mode access
interface FastEthernet0/22
switchport access vlan 210
switchport mode access
interface FastEthernet0/23
switchport access vlan 210
switchport mode access
interface FastEthernet0/24
switchport access vlan 210
switchport mode access
interface GigabitEthernet0/1
switchport access vlan 210
switchport mode access
interface GigabitEthernet0/2
switchport access vlan 210
switchport mode access
interface Vlan1
no ip address
shutdown
interface Vlan219
description LAN
mac-address 00d0.bcb5.2001
ip address 192.168.119.103 255.255.255.0
ip default-gateway 192.168.114.1
```

line con 0 password Polina login exec-timeout 60 0 line vty 0 4 login line vty 5 15 login end Лист БГУИР 961401.001 110 Лист № докум. Подп. Дата

Конфигурация коммутатора Switch4

```
Building configuration...
Current configuration: 3037 bytes
version 12.2
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
hostname Switch
enable secret 5 $1$mERr$ZX9nCVjjxd165vnoOu0jg.
vtp mode transparent
spanning-tree mode pvst
spanning-tree extend system-id
vlan 210
name Useless
vlan 211
name Wireless
vlan 212
name R
vlan 213
name O
vlan 214
name Y
vlan 215
name G
vlan 216
name B
vlan 217
name N
vlan 218
name Trunk
vlan 219
name Admin
vlan 220
name Server
interface FastEthernet0/1
```

```
switchport access vlan 216
switchport mode access
interface FastEthernet0/2
switchport access vlan 216
switchport mode access
interface FastEthernet0/3
switchport access vlan 216
switchport mode access
interface FastEthernet0/4
switchport access vlan 216
switchport mode access
interface FastEthernet0/5
switchport access vlan 216
switchport mode access
interface FastEthernet0/6
switchport access vlan 216
switchport mode access
interface FastEthernet0/7
switchport access vlan 216
switchport mode access
interface FastEthernet0/8
switchport access vlan 216
switchport mode access
interface FastEthernet0/9
switchport access vlan 210
switchport mode access
switchport voice vlan 216
interface FastEthernet0/10
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/11
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/12
switchport access vlan 210
switchport mode access
switchport voice vlan 217
interface FastEthernet0/13
switchport trunk native vlan 218
switchport mode trunk
interface FastEthernet0/14
switchport access vlan 210
switchport mode access
```

```
interface FastEthernet0/15
switchport access vlan 210
switchport mode access
interface FastEthernet0/16
switchport access vlan 210
switchport mode access
interface FastEthernet0/17
switchport access vlan 210
switchport mode access
interface FastEthernet0/18
switchport access vlan 210
switchport mode access
interface FastEthernet0/19
switchport access vlan 210
switchport mode access
interface FastEthernet0/20
switchport access vlan 210
switchport mode access
interface FastEthernet0/21
switchport access vlan 210
switchport mode access
interface FastEthernet0/22
switchport access vlan 210
switchport mode access
interface FastEthernet0/23
switchport access vlan 210
switchport mode access
interface FastEthernet0/24
switchport access vlan 210
switchport mode access
interface GigabitEthernet0/1
switchport access vlan 210
switchport mode access
interface GigabitEthernet0/2
switchport access vlan 210
switchport mode access
interface Vlan1
no ip address
shutdown
interface Vlan219
description LAN
mac-address 00d0.bc08.4501
ip address 192.168.119.105 255.255.255.0
ip default-gateway 192.168.116.1
```

line con 0 password Polina login exec-timeout 60 0 line vty 0 4 login line vty 5 15 login end Лист БГУИР 961401.001 115 Лист № докум. Подп. Дата