

OSSP

Socket server/client

Socket server

```
polisettyreesharsha@SREEHA x + v
GNU nano 8.7.1 socketserver.c *
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>

#define SOCKET_PATH "/tmp/my_socket"

int main(){
int server_fd, client_fd;
struct sockaddr_un address;
char buffer[100];

server_fd = socket(AF_UNIX, SOCK_STREAM, 0);

address.sun_family = AF_UNIX;
strcpy(address.sun_path, SOCKET_PATH);

unlink(SOCKET_PATH);

bind(server_fd, (struct sockaddr *)&address, sizeof(address));

listen(server_fd, 5);

printf("Server waiting ... \n");

client_fd = accept(server_fd, NULL, NULL);

read(client_fd, buffer, sizeof(buffer));

printf("Message from client: %s\n", buffer);

close(client_fd);
close(server_fd);
unlink(SOCKET_PATH);
return 0;
}
```

Socket Client

```
polisettyreesharsha@SREEHA x + v
GNU nano 8.7.1 socketclient.c
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>

#define SOCKET_PATH "/tmp/my_socket"

int main()
{
int client_fd;
struct sockaddr_un address;

// Create socket
client_fd = socket(AF_UNIX, SOCK_STREAM, 0);

// Set socket address
address.sun_family = AF_UNIX;
strcpy(address.sun_path, SOCKET_PATH);

// Connect to server
connect(client_fd, (struct sockaddr *)&address, sizeof(address));
// Send message
write(client_fd, "Hello Server", 12);

printf("Message sent to server.\n");

close(client_fd);

return 0;
}
```

Output:

```
polisettyreesharsha@SREEHA x + v
polisettyreesharsha@SREEHARSHA:~$ gcc socketserver.c -o socketserver
polisettyreesharsha@SREEHARSHA:~$ ./socketserver
Server waiting ...
Message from client: Hello Server
polisettyreesharsha@SREEHARSHA:~$ |

polisettyreesharsha@SREEHARSHA:~$ gcc socketclient.c -o socketclient
polisettyreesharsha@SREEHARSHA:~$ ./socketclient
Message sent to server.
polisettyreesharsha@SREEHARSHA:~$ |
```