

# Numerical Methods, project A, Number 31

Krzysztof Rudnicki  
Student number: 307585  
Advisor: dr Adam Krzemieniowski

November 11, 2021

# Contents

<b>1</b>	<b>Problem 1 - Finding machine epsilon</b>	<b>3</b>
1.1	Problem . . . . .	3
1.2	Theoretical Introduction . . . . .	3
1.2.1	Definition of machine epsilon . . . . .	3
1.2.2	Practical applications of machine epsilon . . . . .	3
1.3	Solution . . . . .	4
1.3.1	Matlab code . . . . .	4
1.4	Discussion of the result . . . . .	4
<b>2</b>	<b>Problem 2 - Solving a system of n linear equations - indicated method</b>	<b>6</b>
2.1	Problem . . . . .	6
2.2	Theoretical Introduction . . . . .	6
2.2.1	Transform matrix into upper-triangular matrix . . . . .	6
2.2.2	Backward substitution . . . . .	8
2.2.3	Partial Pivoting . . . . .	8
2.3	Solution . . . . .	9
2.4	Discussion of the result . . . . .	9

<b>3</b>	<b>Problem 3 - Solving a system of n linear equations - iterative algorithm</b>	<b>11</b>
3.1	Problem . . . . .	11
3.2	Theoretical introduction . . . . .	11
3.2.1	Procedure . . . . .	12
3.3	Solution . . . . .	16
3.4	Discussion of the result . . . . .	16
<b>4</b>	<b>Problem 4 - QR method of finding eigenvalues</b>	<b>17</b>
4.1	Problem . . . . .	17
4.2	Theoretical introduction . . . . .	17
4.3	Solution . . . . .	17
4.4	Discussion of the result . . . . .	17
<b>5</b>	<b>Code appendix</b>	<b>18</b>
5.1	Task 2 Code . . . . .	18
5.1.1	Main function . . . . .	18
5.1.2	checkIfMatrixIsSquareMatrix . . . . .	18
5.1.3	gaussianEliminationWithPartialPivoting . . . . .	20
5.1.4	partialPivoting . . . . .	20
5.1.5	partialPivotingSwapOneRow . . . . .	20
5.1.6	swapRowMatrix . . . . .	20
5.1.7	swapValueVector . . . . .	21
5.1.8	gaussianElimination . . . . .	21
5.1.9	subtractRows . . . . .	21
5.1.10	backSubstitutionPhase . . . . .	22
5.1.11	iterativeResidualCorrection . . . . .	22
5.1.12	improveSolution . . . . .	22

# Chapter 1

## Problem 1 - Finding machine epsilon

### 1.1 Problem

Write a program finding macheps in the MATLAB environment

### 1.2 Theoretical Introduction

#### 1.2.1 Definition of machine epsilon

Machine epsilon is the maximal possible relative error of the floating-point representation. (Tatjewski, p.14) Machine epsilon is equal to  $2^{-t}$  where  $t$  is number of bits in the mantissa. In our case when we use IEEE Standard 754, mantissa is 53 bits long with first bit omitted as it is always equal to '1', so we technically work with 52 bits mantissa which makes the machine epsilon equal to:  $2^{-52} = 2.220446\text{e-}16$

#### 1.2.2 Practical applications of machine epsilon

Since macheps is connected to IEEE754 standard it is always equal to the same number, which means that we can safely compare results from different machines without worrying about their individual errors.

Macheps is also essential when we calculate cumulation of errors of given mathematical operation.

## 1.3 Solution

### 1.3.1 Matlab code

```
1 macheps = 1;
2 while 1.0 + macheps / 2 > 1.0
3     macheps = macheps/2;
4 end
```

Code above shifts macheps one bit to the right each iteration (by dividing by 2), it ends when we run out of mantissa bits which renders us unable to save smaller number. Due to underflow the value of macheps becomes 0 and therefore  $1.0 > (\text{macheps} / 2) > 1.0$  will become false.

## 1.4 Discussion of the result

```
1 format long
2 disp(Display calculated macheps:)
3 disp(macheps);
4 disp(Display actual eps:)
5 disp(eps);
6 disp(Display 2^-52)
7 disp(2^-52)
8 disp(Display difference between calculated macheps and actual eps:)
9 disp(macheps - eps)
10 disp(Display difference between 2^-52 and actual eps:)
11 disp(2^-52 - eps) \
12 disp(Display difference between calculated macheps and 2^-52:)
13 disp(macheps - 2^-52)
```

Display calculated macheps:

2.220446049250313e-16

Display actual eps:

2.220446049250313e-16

Display  $2^{-52}$ :

2.220446049250313e-16

Display difference between calculated macheps and actual eps:

0

Display difference between  $2^{-52}$  and actual eps:

0

Display difference between calculated macheps and  $2^{-52}$ :

0

As expected they are all equal to eachother. It means that our method of calculating macheps was correct.

## Chapter 2

# Problem 2 - Solving a system of n linear equations - indicated method

### 2.1 Problem

Write a program solving a system of  $n$  linear equations  $Ax = b$  using the indicated method (Gaussian elimination with partial pivoting).

### 2.2 Theoretical Introduction

Gaussian elimination with partial pivoting consists of 3 main steps:

#### 2.2.1 Transform matrix into upper-triangular matrix

##### Starting conditions

We start with the system of linear equations looking like this:

$$\begin{array}{cccccc} a_{11}x_1 & + & a_{12}x_2 & + & \dots & + & a_{1n}x_n & = & b_1, \\ a_{21}x_1 & + & a_{22}x_2 & + & \dots & + & a_{2n}x_n & = & b_2, \\ \vdots & & \vdots & & & & \vdots & & \vdots \\ a_{n1}x_1 & + & a_{n2}x_2 & + & \dots & + & a_{nn}x_n & = & b_n. \end{array}$$

In order for this method to work all the elements of **diagonal** line:

$$a_{11}, a_{22}, \dots, a_{nn}$$

Must be different from zero since we will be dividing by them.

We will denote rows as ' $w_i$ ' where 'i' is number of the row.

### Zeroing first column

We start transforming the system by **zeroing** elements in first column excluding first row element. We do it by multiplying first row by  $l_{i1}$ , where:

$$l_{i1} = \frac{a_{i1}^{(1)}}{a_{11}^{(1)}}$$

And then subtracting what we got ( $l_{i1}w_1$ ), from  $i$  row.

Doing so we obtain a system of linear equations:

$$\begin{array}{ccccccccc} a_{11}x_1 & + & a_{12}x_2 & + & \dots & + & a_{1n}x_n & = & b_1, \\ 0 & + & (a_{22} - a_{12}l_{21})x_2 & + & \dots & + & (a_{2n} - a_{1n}l_{21})x_n & = & b_2 - b_1l_{21}, \\ \vdots & & \vdots & & & & \vdots & & \vdots \\ 0 & + & (a_{n2} - a_{12}l_{n1})x_2 & + & \dots & + & (a_{nn} - a_{1n}l_{n1})x_n & = & b_n - b_1l_{n1}. \end{array}$$

### Zeroing second column

We continue onto the second column, this time we will zero all elements except first and second rows. Row multiplier becomes:

$$l_{i2} = \frac{a_{i2}^{(2)}}{a_{22}^{(2)}}$$

Where:

$$a_{22}^{(2)} = (a_{22} - a_{12}l_{21})$$

And:

$$a_{i2}^{(2)} = (a_{i2} - a_{12}l_{i1})$$

They are modified values obtained from previous step. We continue as in the first step and we end up with:

$$\begin{array}{ccccccccc} a_{11}x_1 & + & a_{12}x_2 & + & \dots & + & a_{1n}x_n & = & b_1, \\ 0 & + & a_{22}^{(2)}x_2 & + & \dots & + & a_{2n}^{(2)}x_n & = & b_2^{(2)}, \\ \vdots & & \vdots & & & & \vdots & & \vdots \\ 0 & + & 0 & + & \dots & + & a_{nn}^{(3)}x_n & = & b_2^{(3)}, \end{array}$$

### Zeroing next columns

We repeat this process  $n - 1$  times and we end up with upper triangular matrix:

$$\begin{array}{ccccccccc} a_{11}x_1 & + & a_{12}x_2 & + & \dots & + & a_{1n}x_n & = & b_1, \\ 0 & + & a_{22}^{(2)}x_2 & + & \dots & + & a_{2n}^{(2)}x_n & = & b_2^{(2)}, \\ \vdots & & \vdots & & & & \vdots & & \vdots \\ 0 & + & 0 & + & \dots & + & a_{nn}^{(n)}x_n & = & b_2^{(n)}, \end{array}$$



### 2.2.2 Backward substitution

After transforming the system we solve the system from last to first.  
First we calculate value of last element:

$$x_n = \frac{b_n}{a_{nn}}$$

Then one above:

$$x_{n-1} = \frac{b_{n-1} - a_{n-1,n}x_n}{a_{n-1,n-1}}$$

And so on, for  $x_k$ :

$$x_k = \frac{b_k - \sum_{j=k+1}^n a_{kj}x_j}{a_{kk}}$$

### 2.2.3 Partial Pivoting

Gaussian elimination method has one flaw, where it can come into halt if:

$$a_{kk}^{(k)} = 0$$

To avoid it we use method of pivoting, in our case we will use partial pivoting method. We do it before each Gaussian elimination step since this will lead to smaller error.

We first find a row  $i$  such that:

$$|a_{ik}^k| = \max_j \{|a_{kk}^k|, |a_{k+1,k}^k|, \dots, |a_{nk}^k|\}$$

Then we swap this row with  $k$ -th row. Since the matrix we use is assumed to be nonsingular then  $|a_{ik}^k| \neq 0$  will be always true. After that we continue with the Gaussian elimination method.

## 2.3 Solution

## 2.4 Discussion of the result

Solutions vectors for matrix A and vector A and n = 16:

$$x_{algorithm} = \begin{pmatrix} -0.930056653761514 \\ -1.223503294617857 \\ -1.273786563425385 \\ -1.231189728991652 \\ -1.153115956882885 \\ -1.061491474990357 \\ -0.964691801421511 \\ -0.865917262607523 \\ -0.766393319734375 \\ -0.666596029928932 \\ -0.566728103385765 \\ -0.466921613561691 \\ -0.367370070632649 \\ -0.268521931669581 \\ -0.171529057709426 \\ -0.079398574792031 \end{pmatrix} \quad x_{MatlabMethod} = \begin{pmatrix} -0.930056653761507 \\ -1.223503294617854 \\ -1.273786563425390 \\ -1.231189728991649 \\ -1.153115956882891 \\ -1.061491474990357 \\ -0.964691801421514 \\ -0.865917262607518 \\ -0.766393319734373 \\ -0.666596029928935 \\ -0.566728103385765 \\ -0.466921613561692 \\ -0.367370070632646 \\ -0.268521931669579 \\ -0.171529057709426 \\ -0.079398574792031 \end{pmatrix}$$

Error for 'A' method for algorithm:

$$3.383918772654241$$

Error for 'A' method for matlab method:

$$3.383918772654241$$

Solutions vectors for matrix B and vector B and n = 16 (Both multiplied by  $1.0e + 17$ ):

$$x_{algorithm} = \begin{pmatrix} 0.000001960155675 \\ -0.000102773501571 \\ 0.001959454282882 \\ -0.018894079120425 \\ 0.104895022735396 \\ -0.352396798852209 \\ 0.705545645736628 \\ -0.728747526649489 \\ 0.112818247768452 \\ 0.261440075930356 \\ 0.953713133491034 \\ -3.080986443185790 \\ 3.765178552913233 \\ -2.440218622397594 \\ 0.834768953546100 \\ -0.118974790826378 \end{pmatrix} \quad x_{MatlabMethod} = \begin{pmatrix} 0.000001102587209 \\ -0.000066546298462 \\ 0.001476714765758 \\ -0.016859999627589 \\ 0.113920718370153 \\ -0.488374161741872 \\ 1.368641128884513 \\ -2.495283439985873 \\ 2.793405296264694 \\ -1.547642305352008 \\ -0.035332172403445 \\ 0.154726025421297 \\ 0.807694426359552 \\ -1.133485136703852 \\ 0.592810708065954 \\ -0.115632364630554 \end{pmatrix}$$

Error for 'B' method for algorithm:

$$5.699979882700911e + 17$$

Error for 'B' method for matlab method:

$$4.569118543317684e + 17$$

## Chapter 3

# Problem 3 - Solving a system of n linear equations - iterative algorithm

### 3.1 Problem

Write a general program for solving the system of n linear equations  $Ax = b$  using the Gauss-Seidel **and** Jacobi iterative algorithms.

We are given following system:

$$\begin{cases} 10x_1 - 4x_2 + x_3 + 2x_4 = -8 \\ 2x_1 - 6x_2 + 3x_3 - x_4 = -12 \\ x_1 + 4x_2 - 12x_3 + x_4 = 4 \\ 2x_1 + 3x_2 - 3x_3 - 10x_4 = 1 \end{cases}$$

Then we need to compare the results of iterations plotting norm of the solution error versus the iteration number  $k$ , until we get accuracy better than  $10^{-10}$ .

We should also try to solve the equations from problem 2a) and 2b) for  $n = 10$  using iterative method of our choice.

### 3.2 Theoretical introduction

We should also answer the question what happens if the sufficient condition is not fulfilled.

Iterative methods differ from the Gauss elimination method since they are iterative, which means that our solution will improve with each iteration. Building on that we can conclude that the number of iterations will depend on what accuracy we want to achieve. Since we are using iterative method we don't

have the guarantee of how many iterations will be needed before we reach the solution,

In general: We start with:  $x^{(0)}$  - being the best known approximation of the solution point

And we generate next vectors  $x^{i+1}$  in such way:

$$\mathbf{x}^{i+1} = \mathbf{M}\mathbf{x}^{(i)} + \mathbf{w}$$

Where  $\mathbf{M}$  is some matrix.

### 3.2.1 Procedure

#### Decomposing matrix

For both Jacobi and Gauss-Seidel method we first decompose starting matrix  $\mathbf{A}$  to:

$$\mathbf{A} = \mathbf{L} + \mathbf{D} + \mathbf{U}$$

where:  $\mathbf{L}$  - Subdiagonal matrix  $\mathbf{D}$  - Diagonal matrix  $\mathbf{U}$  - Matrix with entries over the diagonal.

For example: For:

$$\mathbf{A} = \begin{bmatrix} 2 & 3 & 3 \\ 1 & 2 & 3 \\ 1 & 1 & 2 \end{bmatrix}$$

We can get:

$$\mathbf{L} = \begin{bmatrix} 0 & 0 & 0 \\ 1 & 0 & 0 \\ 1 & 1 & 0 \end{bmatrix}$$

$$\mathbf{D} = \begin{bmatrix} 2 & 0 & 0 \\ 0 & 2 & 0 \\ 0 & 0 & 2 \end{bmatrix}$$

$$\mathbf{U} = \begin{bmatrix} 0 & 3 & 3 \\ 0 & 0 & 3 \\ 0 & 0 & 0 \end{bmatrix}$$

so:

$$\mathbf{A} = \mathbf{L} + \mathbf{D} + \mathbf{U}$$

$$\begin{bmatrix} 2 & 3 & 3 \\ 1 & 2 & 3 \\ 1 & 1 & 2 \end{bmatrix} = \begin{bmatrix} 0 & 0 & 0 \\ 1 & 0 & 0 \\ 1 & 1 & 0 \end{bmatrix} + \begin{bmatrix} 2 & 0 & 0 \\ 0 & 2 & 0 \\ 0 & 0 & 2 \end{bmatrix} + \begin{bmatrix} 0 & 3 & 3 \\ 0 & 0 & 3 \\ 0 & 0 & 0 \end{bmatrix}$$

### Jacobi's method

After decomposing matrix we can write the system of equations

$$\mathbf{Ax} = \mathbf{b}$$

in the form:

$$\mathbf{Dx} = -(\mathbf{L} + \mathbf{U})\mathbf{x} + \mathbf{b}$$

If we assume that diagonal entries of matrix  $\mathbf{A}$  are nonzero, then matrix  $\mathbf{D}$  is nonsingular therefore we can propose such an iterative method:

$$\mathbf{x}^{i+1} = -\mathbf{D}^{-1}(\mathbf{L} + \mathbf{U})\mathbf{x}^{(i)} + \mathbf{D}^{-1}\mathbf{b}$$

This is the Jacobi's method. We can rewrite this equation in the form of  $n$  independent scalar equations:

$$x_j^{i+1} = -\frac{1}{d_{jj}} \left( \sum_{k=1}^n (l_{jk} + u_{jk}) x_k^{(i)} + b_j \right)$$

Where  $d_{jj}$ ;  $l_{jk}$ ;  $u_{jk}$  are the elements of the respective matrixes  $\mathbf{D}$ ,  $\mathbf{L}$ ,  $\mathbf{U}$

Thanks to this we can do those computations in parallel, totally or partially if we are using a computer that enables a parallelization of the computations.

**Converging** Jacobi's method is convergent if we have strong diagonal dominance of the matrix  $\mathbf{A}$

### Gauss-Seidel method

After decomposing matrix we can write the system of equations

$$\mathbf{Ax} = \mathbf{b}$$

in the form:

$$(\mathbf{L} + \mathbf{D})\mathbf{x} = -\mathbf{Ux} + \mathbf{b}$$

Again we assume that  $\mathbf{D}$  is nonsingular, in doing so we propose following iterative method:

$$\mathbf{Dx}^{(i+1)} = -\mathbf{Lx}^{(i+1)} - \mathbf{Ux}^{(i)} + \mathbf{b}$$

Since matrix  $\mathbf{L}$  is subdiagonal, provided that we organise the calculation of elements of the vector  $x^{(i+1)}$  in a proper way, it does not hurt that  $x^{(i)}$  is on the right side of the equation. In order to organise the calculation in the correct way we: First take into account the structure of matrixes  $\mathbf{D}$  and  $\mathbf{L}$ :

$$\begin{bmatrix} d_{11}x_1^{(i_1)} \\ d_{22}x_2^{(i_1)} \\ d_{33}x_3^{(i_1)} \\ \vdots \\ d_{nn}x_n^{(i_1)} \end{bmatrix} = - \begin{bmatrix} 0 & 0 & 0 & \cdots & 0 \\ l_{21} & 0 & 0 & \cdots & 0 \\ l_{32} & l_{32} & 0 & \cdots & 0 \\ \vdots & \vdots & \vdots & \vdots & \vdots \\ l_{n1} & l_{n2} & l_{n3} & \cdots & 0 \end{bmatrix} \begin{bmatrix} x_1^{(i_1)} \\ x_2^{(i_1)} \\ x_3^{(i_1)} \\ \vdots \\ x_n^{(i_1)} \end{bmatrix} - \mathbf{w}^{(i)}$$

Where

$$\mathbf{w}^{(i)} = \mathbf{U}\mathbf{x}^{(i)} - \mathbf{b}$$

So the order of calculations is as follows:

$$\begin{aligned}x_1^{(i+1)} &= -\frac{w_1^{(i)}}{d_{11}} \\x_2^{(i+1)} &= -\frac{-l_{21}x_1^{(i+1)} - w_2^{(i)}}{d_{22}} \\x_3^{(i+1)} &= -\frac{-l_{31}x_1^{(i+1)} - l_{32}x_2^{(i+1)} - w_3^{(i)}}{d_{33}}\end{aligned}$$

And so on

As opposed to Jacobi's method, Gauss-Seidel method computations must be performed sequentially. Every subsequent scalar equations uses results from the computation of the previous equations.

**Converging** Gauss-Seidel method is convergent if the matrix  $\mathbf{A}$  is strongly row or column diagonally dominant. If the matrix is symmetric, the method is also convergent if the matrix  $\mathbf{A}$  is positive definite. This method is also usually faster convergent compared to Jacobi's method.

### Stop tests

There are two ways to check when to terminate iterations of the methods we just discussed:

1. Check differences between two subsequent iteration points

$$\|\mathbf{x}^{(i+1)} - \mathbf{x}^{(i)}\| \leq \delta$$

Where  $\delta$  is an assumed tolerance, (in our case  $10^{-10}$ ). What we are really interested in though is whether the solution of the system of equation has required accuracy. If we want to check that we can additionally check (higher level, more computationally demanding test):

2. Check differences between two subsequent iteration points

$$\|\mathbf{Ax}^{(i+1)} - \mathbf{b}\| \leq \delta_2$$

Where  $\delta_2$  is an assumed tolerance. If this test is not passed then we can diminish the value of  $\delta_2$  and continue with the iterations. Value of  $\delta_2$  can not be too small since we are limited by the numerical errors.

### A and b

We have been given with the following system:

$$\begin{cases} 10x_1 - 4x_2 + x_3 + 2x_4 = -8 \\ 2x_1 - 6x_2 + 3x_3 - x_4 = -12 \\ x_1 + 4x_2 - 12x_3 + x_4 = 4 \\ 2x_1 + 3x_2 - 3x_3 - 10x_4 = 1 \end{cases}$$



Therefore our matrices will look like this:

$$\mathbf{A} = \begin{bmatrix} 10 & -4 & 1 & 2 \\ 2 & -6 & 3 & -1 \\ 1 & 4 & -12 & 1 \\ 2 & 3 & -3 & -10 \end{bmatrix} \quad \mathbf{b} = \begin{bmatrix} -8 \\ -12 \\ 4 \\ 11 \end{bmatrix}$$

So:

$$\mathbf{L} = \begin{bmatrix} 0 & 0 & 0 & 0 \\ 2 & 0 & 0 & 0 \\ 1 & 4 & 0 & 0 \\ 2 & 3 & -3 & 0 \end{bmatrix} \quad \mathbf{D} = \begin{bmatrix} 10 & 0 & 0 & 0 \\ 0 & -6 & 0 & 0 \\ 0 & 0 & -12 & 0 \\ 0 & 0 & 0 & -10 \end{bmatrix} \quad \mathbf{U} = \begin{bmatrix} 0 & -4 & 1 & 2 \\ 0 & 0 & 3 & -1 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 \end{bmatrix}$$

$$\mathbf{D}^{-1} = \begin{bmatrix} \frac{1}{10} & 0 & 0 & 0 \\ 0 & -\frac{1}{6} & 0 & 0 \\ 0 & 0 & -\frac{1}{12} & 0 \\ 0 & 0 & 0 & -\frac{1}{10} \end{bmatrix}$$

### 3.3 Solution

### 3.4 Discussion of the result

## Chapter 4

# Problem 4 - QR method of finding eigenvalues

4.1 Problem

4.2 Theoretical introduction

4.3 Solution

4.4 Discussion of the result

## Chapter 5

# Code appendix

### 5.1 Task 2 Code

#### 5.1.1 Main function

```
1 function x = indicatedMethod(Matrix, Vector) % Name of the method
   as in the textbook
2 % x stands for obtained result
3     [~,Columns] = size(Matrix); % We need to know how big the
   matrix is in next steps
4     % notice the '~', since we assume we use square matrix, we do
   not need
5     % to have another variable for number of rows since it is the
   same as
6     % number of columns
7     checkIfMatrixIsSquareMatrix(Matrix);
8     [Matrix, Vector] = gaussianEliminationWithPartialPivoting(
   Columns, Matrix, Vector);
9     % Change matrix to upper triangular matrix
10    [Matrix, Vector, x] = backSubstitutionPhase(Columns, Matrix,
   Vector);
11    % Get the solution
12    x = iterativeResidualCorrection(Matrix, x, Vector); % Improve
   on the solution
13 end % end function
```

#### 5.1.2 checkIfMatrixIsSquareMatrix

```
1 function checkIfMatrixIsSquareMatrix(Matrix)
2     [Rows,Columns] = size(Matrix);
```

```
3     if Rows ~= Columns
4         error ('Matrix is not square matrix!');
5     end % end if
6 end % end function
```

### 5.1.3 gaussianEliminationWithPartialPivoting

```
1 function [Matrix, Vector] = gaussianEliminationWithPartialPivoting(  
    Columns, Matrix, Vector)  
2     for j = 1 : Columns  
3         centralElement = max(Matrix(j:Columns,j));  
4         % we stay in the same row (j) but we change columns, as  
           in the  
5         % textbook  
6         [Matrix, Vector] = partialPivoting(Matrix, Vector, j,  
           centralElement, Columns);  
7         % ensures that a_kk != 0 and reduces errors  
8         [Matrix, Vector] = gaussianElimination(j, Columns,  
           Matrix, Vector);  
9         % change matrix into upper triangular matrix  
10    end % end for  
11 end % end function
```

### 5.1.4 partialPivoting

```
1 function [Matrix, Vector] = partialPivoting(Matrix, Vector, j,  
    centralElement, Columns)  
2     for k = j : Columns  
3         partialPivotingSwapOneRow(Matrix, Vector, j, k,  
           centralElement);  
4     end % end for  
5 end % end function
```

### 5.1.5 partialPivotingSwapOneRow

```
1 function [Matrix, Vector] = partialPivotingSwapOneRow(Matrix,  
    Vector, j, k, centralElement)  
2     if Matrix(k,j) == centralElement  
3         swapRowMatrix(Matrix, j, k); % swap jth row with kth row  
4         swapValueVector(Vector, j, k); % swap jth value with kth value  
5     end % end if  
6 end % end function
```

### 5.1.6 swapRowMatrix

```
1 function Matrix = swapRowMatrix(Matrix, j, k)  
2     temp = Matrix(j , :); % ' : ' denote all elements in jth row
```

```

3   Matrix(j , :) = Matrix(k, :);
4   Matrix(k, :) = temp; % temp equal to previous value of jth row
5 end

```

### 5.1.7 swapValueVector

```

1 function Vector = swapValueVector(Vector, j, k)
2     temp = Vector(j);
3     Vector(j) = Vector(k);
4     Vector(k) = temp; % temp equal to previous value of k element
                        % of vector
5 end % end function

```

### 5.1.8 gaussianElimination

```

1 function [Matrix, Vector] = gaussianElimination(j, Columns, Matrix,
    Vector)
2     for i = j + 1 : Columns
3         rowMultiplier = Matrix(i,j) / Matrix(j,j);
4         [Matrix, Vector] = subtractRows(Matrix, Vector, i,
            rowMultiplier, j, Columns);
5     end % end for
6 end % end function

```

### 5.1.9 subtractRows

```

1 function [Matrix, Vector] = subtractRows(Matrix, Vector, i,
    rowMultiplier, j, Columns)
2     Vector(i) = Vector(i) - rowMultiplier * Vector(j);
3     for curentColumn = 1 : Columns
4         Matrix(i,curentColumn) = Matrix(i,curentColumn) -
            rowMultiplier * Matrix(j, curentColumn);
5     end % end for
6 end % end function

```

### 5.1.10 backSubstitutionPhase

```
1 function [Matrix, Vector, x] = backSubstitutionPhase(Columns,  
    Matrix, Vector)  
2     for k = Columns : -1 : 1  
3         % Start at final column and move by -1 each iteration until we  
        reach 1  
4         equation = 0;  
5         for j = k+1 : Columns  
6             equation = equation + Matrix(k,j) * x(j, 1);  
7             % even though x is a vector we still need to put '1' to  
                ensure  
8             % that number of columns in the first matrix matches  
                number of  
9             % rows in second matrix  
10        end % end for  
11  
12        x(k, 1) = (Vector(k,1) - equation) / Matrix(k,k);  
13        % even though x is a vector we still need to put '1' to  
            ensure  
14        % that we do not exceed array bounds  
15    end % end for  
16 end % end function
```

### 5.1.11 iterativeResidualCorrection

```
1 function x = iterativeResidualCorrection(Matrix, x, Vector)  
2     residuum = Matrix*x - Vector; % as in the book  
3     newResiduum = residuum;  
4     x = improveSolution(x, newResiduum, residuum, Matrix, Vector);  
5 end % end function
```

### 5.1.12 improveSolution

```
1 function x = improveSolution(x, newResiduum, oldResiduum, Matrix,  
    Vector)  
2     while newResiduum <= oldResiduum  
3         oldResiduum = newResiduum;  
4         residuum = Matrix*x - Vector;  
5         x = x - residuum;  
6         newResiduum = residuum;  
7     end % end while  
8 end % end function
```

# Bibliography

- [1] Piotr Tatjewski (2014) *Numerical Methods*, Oficyna Wydawnicza Politechniki Warszawskiej