

ASE 375 Electromechanical Systems Section 14115

Monday: 3:00 - 6:00 pm

Report 4: Measuring Pressure Vessels

Andrew Doty, Andres Suniaga, Dennis Hom Due Date: 02/26/2024

Contents

1	Introduction	2
2	Equipment	2
3	Procedure	2
4	Data Processing	2
5	Results and Analysis	2
6	Conclusion	2

- 1 Introduction
- 2 Equipment
- 3 Procedure
- 4 Data Processing

For part 1, our first values will be in voltages. We will convert these to pressures using the following equation:

$$P = \frac{V}{0.004} - 14.7$$

What are any of the sources of error or discrepancies in the data? How can we account for these? - The gauge on the pressure vessel may not be accurate - The true measurements were likely taken with an inaccurate gauge, and our uncertainties are likely larger than we think - Over time, the pressure vessel leaked - The pressure vessel could be at a different temperature than the room temperature - The DAQ could be interpreting the data incorrectly from an error in the voltage. - Delay in pressure changes from the valve opening.

- 5 Results and Analysis
- 6 Conclusion



Appendix: t-Distribution Tables

Table A11. t-Distribution

Values of z for given values of the distribution function F(z) (cf. p. 754).

Example: For 9 degrees of freedom, z = 1.83 when F(z) = 0.95.

		Number of Degrees of Freedom								
F(z)	1	2	3	4	5	6	7	8	9	10
0.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
0.6	0.33	0.29	0.28	0.27	0.27	0.27	0.26	0.26	0.26	0.26
0.7	0.73	0.62	0.58	0.57	0.56	0.55	0.55	0.55	0.54	0.54
0.8	1.38	1.06	0.98	0.94	0.92	0.91	0.90	0.89	0.88	0.88
0.9	3.08	1.89	1.64	1.53	1.48	1.44	1.42	1.40	1.38	1.37
0.95	6.31	2.92	2.35	2.13	2.02	1.94	1.90	1.86	1.83	1.81
0.975	12.7	4.30	3.18	2.78	2.57	2.45	2.37	2.31	2.26	2.23
0.99	31.8	6.97	4.54	3.75	3.37	3.14	3.00	2.90	2.82	2.76
0.995	63.7	9.93	5.84	4.60	4.03	3.71	3.50	3.36	3.25	3.17
0.999	318.3	22.3	10.2	7.17	5.89	5.21	4.79	4.50	4.30	4.14

			N	umber of	Degrees	of Free	dom			
F(z)	11	12	13	14	15	16	17	18	19	20
0.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
0.6	0.26	0.26	0.26	0.26	0.26	0.26	0.26	0.26	0.26	0.26
0.7	0.54	0.54	0.54	0.54	0.54	0.54	0.53	0.53	0.53	0.53
0.8	0.88	0.87	0.87	0.87	0.87	0.87	0.86	0.86	0.86	0.86
0.9	1.36	1.36	1.35	1.35	1.34	1.34	1.33	1.33	1.33	1.33
0.95	1.80	1.78	1.77	1.76	1.75	1.75	1.74	1.73	1.73	1.73
0.975	2.20	2.18	2.16	2.15	2.13	2.12	2.11	2.10	2.09	2.09
0.99	2.72	2.68	2.65	2.62	2.60	2.58	2.57	2.55	2.54	2.53
0.995	3.11	3.06	3.01	2.98	2.95	2.92	2.90	2.88	2.86	2.85
0.999	4.03	3.93	3.85	3.79	3.73	3.69	3.65	3.61	3.58	3.55

	Number of Degrees of Freedom									
F(z)	22	24	26	28	30	40	50	100	200	ø,
0.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
0.6	0.26	0.26	0.26	0.26	0.26	0.26	0.26	0.25	0.25	0.25
0.7	0.53	0.53	0.53	0.53	0.53	0.53	0.53	0.53	0.53	0.52
0.8	0.86	0.86	0.86	0.86	0.85	0.85	0.85	0.85	0.84	0.84
0.9	1.32	1.32	1.32	1.31	1.31	1.30	1.30	1.29	1.29	1.28
0.95	1.72	1.71	1.71	1.70	1.70	1.68	1.68	1.66	1.65	1.65
0.975	2.07	2.06	2.06	2.05	2.04	2.02	2.01	1.98	1.97	1.96
0.99	2.51	2.49	2.48	2.47	2.46	2.42	2.40	2.37	2.35	2.33
0.995	2.82	2.80	2.78	2.76	2.75	2.70	2.68	2.63	2.60	2.58
0.999	3.51	3.47	3.44	3.41	3.39	3.31	3.26	3.17	3.13	3.09