File Edit View Run Kernel Settings Help

B + % □ □ ► ■ C → Code ✓

JupyterLab □ ★ Python 3 (ipykernel) ○

```
MARTINS POLO ATUBI S8112402 MOBILE APP DEVELOPMENT LAB 1
 []:
[43]: class Employee:
          def __init__(self,name,salary):
              self.name= name
              self.salary= salary
          def raiseSalary(self, bypercent):
               self.salary += self.salary* (bypercent /100)
      harry_hacker=Employee("harry_hacker",55000)
      harry_hacker.raiseSalary(10)
      print("{} salary is {} ".format(harry_hacker.name, harry_hacker.salary))
      harry_hacker salary is 60500.0
[67]: class Student:
                                                                                                                         ★ 回 ↑ ↓ 占 무
          def __init__(self,name):
              self.name=name
              self.total_quiz_score=0
              self.total_no_of_quiz=0
          def getName(self):
              return self.name
          def addQuiz(self,score):
              self.total_quiz_score += score
              self.total_no_of_quiz +=1
          def getTotalQuizScore(self):
              return self.total_quiz_score
          def getAverageScore(self):
              if self.total_no_of_quiz == 0:
                  return 0
              return self.total_quiz_score / self.total_no_of_quiz
```