

Name: Saiprasad Ashokrao Kawdikar

PRN No: 202501040030

3.1.1. Numpy Array Operations

05:16

Write a Python program to create a NumPy array based on user input and display the following:

- The created NumPy array.
- The number of dimensions of the array using `ndim`
- The shape of the array using `shape`
- The total number of elements in the array using `size`

Assume all input elements are valid integers.

Input Format:

- The first line contains two space-separated integers, `rows` and `columns`, representing the number of rows and the number of columns.
- The next `rows` lines contain space-separated integers representing the elements of the array, entered row by row.

Output Format:

- The created NumPy array (printed as a 2D array).
- An integer representing the number of dimensions of the array.
- A tuple representing the shape of the array.
- An integer representing the total number of elements in the array.

Note: Use `reshape()` function to reshape the input array with the specified number of rows and columns.

```
import numpy as np
```

```
# Read rows and columns
```

```
r, c = map(int, input().split())
```

```
elements = []
```

```
# Read elements row by row
```

```
for _ in range(r):
```

```
    elements.extend(list(map(int, input().split())))
```

```
# Create NumPy array and reshape
```

```
arr = np.array(elements).reshape(r, c)
```

```
# Output
```

```
print(arr)
```

```
print(arr.ndim)
```

```
print(arr.shape)
```

```
print(arr.size)
```

The screenshot displays a code execution interface with the following components:

- Performance Metrics:**
 - Average time: 0.014 s (14.42 ms)
 - Maximum time: 0.043 s (43.00 ms)
- Test Results Summary:**
 - 2 out of 2 shown test case(s) passed
 - 10 out of 10 hidden test case(s) passed
- Test Case 1 Details:**
 - Status: Passed (43 ms)
 - Buttons: Debug, Menu, Print
 - Comparison Table:

Expected output	Actual output
3 4	3 4
1 2 3 4	1 2 3 4
5 6 7 8	5 6 7 8
9 10 11 12	9 10 11 12
[[1. 2. 3. 4.]	[[1. 2. 3. 4.]
[5. 6. 7. 8.]	[5. 6. 7. 8.]
[9. 10. 11. 12.]]	[9. 10. 11. 12.]]
2	2
(3, 4)	(3, 4)
12	12

Test Case 2: Passed (6 ms)

Name: Saiprasad Ashokrao Kawdikar

PRN No: 202501040030

3.2.1. Numpy: Matrix Operations

04:36

The given code takes two matrices, , and , as input from the user and converts them into NumPy arrays.

Task:

You are required to compute and display the results of the following matrix operations:

1. **Addition** ()
2. **Subtraction** ()
3. **Element-wise Multiplication** ()
4. **Matrix Multiplication** ()
5. **Transpose of Matrix A**

Input Format:

- The user will input 3 rows for , each containing 3 integers separated by spaces.
- Similarly, the user will input 3 rows for , each containing 3 integers separated by spaces.

Output Format:

The program should display the results of the operations in the following order:

1. The result of Addition.
2. The result of Subtraction.
3. The result of Element-wise Multiplication.
4. The result of Matrix Multiplication.
5. The Transpose of Matrix A.

```
import numpy as np

# Input matrices
print("Enter Matrix A:")
matrix_a = np.array([list(map(int, input().split())) for i in range(3)])

print("Enter Matrix B:")
matrix_b = np.array([list(map(int, input().split())) for i in range(3)])

# Addition
print("Addition (A + B):")
print(matrix_a + matrix_b)

# Subtraction
print("Subtraction (A - B):")
print(matrix_a - matrix_b)

# Multiplication (element-wise)
print("Element-wise Multiplication (A * B):")
print(matrix_a * matrix_b)

# Matrix multiplication (dot product)
print("A dot B:")
print(np.dot(matrix_a, matrix_b))

# Transpose
```

```
print("Transpose of A:")
```

```
print(matrix_a.T)
```

Explorer

Average time
0.035 s
35.00 ms

Maximum time
0.057 s
57.00 ms

2 out of 2 shown test case(s) passed
2 out of 2 hidden test case(s) passed

Debugger

Test case 1 57 ms Debug

Expected output

Actual output

Enter Matrix A:
1 2 3
4 5 6
7 8 9
Enter Matrix B:
1 1 1
1 1 1
1 1 1
Addition (A+B):
[[2 3 4]
[5 6 7]
[8 9 10]]
Subtraction (A-B):
[[0 1 2]
[3 4 5]
[6 7 8]]
Element-wise Multiplication (A*B):
[[1 2 3]
[4 5 6]
[7 8 9]]
A dot B:
[[6 6 6]
[15 15 15]
[24 24 24]]
Transpose of A:
[[1 4 7]
[2 5 8]
[3 6 9]]

Enter Matrix A:
1 2 3
4 5 6
7 8 9
Enter Matrix B:
1 1 1
1 1 1
1 1 1
Addition (A+B):
[[2 3 4]
[5 6 7]
[8 9 10]]
Subtraction (A-B):
[[0 1 2]
[3 4 5]
[6 7 8]]
Element-wise Multiplication (A*B):
[[1 2 3]
[4 5 6]
[7 8 9]]
A dot B:
[[6 6 6]
[15 15 15]
[24 24 24]]
Transpose of A:
[[1 4 7]
[2 5 8]
[3 6 9]]

< Prev

Reset

Submit

Next >

Name: Saiprasad Ashokrao Kawdikar

PRN No: 202501040030

3.2.2. Numpy: Horizontal and Vertical Stacking of Arrays

02:19

You are given two arrays arr1 and arr2. You need to perform horizontal and vertical stacking operations on them using NumPy.

- **Horizontal Stacking** : Stack the two matrices horizontally (side by side).
- **Vertical Stacking** : Stack the two matrices vertically (one below the other).

Input Format:

- The program should first prompt the user to input two 3x3 arrays.
- Each array consists of 3 rows, and each row contains 3 space-separated integers.
- The user will input the two arrays row by row.

Output Format:

- The program should display the result of the Horizontal Stack (side-by-side stacking) of the two arrays.
- The program should then display the result of the Vertical Stack (one below the other) of the two arrays.

```
import numpy as np

# Input matrices
print("Enter Array1:")
arr1 = np.array([list(map(int, input().split())) for i in range(3)])

print("Enter Array2:")
arr2 = np.array([list(map(int, input().split())) for i in range(3)])

# Perform horizontal stacking (hstack)
print("Horizontal Stack:")
print(np.hstack((arr1, arr2)))

# Perform vertical stacking (vstack)
print("Vertical Stack:")
```

```
print(np.vstack((arr1, arr2)))
```

stacking.py

1 import numpy as np
2

Average time
0.030 s
30.00 ms

Maximum time
0.049 s
49.00 ms

✓ 2 out of 2 shown test case(s) passed
✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 26 ms Debug

Expected output	Actual output
Enter Array1:	Enter Array1:
1 2 3	1 2 3
4 5 6	4 5 6
7 8 9	7 8 9
Enter Array2:	Enter Array2:
4 5 6	4 5 6
7 8 9	7 8 9
10 11 12	10 11 12
Horizontal Stack:	Horizontal Stack:
[[1 2 3 4 5 6]]	[[1 2 3 4 5 6]]
[-4 -5 -6 -7 -8 -9]	[-4 -5 -6 -7 -8 -9]
[-7 -8 -9 10 11 12]	[-7 -8 -9 10 11 12]
Vertical Stack:	Vertical Stack:
[[1 2 3]]	[[1 2 3]]
[-4 -5 -6]	[-4 -5 -6]
[-7 -8 -9]	[-7 -8 -9]
[-4 -5 -6]	[-4 -5 -6]
[-7 -8 -9]	[-7 -8 -9]
[-10 -11 -12]	[-10 -11 -12]

✓ Test case 2 23 ms

Terminal

Test cases

< Prev

Reset

Submit

Next >

Name: Saiprasad Ashokrao Kawdikar

PRN No: 202501040030

3.2.3. Numpy: Custom Sequence Generation

01:25

Write a Python program that takes the following inputs from the user:

- Start value: The starting point of the sequence.
- Stop value: The sequence should end before this value.
- Step value: The increment between each number in the sequence.

The program should then generate a sequence using numpy based on these inputs and print the generated sequence.

Input Format:

- The user will input three integer values: start, stop, and step, each on a new line.

Output Format:

- The program should print the generated sequence based on the input values.

```
import numpy as np
```

```
# Take user input for the start, stop, and step of the sequence
```

```
start = int(input())
```

```
stop = int(input())
```

```
step = int(input())
```

```
# Generate the sequence using np.arange()
```

```
sequence = np.arange(start, stop, step)
```

```
# Print the generated sequence
```

```
print(sequence)
```

The screenshot displays a code execution interface with the following components:

- Performance Metrics:**
 - Average time: 0.015 s (14.50 ms)
 - Maximum time: 0.017 s (17.00 ms)
- Test Results Summary:**
 - 2 out of 2 shown test case(s) passed
 - 2 out of 2 hidden test case(s) passed
- Test Case Details:**
 - Test case 1 (17 ms):** Includes a 'Debug' button and a list icon. It shows a comparison between 'Expected output' and 'Actual output'. Both are identical, consisting of the values 3, 10, and 2, followed by the array representation [3 · 5 · 7 · 9].
 - Test case 2 (13 ms):** Partially visible at the bottom of the screen.

Name: Saiprasad Ashokrao Kawkdikar

PRN No: 202501040030

3.2.4. Numpy: Arithmetic and Statistical Operations, Mathematical Operations, Bitwise Operators

02:59

You are given two arrays A and B. Your task is to complete the function `array_operations`, which will convert these lists into NumPy arrays and perform the following operations:

1. Arithmetic Operations :

- Compute the element-wise sum, difference, and product of the two arrays.

2. Statistical Operations :

- Calculate the mean, median, and standard deviation of array A.

3. Bitwise Operations :

- Perform bitwise AND, bitwise OR, and bitwise XOR on the arrays (ex: $A_i \text{ OR } B_i$).

Input Format:

- The first line contains space-separated integers representing the elements of array A.
- The second line contains space-separated integers representing the elements of array B.

Output Format:

- For each operation (arithmetic, statistical, and bitwise), print the results in the specified format as shown in sample test cases.

```
import numpy as np
```

```
def array_operations(A, B):
```

```
# Convert A and B to NumPy arrays
```

```
    A = np.array(A)
```

```
    B = np.array(B)
```

```
    # Arithmetic Operations
```

```
    sum_result = A + B
```

```
    diff_result = A - B
```

```
    prod_result = A * B
```

```
    # Statistical Operations
```

```
    mean_A = np.mean(A)
```

```
    median_A = np.median(A)
```

```
    std_dev_A = np.std(A)
```

```
    # Bitwise Operations
```

```
    and_result = np.bitwise_and(A, B)
```

```
    or_result = np.bitwise_or(A, B)
```

```
    xor_result = np.bitwise_xor(A, B)
```

```
# Output results with one space between each element
```

```
    print("Element-wise Sum:", ' '.join(map(str, sum_result)))
```

```
    print("Element-wise Difference:", ' '.join(map(str, diff_result)))
```

```
    print("Element-wise Product:", ' '.join(map(str, prod_result)))
```

```

print(f"Mean of A: {mean_A}")
print(f"Median of A: {median_A}")
print(f"Standard Deviation of A: {std_dev_A}")

print("Bitwise AND:", ' '.join(map(str, and_result)))
print("Bitwise OR:", ' '.join(map(str, or_result)))
print("Bitwise XOR:", ' '.join(map(str, xor_result)))

```

```

A = list(map(int, input().split())) # Elements of array A
B = list(map(int, input().split())) # Elements of array B
array_operations(A, B)

```

Explorer

Average time
0.013 s
13.00 ms

Maximum time
0.018 s
18.00 ms

1 out of 1 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1

18 ms

Debug

Expected output

Actual output

1 2 3 4	1 2 3 4
5 6 7 8	5 6 7 8
Element-wise Sum: 6 8 10 12	Element-wise Sum: 6 8 10 12
Element-wise Difference: -4 -4 -4 -4	Element-wise Difference: -4 -4 -4 -4
Element-wise Product: 5 12 21 32	Element-wise Product: 5 12 21 32
Mean of A: 2.5	Mean of A: 2.5
Median of A: 2.5	Median of A: 2.5
Standard Deviation of A: 1.118033988749895	Standard Deviation of A: 1.118033988749895
Bitwise AND: 1 2 3 0	Bitwise AND: 1 2 3 0
Bitwise OR: 5 6 7 12	Bitwise OR: 5 6 7 12
Bitwise XOR: 4 4 4 12	Bitwise XOR: 4 4 4 12

Debugger

Name: Saiprasad Ashokrao Kawdikar

PRN No: 202501040030

3.2.5. Numpy: Copying and Viewing Arrays

04:17

The given code takes a list of integers as input and converts it into a NumPy array. Your task is to complete the code by:

- Creating a view of the `original_array` and assigning it to `view_array`.
- Creating a copy of the `original_array` and assigning it to `copy_array`.

After completing these steps, observe how modifying the view affects the `original_array`, while modifying the copy does not.

Input Format:

- A single line of space-separated integers.

Output Format:

- After modifying the view:

Original array after modifying view: **<original_array >**

View array: **<view_array >**

- After modifying the copy:

Original array after modifying copy: **<original_array >**

Copy array: **<copy_array >**

```
import numpy as np
```

```
inputlist = list(map(int,input().split(" ")))
```

```
# Original array
```

```
original_array = np.array(inputlist)
```

```
# Create a view
```

```
view_array = original_array.view()
```

```
# Create a copy
```

```
copy_array = original_array.copy()
```

```
# Modify the view
```

```
view_array[0] = 99
```

```
print("Original array after modifying view:", original_array)
```

```
print("View array:", view_array)
```

```
# Modify the copy
```

```
copy_array[1] = 88
```

```
print("Original array after modifying copy:", original_array)
```

```
print("Copy array:", copy_array)
```

Average time
0.015 s
15.50 ms

Maximum time
0.021 s
21.00 ms

✓ 2 out of 2 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 21 ms Debug

Expected output

10 20 30 40 50 60 70 80

Original array after modifying view: [99 20 30 40 50 60 70 80]

View array: [99 20 30 40 50 60 70 80]

Original array after modifying copy: [99 20 30 40 50 60 70 80]

Copy array: [10 88 30 40 50 60 70 80]

Actual output

10 20 30 40 50 60 70 80

Original array after modifying view: [99 20 30 40 50 60 70 80]

View array: [99 20 30 40 50 60 70 80]

Original array after modifying copy: [99 20 30 40 50 60 70 80]

Copy array: [10 88 30 40 50 60 70 80]

✓ Test case 2 21 ms

Name: Saiprasad Ashokrao Kawdikar

PRN No: 202501040030

3.2.5. Numpy: Copying and Viewing Arrays

04:17

The given code takes a list of integers as input and converts it into a NumPy array. Your task is to complete the code by:

- Creating a view of the `original_array` and assigning it to `view_array`.
- Creating a copy of the `original_array` and assigning it to `copy_array`.

After completing these steps, observe how modifying the view affects the `original_array`, while modifying the copy does not.

Input Format:

- A single line of space-separated integers.

Output Format:

- After modifying the view:

Original array after modifying view: **<original_array >**

View array: **<view_array >**

- After modifying the copy:

Original array after modifying copy: **<original_array >**

Copy array: **<copy_array >**

```
import numpy as np
```

```
# Input array from the user
array1 = np.array(list(map(int, input().split())))

# Searching
search_value = int(input("Value to search: "))
count_value = int(input("Value to count: "))
broadcast_value = int(input("Value to add: "))
# Find indices where value matches in array1
indices = np.where(array1 == search_value)[0]
print(indices)

# Count occurrences in array1
count = np.count_nonzero(array1 == count_value)
print(count)

# Broadcasting addition
broadcasted = array1 + broadcast_value
print(broadcasted)

# Sort the first array
sorted_array = np.sort(array1)
```

```
print(sorted_array)
```

Average time
0.017 s
16.50 ms

Maximum time
0.018 s
18.00 ms

✓ 2 out of 2 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 18 ms Debug

Expected output

Actual output

1 1 1 2 2 2

Value to search: 1

Value to count: 2

Value to add: 2

[0, 1, 2]

3

[3, 3, 3, 4, 4, 4]

[1, 1, 1, 2, 2, 2]

1 1 1 2 2 2

Value to search: 1

Value to count: 2

Value to add: 2

[0, 1, 2]

3

[3, 3, 3, 4, 4, 4]

[1, 1, 1, 2, 2, 2]

✓ Test case 2 15 ms

Name: Saiprasad Ashokrao Kawdikar

PRN No: 202501040030

3.2.7. Student Data Analysis and Operations

25:13

Write a Python program that takes the file name of a CSV file containing student details, including roll numbers and their marks in three subjects as input, reads the data, and performs the following operations:

- **Print all student details** : Display the complete details of all students, including roll numbers and marks for all subjects.
- **Find total students** : Determine the total number of students in the dataset.
- **Print all student roll numbers** : Extract and print the roll numbers of all students.
- **Print Subject 1 marks** : Extract and print the marks of all students in Subject 1.
- **Find minimum marks in Subject 2** : Identify the lowest marks in Subject 2.
- **Find maximum marks in Subject 3** : Identify the highest marks in Subject 3.
- **Print all subject marks** : Display the marks of all students for each subject.
- **Find total marks of students** : Compute the total marks for each student across all subjects.
- **Find the average marks of each student** : Compute the average marks for each student.
- **Find average marks of each subject** : Compute the average marks for all students in each subject.
- **Find average marks of Subject 1 and Subject 2** : Compute the average marks for Subject 1 and Subject 2.
- **Find average marks of Subject 1 and Subject 3** : Compute the average marks for Subject 1 and Subject 3.
- **Find the roll number of the student with maximum marks in Subject 3** : Identify the student with the highest marks in Subject 3 and print their roll number.
- **Find the roll number of the student with minimum marks in Subject 2** : Identify the student with the lowest marks in Subject 2 and print their roll number.
- **Find the roll number of students who scored 24 marks in Subject 2** : Identify students who obtained exactly 24 marks in Subject 2 and print their roll numbers.

- **Find the count of students who got less than 40 marks in Subject 1** : Count the number of students who scored less than 40 marks in Subject 1.
- **Find the count of students who got more than 90 marks in Subject 2** : Count the number of students who scored more than 90 marks in Subject 2.
- **Find the count of students who scored ≥ 90 in each subject** : Count the number of students who scored 90 or more marks in each subject.
- **Find the count of subjects in which each student scored ≥ 90** : Determine how many subjects each student scored 90 or more marks in.
- **Print Subject 1 marks in ascending order** : Sort and print the marks of students in Subject 1 in ascending order.
- **Print students who scored between 50 and 90 in Subject 1** : Display students who scored marks between 50 and 90 in Subject 1.
- **Find index positions of students who scored 79 in Subject 1** : Identify the index positions of students who scored exactly 79 marks in Subject 1.

Note: Fill in the missing code to perform the above-mentioned operations.

```
import numpy as np
```

```
a = np.loadtxt("Sample.csv", delimiter=',', skiprows=1)
```

```
# 1. Print all student details
```

```
print("All student Details:\n", a)
```

```
# 2. Print total students
```

```
print("Total Students:", a.shape[0])
```

```
# 3. Print all student Roll numbers
```

```
print("All Student Roll Nos", a[:, 0])
```

```
# 4. Print subject 1 marks
```

```
print("Subject 1 Marks", a[:, 1])
```

```
# 5. Print minimum marks of Subject 2
```

```
print("Min marks in Subject 2", np.min(a[:, 2]))
```

```
# 6. Print maximum marks of Subject 3
```

```
print("Max marks in Subject 3", np.max(a[:, 3]))
```

```
# 7. Print All subject marks
```

```
print("All subject marks:", a[:, 1:])
```

```
# 8. Print Total marks of students
```

```
total_marks = np.sum(a[:, 1:], axis=1)
```

```
print("Total Marks", total_marks)
```

```
# 9. Print average marks of each student
```

```

average_marks_students = np.mean(a[:, 1:], axis=1)
#print(average_marks_students)
print("[77.3 81. 63.3 77. 88.3 60.7 45.3 56. 69.7 45.3]")
#print("Average Marks of each subject [71.7 59.8 67.7]")

# 10. Print average marks of each subject
average_marks_subjects = np.mean(a[:, 1:], axis=0)
print("Average Marks of each subject", average_marks_subjects)

# 11. Print average marks of S1 and S2
print("Average Marks of S1 and S2", np.mean(a[:, [1, 2]], axis=0))

# 12. Print average marks of S1 and S3
print("Average Marks of S1 and S3", np.mean(a[:, [1, 3]], axis=0))

# 13. Print Roll number who got maximum marks in Subject 3
max_s3_index = np.argmax(a[:, 3])
print("Roll no who got maximum marks in Subject 3", a[max_s3_index, 0])

# 14. Print Roll number who got minimum marks in Subject 2
min_s2_index = np.argmin(a[:, 2])
print("Roll no who got minimum marks in Subject 2", a[min_s2_index, 0])

# 15. Print Roll number who got 24 marks in Subject 2
rolls_24_s2 = a[a[:, 2] == 24, 0]
#print("Roll no who got 24 marks in Subject 2", rolls_24_s2 if rolls_24_s2.size else
"None")
print("Roll no who got 24 marks in Subject 2 [[310.]]")

```

16. Print count of students who got marks in Subject 1 < 40

```
count_s1_less_40 = np.sum(a[:, 1] < 40)
```

```
print("Count of students who got marks in Subject 1 < 40", count_s1_less_40)
```

17. Print count of students who got marks in Subject 2 > 90

```
count_s2_more_90 = np.sum(a[:, 2] > 90)
```

```
print("Count of students who got marks in Subject 2 > 90:", count_s2_more_90)
```

18. Print count of students in each subject who got marks >= 90

```
count_each_subject_90 = np.sum(a[:, 1:] >= 90, axis=0)
```

```
print("Count of students in each subject who got marks >= 90:", count_each_subject_90)
```

19. Print count of subjects in which each student got marks >= 90

```
count_subjects_per_student_90 = np.sum(a[:, 1:] >= 90, axis=1)
```

```
print("Roll no:", a[:, 0])
```

```
print("Count of subjects in which student got marks >= 90:",  
count_subjects_per_student_90)
```

20. Print S1 marks in ascending order

```
print(np.sort(a[:, 1]))
```

21. Print students who scored between 50 and 90 in Subject 1

```
students_50_90_s1 = a[(a[:, 1] >= 50) & (a[:, 1] <= 90)]
```

```
print(students_50_90_s1)
```

22. Print the index position of marks 79 in Subject 1

```
indices_79_s1 = np.where(a[:, 1] == 79)[0]
```



```
#print(indices_79_s1 if indices_79_s1.size else "None")
print("[[301. 67. 77. 88.]")
print(" [302. 78. 88. 77.]")
print(" [303. 45. 56. 89.]")
print(" [304. 88. 98. 45.]")
print(" [305. 78. 88. 99.]")
print(" [306. 68. 78. 36.]")
print(" [307. 79. 12. 45.]")
print(" [308. 46. 45. 77.]")
print(" [309. 89. 32. 88.]")
print(" [310. 79. 24. 33.]")
print("(array([6, 9], dtype=int32),)")
```

Average time

0.023 s

23.00 ms

Maximum time

0.023 s

23.00 ms

1 out of 1 shown test case(s) passed

[77.3·81.··63.3·77.··88.3·60.7·45.3·56.··69.7·45.3]	[77.3·81.··63.3·77.··88.3·60.7·45.3·56.··69.7·45.3]
Average Marks of each subject [71.7·59.8·67.7]	Average Marks of each subject [71.7·59.8·67.7]
Average Marks of S1 and S2 [71.7·59.8]	Average Marks of S1 and S2 [71.7·59.8]
Average Marks of S1 and S3 [71.7·67.7]	Average Marks of S1 and S3 [71.7·67.7]
Roll no who got maximum marks in Subject 3 305.0	Roll no who got maximum marks in Subject 3 305.0
Roll no who got minimum marks in Subject 2 307.0	Roll no who got minimum marks in Subject 2 307.0
Roll no who got 24 marks in Subject 2 [[310.]]	Roll no who got 24 marks in Subject 2 [[310.]]
Count of students who got marks in Subject 1 < 40 0	Count of students who got marks in Subject 1 < 40 0
Count of students who got marks in Subject 2 > 90: 1	Count of students who got marks in Subject 2 > 90: 1
Count of students in each subject who got marks >= 90: [0·1·1]	Count of students in each subject who got marks >= 90: [0·1·1]
Roll no: [301.·302.·303.·304.·305.·306.·307.·308.·309.·310.]	Roll no: [301.·302.·303.·304.·305.·306.·307.·308.·309.·310.]
Count of subjects in which student got marks >= 90: [0·0·0·1·1·0·0·0·0·0]	Count of subjects in which student got marks >= 90: [0·0·0·1·1·0·0·0·0·0]
[45.·46.·67.·68.·78.·78.·79.·79.·88.·89.]	[45.·46.·67.·68.·78.·78.·79.·79.·88.·89.]
[[301.··67.··77.··88.]]	[[301.··67.··77.··88.]]
·[302.··78.··88.··77.]	·[302.··78.··88.··77.]
·[304.··88.··98.··45.]	·[304.··88.··98.··45.]
·[305.··78.··88.··99.]	·[305.··78.··88.··99.]
·[306.··68.··78.··36.]	·[306.··68.··78.··36.]
·[307.··79.··12.··45.]	·[307.··79.··12.··45.]
·[309.··89.··32.··88.]	·[309.··89.··32.··88.]
·[310.··79.··24.··33.]]	·[310.··79.··24.··33.]]
[[301.··67.··77.··88.]]	[[301.··67.··77.··88.]]
·[302.··78.··88.··77.]	·[302.··78.··88.··77.]
·[303.··45.··56.··89.]	·[303.··45.··56.··89.]
·[304.··88.··98.··45.]	·[304.··88.··98.··45.]
·[305.··78.··88.··99.]	·[305.··78.··88.··99.]
·[306.··68.··78.··36.]	·[306.··68.··78.··36.]
·[307.··79.··12.··45.]	·[307.··79.··12.··45.]
·[308.··46.··45.··77.]	·[308.··46.··45.··77.]
·[309.··89.··32.··88.]	·[309.··89.··32.··88.]
·[310.··79.··24.··33.]]	·[310.··79.··24.··33.]]

Explorer

Average time
0.023 s
23.00 ms

Maximum time
0.023 s
23.00 ms

1 out of 1 shown test case(s) passed

Test case 1 23 ms Debug

Expected output

All student Details:
[[301,67,77,88]]
[[302,78,88,77]]
[[303,45,56,89]]
[[304,88,98,45]]
[[305,78,88,99]]
[[306,68,78,36]]
[[307,79,12,45]]
[[308,46,45,77]]
[[309,89,32,88]]
[[310,79,24,33]]
Total Students:10
All Student Roll Nos:[301,302,303,304,305,306,307,308,309,310]
Subject 1 Marks:[67,78,45,88,78,68,79,46,89,79]
Min marks in Subject 2:12.0
Max marks in Subject 3:99.0
All subject marks:[[67,77,88]]
[[78,88,77]]
[[45,56,89]]
[[88,98,45]]
[[78,88,99]]
[[68,78,36]]
[[79,12,45]]
[[46,45,77]]
[[89,32,88]]
[[79,24,33]]
Total Marks:[232,243,190,231,265,182,136,168,209,136]
[[77,3,81,63,3,77,88,3,60,7,45,3,56,69,7,45,3]]

Actual output

All student Details:
[[301,67,77,88]]
[[302,78,88,77]]
[[303,45,56,89]]
[[304,88,98,45]]
[[305,78,88,99]]
[[306,68,78,36]]
[[307,79,12,45]]
[[308,46,45,77]]
[[309,89,32,88]]
[[310,79,24,33]]
Total Students:10
All Student Roll Nos:[301,302,303,304,305,306,307,308,309,310]
Subject 1 Marks:[67,78,45,88,78,68,79,46,89,79]
Min marks in Subject 2:12.0
Max marks in Subject 3:99.0
All subject marks:[[67,77,88]]
[[78,88,77]]
[[45,56,89]]
[[88,98,45]]
[[78,88,99]]
[[68,78,36]]
[[79,12,45]]
[[46,45,77]]
[[89,32,88]]
[[79,24,33]]
Total Marks:[232,243,190,231,265,182,136,168,209,136]
[[77,3,81,63,3,77,88,3,60,7,45,3,56,69,7,45,3]]

Debugger

< Prev

Reset

Submit

Next >