



Entity Component Systems for Compilers

Reimagining the Abstract Syntax Tree

or

“How not to build a compiler”

J Pratt
[they/them](#)

Arcs (Sydney)
Raksha

[jopra@](#)
[Cypher1](#)

What on earth is an ECS?

Entity Component System

Used in Game development

Alternative to Object Oriented Programming

What do I mean by ECS?

Entity

A unique object (e.g. a character)

What do I mean by ECS?

Entity **Component**

A group of properties / values
(e.g. A character's items, skills, etc.)

What do I mean by ECS?

Entity Component **System**

A structured way to handle the components

e.g.

A renderer,

A physics simulator,

A damage system

What do I mean by ECS?

Let's compare to OOP


What do I mean by ECS?

Extra terminology:

Archetype = A group of components

System = A thing that processes entities


Chunk = Group of co-located instances of the same component/archetype



OOP → A GameObject is a container.



ECS → An entity is a key.



What is an ECS like?

1. Systems operate over components
2. Components are co-located in memory
3. Look up time for each component is small (normally $O(1)$)
4. Systems perform the same (or similar) actions on each component

Why is ECS used in Game development?

1. Separates concerns
2. Systems can operate independently
 - a. Systems can operate in parallel*
 - b. Systems can run at different times
3. Cache & Memory locality
4. Avoiding branches

Sources:

<https://rams3s.github.io/blog/2019-01-09-ecs-deep-dive/> <- This one is probably the best imo
<https://www.richardlord.net/blog/ecs/why-use-an-entity-framework.html>
<https://www.gamedevs.org/uploads/data-driven-game-object-system.pdf>
<https://web.archive.org/web/20171030021158/http://entity-systems-wiki.t-machine.org/>
<http://gameprogrammingpatterns.com/component.html>

*separable systems: i.e. those using non-overlapping sets of components and global data


How is program data stored in compilers?

Abstract Syntax Tree!

AST for short

What do I mean by AST?


Abstract Syntax Tree



What do I mean by AST?

Abstract vs Concrete


We're happy to throw away some
information



What do I mean by AST?

Abstract **Syntax** vs Semantics


This doesn't (normally) model the
runtime behaviour



What do I mean by AST?

Abstract Syntax **Tree** vsGraph?


They (typically) only branch out...





How is program data stored in compilers?

e.g.



$A * (B - C) + D + E$



How is program data stored in compilers?




How is program data stored in compilers?



Nodes	
0:	Symbol "A"
1:	Operator "*", Children(0, 2)
2:	Symbol "B"
3:	Operator "-", Children(2, 4)
4:	Symbol "C",
5:	Operator "+", Children(2, 4)
6:	Symbol "D"
7:	Operator "+"
8:	Symbol "E"


What would this look like in an ECS?



What would this look like in an ECS?

IsSymbol


A	
B	
C	
D	
E	



What would this look like in an ECS?

IsSymbol


0: A
1: B
2: C
3: D
4: E



What would this look like in an ECS?

IsSymbol

0: A
1: B
2: C
3: D
4: E




Entities

0: IsSymbol 0
2: IsSymbol 1
4: IsSymbol 2
6: IsSymbol 3
8: IsSymbol 4

What would this look like in an ECS?

IsSymbol

0: E0, A
1: E2, B
2: E4, C
3: E6, D
4: E8, E




Entities

0: IsSymbol 0
2: IsSymbol 1
4: IsSymbol 2
6: IsSymbol 3
8: IsSymbol 4

What would this look like in an ECS?

IsSymbol

0: E0, A
1: E2, B
2: E4, C
3: E6, D
4: E8, E



Entities

0: IsSymbol 0
1: IsOperator 0
2: IsSymbol 1
3: IsOperator 1
4: IsSymbol 2
5: IsOperator 2, IsRoot
6: IsSymbol 3
7: IsOperator 3
8: IsSymbol 4

What would this look like in an ECS?

IsOperator


*
-
+
+

IsSymbol

0: E0, A
1: E2, B
2: E4, C
3: E6, D
4: E8, E

Entities

0: IsSymbol 0
1: IsOperator 0
2: IsSymbol 1
3: IsOperator 1
4: IsSymbol 2
5: IsOperator 2, IsRoot
6: IsSymbol 3
7: IsOperator 3
8: IsSymbol 4




What would this look like in an ECS?

IsOperator

0: *
1: -
2: +
3: +

IsSymbol

0: E0, A
1: E2, B
2: E4, C
3: E6, D
4: E8, E



Entities

0: IsSymbol 0
1: IsOperator 0
2: IsSymbol 1
3: IsOperator 1
4: IsSymbol 2
5: IsOperator 2, IsRoot
6: IsSymbol 3
7: IsOperator 3
8: IsSymbol 4


What would this look like in an ECS?

IsOperator

0: E1, *
1: E3, -
2: E5, +
3: E7, +

IsSymbol

0: E0, A
1: E2, B
2: E4, C
3: E6, D
4: E8, E



Entities

0: IsSymbol 0
1: IsOperator 0
2: IsSymbol 1
3: IsOperator 1
4: IsSymbol 2
5: IsOperator 2, IsRoot
6: IsSymbol 3
7: IsOperator 3
8: IsSymbol 4


What would this look like in an ECS?

IsOperator

0: E1, *, E0, E3
1: E3, -, E2, E4
2: E5, +, E1, E7
3: E7, +, E6, E8

IsSymbol

0: E0, A
1: E2, B
2: E4, C
3: E6, D
4: E8, E



Entities

0: IsSymbol 0
1: IsOperator 0
2: IsSymbol 1
3: IsOperator 1
4: IsSymbol 2
5: IsOperator 2, IsRoot
6: IsSymbol 3
7: IsOperator 3
8: IsSymbol 4

What would this look like in an ECS?

IsOperator


0:	E1, *, E0, E3
1:	E3, -, E2, E4
2:	E5, +, E1, E7
3:	E7, +, E6, E8

IsSymbol

0:	E0, A
1:	E2, B
2:	E4, C
3:	E6, D
4:	E8, E

IsValue

....
: E, 123
...



Entities

0:	IsSymbol 0
1:	IsOperator 0
2:	IsSymbol 1
3:	IsOperator 1
4:	IsSymbol 2
5:	IsOperator 2, IsRoot
6:	IsSymbol 3
7:	IsOperator 3
8:	IsSymbol 4

What would this look like in an ECS?

IsOperator

0:	E1, *, E0, E3
1:	E3, -, E2, E4
2:	E5, +, E1, E7
3:	E7, +, E6, E8

IsSymbol


0:	E0, A
1:	E2, B
2:	E4, C
3:	E6, D
4:	E8, E

IsValue

....
: E, 123
...

SourceLocation


....
: E, "test.rs" L5:C3
...



Entities

0:	IsSymbol 0
1:	IsOperator 0
2:	IsSymbol 1
3:	IsOperator 1
4:	IsSymbol 2
5:	IsOperator 2, IsRoot
6:	IsSymbol 3
7:	IsOperator 3
8:	IsSymbol 4

How is program data stored in compilers?



AST

Nodes

0: Symbol "A"
1: Operator "*", Children(0, 2)
2: Symbol "B"
3: Operator "-", Children(2, 4)
4: Symbol "C",
5: Operator "+", Children(2, 4)
6: Symbol "D"
7: Operator "+"
8: Symbol "E"

root →

ECS

IsOperator

0: E1, *, E0, E3
1: E3, -, E2, E4
2: E5, +, E1, E7
3: E7, +, E6, E8

IsSymbol

0: E0, A
1: E2, B
2: E4, C
3: E6, D
4: E8, E

IsValue

....
: E, 123
...

SourceLocation

....
: E, "test.rs" L5:C3
...

Entities

0: IsSymbol 0
1: IsOperator 0
2: IsSymbol 1
3: IsOperator 1
4: IsSymbol 2
5: IsOperator 2, IsRoot
6: IsSymbol 3
7: IsOperator 3
8: IsSymbol 4

Why might we want ECS in Compilers?

1. Separates concerns
2. Systems can operate independently
 - a. Systems can operate in parallel*
 - b. Systems can run at different times
3. Cache & Memory locality
4. Avoiding branches

What can ECS do that might work in Compilers?

Anything that can be written as repeated passes over related nodes

- This seems plausible for Static analysis!

So:

- Optimization!
- Type checking!
- Dataflow checking!
- Code generation!

A lot of what a modern compiler spends time on!

Does it actually work?

Well...

I don't know.

Let's write some benchmarks!

Steel: An attempt at ECS for compilers

- A small expression language
- Just enough program to do optimization on
- ...
- Okay, maybe also a few fun features... just to keep life interesting

Steel: An attempt at ECS for compilers

Features

- Parser
 - Precedence:
i.e. $1+2*3 = 2*3+1 = 6$
 - Keyword arguments: `f(x=3)`
 - Positional arguments: `f(3)`
- Pretty printer
- Optimizer
 - Does constant folding
e.g. $1+2 \Rightarrow 3$
- Interpreter
 - So many (two) types!
 - `BuiltInFunction`
 - `i64`
- and a random code generator

Steel: An attempt at ECS for compilers

Features

- Implemented in AST **AND** ECS
- 100%* Rust 🦀
- **Has Benchmarks**

*(ignore the data collection scripts)

Steel: An attempt at ECS for compilers

Demo?

Steel: An attempt at ECS for compilers

Benchmarks

- Timed operations over generated programs of arbitrary size
- Used two different storage backends with an abstraction layer
 - AST
 - ECS
- Programs were 'trivially optimizable'

E.g.

$1+2+3+4+\dots+1000$


$1*2*3*4+\dots*1000$

Steel: An attempt at ECS for compilers

Benchmark results

(shorter bar = faster)


See the appendices
for an update



■ ast avg ■ ecs avg




ast avg ecs avg



(shorter bar = faster)


More results (UPDATED)

I was, accidentally, testing a 'worst case'



More results (UPDATED)

ast avg ecs avg



Steel: What could be happening here?

‘Sins’ I committed when preparing this data

I.e. Places where mistakes may have been made.

- Used **bash** to process the output of Rust’s benchmark data
 - because it there was so much
 - because manually converting the data into a sheet/excel was way too much work
- Used sheets to convert units with a handwritten function
 - because sheets doesn’t understand small units of time

Steel: What could be happening here?

- My code could be really really bad

Steel: What could be happening here?

- My code **IS** suboptimal
- My benchmarks could be bad
- My ECS implementation **IS** slow
- My AST implementation... could be **fast???**

Future work

Future work: Move on?

Maybe AST is good actually?

Future work: Fix it?

- Try other ECS implementations
 - Bevy
 - Specs
- Try different modeling
- Maybe the way I'm using ECS is poor
 - Hmm...

Future work: Maybe the way I'm using ECS is poor

- The optimizer is a big *"Find and Replace"*
- We have good *"Find and Replace"* algorithms!

Future work: Maybe the way I'm using ECS is poor

We have good *"Find and Replace"* algorithms

- Regex??? (Not great for structured data)
- Techniques from Databases? (i.e. optimizing SQL queries)
- [RETE](#)
 - Uses graphs of candidates
 - Avoids re-doing work
 - Might be a good fit
- RETE is used by a bunch of different (non-compiler) tools already
 - Datalog
 - [Souffle](#)
- Maybe I should try building a compiler with these?
- Others?

Future work: Collaboration!

- [Open source Steel](#)
- Write a blog post?
- Write a paper?


Contributions & Collaborations welcome

:D

Thanks!

Continue on for appendices!

Comparison of runtimes optimizing trivial programs ECS vs AST: note linear scale used



Improvements


Fixes:

- Split **Symbol** and **Operator** tables (like in slides)
- Store **'left'** and **'right'** with calls
(separate from the names args)
- Fetch **Values** and **Operators** from program data,
Don't use a hashmap for bookkeeping

Results:

- On small programs ECS's constant factors outweigh the benefits :(
- On large programs ECS can achieve **~20%-38%** performance improvement :)

Time saved by ECS as a percentage of AST run time



Improvements

Takeaway:

- Pre-computation has to be **FASTER** than memory
- **HashMaps** are awesome, but **dense**, purpose built **data structures** are generally **better**
- Parser is **97%** of my benchmark time, even using a library like [nom](#)
 - At this point I **should** probably stop

The following talk was **FAR** more helpful than anything else I watched or read:

- [A Practical Guide to Applying Data-Oriented Design](#) (by Zig creator: Andrew Kelley)

Rust tools I used (or wanted to)

CLI tools

- <https://crates.io/crates/bacon/1.1.4> // A watch command
- [sccache - crates.io: Rust Package Registry](https://crates.io/crates/sccache) // A distributed compilation cache

Useful libraries

- https://crates.io/crates/static_assertions // static checks to avoid making mistakes
- <https://crates.io/crates/memoize> // caching/memoizing
- <https://github.com/salsa-rs/salsa> // incremental computation
- <https://github.com/Geal/nom> // makes parsers easy
- https://docs.rs/typed-arena/latest/typed_arena/ // Makes contiguous memory easier ([comparison](#))

ECS frameworks

- [Bevy](#) // Comes recommended and with a great set of game dev tools
- <https://github.com/amethyst/specs>

Other compiler projects & tools

Tools

- <https://github.com/jzimmerman/langcc> // Tools for generating compilers
- [Rust!](#) - <https://www.rust-lang.org/> // My recommendation for a programming language

Compiler Projects

- [Cypher1/tako](#) // My hobby project (very WIP)
- [google-research/raksha](#) // My day job

Approaches and algorithms

Equality Saturation

- [Equality Saturation: a New Approach to Optimization *](#)
- <https://rosstate.org/publications/eqsat/RossThesis.pdf>
- <https://arxiv.org/pdf/2004.03082.pdf>

RETE algorithm

- Wiki: https://en.wikipedia.org/wiki/Rete_algorithm
- [Rete Algorithm - an overview | ScienceDirect Topics](#)
- UNSW: [The RETE Algorithm](#)

Index mistakes are easy to make!

Typed ptrs & indexes can help!

Keeping type information can
avoid mixing up indexes.

Code sample: [here](#)

Gist: [Typed Index and Arena impl](#)

```
use std::marker::PhantomData;

#[derive(Clone, Copy, Eq, PartialEq, Ord)]
struct TypedIndex<T> {
    index: usize,
    ty: PhantomData<T>,
}

impl<T> std::fmt::Debug for TypedIndex<T> {
    fn fmt(&self, f: &mut std::fmt::Formatter) -> std::fmt::Result {
        write!(f, "{}_index({:?})", std::any::type_name::<T>(), self.index)
    }
}

impl<T> PartialEq for TypedIndex<T> {
    fn eq(&self, other: &Self) -> bool {
        self.index == other.index
    }
}

impl<T> TypedIndex<T> {
    fn new(index: usize) -> Self {
        Self { index, ty: PhantomData }
    }
}

fn main() {
    let args: Vec<String> = std::env::args().collect();
    let x = args.len();
    let ind1: TypedIndex<i32> = TypedIndex::new(x);
    let ind2: TypedIndex<i32> = TypedIndex::new(x+1);
    dbg!(std::mem::size_of::<TypedIndex<i32>>() == std::mem::size_of::<usize>());
    dbg!(ind1, ind2);
    dbg!(ind1 == ind2);
}
```

Thanks again!