

COPY A: Q1 / Q2; J1 power; J2 load; J3/J4 Vbe

SUPPLY: J1 -> R1 -> D4 -> VCC. R1 is a resistor, not a fuse.







R7=120 ohm nominal fixed resistor; measured 117.6 ohm matches updated LT RV1 parameter.

P4: 9.8V input, Rs=662 ohm, C1=1.33nF. J2/J3/J4 are measurement headers, not jumpers.

DC volts: red pin 1 / black pin 2. J2 across R6; J3 Q1 base-emitter; J4 Q2 base-emitter.


LT names: R1=F1, R2=Rs, R3=R1a, R4=Re1, R5=Re2, R6=Rload, D3=Dz.


All resistors 1/4 W. Labels with matching names are electrically connected.


A_ and B_ nets are separate, including GND. No copper or power rail is shared between the two copies.

COPY B: Q101 / Q102; J101 power; J102 load; J103/J104 Vbe

SUPPLY: J101 -> R101 -> D104 -> VCC. R101 is a resistor, not a fuse.







R107=120 ohm nominal fixed resistor; measured 117.6 ohm matches updated LT RV1 parameter.

P4: 9.8V input, Rs=662 ohm, C101=1.33nF. J102/J103/J104 are measurement headers, not jumpers.

DC volts: red pin 1 / black pin 2. J102 across R106; J103 Q101 base-emitter; J104 Q102 base-emitter.

LT names: R101=F1, R102=Rs, R103=R1a, R104=Re1, R105=Re2, R106=Rload, D103=Dz.

All resistors 1/4 W. Labels with matching names are electrically connected.

Sheet: /
File: dual_current_mirror.kicad_sch

Title: Two isolated current mirrors — 150 x 100 mm panel

Size: A2	Date:	**Rev: P4 — 2x ISOLATED HEAD**
KiCad E.D.A. 10.0.7		Id: 1/1