# **Fuzzy Controller Class**

This class implements a fuzzy controller containing the rules and membership functions depicted in fuzzy\_settings.pdf. If you don't know how a fuzzy controller works, check Fuzzy.pdf for more information. To summarize, it works by replacing a PID to control a system, receiving the error as the input and outputting the control signal. For this controller, it receives a ratio to quantify the position of the robot and its angle, and outputs the left and right wheel velocity in percentage. To understand how the ratio is calculated, let  $b_R$  and  $b_L$  be the right and left model's intercept, respectively. Let  $b_{max} = max(|b_R|, |b_L|)$  and  $b_{min} = min(|b_R|, |b_L|)$ , this way we can calculate the ratio by doing  $r = \frac{b_{min}}{b_{max}} - 1$  and multiply by -1 if  $|b_R| < |b_L|$ . This class utilizes the open library fuzzylite, for more information go to <a href="https://fuzzylite.com/">https://fuzzylite.com/</a>.

# **Public Methods**

```
◆ FuzzyController ( )
    FuzzyController::FuzzyController
    (
        fl::Tnorm* AndMethod = new fl::Minimum,
        fl::Snorm* OrMethod = new fl::Maximum,
        fl::Tnorm* ImplicationMethod = new fl::AlgebraicProduct,
        fl::Snorm* AggregationMethod = new fl::Maximum,
        fl::Defuzzifier* defuzzMethod = new fl::Centroid(100)
    )
```

Default constructor that assigns default operators to the fuzzy controller, adding the possibility of changing

#### **Parameters**

AndMethod is the and / conjunction operator
OrMethod is the or / disjunction operator
ImplicationMethod is the implication operator
AggregationMethod is the aggregation operator
defuzzMethod is the defuzzification operator

```
    getOutputValues ( )
        FuzzyController::getOutputValues ( const double ratio, const double ang )
```

Receives the input data, calculates and returns the controller's output

## **Parameters**

*ratio* is the ratio explained previously*ang* is robot's angle

• friend operator << () std::ostream & operator << (std::ostream & out, const FuzzyController & fz )</p>

Print fuzzy controller object

## **Parameters**

out is where to print, normally terminalfz is the object to be printed