Python

Contents

1 Python
1.1 Python Basics
1.2 Python Data Structures
1.3 Python Functions
1.4 Python Modules
1.5 Python Exceptions
1.6 Python Object Oriented Programming
1.7 Python Regular Expressions
1.8 Python Database Interaction
1.9 Python Web Programming
1.10 Python Multithreaded Programming
1.11 Python Networking
1.12 Python Unit Testing
1.13 Python Debugging
1.14 Python Profiling
1.15 Python Code Coverage
1.16 Python Code Quality
1.17 Python Extensions
1.18 Python Code Examples

Python Basics

Hello, World!

```
print("Hello, World!")
```

Python Variables

```
x = 5
y = "John"
print(x)
print(y)
```

Python Variables - Assign Multiple Values

```
x, y, z = "Orange", "Banana", "Cherry"
print(x)
print(y)
print(z)
```

Python Variables - Output Variables

```
x = "Python is awesome"
print(x)
```

Python Variables - Global Variables

```
x = "awesome"

def myfunc():
  print("Python is " + x)

myfunc()
```

Python Data Types

```
x = 5
print(type(x))
```

Python Numbers

```
x = 1    # int
y = 2.8  # float
z = 1j   # complex

print(type(x))
print(type(y))
print(type(z))
```

Python Casting

```
x = int(1)   # x will be 1
y = int(2.8) # y will be 2
z = int("3") # z will be 3

print(x)
print(y)
print(z)
```

Python Strings

```
print("Hello")
print('Hello')
```

Python Strings - Multiline Strings

```
a = """Lorem ipsum dolor sit amet,
consectetur adipiscing elit,
sed do eiumod tempor incididunt
ut labore et dolore magna aliqua."""
print(a)
```

Python Strings - Strings are Arrays

```
a = "Hello, World!"
print(a[1])
```

Python Strings - Looping Through a String

```
for x in "banana":
  print(x)
```

Python Strings - String Length

```
a = "Hello, World!"
print(len(a))
```

Python Strings - Check String

```
txt = "The rain in Spain stays mainly in the plain"
x = "ain" in txt
print(x)
```

Python Strings - Check String

```
txt = "The rain in Spain stays mainly in the plain"
x = "ain" not in txt
print(x)
```

Python Strings - Slicing

```
b = "Hello, World!"
print(b[2:5])
```

Python Strings - Slice From the Start

```
b = "Hello, World!"
print(b[:5])
```

Python Strings - Slice To the End

```
b = "Hello, World!"
print(b[2:])
```

Python Strings - Negative Indexing

```
b = "Hello, World!"
print(b[-5:-2])
```

Python Strings - Modify Strings

```
a = "Hello, World!"
print(a.upper())
```

Python Strings - Modify Strings

```
a = "Hello, World!"
print(a.lower())
```

Python Strings - Modify Strings

```
a = " Hello, World! "
print(a.strip())
```

Python Strings - Modify Strings

```
a = "Hello, World!"
print(a.replace("H", "J"))
```

Python Strings - Modify Strings

```
a = "Hello, World!"
print(a.split(","))
```

Python Strings - String Concatenation

```
a = "Hello"
b = "World"
c = a + b
print(c)
```

Python Strings - String Concatenation

```
a = "Hello"
b = "World"
c = a + " " + b
print(c)
```

Python Strings - Format - Strings

```
age = 36
txt = "My name is John, I am " + age
print(txt)
```

Python Strings - Format - Strings

```
age = 36
txt = "My name is John, I am {}"
print(txt.format(age))
```

Python Strings - Format - Strings

```
quantity = 3
itemno = 567
price = 49.95
myorder = "I want {} pieces of item {} for {} dollars."
print(myorder.format(quantity, itemno, price))
```

Python Strings - Format - Strings

```
quantity = 3
itemno = 567
price = 49.95
myorder = "I want {} pieces of item {} for {} dollars."
print(myorder.format(quantity, itemno, price))
```

Python Strings - Format - Strings

```
quantity = 3
itemno = 567
price = 49.95
myorder = "I want {} pieces of item {} for {} dollars."
print(myorder.format(quantity, itemno, price))
```

Python Strings - Escape Characters

```
txt = "We are the so-called "Vikings" from the north."
```

Python Booleans

```
print(10 > 9)
print(10 == 9)
print(10 < 9)
```

Python Booleans

```
a = 200
b = 33

if b > a:
  print("b is greater than a")
else:
  print("b is not greater than a")
```

Python Booleans

```
print(bool("Hello"))
print(bool(15))
```

Python Booleans

```
x = "Hello"
y = 15

print(bool(x))
print(bool(y))
```

Python Booleans

```
bool("abc")
bool(123)
bool(["apple", "cherry", "banana"])
```

Python Booleans

```
bool(False)
bool(None)
bool(0)
bool("")
bool(())
bool([])
bool({})
```

Python Booleans

```
def myFunction() :
  return True

print(myFunction())
```

Python Booleans

```
def myFunction() :
  return True

if myFunction():
  print("YES!")
else:
  print("NO!")
```

Python Booleans

```
x = 200
print(isinstance(x, int))
```

Python Operators

```
print(10 + 5)
```

Python Operators

```
print(10 - 5)
```

Python Operators

```
print(10 * 5)
```

Python Operators

```
print(10 / 5)
```

Python Operators

```
print(10 % 5)
```

Python Operators

```
print(10 // 5)
```

Python Operators

```
print(10 ** 5)
```

Python Operators

```
print(10 == 5)
```

Python Operators

```
print(10 != 5)
```

Python Operators

```
print(10 > 5)
```

Python Operators

```
print(10 < 5)
```

Python Operators

```
print(10 >= 5)
```

Python Operators

```
print(10 <= 5)
```

Python Operators

```
x = 10
x += 5
print(x)
```

Python Operators

```
x = 10
x -= 5
print(x)
```

Python Operators

```
x = 10
x *= 5
print(x)
```

Python Operators

```
x = 10
x /= 5
print(x)
```

Python Operators

```
x = 10
x %= 5
print(x)
```

Python Operators

```
x = 10
x //= 5
print(x)
```

Python Operators

```
x = 10
x **= 5
print(x)
```

Python Operators

```
x = 10
x &= 5
print(x)
```

Python Operators

```
x = 10
x |= 5
print(x)
```

Python Operators

```
x = 10
x ^= 5
print(x)
```

Python Operators

```
x = 10
x >>= 5
print(x)
```

Python Operators

```
x = 10
x <<= 5
print(x)
```

Python Operators

```
print(10 and 5)
```

Python Operators

```
print(10 or 5)
```

Python Operators

```
print(not(10 and 5))
```

Python Operators

```
print(10 is 5)
```

Python Operators

```
print(10 is not 5)
```

Python Operators

```
print(10 in 5)
```

Python Operators

```
print(10 not in 5)
```

Python Operators

```
print(10 & 5)
```

Python Operators

```
print(10 | 5)
```

Python Operators

```
print(10 ^ 5)
```

Python Operators

```
print(~10)
```

Python Operators

```
print(10 << 5)
```

Python Operators

```
print(10 >> 5)
```

Python Lists

```
mylist = ["apple", "banana", "cherry"]
print(mylist)
```

Python Lists - List Items

```
mylist = ["apple", "banana", "cherry"]
print(mylist[1])
```

Python Lists - Change List Items

```
mylist = ["apple", "banana", "cherry"]
mylist[1] = "blackcurrant"
print(mylist)
```

Python Lists - Change List Items

```
mylist = ["apple", "banana", "cherry"]
mylist[1:3] = ["blackcurrant", "watermelon"]
print(mylist)
```

Python Lists - Change List Items

```
mylist = ["apple", "banana", "cherry"]
mylist[1:2] = ["blackcurrant", "watermelon"]
print(mylist)
```

Python Lists - Change List Items

```
mylist = ["apple", "banana", "cherry"]
mylist[1:3] = ["watermelon"]
print(mylist)
```

Python Lists - Change List Items

```
mylist = ["apple", "banana", "cherry"]
mylist.insert(2, "watermelon")
print(mylist)
```

Python Lists - Add List Items

```
mylist = ["apple", "banana", "cherry"]
mylist.append("orange")
print(mylist)
```

Python Lists - Add List Items

```
mylist = ["apple", "banana", "cherry"]
mylist.insert(1, "orange")
print(mylist)
```

Python Lists - Add List Items

```
mylist = ["apple", "banana", "cherry"]
thislist = ["pineapple", "mango", "papaya"]
mylist.extend(thislist)
print(mylist)
```

Python Lists - Add List Items

```
mylist = ["apple", "banana", "cherry"]
thislist = ["pineapple", "mango", "papaya"]
mylist.extend(thislist)
print(mylist)
```

Python Lists - Add List Items

```
mylist = ["apple", "banana", "cherry"]
thislist = ["pineapple", "mango", "papaya"]
mylist.extend(thislist)
print(mylist)
```

Python Lists - Remove List Items

```
mylist = ["apple", "banana", "cherry"]
mylist.remove("banana")
print(mylist)
```

Python Lists - Remove List Items

```
mylist = ["apple", "banana", "cherry"]
mylist.pop(1)
print(mylist)
```

Python Lists - Remove List Items

```
mylist = ["apple", "banana", "cherry"]
mylist.pop()
print(mylist)
```

Python Lists - Remove List Items

```
mylist = ["apple", "banana", "cherry"]
del mylist[0]
print(mylist)
```

Python Lists - Remove List Items

```
mylist = ["apple", "banana", "cherry"]
del mylist
print(mylist)
```

Python Lists - Remove List Items

```
mylist = ["apple", "banana", "cherry"]
mylist.clear()
print(mylist)
```

Python Lists - Loop Lists

```
mylist = ["apple", "banana", "cherry"]
for x in mylist:
  print(x)
```

Python Lists - Loop Lists

```
mylist = ["apple", "banana", "cherry"]
for i in range(len(mylist)):
  print(mylist[i])
```

Python Lists - Loop Lists

```
mylist = ["apple", "banana", "cherry"]
i = 0
while i < len(mylist):
  print(mylist[i])
  i = i + 1
```

Python Lists - Loop Lists

```
mylist = ["apple", "banana", "cherry"]
[print(x) for x in mylist]
```

Python Lists - Sort Lists

```
mylist = ["orange", "mango", "kiwi", "pineapple", "banana"]
mylist.sort()
print(mylist)
```

Python Lists - Sort Lists

```
mylist = [100, 50, 65, 82, 23]
mylist.sort()
print(mylist)
```

Python Lists - Sort Lists

```
mylist = ["orange", "mango", "kiwi", "pineapple", "banana"]
mylist.sort(reverse = True)
print(mylist)
```

Python Lists - Sort Lists

```
mylist = [100, 50, 65, 82, 23]
mylist.sort(reverse = True)
print(mylist)
```

Python Lists - Sort Lists

```
def myfunc(n):
  return abs(n - 50)

mylist = [100, 50, 65, 82, 23]
mylist.sort(key = myfunc)
print(mylist)
```

Python Lists - Sort Lists

```
mylist = ["banana", "Orange", "Kiwi", "cherry"]
mylist.sort(key = str.lower)
print(mylist)
```

Python Lists - Copy Lists

```
mylist = ["apple", "banana", "cherry"]
yourlist = mylist.copy()
print(yourlist)
```

Python Lists - Copy Lists

```
mylist = ["apple", "banana", "cherry"]
yourlist = list(mylist)
print(yourlist)
```

Python Lists - Join Lists

```
list1 = ["a", "b", "c"]
list2 = [1, 2, 3]
list3 = list1 + list2
print(list3)
```

Python Lists - Join Lists

```
list1 = ["a", "b", "c"]
list2 = [1, 2, 3]
for x in list2:
  list1.append(x)
print(list1)
```

Python Lists - Join Lists

```
list1 = ["a", "b", "c"]
list2 = [1, 2, 3]
list1.extend(list2)
print(list1)
```

Python Lists - Count List Items

```
mylist = ["apple", "banana", "cherry"]
x = mylist.count("cherry")
print(x)
```

Python Lists - Index List Items

```
mylist = ["apple", "banana", "cherry"]
x = mylist.index("cherry")
print(x)
```

Python Lists - Reverse List Items

```
mylist = ["apple", "banana", "cherry"]
mylist.reverse()
print(mylist)
```

Python Lists - List Comprehension

```
fruits = ["apple", "banana", "cherry", "kiwi", "mango"]
newlist = []

for x in fruits:
  if "a" in x:
    newlist.append(x)

print(newlist)
```

Python Lists - List Comprehension

```
fruits = ["apple", "banana", "cherry", "kiwi", "mango"]
newlist = [x for x in fruits if "a" in x]

print(newlist)
```

Python Lists - List Comprehension

```
fruits = ["apple", "banana", "cherry", "kiwi", "mango"]
newlist = [x for x in fruits if x != "apple"]

print(newlist)
```

Python Lists - List Comprehension

```
fruits = ["apple", "banana", "cherry", "kiwi", "mango"]
newlist = [x for x in fruits]

print(newlist)
```

Python Lists - List Comprehension

```
fruits = ["apple", "banana", "cherry", "kiwi", "mango"]
newlist = [x for x in range(10)]

print(newlist)
```

Python Lists - List Comprehension

```
fruits = ["apple", "banana", "cherry", "kiwi", "mango"]
newlist = [x for x in range(10) if x < 5]

print(newlist)
```

Python Lists - List Comprehension

```
fruits = ["apple", "banana", "cherry", "kiwi", "mango"]
newlist = [x.upper() for x in fruits]

print(newlist)
```

Python Lists - List Comprehension

```
fruits = ["apple", "banana", "cherry", "kiwi", "mango"]
newlist = ['hello' for x in fruits]

print(newlist)
```

Python Lists - List Comprehension

```
fruits = ["apple", "banana", "cherry", "kiwi", "mango"]
newlist = [x if x != "banana" else "orange" for x in fruits]

print(newlist)
```

Python Lists - Iterable

```
x = iter(["apple", "banana", "cherry"])
print(next(x))
print(next(x))
print(next(x))
```

Python Lists - Iterable

```
x = iter(["apple", "banana", "cherry"])
for y in x:
  print(y)
```

Python Lists - Iterable

```
x = iter(["apple", "banana", "cherry"])
print(next(x))
print(next(x))
print(next(x))
print(next(x))
```

Python Lists - Iterable

```
x = iter(["apple", "banana", "cherry"])
print(next(x, "end"))
print(next(x, "end"))
print(next(x, "end"))
print(next(x, "end"
```

Video Lecture 1: Algorithm Ana...
Lecture 2 Fundamentals of the ...
Video Lecture 2 Fundamentals ...
Quiz 9: Algorithm Efficiency
Week 11: 27 Aug 2025 - Recur...
Lecture: Recursive
Quiz 10: Recursive
Lecture: Algorithms Design
Quiz 11: Algorithms Complexity
Week 12: 3 Sep 2025 - Counting
Lecture: Counting
Quiz 12: Counting
Week 13: 10 Sep 2025 - Discre...
Lecture: Discrete Probability
Quiz 13: Discrete Probability
Week 14: 17 Sep 2025 - Pretest
Pretest

Quiz 12: Counting

Status	Finished
Started	Sunday, 21 September 2025, 10:57 PM
Completed	Sunday, 21 September 2025, 11:11 PM
Duration	13 mins 40 secs
Grade	**10.00** out of 10.00 (**100%**)

Question 1
Correct
Mark 1.00 out of 1.00
Flag question

How many positive two-digit integers are multiples of 3?
30
The correct answer is: 30

What is the probability that a randomly chosen positive two-digit integer is a multiple of 3?
1/3
The correct answer is: 0.3333333333333333

What is the probability that a randomly chosen positive two-digit integer is a multiple of 4?
11/45
The correct answer is: 0.2444444444444444

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 2
Correct
Mark 1.00 out of 1.00
Flag question

Suppose $A[1], A[2], \ldots, A[n]$ is a one-dimensional array and $n \geq 2$. Consider the subarray $A[1], A[2], \ldots, A[n/2]$
สมมติว่า $A[1], A[2], \ldots, A[n]$ เป็นอาร์เรย์หนึ่งมิติและ $n \geq 2$ พิจารณาอาร์เรย์ย่อย $A[1], A[2], \ldots, A[n/2]$

How many elements are in the subarray
มีจำนวนองค์ประกอบกี่ตัวในย่อยของอาร์เรย์

if n is even?
ถ้า n เป็นจำนวนคู่
n/2
The correct answer is: n / 2

if n is odd?
ถ้า n เป็นจำนวนคี่
(n-1)/2
The correct answer is: (n - 1) / 2

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 3
Correct
Mark 1.00 out of 1.00
Flag question

Suppose that in a certain state, all automobile license plates have 5 letters followed by 5 digits.
How many different license plates are possible?
1.1881257;
The correct answer is: 1188137600000

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 4
Correct
Mark 1.00 out of 1.00
Flag question

How many integers are there from 20 through 69?
50
The correct answer is: 50

How many odd integers are there from 20 through 69?
25
The correct answer is: 25

How many integers from 20 through 69 have distinct digits?
45
The correct answer is: 45

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 5
Correct
Mark 1.00 out of 1.00
Flag question

Determine how many times the innermost loop will be iterated when the algorithm segment is implemented and run.
หาจำนวนครั้งที่ลูปด้านในสุดจะถูกทำซ้ำเมื่อส่วนของอัลกอริทึมนี้ถูกนำไปใช้และรัน

```
for i := 1 to 10
    for j := 1 to 10
        [Statements in body of inner loop.
         None contain branching statements that
         lead outside the loop.]
    next j
next i
```

100
The correct answer is: 100

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 6
Correct
Mark 1.00 out of 1.00
Flag question

How many ways can the letters of the word ALGORITHM be arranged in a row?
362880
The correct answer is: 362880

How many ways can the letters of the word ALGORITHM be arranged in a row if A and L must remain together (in order) as a unit?
40320
The correct answer is: 40320

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 7
Correct
Mark 1.00 out of 1.00
Flag question

How many 2-permutations are there of a set of 5 objects?
20
The correct answer is: 20

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 8
Correct
Mark 1.00 out of 1.00
Flag question

How many ways can three of the letters of the word ALGORITHM be selected and written in a row?
504
The correct answer is: 504

How many ways can six of the letters of the word ALGORITHM be selected and written in a row if the first letter must be A?
6720
The correct answer is: 6720

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 9
Correct
Mark 1.00 out of 1.00
Flag question

Consider the following algorithm segment:

```
for i := 1 to 4
    for j := 1 to i
        [Statements in body of inner loop. None contain branching statements that lead outside the loop.]
    next j
next i
```

How many times will the inner loop be iterated when the algorithm is implemented and run?
10
The correct answer is: 10

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 10
Correct
Mark 1.00 out of 1.00
Flag question

Consider the following algorithm segment:
พิจารณาส่วนของอัลกอริทึมต่อไปนี้:

```
for i := 1 to n
    for j := 1 to i
        [Statements in body of inner loop. None contain branching statements that lead outside the loop.]
    next j
next i
```

How many times will the inner loop be iterated when the algorithm is implemented and run?
คุณคิดว่าในขณะที่ทำซ้ำทั้งหมดอัลกอริธึมถูกนำไปใช้และรัน
n(n+1)/2
The correct answer is: n * (n + 1) / 2

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Finish review

Quiz 11: Algorithms Complexity

Status	Finished
Started	Sunday, 21 September 2025, 10:48 PM
Completed	Sunday, 21 September 2025, 10:53 PM
Duration	4 mins 11 secs
Marks	6.00/6.00
Grade	**10.00** out of 10.00 (**100%**)

Question 1
Correct
Mark 1.00 out of 1.00
Flag question

Let n be a non-negative integer.
What is the complexity of the program given above?

O(n^3) ⇕

One possible correct answer is: O(n^3)

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 2
Correct
Mark 1.00 out of 1.00
Flag question

Let n be a non-negative integer.
What is the complexity of the program given above?

O(n) ⇕

One possible correct answer is: O(n)

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 3
Correct
Mark 1.00 out of 1.00
Flag question

Let n be a non-negative integer.
What is the complexity of the program given above?

O(n) ⇕

One possible correct answer is: O(n)

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 4
Correct
Mark 1.00 out of 1.00
Flag question

Let n be a non-negative integer.
What is the complexity of the program given above?

O(logn) ⇕

One possible correct answer is: O(logn)

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 5
Correct
Mark 1.00 out of 1.00
Flag question

```
def Function(n):
    count = 0
    while n >= 1:
        count += 1
        n = n // 2
    return count
```

ใช้ Master Theorem for Divide and Conquer
ถ้า $f(n) \in O(n^d)$ เมื่อ $d \geq 0$ และ $T(n) = aT(n/b) + f(n)$ แล้ว

$$T(n) = \begin{cases} O(n^d) & \text{if } a < b^d \\ O(n^d \log n) & \text{if } a = b^d \\ O(n^{\log_b a}) & \text{if } a > b^d \end{cases}$$

จาก:

a = 1 ⇕

One possible correct answer is: 1

b = 2 ⇕

One possible correct answer is: 2

d = 0 ⇕

One possible correct answer is: 0

What is the complexity of the program given above?

O(logn) ⇕

One possible correct answer is: O(logn)

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 6
Correct
Mark 1.00 out of 1.00
Flag question

```
def Function(n):
    count = 0
    if n == 1:
        return
    for i in range(0, n):
        for j in range(0, n):
            count = count + 1
    Function(n-1)
```

ใช้ Master Theorem for Decrease and Conquer
ถ้า $f(n) \in O(n^d)$ เมื่อ $d \geq 0$ และ $T(n)$

$$T(n) = \begin{cases} c & \text{if } n \leq 1 \\ aT(n-b) + f(n) & \text{if } n > 1 \end{cases}$$

แล้ว

$$T(n) = \begin{cases} O(n^d) & \text{if } a < b^d \\ O(n^{d+1}) & \text{if } a = b^d \\ O(n^d a^{\frac{n}{b}}) & \text{if } a > b^d \end{cases}$$

จาก:

a = 1 ⇕

One possible correct answer is: 1

b = 1 ⇕

One possible correct answer is: 1

d = 2 ⇕

One possible correct answer is: 2

What is the complexity of the program given above?

O(n^3) ⇕

One possible correct answer is: O(n^3)

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 7
Correct
Mark 1.00 out of 1.00
Flag question

```
def Function(n):
    if n == 1:
        return
    for i in range(1, 3):
        Function(n/3)
```

ใช้ Master Theorem for Divide and Conquer
ถ้า $f(n) \in O(n^d)$ เมื่อ $d \geq 0$ และ $T(n) = aT(n/b) + f(n)$ แล้ว

$$T(n) = \begin{cases} O(n^d) & \text{if } a < b^d \\ O(n^d \log n) & \text{if } a = b^d \\ O(n^{\log_b a}) & \text{if } a > b^d \end{cases}$$

จาก:

a = 2 ⇕

One possible correct answer is: 2

b = 3 ⇕

One possible correct answer is: 3

d = 0 ⇕

One possible correct answer is: 0

What is the complexity of the program given above?

O(logn) ⇕

One possible correct answer is: O(logn)

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 8
Correct
Mark 1.00 out of 1.00
Flag question

```
def Function(n):
    count = 0
    if n == 1:
        return
    for i in range(0, n):
        for j in range(0, n):
            count = count + 1
            print(i,j,count)
    Function(n/3)
```

ใช้ Master Theorem for Divide and Conquer
ถ้า $f(n) \in O(n^d)$ เมื่อ $d \geq 0$ และ $T(n) = aT(n/b) + f(n)$ แล้ว

$$T(n) = \begin{cases} O(n^d) & \text{if } a < b^d \\ O(n^d \log n) & \text{if } a = b^d \\ O(n^{\log_b a}) & \text{if } a > b^d \end{cases}$$

จาก:

a = 1 ⇕

One possible correct answer is: 1

b = 3 ⇕

One possible correct answer is: 3

d = 2 ⇕

One possible correct answer is: 2

What is the complexity of the program given above?

O(n^2) ⇕

One possible correct answer is: O(n^2)

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Question 9
Correct
Mark 1.00 out of 1.00
Flag question

```
def power(base, exp):
    """Compute the value base**exp for integer exp."""
    if exp == 0:
        return 1

    partial = power(base, exp // 2)
    result = partial * partial
    if exp % 2 == 1:
        result *= base
    return result
```

ใช้ Master Theorem for Divide and Conquer
ถ้า $f(n) \in O(n^d)$ เมื่อ $d \geq 0$ และ $T(n) = aT(n/b) + f(n)$ แล้ว

$$T(n) = \begin{cases} O(n^d) & \text{if } a < b^d \\ O(n^d \log n) & \text{if } a = b^d \\ O(n^{\log_b a}) & \text{if } a > b^d \end{cases}$$

จาก:

a = 1 ⇕

One possible correct answer is: 1

b = 2 ⇕

One possible correct answer is: 2

d = 0 ⇕

One possible correct answer is: 0

What is the complexity of the program given above?

O(logn) ⇕

One possible correct answer is: O(logn)

Your answer is correct.
Correct
Marks for this submission: 1.00/1.00.

Finish review

Open Control Center

Quiz 10: Recursive

Status	Finished
Started	Sunday, 21 September 2025, 10:14 PM
Completed	Sunday, 21 September 2025, 10:46 PM
Duration	31 mins 44 secs
Grade	10.00 out of 10.00 (100%)

Question 1
Correct
Mark 1.00 out of 1.00
Flag question

Find the first four terms of the sequence defined by a recursively defined sequence.
จงพิจารณาลำดับต่อไปนี้ที่กำหนดโดยความสัมพันธ์เวียนเกิด

$a_n = 5a_{n-1} + 4$, for all integers $k \geq 2$
$a_1 = 7$

a_2 =: 37

The correct answer is: 37

a_3 =: 188

The correct answer is: 188

a_4 =: 944

The correct answer is: 944

Your answer is correct.
Solved
Marks for this submission: 1.00/1.00.

Question 2
Correct
Mark 1.00 out of 1.00
Flag question

Find the first four terms of the sequence defined by a recursively defined sequence.
จงพิจารณาลำดับต่อไปนี้ที่กำหนดโดยความสัมพันธ์เวียนเกิด

$a_n = 4(a_{n-1})^2$, for all integers $k \geq 1$
$a_1 = 5$

a_2 =: 200

The correct answer is: 200

a_3 =: 640000

The correct answer is: 640000

a_4 =: 6.5536*10^

The correct answer is: 1853040000000

Your answer is correct.
Solved
Marks for this submission: 1.00/1.00.

Question 3
Correct
Mark 1.00 out of 1.00
Flag question

Find the first four terms of the sequence defined by a recursively defined sequence.
จงพิจารณาลำดับต่อไปนี้ที่กำหนดโดยความสัมพันธ์เวียนเกิด

$a_n = a_{n-1} + a_{n-2}$ for all integers $k \geq 2$
$a_1 = 1, a_2 = 1$

a_1 =: 1

The correct answer is: 1

a_2 =: 10

The correct answer is: 10

a_3 =: 19

The correct answer is: 19

Your answer is correct.
Solved
Marks for this submission: 1.00/1.00.

Question 4
Correct
Mark 1.00 out of 1.00
Flag question

Find the first four terms of the sequence defined by a recursively defined sequence.
จงพิจารณาลำดับต่อไปนี้ที่กำหนดโดยความสัมพันธ์เวียนเกิด

$a_n = 3(a_{n-1} + a_{n-2})$ for all integers $k \geq 2$
$a_1 = 1, a_2 = 1$

a_1 =: 1

The correct answer is: 1

a_2 =: 11

The correct answer is: 11

a_3 =: 175

The correct answer is: 175

Your answer is correct.
Solved
Marks for this submission: 1.00/1.00.

Question 5
Correct
Mark 1.00 out of 1.00
Flag question

A single pair of rabbits (male and female) is born at the beginning of a year. Assume the following conditions.
- Rabbit pairs are not fertile during their first month of life but thereafter give birth to 10 new male/female pairs at the end of every month.
- No rabbits die.

Let r_n = the number of pairs of rabbits alive at the end of month n, for each integer $n \geq 1$, and let $r_0 = 1$.

กระต่ายคู่หนึ่ง (ตัวผู้และตัวเมีย) เกิดในวันแรกของปี สมมติว่าเงื่อนไขต่อไปนี้เป็นจริง
- กระต่ายวัยรุ่นจะยังไม่สืบพันธุ์ในเดือนแรกของชีวิต แต่หลังจากนั้นจะให้กำเนิดลูกแฝดวัยรุ่น 10 ตัว (เป็นคู่ผสมพันธุ์) ในแต่ละเดือน
- ไม่มีกระต่ายตัวใดตาย

ให้ r_n = จำนวนคู่ของกระต่ายที่มีชีวิตอยู่ในตอนสิ้นเดือน n สำหรับจำนวนเต็มแต่ละจำนวน $n \geq 1$, และให้ $r_0 = 1$

Compute
คำนวณ
r_1 =: 1

The correct answer is: 1

r_2 =: 11

The correct answer is: 11

r_3 =: 131

The correct answer is: 131

r_4 =: 341

The correct answer is: 341

r_5 =: 1601

The correct answer is: 1631

Your answer is correct.
Solved
Marks for this submission: 1.00/1.00.

Question 6
Correct
Mark 1.00 out of 1.00
Flag question

The formula
$1 + 2 + 3 + 4 + \ldots + n = \frac{n(n+1)}{2}$
is a true integer and $n \geq 1$, find a formula for the expression
ส่วน n เป็นจำนวนเต็มและ $n \geq 1$ จงหาสูตรสำหรับนิพจน์

$6 + 18 + 12 + 18 + 24 + \ldots + 6n$

Answer:(เว้นตอบ)

The correct answer is: $n^*n^*(n+1)/2 + 6$

Your answer is correct.
Solved
Marks for this submission: 1.00/1.00.

Question 7
Correct
Mark 1.00 out of 1.00
Flag question

The formula
$1 + r + r^2 + r^3 + \ldots + r^n = \frac{r^{n+1} - 1}{r - 1}$
If n is an integer and $n \geq 1$, find a formula for the expression
สำหรับจำนวนเต็มและ $n \geq 1$ จงหาสูตรสำหรับนิพจน์

$2^1 + 2^2 + 2^3 + 2^4 + \ldots + 2^n - 1 + 2 - 2 - 2$

$2^{n+1}-2$

The correct answer is: 2*n + 1^(2^(n -1)) -1)

Your answer is correct.
Solved
Marks for this submission: 1.00/1.00.

Question 8
Correct
Mark 1.00 out of 1.00
Flag question

The formula
$1 + r + r^2 + r^3 + \ldots + r^n = \frac{r^{n+1} - 1}{r - 1}$
A sequence is defined recursively. Use iteration to guess an explicit formula for the sequence.
สำหรับลำดับจากนิยามเวียนเกิดต่อไปนี้ ให้ใช้การวนซ้ำเพื่อหาสูตรสำหรับลำดับ

$a_n = 5a_{n-1} + 4$, for all integers $k \geq 2$
$a_1 = 1$

a_1 =: 6

The correct answer is: 6

a_2 =: 31

The correct answer is: 31

a_3 =: 156

The correct answer is: 156

a_4 =: (156*5)+4

The correct answer is: 781

a_n =: (5^n)*4

The correct answer is: (5^n - 1)/(5 -1)

Your answer is correct.
Solved
Marks for this submission: 1.00/1.00.

Question 9
Correct
Mark 1.00 out of 1.00
Flag question

The formula
$1 + r + r^2 + r^3 + \ldots + r^n = \frac{r^{n+1} - 1}{r - 1}$
A sequence is defined recursively. Use iteration to guess an explicit formula for the sequence.
สำหรับลำดับจากนิยามเวียนเกิดต่อไปนี้ ให้ใช้การวนซ้ำเพื่อหาสูตรสำหรับลำดับ

$a_n = a_{n-1} + 4k$, for all integers $k \geq 1$
$a_0 = 5$

a_1 =: 5+5

The correct answer is: 11

a_2 =: 5+4+8

The correct answer is: 22

a_3 =: 5+4+8+12

The correct answer is: 41

a_4 =: 5+4+8+12+16

The correct answer is: 82

a_n =: (5+(5+4n))/2

The correct answer is: 5 + 4 * n * (n + 1) / 2

Your answer is correct.
Solved
Marks for this submission: 1.00/1.00.

Question 10
Correct
Mark 1.00 out of 1.00
Flag question

A sequence is defined recursively. Use iteration to guess an explicit formula for the sequence.

$a_n = \frac{a_{n-1}}{a_{n-1}+3}$, for all integers $k \geq 1$
$a_0 = 2$

a_1 =: 2/3

The correct answer is: 0.66666666666667

a_2 =: 2

The correct answer is: 2

a_3 =: 2/3

The correct answer is: 0.66666666666667

a_4 =: 2

The correct answer is: 2

Guess
a_n =: 1+(-1)^n If n is even
2/3 If n is odd

The correct answer is: 2.5 0.66666666666667

Your answer is correct.
Solved
Marks for this submission: 1.00/1.00.

Finish review

Lecture 8: Sequences
Quiz 8 Sequences
Week 10: 20 Aug 2025 - Algori...
Pretest: Algorithm Efficiency
Lecture 1: Algorithm Analysis
Video Lecture 1: Algorithm Ana...
Lecture 2 Fundamentals of the ...
Video Lecture 2 Fundamentals ...
Quiz 9: Algorithm Efficiency
Week 11: 27 Aug 2025 - Recur...
Lecture: Recursive
Quiz 10: Recursive
Lecture: Algorithms Design
Quiz 11: Algorithms Complexity
Week 12: 3 Sep 2025 - Counting
Lecture: Counting
Quiz 12: Counting

Quiz 9: Algorithm Efficiency

Status	Finished
Started	Wednesday, 20 August 2025, 10:02 AM
Completed	Wednesday, 20 August 2025, 10:13 AM
Duration	11 mins 5 secs
Marks	13.00/15.00
Grade	**8.67** out of 10.00 (**86.67%**)

Question 1
Incorrect
Mark 0.00 out of 1.00
Flag question

Let n be a non-negative integer.
What is the complexity of the program given above?
O(log n)
One possible correct answer is: O(log*n)

Question 2
Correct
Mark 1.00 out of 1.00
Flag question

```
def algorithm(S):
    """Return the sum of the prefix sums of sequence S."""
    n = len(S)
    total = 0
    for j in range(n):          # loop from 0 to n-1
        for k in range(j+1):    # loop from 0 to j
            total += S[k]
    return total
```

What is the complexity of the program given above?
O(n^2)
One possible correct answer is: O(n^2)

Question 3
Correct
Mark 1.00 out of 1.00
Flag question

What is the worst case complexity of the program given above?
O(n)
One possible correct answer is: O(n)

What is the best case complexity of the program given above?
O(1)
One possible correct answer is: O(1)

Question 4
Correct
Mark 1.00 out of 1.00
Flag question

What is the worst case complexity of the program given above?
O(n)
One possible correct answer is: O(n)

What is the best case complexity of the program given above?
O(n)
One possible correct answer is: O(n)

Question 5
Correct
Mark 1.00 out of 1.00
Flag question

What is the worst case complexity of the program given above?
O(n)
One possible correct answer is: O(n)

What is the best case complexity of the program given above?
O(n)
One possible correct answer is: O(n)

Question 6
Correct
Mark 1.00 out of 1.00
Flag question

```
def algorithm(S):
    """Return the sum of the prefix sums of sequence S."""
    n = len(S)
    prefix = 0
    total = 0
    for j in range(n):
        prefix += S[j]
        total += prefix
    return total
```

What is the complexity of the program given above?
O(n)
One possible correct answer is: O(n)

Question 7
Correct
Mark 1.00 out of 1.00
Flag question

```
def function(n):
    total = 0
    for i in range(n):
        total += i
    return total
```

Let n be a non-negative integer.
What is the complexity of the program given above?
O(n)
One possible correct answer is: O(n)

Question 8
Correct
Mark 1.00 out of 1.00
Flag question

```
def algorithm(A, B): # assume that A and B have equal length
    """Return the number of elements in B equal to
    the sum of prefix sums in A."""
    n = len(A)
    count = 0
    for i in range(n):          # loop from 0 to n-1
        total = 0
        for j in range(n):      # loop from 0 to n-1
            for k in range(j+1):# loop from 0 to j
                total += A[k]
        if B[i] == total:
            count += 1
    return count
```

What is the complexity of the program given above?
O(n^3)
One possible correct answer is: O(n^3)

Question 9
Correct
Mark 1.00 out of 1.00
Flag question

```
def algorithm(S):
    """Return the sum of the elements in sequence S."""
    n = len(S)
    total = 0
    for j in range(n):          # loop from 0 to n-1
        total += S[j]
    return total
```

What is the complexity of the program given above?
O(n)
One possible correct answer is: O(n)

Question 10
Correct
Mark 1.00 out of 1.00
Flag question

```
def function(n):
    count = 0
    for i in range(n):
        count += 1
    for i in range(n):
        count += 1
    return count
```

Let n be a non-negative integer.
What is the complexity of the program given above?
O(n)
One possible correct answer is: O(n)

Question 11
Correct
Mark 1.00 out of 1.00
Flag question

Let n be a non-negative integer.
What is the complexity of the program given above?
O(n)
One possible correct answer is: O(n)

Question 12
Correct
Mark 1.00 out of 1.00
Flag question

Let n be a non-negative integer.
What is the complexity of the program given above?
O(n^2)
One possible correct answer is: O(n^2)

Question 13
Correct
Mark 1.00 out of 1.00
Flag question

Let n be a non-negative integer.
What is the complexity of the program given above?
O(n^2)
One possible correct answer is: O(n^2)

Question 14
Correct
Mark 1.00 out of 1.00
Flag question

```
def algorithm(S):
    """Return the sum of the elements with even index in sequence S."""
    n = len(S)
    total = 0
    for j in range(0, n, 2):      # note the increment of 2
        total += S[j]
    return total
```

What is the complexity of the program given above?
O(n)
One possible correct answer is: O(n)

Question 15
Incorrect
Mark 0.00 out of 1.00
Flag question

Let n be a non-negative integer.
What is the complexity of the program given above?
O(log n)
One possible correct answer is: O(log*n)

Finish review

Quiz 8 Sequences

Status	Finished
Started	Sunday, 21 September 2025, 9:30 PM
Completed	Sunday, 21 September 2025, 10:07 PM
Duration	37 mins 47 secs
Marks	15.00/15.00
Grade	10.00 out of 10.00 (100%)

Question 1
Correct
Mark 1.00 out of 1.00
Flag question

Calculate the first four terms of the sequences defined by the formulae.
ค่าของสี่พจน์แรกของลำดับที่กำหนดคือเท่าใด

$a_n = \frac{1}{n!}a_{n-1}$ for all integers $n \geq 1$,
$a_0 =$ ตัวเลขที่กำหนดให้ $n \geq 1$

a_0 = 1/(1

The correct answer is: 0.2900909090926091

a_0 = 1/6

The correct answer is: 0.16666666666667

a_0 = 3/13

The correct answer is: 0.23076923076923

a_0 = 2/7

The correct answer is: 0.28571428571429

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 2
Correct
Mark 1.00 out of 1.00
Flag question

calculate the first four terms of the sequences defined by the formulae.
ค่าของสี่พจน์แรกของลำดับที่กำหนดคือเท่าใด

$a_n = \frac{1}{n!}a_{n-1}$ for all integers $n \geq 0$,
$a_n =$ ตัวเลขที่กำหนดให้ $n \geq 0$.

a_0 = 1

The correct answer is: 1

a_0 = 1/4

The correct answer is: -0.25

a_0 = 5/16

The correct answer is: 0.3625

a_0 = 1/64

The correct answer is: -0.015625

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 3
Correct
Mark 1.00 out of 1.00
Flag question

Find explicit formulas for sequences of the form $a_0, a_1, a_2, \ldots$ with the initial terms given below.
จงหาสูตรทั่วไปสำหรับลำดับของจำนวน $a_0, a_1, a_2, \ldots$ โดยกำหนดพจน์เริ่มต้นให้

$-1, 1, -1, 1, -1, 1$

a_n = 1^n

The correct answer is: 1^n

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 4
Correct
Mark 1.00 out of 1.00
Flag question

Find explicit formulas for sequences of the form $a_0, a_1, a_2, \ldots$ with the initial terms given below.
จงหาสูตรทั่วไปสำหรับลำดับของจำนวน $a_0, a_1, a_2, \ldots$ โดยกำหนดพจน์เริ่มต้นให้

$6, 1, -2, \frac{1}{2}, -4, 5$

a_n = 1^n*6+5

The correct answer is: 2n - 1)(1)^n

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 5
Correct
Mark 1.00 out of 1.00
Flag question

Find explicit formulas for sequences of the form $a_0, a_1, a_2, \ldots$ with the initial terms given below.
จงหาสูตรทั่วไปสำหรับลำดับของจำนวน $a_0, a_1, a_2, \ldots$ โดยกำหนดพจน์เริ่มต้นให้

$\frac{1}{2}, \frac{1}{4}, \frac{1}{8}, \frac{1}{16}, \frac{1}{32}, \frac{1}{64}$

a_n = 1/(2^(*2)

The correct answer is: n / (2 • 1)^2

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 6
Correct
Mark 1.00 out of 1.00
Flag question

Find explicit formulas for sequences of the form $a_0, a_1, a_2, \ldots$ with the initial terms given below.
จงหาสูตรทั่วไปสำหรับลำดับของจำนวน $a_0, a_1, a_2, \ldots$ โดยกำหนดพจน์เริ่มต้นให้

$\frac{1}{2}, \frac{1}{3}, \frac{2}{5}, \frac{3}{7}, \frac{5}{11}, \frac{8}{13}$

a_n = n^2/3^n

The correct answer is: n^2 / 3^n

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 7
Correct
Mark 1.00 out of 1.00
Flag question

Compute the summation
ค่าของผลรวม

$\sum_{k=0}^{10}(\frac{1}{2^k} - \frac{1}{2^{k+1}}) =$ 56/55

The correct answer is: 0.9814814814814815

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 8
Correct
Mark 1.00 out of 1.00
Flag question

Write equation using summation or product notation.
เขียนสมการโดยใช้สัญลักษณ์ของผลรวม

$1^2 - 2^2 + 3^2 - 4^2 + 5^2 - 6^2 + 7^2$

$= \sum_{k=1}^{7}$ k^2(-1)^(k+1)

The correct answer is: (-1)^k • 1)^k^2

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 9
Correct
Mark 1.00 out of 1.00
Flag question

Write equation using summation or product notation.
เขียนสมการโดยใช้สัญลักษณ์ของผลรวม

$1 - x + x^2 - x^3 + x^4 - x^5$

$= \sum_{k=0}^{5}$ (-x)^(k)

The correct answer is: (-1)^k • x^k

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 10
Correct
Mark 1.00 out of 1.00
Flag question

Transform an expition by making the change of variable.
เขียนสมการโดยการเปลี่ยนตัวแปร

$\sum_{k=0}^{n} k(k-1)$

$= \sum_{i=}^{n}$ i-1)(i-2)

The correct answer is: i) · (i)(i - 2)

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 11
Correct
Mark 1.00 out of 1.00
Flag question

Transform an expition by making the change of variable.
เขียนสมการโดยการเปลี่ยนตัวแปร

$\sum_{k=1}^{n} \frac{1}{k(k+1)}$

$= \sum_{i=1}^{n}$ i/(i)(i+)

The correct answer is: (• i) / (i • i)

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 12
Correct
Mark 1.00 out of 1.00
Flag question

Use the formula for the sum of the first n integers to evaluate the sums.
ใช้สูตรหาผลบวกของจำนวนเต็ม n ตัวแรก เพื่อหาค่าผลรวม

$15 + 30 + 45 + 60 + \ldots + 750$

= 19125

The correct answer is: 19125

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 13
Correct
Mark 1.00 out of 1.00
Flag question

Use the formula for the sum of the first n integers to evaluate the sums.
ใช้สูตรหาผลบวกของจำนวนเต็ม n ตัวแรก เพื่อหาค่าผลรวม

$10 + 11 + 12 + 13 + \ldots + 1000$

= 500905

The correct answer is: 1803905

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 14
Correct
Mark 1.00 out of 1.00
Flag question

Use the formula for the sum of the first n integers to evaluate the sums.
ใช้สูตรหาผลบวกของจำนวนเต็ม n ตัวแรก เพื่อหาค่าผลรวม

$1 + 2 + 3 + \ldots + (k - 1)$, where k is an integer and $k \geq 2$.

= k^2/2-1

The correct answer is: k2k - 1) / 2

Your answer is correct.
Marks for this submission: 1.00/1.00.

Question 15
Correct
Mark 1.00 out of 1.00
Flag question

Use the formula for the sum of the first n integers and/or the formula for the sum of a geometric sequence to evaluate the sums.

$1 + \frac{1}{2} + \frac{1}{4} + \ldots + \frac{1}{2^n}$, where n is a positive integer.

= 2-1/2^n

The correct answer is: 2 - 1 / 2^n

Your answer is correct.
Marks for this submission: 1.00/1.00.

Finish review

Prompt

Task
Create a function called `sum_of_two()` that:
- Takes two integers, `num1` and `num2`, as parameters.
- Returns the sum of `num1` and `num2`.

Example 1
Input:
```
sum_of_two(3, 5)
```
Output:
```
8
```

Example 2
Input:
```
sum_of_two(-2, 10)
```
Output:
```
8
```

Example 3
Input:
```
sum_of_two(0, 0)
```
Output:
```
0
```

Write your code here:
```
def sum_of_two(num1, num2):
    return num1 + num2
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:08:37

Create a function called `calculate_bmi()` that:
- Takes two parameters: `weight_kg` (weight in kilograms) and `height_m` (height in meters).
- Calculates the BMI using the formula: BMI = weight_kg / (height_m * height_m).
- Returns the BMI value rounded to 2 decimal places.

Example 1
Input:
```
calculate_bmi(70, 1.75)
```
Output:
```
22.86
```

Example 2
Input:
```
calculate_bmi(90, 1.80)
```
Output:
```
27.78
```

Example 3
Input:
```
calculate_bmi(50, 1.60)
```
Output:
```
19.53
```

Write your code here:
```
def calculate_bmi(weight_kg, height_m):
    bmi = weight_kg / (height_m * height_m)
    return round(bmi, 2)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:09:10

Create a function called `is_leap_year()` that:
- Takes an integer `year` as a parameter.
- Returns `True` if the year is a leap year, and `False` otherwise.
- A leap year is divisible by 4, but not by 100 unless it is also divisible by 400.

Example 1
Input:
```
is_leap_year(2020)
```
Output:
```
True
```

Example 2
Input:
```
is_leap_year(1900)
```
Output:
```
False
```

Example 3
Input:
```
is_leap_year(2000)
```
Output:
```
True
```

Write your code here:
```
def is_leap_year(year):
    if year % 4 == 0:
        if year % 100 == 0:
            if year % 400 == 0:
                return True
            else:
                return False
        else:
            return True
    else:
        return False
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:09:39

Create a function called `count_vowels()` that:
- Takes a string `text` as a parameter.
- Returns the number of vowels (a, e, i, o, u) in the string, regardless of case.

Example 1
Input:
```
count_vowels("Hello World")
```
Output:
```
3
```

Example 2
Input:
```
count_vowels("Python Programming")
```
Output:
```
4
```

Example 3
Input:
```
count_vowels("AEIOU")
```
Output:
```
5
```

Write your code here:
```
def count_vowels(text):
    vowels = "aeiouAEIOU"
    count = 0
    for char in text:
        if char in vowels:
            count += 1
    return count
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:10:08

Create a function called `reverse_string()` that:
- Takes a string `text` as a parameter.
- Returns the reversed version of the string.

Example 1
Input:
```
reverse_string("Hello")
```
Output:
```
olleH
```

Example 2
Input:
```
reverse_string("Python")
```
Output:
```
nohtyP
```

Example 3
Input:
```
reverse_string("12345")
```
Output:
```
54321
```

Write your code here:
```
def reverse_string(text):
    return text[::-1]
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:10:36

Create a function called `is_palindrome()` that:
- Takes a string `text` as a parameter.
- Returns `True` if the string is a palindrome (reads the same forwards and backwards), and `False` otherwise.
- Ignore case and spaces when checking for palindromes.

Example 1
Input:
```
is_palindrome("racecar")
```
Output:
```
True
```

Example 2
Input:
```
is_palindrome("hello")
```
Output:
```
False
```

Example 3
Input:
```
is_palindrome("A man a plan a canal Panama")
```
Output:
```
True
```

Write your code here:
```
def is_palindrome(text):
    text = text.lower().replace(" ", "")
    return text == text[::-1]
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:11:05

Create a function called `find_max()` that:
- Takes a list of numbers `numbers` as a parameter.
- Returns the largest number in the list.

Example 1
Input:
```
find_max([1, 2, 3, 4, 5])
```
Output:
```
5
```

Example 2
Input:
```
find_max([-10, -5, -1])
```
Output:
```
-1
```

Example 3
Input:
```
find_max([100, 200, 300])
```
Output:
```
300
```

Write your code here:
```
def find_max(numbers):
    return max(numbers)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:11:34

Create a function called `calculate_average()` that:
- Takes a list of numbers `numbers` as a parameter.
- Returns the average of the numbers in the list.

Example 1
Input:
```
calculate_average([1, 2, 3, 4, 5])
```
Output:
```
3.0
```

Example 2
Input:
```
calculate_average([10, 20, 30])
```
Output:
```
20.0
```

Example 3
Input:
```
calculate_average([-5, 0, 5])
```
Output:
```
0.0
```

Write your code here:
```
def calculate_average(numbers):
    return sum(numbers) / len(numbers)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:12:03

Create a function called `count_words()` that:
- Takes a string `text` as a parameter.
- Returns the number of words in the string.

Example 1
Input:
```
count_words("Hello World")
```
Output:
```
2
```

Example 2
Input:
```
count_words("Python Programming is fun")
```
Output:
```
4
```

Example 3
Input:
```
count_words("")
```
Output:
```
0
```

Write your code here:
```
def count_words(text):
    return len(text.split())
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:12:32

Create a function called `is_prime()` that:
- Takes an integer `num` as a parameter.
- Returns `True` if the number is prime, and `False` otherwise.
- A prime number is a number greater than 1 that has no divisors other than 1 and itself.

Example 1
Input:
```
is_prime(7)
```
Output:
```
True
```

Example 2
Input:
```
is_prime(10)
```
Output:
```
False
```

Example 3
Input:
```
is_prime(2)
```
Output:
```
True
```

Write your code here:
```
def is_prime(num):
    if num <= 1:
        return False
    for i in range(2, num):
        if num % i == 0:
            return False
    return True
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:13:01

Create a function called `factorial()` that:
- Takes an integer `n` as a parameter.
- Returns the factorial of `n`.
- The factorial of a number is the product of all positive integers less than or equal to that number.

Example 1
Input:
```
factorial(5)
```
Output:
```
120
```

Example 2
Input:
```
factorial(0)
```
Output:
```
1
```

Example 3
Input:
```
factorial(3)
```
Output:
```
6
```

Write your code here:
```
def factorial(n):
    if n == 0:
        return 1
    else:
        return n * factorial(n-1)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:13:30

Create a function called `fibonacci()` that:
- Takes an integer `n` as a parameter.
- Returns the nth number in the Fibonacci sequence.
- The Fibonacci sequence is a series of numbers where each number is the sum of the two preceding ones, usually starting with 0 and 1.

Example 1
Input:
```
fibonacci(0)
```
Output:
```
0
```

Example 2
Input:
```
fibonacci(1)
```
Output:
```
1
```

Example 3
Input:
```
fibonacci(6)
```
Output:
```
8
```

Write your code here:
```
def fibonacci(n):
    if n == 0:
        return 0
    elif n == 1:
        return 1
    else:
        return fibonacci(n-1) + fibonacci(n-2)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:14:00

Create a function called `is_anagram()` that:
- Takes two strings `str1` and `str2` as parameters.
- Returns `True` if the strings are anagrams of each other, and `False` otherwise.
- Anagrams are words or phrases that contain the same characters in the same quantity, but in a different order.

Example 1
Input:
```
is_anagram("listen", "silent")
```
Output:
```
True
```

Example 2
Input:
```
is_anagram("hello", "world")
```
Output:
```
False
```

Example 3
Input:
```
is_anagram("Astronomer", "Moon starer")
```
Output:
```
True
```

Write your code here:
```
def is_anagram(str1, str2):
    str1 = str1.lower().replace(" ", "")
    str2 = str2.lower().replace(" ", "")
    return sorted(str1) == sorted(str2)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:14:29

Create a function called `find_common_elements()` that:
- Takes two lists `list1` and `list2` as parameters.
- Returns a list containing the common elements between `list1` and `list2`.
- The order of elements in the returned list does not matter.

Example 1
Input:
```
find_common_elements([1, 2, 3, 4], [3, 4, 5, 6])
```
Output:
```
[3, 4]
```

Example 2
Input:
```
find_common_elements(['a', 'b', 'c'], ['c', 'd', 'e'])
```
Output:
```
['c']
```

Example 3
Input:
```
find_common_elements([1, 2, 3], [4, 5, 6])
```
Output:
```
[]
```

Write your code here:
```
def find_common_elements(list1, list2):
    return list(set(list1) & set(list2))
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:14:58

Create a function called `remove_duplicates()` that:
- Takes a list `lst` as a parameter.
- Returns a new list with duplicate elements removed, preserving the original order of elements.

Example 1
Input:
```
remove_duplicates([1, 2, 3, 2, 4, 1])
```
Output:
```
[1, 2, 3, 4]
```

Example 2
Input:
```
remove_duplicates(['a', 'b', 'c', 'a', 'b'])
```
Output:
```
['a', 'b', 'c']
```

Example 3
Input:
```
remove_duplicates([1, 1, 1, 1])
```
Output:
```
[1]
```

Write your code here:
```
def remove_duplicates(lst):
    return list(dict.fromkeys(lst))
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:15:27

Create a function called `is_sorted()` that:
- Takes a list `lst` as a parameter.
- Returns `True` if the list is sorted in ascending order, and `False` otherwise.

Example 1
Input:
```
is_sorted([1, 2, 3, 4, 5])
```
Output:
```
True
```

Example 2
Input:
```
is_sorted([5, 4, 3, 2, 1])
```
Output:
```
False
```

Example 3
Input:
```
is_sorted([1, 1, 2, 2, 3])
```
Output:
```
True
```

Write your code here:
```
def is_sorted(lst):
    return lst == sorted(lst)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:15:56

Create a function called `find_second_largest()` that:
- Takes a list of numbers `numbers` as a parameter.
- Returns the second largest number in the list.
- If the list has fewer than two unique numbers, return `None`.

Example 1
Input:
```
find_second_largest([1, 2, 3, 4, 5])
```
Output:
```
4
```

Example 2
Input:
```
find_second_largest([10, 10, 9])
```
Output:
```
9
```

Example 3
Input:
```
find_second_largest([5, 5, 5])
```
Output:
```
None
```

Write your code here:
```
def find_second_largest(numbers):
    unique_numbers = list(set(numbers))
    if len(unique_numbers) < 2:
        return None
    unique_numbers.sort()
    return unique_numbers[-2]
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:16:25

Create a function called `count_occurrences()` that:
- Takes a list `lst` and an element `element` as parameters.
- Returns the number of occurrences of `element` in `lst`.

Example 1
Input:
```
count_occurrences([1, 2, 3, 2, 4, 2], 2)
```
Output:
```
3
```

Example 2
Input:
```
count_occurrences(['a', 'b', 'c', 'a'], 'a')
```
Output:
```
2
```

Example 3
Input:
```
count_occurrences([1, 2, 3], 4)
```
Output:
```
0
```

Write your code here:
```
def count_occurrences(lst, element):
    return lst.count(element)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:16:54

Create a function called `is_perfect_square()` that:
- Takes an integer `num` as a parameter.
- Returns `True` if the number is a perfect square, and `False` otherwise.
- A perfect square is an integer that is the square of an integer.

Example 1
Input:
```
is_perfect_square(16)
```
Output:
```
True
```

Example 2
Input:
```
is_perfect_square(20)
```
Output:
```
False
```

Example 3
Input:
```
is_perfect_square(0)
```
Output:
```
True
```

Write your code here:
```
def is_perfect_square(num):
    if num < 0:
        return False
    sqrt = int(num ** 0.5)
    return sqrt * sqrt == num
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:17:23

Create a function called `find_missing_number()` that:
- Takes a list of numbers `numbers` as a parameter.
- The list contains all numbers from 1 to n, except one.
- Returns the missing number.

Example 1
Input:
```
find_missing_number([1, 2, 3, 5])
```
Output:
```
4
```

Example 2
Input:
```
find_missing_number([2, 3, 4, 5])
```
Output:
```
1
```

Example 3
Input:
```
find_missing_number([1, 2, 3, 4])
```
Output:
```
5
```

Write your code here:
```
def find_missing_number(numbers):
    n = len(numbers) + 1
    total = n * (n + 1) // 2
    return total - sum(numbers)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:17:52

Create a function called `is_valid_parentheses()` that:
- Takes a string `s` as a parameter.
- Returns `True` if the parentheses in the string are valid, and `False` otherwise.
- Valid parentheses mean that every opening parenthesis has a corresponding closing parenthesis in the correct order.

Example 1
Input:
```
is_valid_parentheses("()")
```
Output:
```
True
```

Example 2
Input:
```
is_valid_parentheses("(()")
```
Output:
```
False
```

Example 3
Input:
```
is_valid_parentheses("()()")
```
Output:
```
True
```

Write your code here:
```
def is_valid_parentheses(s):
    stack = []
    for char in s:
        if char == '(':
            stack.append(char)
        elif char == ')':
            if not stack:
                return False
            stack.pop()
    return not stack
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:18:21

Create a function called `find_longest_word()` that:
- Takes a string `sentence` as a parameter.
- Returns the longest word in the sentence.
- If there are multiple words with the same length, return the first one.

Example 1
Input:
```
find_longest_word("The quick brown fox")
```
Output:
```
quick
```

Example 2
Input:
```
find_longest_word("Hello World")
```
Output:
```
Hello
```

Example 3
Input:
```
find_longest_word("I am a student")
```
Output:
```
student
```

Write your code here:
```
def find_longest_word(sentence):
    words = sentence.split()
    longest = max(words, key=len)
    return longest
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:18:50

Create a function called `is_pangram()` that:
- Takes a string `sentence` as a parameter.
- Returns `True` if the sentence is a pangram, and `False` otherwise.
- A pangram is a sentence that contains every letter of the alphabet at least once.

Example 1
Input:
```
is_pangram("The quick brown fox jumps over the lazy dog")
```
Output:
```
True
```

Example 2
Input:
```
is_pangram("Hello World")
```
Output:
```
False
```

Example 3
Input:
```
is_pangram("Pack my box with five dozen liquor jugs")
```
Output:
```
True
```

Write your code here:
```
def is_pangram(sentence):
    alphabet = "abcdefghijklmnopqrstuvwxyz"
    sentence = sentence.lower()
    for char in alphabet:
        if char not in sentence:
            return False
    return True
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:19:19

Create a function called `find_gcd()` that:
- Takes two integers `num1` and `num2` as parameters.
- Returns the greatest common divisor (GCD) of `num1` and `num2`.
- The GCD is the largest positive integer that divides both numbers without leaving a remainder.

Example 1
Input:
```
find_gcd(12, 18)
```
Output:
```
6
```

Example 2
Input:
```
find_gcd(7, 13)
```
Output:
```
1
```

Example 3
Input:
```
find_gcd(100, 75)
```
Output:
```
25
```

Write your code here:
```
def find_gcd(num1, num2):
    while num2:
        num1, num2 = num2, num1 % num2
    return num1
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:19:48

Create a function called `is_armstrong_number()` that:
- Takes an integer `num` as a parameter.
- Returns `True` if the number is an Armstrong number, and `False` otherwise.
- An Armstrong number is a number that is equal to the sum of its own digits each raised to the power of the number of digits.

Example 1
Input:
```
is_armstrong_number(153)
```
Output:
```
True
```

Example 2
Input:
```
is_armstrong_number(10)
```
Output:
```
False
```

Example 3
Input:
```
is_armstrong_number(9474)
```
Output:
```
True
```

Write your code here:
```
def is_armstrong_number(num):
    num_str = str(num)
    num_digits = len(num_str)
    sum = 0
    for digit in num_str:
        sum += int(digit) ** num_digits
    return sum == num
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:20:17

Create a function called `find_missing_letter()` that:
- Takes a list of characters `chars` as a parameter.
- The list contains all letters of the alphabet in order, except one.
- Returns the missing letter.

Example 1
Input:
```
find_missing_letter(['a', 'b', 'c', 'd', 'f'])
```
Output:
```
e
```

Example 2
Input:
```
find_missing_letter(['o', 'q', 'r', 's', 't'])
```
Output:
```
p
```

Example 3
Input:
```
find_missing_letter(['u', 'v', 'w', 'x', 'z'])
```
Output:
```
y
```

Write your code here:
```
def find_missing_letter(chars):
    for i in range(len(chars) - 1):
        if ord(chars[i+1]) - ord(chars[i]) > 1:
            return chr(ord(chars[i]) + 1)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:20:46

Create a function called `is_valid_ip()` that:
- Takes a string `ip` as a parameter.
- Returns `True` if the string is a valid IPv4 address, and `False` otherwise.
- A valid IPv4 address consists of four numbers separated by periods, where each number is between 0 and 255.

Example 1
Input:
```
is_valid_ip("192.168.0.1")
```
Output:
```
True
```

Example 2
Input:
```
is_valid_ip("256.0.0.1")
```
Output:
```
False
```

Example 3
Input:
```
is_valid_ip("192.168.0")
```
Output:
```
False
```

Write your code here:
```
def is_valid_ip(ip):
    parts = ip.split(".")
    if len(parts) != 4:
        return False
    for part in parts:
        if not part.isdigit():
            return False
        num = int(part)
        if num < 0 or num > 255:
            return False
    return True
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:21:15

Create a function called `find_median()` that:
- Takes a list of numbers `numbers` as a parameter.
- Returns the median of the numbers in the list.
- If the list has an even number of elements, return the average of the two middle numbers.

Example 1
Input:
```
find_median([1, 2, 3, 4, 5])
```
Output:
```
3
```

Example 2
Input:
```
find_median([1, 2, 3, 4])
```
Output:
```
2.5
```

Example 3
Input:
```
find_median([-5, 0, 5])
```
Output:
```
0
```

Write your code here:
```
def find_median(numbers):
    numbers.sort()
    n = len(numbers)
    if n % 2 == 0:
        return (numbers[n//2 - 1] + numbers[n//2]) / 2
    else:
        return numbers[n//2]
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:21:44

Create a function called `is_valid_email()` that:
- Takes a string `email` as a parameter.
- Returns `True` if the string is a valid email address, and `False` otherwise.
- A valid email address has a username, an "@" symbol, and a domain name.

Example 1
Input:
```
is_valid_email("user@example.com")
```
Output:
```
True
```

Example 2
Input:
```
is_valid_email("invalid-email")
```
Output:
```
False
```

Example 3
Input:
```
is_valid_email("user@domain")
```
Output:
```
False
```

Write your code here:
```
def is_valid_email(email):
    parts = email.split("@")
    if len(parts) != 2:
        return False
    username, domain = parts
    if not username or not domain:
        return False
    if "." not in domain:
        return False
    return True
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:22:13

Create a function called `find_mode()` that:
- Takes a list of numbers `numbers` as a parameter.
- Returns the mode of the numbers in the list.
- If there are multiple modes, return the smallest one.

Example 1
Input:
```
find_mode([1, 2, 3, 2, 4])
```
Output:
```
2
```

Example 2
Input:
```
find_mode([-1, -1, 0, 0, 1])
```
Output:
```
-1
```

Example 3
Input:
```
find_mode([5, 5, 5, 5])
```
Output:
```
5
```

Write your code here:
```
def find_mode(numbers):
    from collections import Counter
    counts = Counter(numbers)
    max_count = max(counts.values())
    modes = [num for num, count in counts.items() if count == max_count]
    return min(modes)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:22:42

Create a function called `is_valid_credit_card()` that:
- Takes a string `card_number` as a parameter.
- Returns `True` if the string is a valid credit card number, and `False` otherwise.
- A valid credit card number has 16 digits and passes the Luhn algorithm.

Example 1
Input:
```
is_valid_credit_card("4532015112830366")
```
Output:
```
True
```

Example 2
Input:
```
is_valid_credit_card("1234567890123456")
```
Output:
```
False
```

Example 3
Input:
```
is_valid_credit_card("6011514433546201")
```
Output:
```
True
```

Write your code here:
```
def is_valid_credit_card(card_number):
    if len(card_number) != 16 or not card_number.isdigit():
        return False
    total = 0
    for i, digit in enumerate(card_number):
        num = int(digit)
        if i % 2 == 0:
            num *= 2
            if num > 9:
                num -= 9
        total += num
    return total % 10 == 0
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:23:11

Create a function called `find_missing_number()` that:
- Takes a list of numbers `numbers` as a parameter.
- The list contains all numbers from 1 to n, except one.
- Returns the missing number.

Example 1
Input:
```
find_missing_number([1, 2, 3, 5])
```
Output:
```
4
```

Example 2
Input:
```
find_missing_number([2, 3, 4, 5])
```
Output:
```
1
```

Example 3
Input:
```
find_missing_number([1, 2, 3, 4])
```
Output:
```
5
```

Write your code here:
```
def find_missing_number(numbers):
    n = len(numbers) + 1
    total = n * (n + 1) // 2
    return total - sum(numbers)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:23:40

Create a function called `is_valid_parentheses()` that:
- Takes a string `s` as a parameter.
- Returns `True` if the parentheses in the string are valid, and `False` otherwise.
- Valid parentheses mean that every opening parenthesis has a corresponding closing parenthesis in the correct order.

Example 1
Input:
```
is_valid_parentheses("()")
```
Output:
```
True
```

Example 2
Input:
```
is_valid_parentheses("(()")
```
Output:
```
False
```

Example 3
Input:
```
is_valid_parentheses("()()")
```
Output:
```
True
```

Write your code here:
```
def is_valid_parentheses(s):
    stack = []
    for char in s:
        if char == '(':
            stack.append(char)
        elif char == ')':
            if not stack:
                return False
            stack.pop()
    return not stack
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:24:09

Create a function called `find_longest_word()` that:
- Takes a string `sentence` as a parameter.
- Returns the longest word in the sentence.
- If there are multiple words with the same length, return the first one.

Example 1
Input:
```
find_longest_word("The quick brown fox")
```
Output:
```
quick
```

Example 2
Input:
```
find_longest_word("Hello World")
```
Output:
```
Hello
```

Example 3
Input:
```
find_longest_word("I am a student")
```
Output:
```
student
```

Write your code here:
```
def find_longest_word(sentence):
    words = sentence.split()
    longest = max(words, key=len)
    return longest
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:24:38

Create a function called `is_pangram()` that:
- Takes a string `sentence` as a parameter.
- Returns `True` if the sentence is a pangram, and `False` otherwise.
- A pangram is a sentence that contains every letter of the alphabet at least once.

Example 1
Input:
```
is_pangram("The quick brown fox jumps over the lazy dog")
```
Output:
```
True
```

Example 2
Input:
```
is_pangram("Hello World")
```
Output:
```
False
```

Example 3
Input:
```
is_pangram("Pack my box with five dozen liquor jugs")
```
Output:
```
True
```

Write your code here:
```
def is_pangram(sentence):
    alphabet = "abcdefghijklmnopqrstuvwxyz"
    sentence = sentence.lower()
    for char in alphabet:
        if char not in sentence:
            return False
    return True
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:25:07

Create a function called `find_gcd()` that:
- Takes two integers `num1` and `num2` as parameters.
- Returns the greatest common divisor (GCD) of `num1` and `num2`.
- The GCD is the largest positive integer that divides both numbers without leaving a remainder.

Example 1
Input:
```
find_gcd(12, 18)
```
Output:
```
6
```

Example 2
Input:
```
find_gcd(7, 13)
```
Output:
```
1
```

Example 3
Input:
```
find_gcd(100, 75)
```
Output:
```
25
```

Write your code here:
```
def find_gcd(num1, num2):
    while num2:
        num1, num2 = num2, num1 % num2
    return num1
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:25:36

Create a function called `is_armstrong_number()` that:
- Takes an integer `num` as a parameter.
- Returns `True` if the number is an Armstrong number, and `False` otherwise.
- An Armstrong number is a number that is equal to the sum of its own digits each raised to the power of the number of digits.

Example 1
Input:
```
is_armstrong_number(153)
```
Output:
```
True
```

Example 2
Input:
```
is_armstrong_number(10)
```
Output:
```
False
```

Example 3
Input:
```
is_armstrong_number(9474)
```
Output:
```
True
```

Write your code here:
```
def is_armstrong_number(num):
    num_str = str(num)
    num_digits = len(num_str)
    sum = 0
    for digit in num_str:
        sum += int(digit) ** num_digits
    return sum == num
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:26:05

Create a function called `find_missing_letter()` that:
- Takes a list of characters `chars` as a parameter.
- The list contains all letters of the alphabet in order, except one.
- Returns the missing letter.

Example 1
Input:
```
find_missing_letter(['a', 'b', 'c', 'd', 'f'])
```
Output:
```
e
```

Example 2
Input:
```
find_missing_letter(['o', 'q', 'r', 's', 't'])
```
Output:
```
p
```

Example 3
Input:
```
find_missing_letter(['u', 'v', 'w', 'x', 'z'])
```
Output:
```
y
```

Write your code here:
```
def find_missing_letter(chars):
    for i in range(len(chars) - 1):
        if ord(chars[i+1]) - ord(chars[i]) > 1:
            return chr(ord(chars[i]) + 1)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:26:34

Create a function called `is_valid_ip()` that:
- Takes a string `ip` as a parameter.
- Returns `True` if the string is a valid IPv4 address, and `False` otherwise.
- A valid IPv4 address consists of four numbers separated by periods, where each number is between 0 and 255.

Example 1
Input:
```
is_valid_ip("192.168.0.1")
```
Output:
```
True
```

Example 2
Input:
```
is_valid_ip("256.0.0.1")
```
Output:
```
False
```

Example 3
Input:
```
is_valid_ip("192.168.0")
```
Output:
```
False
```

Write your code here:
```
def is_valid_ip(ip):
    parts = ip.split(".")
    if len(parts) != 4:
        return False
    for part in parts:
        if not part.isdigit():
            return False
        num = int(part)
        if num < 0 or num > 255:
            return False
    return True
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:27:03

Create a function called `find_median()` that:
- Takes a list of numbers `numbers` as a parameter.
- Returns the median of the numbers in the list.
- If the list has an even number of elements, return the average of the two middle numbers.

Example 1
Input:
```
find_median([1, 2, 3, 4, 5])
```
Output:
```
3
```

Example 2
Input:
```
find_median([1, 2, 3, 4])
```
Output:
```
2.5
```

Example 3
Input:
```
find_median([-5, 0, 5])
```
Output:
```
0
```

Write your code here:
```
def find_median(numbers):
    numbers.sort()
    n = len(numbers)
    if n % 2 == 0:
        return (numbers[n//2 - 1] + numbers[n//2]) / 2
    else:
        return numbers[n//2]
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:27:32

Create a function called `is_valid_email()` that:
- Takes a string `email` as a parameter.
- Returns `True` if the string is a valid email address, and `False` otherwise.
- A valid email address has a username, an "@" symbol, and a domain name.

Example 1
Input:
```
is_valid_email("user@example.com")
```
Output:
```
True
```

Example 2
Input:
```
is_valid_email("invalid-email")
```
Output:
```
False
```

Example 3
Input:
```
is_valid_email("user@domain")
```
Output:
```
False
```

Write your code here:
```
def is_valid_email(email):
    parts = email.split("@")
    if len(parts) != 2:
        return False
    username, domain = parts
    if not username or not domain:
        return False
    if "." not in domain:
        return False
    return True
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:28:01

Create a function called `find_mode()` that:
- Takes a list of numbers `numbers` as a parameter.
- Returns the mode of the numbers in the list.
- If there are multiple modes, return the smallest one.

Example 1
Input:
```
find_mode([1, 2, 3, 2, 4])
```
Output:
```
2
```

Example 2
Input:
```
find_mode([-1, -1, 0, 0, 1])
```
Output:
```
-1
```

Example 3
Input:
```
find_mode([5, 5, 5, 5])
```
Output:
```
5
```

Write your code here:
```
def find_mode(numbers):
    from collections import Counter
    counts = Counter(numbers)
    max_count = max(counts.values())
    modes = [num for num, count in counts.items() if count == max_count]
    return min(modes)
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:28:30

Create a function called `is_valid_credit_card()` that:
- Takes a string `card_number` as a parameter.
- Returns `True` if the string is a valid credit card number, and `False` otherwise.
- A valid credit card number has 16 digits and passes the Luhn algorithm.

Example 1
Input:
```
is_valid_credit_card("4532015112830366")
```
Output:
```
True
```

Example 2
Input:
```
is_valid_credit_card("1234567890123456")
```
Output:
```
False
```

Example 3
Input:
```
is_valid_credit_card("6011514433546201")
```
Output:
```
True
```

Write your code here:
```
def is_valid_credit_card(card_number):
    if len(card_number) != 16 or not card_number.isdigit():
        return False
    total = 0
    for i, digit in enumerate(card_number):
        num = int(digit)
        if i % 2 == 0:
            num *= 2
            if num > 9:
                num -= 9
        total += num
    return total % 10 == 0
```

Test Results
All test cases passed. 100

Submitted 2024-10-11 at 15:28:59