Fetal Doppler



Trend display

Large color LCD enables trend of FHR on screen.

Acoustic Stimulator

Stimulate sleeping fetus to acquire more accurate FHR. High(100Hz) / Low(75Hz)



220L

Interchangeable probe

2MHz or 3MHz probe can be used on one main unit

Recharging kit (Optional)

Just plug-in to microUSB cable recharge the battery and no need to change disposable battery.

BISTOS Fetal Dopplers and Vascular Doppler Technical Specification

Category	Fetal Doppler BT-200			
Model				
Order code	2005	200L	200C	
Frequency (MHz)	2	2	2	
Detection Range (BPM)	50 - 240	50 - 240	50 - 240	
Audio Output (W)	1.2	1.2	1.2	
Headphone Output	•	•	•	
Interchangeable probe				
Waterproof probe	IP X 7	IP X 7	IP X 7	
Display type		Mono	Color	
Trend display				
Trend saving				
Patient ID				
Event Mark				
Quick Guide				
Multi Language				
Acoustic Stimulator				
Adult Heart Rate (BPM)				
Body Fat Measurement				
Battery Type	2 X 1.5V AA	2 X 1.5V AA	2 X 1.5V AA	
Battery Run Time (h)	5	5	5	
Rechargeable Battery	0	0	0	
BCM-200 Software	•	•	•	
BCM-350 Central Monitoring Software				
Weight (g)	190	190	190	
Dimensions (mm) Main Unit (HxWxD)	128 X 75 X 26			
Carrying Pouch	•	•	•	
Opional Accessories				
Warranty (Main unit)	1year	1year	1year	

	Vascular Doppl			
BT-200	BT-220		BT-250	BT-200
200T	220L	220C	250	200V
3	2 or 3	2 or 3	2	4, 5, 8
50 - 240	50 - 240	30 - 240	30 - 240	50 - 240
1.2	1.2	1.2	5	1.2
•	•	•	•	•
	•	•	•	•
IP X 7	IP X 7	IP X 7	IP X 7	IP X 2
Mono	Mono	2.4" Color	3.2 " Color	Mono
		•	•	
			4 Hours	
			•	
			•	
			•	
			•	
	•	•		
		40-200		
		•		
2 X 1.5V AA	2 X 1.5V AA	2 X 1.5V AA	3.7V Li-ion	2 X 1.5V AA
5	5	4	5	5
0	0	0	•	0
•	•	•	•	
			•	
190	190	200	1,100	190
128 X 75 X 26	132 X 66 X 27		90 X 250 X 118	128 X 75 X 26
•	•	•	0	•
	Rechargeable kit	Rechargeable kit	Clamp	
1year	1year	1year	2year	1year