

MFE 40 (604040510) WALL CHASER

(220-240 V / 50 - 60 HZ); PLASTIC CARRY CASE

Order no.: 604040510 | EAN: 4007430327598



Compare Products

Add to wish list

Data Sheet (.pdf)

Images (.zip)

Adjustable cutting depth: **10 - 40 mm // 3/8 - 1 9/16 "**

Possible groove widths: **9 / 15.5 / 22 / 28.5 / 35 mm / 3/8 / 5/8 / 7/8 / 1 1/8 / 1 3/8 "**

Cutting disc Ø: **125 mm / 5 "**

Rated input power: **1900 W**

Weight (without power cable): **4.6 kg / 10.1 lbs**



[MANUAL >](#)

[SPARE-PARTS LIST >](#)



GENERAL

ABOUT US

Data privacy

Company

Imprint

Career

Legal notes

Contact

Social Media

TOP CATEGORIES ~

TOP SO

metabo



MTE 45 8.0Ah



metabo

- Ideal for electric installations to lay cables and empty pipes under plaster with cutting depths up to 40 mm
- Maximum work progress by means of powerful motor, constant speed and two-speed high-performance gear
- Robust aluminium die-cast hood with rubber rolls and optimal handle position for comfortable guiding of the machine
- Pushing cut for optimal view of the marking line
- Channel width and cutting depth can be set
- Metabo Marathon motor with patented dust protection for long service life
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- Electronic soft start and restart protection for safe working
- LED signal informs about overload or active restart protection
- Clean, low-dust working by means of connecting a Metabo all-purpose vacuum cleaner (certified with ASR 35 MACP)
- Suitable for slitting grooves up to a width of 30 mm without centre in one workstep (with special accessories)
- Also suitable for cutting with only one diamond cutting disc
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the disc stop unexpectedly

The machine shown may differ in equipment and technical details depending on the configuration. Kindly pay attention to delivery scope and product description. Accessories included only if listed in the delivery scope.

Characteristics

Adjustable cutting depth	10 - 40 mm // 3/8 - 1 9/16 "
Possible groove widths	9 / 15.5 / 22 / 28.5 / 35 mm / 3/8 / 5/8 / 7/8 / 1 1/8 / 1 3/8 "
Cutting disc Ø	125 mm / 5 "
Rated input power	1900 W
Output power	1120 W
No-load speed	5000 rpm
Speed at rated load	4200 rpm
Torque	6 Nm / 53 in-lbs
Weight (without power cable)	4.6 kg / 10.1 lbs
Cable length	4 m / 13 ft

Vibration

Vibration	5.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

Spacer Rings
Plastic carry case
Flange nut
Face pin wrench

You might also be interested in

