Compulsory Assignment 3

Machine Learning and Deep Learning (CDSCO2041C)

Group: MLS26_CA03 1

Student IDs: 185912, 161989, 160714 & 160363

Dataset: CIFAR-100 dataset

1.1 Data Preparation

In [1]:
```
# Setup and imports

import os
os.environ['KERAS_HOME'] = os.path.join(os.path.dirname(os.path.abs

import pickle
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns

from tensorflow import keras
from tensorflow.keras import layers, Model
from sklearn.model_selection import train_test_split
from sklearn.neighbors import KNeighborsClassifier
from sklearn.metrics import accuracy_score
```

```
2026-03-25 10:55:09.626117: I tensorflow/core/platform/cpu_feature_g
uard.cc:210] This TensorFlow binary is optimized to use available CP
U instructions in performance-critical operations.
To enable the following instructions: AVX2 FMA, in other operations,
rebuild TensorFlow with the appropriate compiler flags.
```

In [ ]:
```
# Design

FIG_W = 9
DPI = 140
PAL_10 = sns.color_palette("rocket_r", 10)
sns.set_theme(style="white", context="notebook")
plt.rcParams.update({"figure.dpi": DPI})

def clean_ax(ax):
    """Remove top and right spines."""
    ax.spines["top"].set_visible(False)
    ax.spines["right"].set_visible(False)
```

```
# Caption helpers
from IPython.display import display, HTML

def fig_caption(fig, number, text):
    """Show a numbered caption as a separate HTML row below the fig
    plt.show()
    display(HTML(
        f'<p style="text-align:center; font-style:italic; font-size
        f'margin-top:2px; margin-bottom:16px;">'
        f'Figure {number}: {text}</p>'
    ))

def table_style(styler, number, text):
    """Apply consistent table styling with a numbered caption above
    return (styler
        .set_caption(f"Table {number}: {text}")
        .set_table_styles([
            {"selector": "caption", "props": [
                ("font-weight", "bold"), ("font-size", "14px"),
                ("margin-bottom", "8px"), ("font-style", "italic")]
            {"selector": "th, td", "props": [
                ("border", "1px solid black"), ("padding", "6px 12p
                ("text-align", "center")]},
            {"selector": "table", "props": [
                ("border-collapse", "collapse"), ("margin", "0 auto
        ])
    )
```

This was the code used to download the dataset to the local `data` folder:

```
(x_train_full, y_train_full), (x_test, y_test) =
keras.datasets.cifar100.load_data()

print(f"Train images: {x_train_full.shape}")
print(f"Test images:  {x_test.shape}")
```

In [3]:

```
# Load CIFAR-100 from local data folder
data_dir = "data/datasets/cifar-100-python-target/cifar-100-python"

with open(f"{data_dir}/train", "rb") as f:
    train_batch = pickle.load(f, encoding="bytes")

with open(f"{data_dir}/test", "rb") as f:
    test_batch = pickle.load(f, encoding="bytes")

x_train_full = train_batch[b"data"].reshape(-1, 3, 32, 32).transpos
y_train_full = np.array(train_batch[b"fine_labels"])

x_test = test_batch[b"data"].reshape(-1, 3, 32, 32).transpose(0, 2,
y_test = np.array(test_batch[b"fine_labels"])

print(f"Train: {x_train_full.shape}  |  Test: {x_test.shape}")
print(f"Classes: {len(np.unique(y_train_full))}")
```

```
Train: (50000, 32, 32, 3)  |  Test: (10000, 32, 32, 3)
Classes: 100
```

After loading the now local dataset, we see that the dataset contains 50,000 training images and 10,000 test images, each labeled with one of 100 fine-grained classes. To create a validation set, we performed a stratified split of the training data, reserving 10% (5,000 images) for validation while keeping the class distribution proportional across all splits. With 100 classes, a random split risks underrepresenting some classes in smaller partitions.

In [4]:
```
# 90/10 stratified validation split
x_train, x_val, y_train, y_val = train_test_split(
    x_train_full, y_train_full,
    test_size=0.1,
    random_state=42,
    stratify=y_train_full
)

print(f"Train: {x_train.shape}  |  Val: {x_val.shape}")
```

```
Train: (45000, 32, 32, 3)  |  Val: (5000, 32, 32, 3)
```

In [5]:
```
# Per-channel mean and std computed on training set only
x_train_f = x_train.astype("float32")
x_val_f   = x_val.astype("float32")
x_test_f  = x_test.astype("float32")

channel_mean = x_train_f.mean(axis=(0, 1, 2))  # shape (3,)
channel_std  = x_train_f.std(axis=(0, 1, 2))   # shape (3,)

print(f"Channel means: {channel_mean}")
print(f"Channel stds:  {channel_std}")

# Normalize all splits using training statistics
x_train_norm = (x_train_f - channel_mean) / channel_std
x_val_norm   = (x_val_f   - channel_mean) / channel_std
x_test_norm  = (x_test_f  - channel_mean) / channel_std

# Flatten for Part 1.3 (pixel-based KNN classification)
x_train_flat = x_train_norm.reshape(x_train_norm.shape[0], -1)  # (
x_val_flat   = x_val_norm.reshape(x_val_norm.shape[0], -1)      # (
x_test_flat  = x_test_norm.reshape(x_test_norm.shape[0], -1)    # (

print(f"\nFlat shapes:    train {x_train_flat.shape}, val {x_val_fl
print(f"Spatial shapes: train {x_train_norm.shape}  (kept for Parts
```

```
Channel means: [129.29881  124.03771  112.348564]
Channel stds:  [68.1466  65.36531 70.38802]

Flat shapes:    train (45000, 3072), val (5000, 3072), test (10000,
3072)
Spatial shapes: train (45000, 32, 32, 3)  (kept for Parts 1.2 & 1.4)
```

The CIFAR-100 dataset was loaded from local pickle files, yielding 50,000 training images and 10,000 test images across 100 fine-grained classes. A

validation set was created by splitting 10% from the training data using stratified sampling, ensuring all 100 classes remain proportionally represented in both the 45,000-image training set and the 5,000-image validation set. Stratification keeps minority classes proportionally represented across both partitions.

Per-channel mean and standard deviation were computed on the training set only, then applied to normalize all three splits. Computing statistics solely on training data prevents information leakage from validation and test sets into the preprocessing step. Each normalized image was also flattened into a 3,072-dimensional vector for the pixel-based classification in Part 1.3, while the spatial 32x32x3 arrays were retained for the convolutional autoencoder (Part 1.2) and CNN (Part 1.4).

1.2 Autoencoder-Based Feature Learning

In [6]:
```
# Build encoder
# Two convolutional blocks: Conv2D -> ReLU -> MaxPooling each
# Then flatten and compress to a 256-dim latent vector

latent_dim = 256

encoder_input = keras.Input(shape=(32, 32, 3), name="encoder_input"

# Block 1: 32 filters, 3x3 kernel
x = layers.Conv2D(32, (3, 3), activation="relu", padding="same")(en
x = layers.MaxPooling2D((2, 2))(x)  # -> 16x16x32

# Block 2: 64 filters, 3x3 kernel
x = layers.Conv2D(64, (3, 3), activation="relu", padding="same")(x)
x = layers.MaxPooling2D((2, 2))(x)  # -> 8x8x64

# Flatten and compress to latent vector
x = layers.Flatten()(x)  # -> 4096
latent = layers.Dense(latent_dim, activation="relu", name="latent")

encoder = Model(encoder_input, latent, name="encoder")
encoder.summary()
```

Model: "encoder"

Layer (type)	Output Shape	
encoder_input (InputLayer)	(None, 32, 32, 3)	
conv2d (Conv2D)	(None, 32, 32, 32)	
max_pooling2d (MaxPooling2D)	(None, 16, 16, 32)	
conv2d_1 (Conv2D)	(None, 16, 16, 64)	
max_pooling2d_1 (MaxPooling2D)	(None, 8, 8, 64)	
flatten (Flatten)	(None, 4096)	
latent (Dense)	(None, 256)	

Total params: 1,068,224 (4.07 MB)

Trainable params: 1,068,224 (4.07 MB)

Non-trainable params: 0 (0.00 B)

In [7]:
```
# Build decoder (symmetric to encoder)
# Dense back to 8x8x64, then two blocks of UpSampling2D -> Conv2D m

decoder_input = keras.Input(shape=(latent_dim,), name="decoder_inpu

x = layers.Dense(8 * 8 * 64, activation="relu")(decoder_input)
x = layers.Reshape((8, 8, 64))(x)

# Block 1 (mirrors encoder block 2): upsample then conv
x = layers.UpSampling2D((2, 2))(x)  # -> 16x16x64
x = layers.Conv2D(64, (3, 3), activation="relu", padding="same")(x)

# Block 2 (mirrors encoder block 1): upsample then conv
x = layers.UpSampling2D((2, 2))(x)  # -> 32x32x64
x = layers.Conv2D(32, (3, 3), activation="relu", padding="same")(x)

# Output layer: reconstruct 3 channels, linear activation (data is
decoder_output = layers.Conv2D(3, (3, 3), activation="linear", padd

decoder = Model(decoder_input, decoder_output, name="decoder")
decoder.summary()
```

Model: "decoder"

Layer (type)	Output Shape	
decoder_input (InputLayer)	(None, 256)	
dense (Dense)	(None, 4096)	
reshape (Reshape)	(None, 8, 8, 64)	
up_sampling2d (UpSampling2D)	(None, 16, 16, 64)	
conv2d_2 (Conv2D)	(None, 16, 16, 64)	
up_sampling2d_1 (UpSampling2D)	(None, 32, 32, 64)	
conv2d_3 (Conv2D)	(None, 32, 32, 32)	
conv2d_4 (Conv2D)	(None, 32, 32, 3)	

Total params: 1,108,931 (4.23 MB)
Trainable params: 1,108,931 (4.23 MB)
Non-trainable params: 0 (0.00 B)

In [8]:
```
# Combine encoder + decoder into full autoencoder and train with MS

autoencoder_input = keras.Input(shape=(32, 32, 3))
encoded = encoder(autoencoder_input)
decoded = decoder(encoded)
autoencoder = Model(autoencoder_input, decoded, name="autoencoder")

autoencoder.compile(optimizer="adam", loss="mse")
autoencoder.summary()

# Train on normalized spatial images; target is the input itself
history = autoencoder.fit(
    x_train_norm, x_train_norm,
    epochs=20,
    batch_size=128,
    shuffle=True,
    validation_data=(x_val_norm, x_val_norm)
)
```

Model: "autoencoder"

Layer (type)	Output Shape	
input_layer (InputLayer)	(None, 32, 32, 3)	
encoder (Functional)	(None, 256)	
decoder (Functional)	(None, 32, 32, 3)	

Total params: 2,177,155 (8.31 MB)
Trainable params: 2,177,155 (8.31 MB)

```
Non-trainable params: 0 (0.00 B)
Epoch 1/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 145s 400ms/step - loss: 0.2567 - val_lo
ss: 0.1556
Epoch 2/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 144s 410ms/step - loss: 0.1308 - val_lo
ss: 0.1138
Epoch 3/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 152s 432ms/step - loss: 0.1078 - val_lo
ss: 0.1011
Epoch 4/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 147s 416ms/step - loss: 0.0963 - val_lo
ss: 0.0916
Epoch 5/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 105s 297ms/step - loss: 0.0893 - val_lo
ss: 0.0842
Epoch 6/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 101s 286ms/step - loss: 0.0843 - val_lo
ss: 0.0822
Epoch 7/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 102s 289ms/step - loss: 0.0802 - val_lo
ss: 0.0800
Epoch 8/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 102s 289ms/step - loss: 0.0771 - val_lo
ss: 0.0768
Epoch 9/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 102s 291ms/step - loss: 0.0749 - val_lo
ss: 0.0751
Epoch 10/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 105s 299ms/step - loss: 0.0727 - val_lo
ss: 0.0725
Epoch 11/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 99s 282ms/step - loss: 0.0707 - val_los
s: 0.0697
Epoch 12/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 101s 286ms/step - loss: 0.0696 - val_lo
ss: 0.0719
Epoch 13/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 106s 302ms/step - loss: 0.0681 - val_lo
ss: 0.0717
Epoch 14/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 97s 274ms/step - loss: 0.0672 - val_los
s: 0.0672
Epoch 15/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 109s 310ms/step - loss: 0.0661 - val_lo
ss: 0.0662
Epoch 16/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 105s 297ms/step - loss: 0.0650 - val_lo
ss: 0.0648
Epoch 17/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 108s 306ms/step - loss: 0.0644 - val_lo
ss: 0.0663
Epoch 18/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 104s 297ms/step - loss: 0.0633 - val_lo
ss: 0.0643
Epoch 19/20
```

```
352/352 ━━━━━━━━━━━━━━━━━━━━ 103s 294ms/step - loss: 0.0630 - val_lo
ss: 0.0682
Epoch 20/20
352/352 ━━━━━━━━━━━━━━━━━━━━ 104s 296ms/step - loss: 0.0624 - val_lo
ss: 0.0619
```

In [9]:

```
# Extract latent features using the trained encoder

x_train_latent = encoder.predict(x_train_norm)
x_val_latent   = encoder.predict(x_val_norm)
x_test_latent  = encoder.predict(x_test_norm)

print(f"Latent shapes: train {x_train_latent.shape}, val {x_val_lat
```

```
1407/1407 ━━━━━━━━━━━━━━━━━━━━ 19s 13ms/step
157/157 ━━━━━━━━━━━━━━━━━━━━ 2s 13ms/step
313/313 ━━━━━━━━━━━━━━━━━━━━ 4s 13ms/step
Latent shapes: train (45000, 256), val (5000, 256), test (10000, 25
6)
```

In [ ]:

```
# Plot reconstruction loss over epochs
fig, ax = plt.subplots(figsize=(FIG_W, 3.6), constrained_layout=Tru
ax.plot(history.history["loss"],     label="Train", color=PAL_10[7]
ax.plot(history.history["val_loss"], label="Val",   color=PAL_10[4]
ax.set_xlabel("Epoch")
ax.set_ylabel("MSE")
ax.legend(frameon=False)
clean_ax(ax)
fig_caption(fig, 1, "Autoencoder reconstruction loss (MSE) over tra

# Visualize a few reconstructions
n = 6
reconstructed = autoencoder.predict(x_test_norm[:n])

fig, axes = plt.subplots(2, n, figsize=(FIG_W * 1.4, 3), constraine
for i in range(n):
    orig  = (x_test_norm[i] * channel_std + channel_mean).astype("u
    recon = (reconstructed[i] * channel_std + channel_mean).clip(0,

    axes[0, i].imshow(orig)
    axes[0, i].set_title("Original", fontsize=9)
    axes[0, i].axis("off")

    axes[1, i].imshow(recon)
    axes[1, i].set_title("Reconstructed", fontsize=9)
    axes[1, i].axis("off")

fig_caption(fig, 2, "Autoencoder original vs reconstructed test ima
```



Figure 1: Autoencoder reconstruction loss (MSE) over training epochs

Figure 2: Autoencoder original vs reconstructed test images

A convolutional autoencoder was built following the encoder-decoder pattern from L11. The encoder consists of two convolutional blocks, each with a Conv2D layer (ReLU activation) followed by MaxPooling, progressively reducing spatial dimensions from 32x32 to 8x8 while increasing feature depth (3 -> 32 -> 64 channels). The resulting feature maps are flattened and compressed through a dense layer into a 256-dimensional latent vector.

The decoder mirrors the encoder symmetrically: a dense layer expands the latent vector back to 8x8x64, followed by two blocks of UpSampling2D and Conv2D that restore the original 32x32x3 spatial resolution. Linear activation is used in the output layer because the target images are z-score normalized (not bounded to [0, 1]).

A latent dimension of 256 was chosen as a balance between compression and information retention. The encoder compresses 4,096 features (8x8x64 flattened) down to 256, a ~16x reduction that forces the network to learn meaningful structure while keeping enough capacity for downstream classification across 100 classes.

The autoencoder was trained using MSE reconstruction loss and the Adam optimizer for 20 epochs. The trained encoder then extracts 256-dimensional latent feature vectors for the training, validation, and test sets, which will be used as an alternative feature representation for classification in Part 1.3.

1.3 Classification Using Pixel and Latent Features

In [11]:
```
# KNN on flattened pixel features (3072-dim from Part 1.1)
# Using k=5 as a reasonable default (odd number to avoid ties, not

knn_pixel = KNeighborsClassifier(n_neighbors=5)
knn_pixel.fit(x_train_flat, y_train.ravel())

pixel_val_acc  = accuracy_score(y_val.ravel(),  knn_pixel.predict(x
pixel_test_acc = accuracy_score(y_test.ravel(), knn_pixel.predict(x

print(f"KNN on pixel features  — Val accuracy: {pixel_val_acc:.4f},
```

```
KNN on pixel features  — Val accuracy: 0.1516, Test accuracy: 0.1477
```

In [12]:
```
# KNN on latent features (256-dim from Part 1.2)
# Same k=5 and default hyperparameters for fair comparison

knn_latent = KNeighborsClassifier(n_neighbors=5)
knn_latent.fit(x_train_latent, y_train.ravel())

latent_val_acc  = accuracy_score(y_val.ravel(),  knn_latent.predict
latent_test_acc = accuracy_score(y_test.ravel(), knn_latent.predict

print(f"KNN on latent features — Val accuracy: {latent_val_acc:.4f}
```

```
KNN on latent features — Val accuracy: 0.2034, Test accuracy: 0.1994
```

In [ ]:
```
# Compare results side by side
results = pd.DataFrame({
    "Feature Set": ["Pixel (3072-dim)", "Latent (256-dim)"],
    "Val Accuracy":  [pixel_val_acc,  latent_val_acc],
    "Test Accuracy": [pixel_test_acc, latent_test_acc]
})

# Styled table with caption above
styled = table_style(
    results.style.format({"Val Accuracy": "{:.4f}", "Test Accuracy"
    1, "KNN Classification Accuracy by Feature Set"
)
display(styled)

# Bar chart comparison
fig, ax = plt.subplots(figsize=(FIG_W, 4), constrained_layout=True)
x_pos = range(len(results))
width = 0.35
ax.bar([p - width/2 for p in x_pos], results["Val Accuracy"],  widt
       label="Validation", color=PAL_10[7], alpha=0.85)
ax.bar([p + width/2 for p in x_pos], results["Test Accuracy"], widt
       label="Test", color=PAL_10[4], alpha=0.85)
ax.set_xticks(list(x_pos))
ax.set_xticklabels(results["Feature Set"])
ax.set_ylabel("Accuracy")
```

```
ax.legend(frameon=False)
ax.set_ylim(0, max(results[["Val Accuracy", "Test Accuracy"]].max()
clean_ax(ax)
fig_caption(fig, 3, "KNN classification accuracy comparing pixel vs
```

Table 1: KNN Classification Accuracy by Feature Set

	Feature Set	Val Accuracy	Test Accuracy
0	Pixel (3072-dim)	0.1516	0.1477
1	Latent (256-dim)	0.2034	0.1994



Figure 3: KNN classification accuracy comparing pixel vs latent features

A K-Nearest Neighbors classifier (k=5) was trained on two feature representations to evaluate their utility for CIFAR-100 classification. The same classifier type and hyperparameters were used for both to ensure a fair comparison.

The first KNN was trained on the 3,072-dimensional flattened pixel vectors from Part 1.1. KNN in high-dimensional spaces suffers from the curse of dimensionality (L04), where distance metrics become less discriminative as dimensions increase. This is expected to limit performance on raw pixel features.

The second KNN was trained on the 256-dimensional latent features extracted by the autoencoder from Part 1.2. By compressing the images into a learned representation, the autoencoder reduces dimensionality by ~12x while retaining structural information, giving the distance-based KNN a more meaningful feature space to work in.

Both models were evaluated on the validation and test sets. The comparison demonstrates the value of learned feature representations over raw pixel data for classification tasks.

1.4 CNN Model

In [24]:
```
# Build CNN architecture for CIFAR-100 classification
# Two convolutional blocks (2 Conv2D each) + dense head
# Following the Conv2D -> MaxPooling pattern from L12

cnn = keras.Sequential([
    # Block 1: two Conv2D layers + MaxPooling
    layers.Conv2D(32, (3, 3), activation="relu", padding="same", in
    layers.Conv2D(32, (3, 3), activation="relu", padding="same"),
    layers.MaxPooling2D((2, 2)),                # -> 16x16x32
    layers.Dropout(0.25),

    # Block 2: two Conv2D layers + MaxPooling
    layers.Conv2D(64, (3, 3), activation="relu", padding="same"),
    layers.Conv2D(64, (3, 3), activation="relu", padding="same"),
    layers.MaxPooling2D((2, 2)),                # -> 8x8x64
    layers.Dropout(0.25),

    # Classification head
    layers.Flatten(),                           # -> 4096
    layers.Dense(256, activation="relu"),
    layers.Dropout(0.5),
    layers.Dense(100, activation="softmax")     # 100 classes
])
```

```
/Applications/anaconda3/envs/py312/lib/python3.12/site-packages/kera
s/src/layers/convolutional/base_conv.py:113: UserWarning: Do not pas
s an `input_shape`/`input_dim` argument to a layer. When using Seque
ntial models, prefer using an `Input(shape)` object as the first lay
er in the model instead.
  super().__init__(activity_regularizer=activity_regularizer, **kwar
gs)
```

In [25]:
```
# Compile and train CNN
cnn.compile(
    optimizer="adam",
    loss="sparse_categorical_crossentropy",
    metrics=["accuracy"]
)

cnn_history = cnn.fit(
    x_train_norm, y_train,
    epochs=30,
    batch_size=128,
    validation_data=(x_val_norm, y_val)
)
```

```
Epoch 1/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 74s 205ms/step - accuracy: 0.0758 - los
s: 4.1002 - val_accuracy: 0.1678 - val_loss: 3.5500
Epoch 2/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 74s 210ms/step - accuracy: 0.1697 - los
s: 3.4931 - val_accuracy: 0.2512 - val_loss: 3.0865
Epoch 3/30
```

```
352/352 ━━━━━━━━━━━━━━━━━━━━ 63s 178ms/step - accuracy: 0.2311 - los
s: 3.1439 - val_accuracy: 0.3022 - val_loss: 2.8098
Epoch 4/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 68s 193ms/step - accuracy: 0.2743 - los
s: 2.9044 - val_accuracy: 0.3422 - val_loss: 2.6066
Epoch 5/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 66s 188ms/step - accuracy: 0.3074 - los
s: 2.7304 - val_accuracy: 0.3702 - val_loss: 2.4581
Epoch 6/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 67s 189ms/step - accuracy: 0.3300 - los
s: 2.6073 - val_accuracy: 0.3846 - val_loss: 2.3964
Epoch 7/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 64s 183ms/step - accuracy: 0.3535 - los
s: 2.4953 - val_accuracy: 0.4062 - val_loss: 2.3170
Epoch 8/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 63s 179ms/step - accuracy: 0.3718 - los
s: 2.3957 - val_accuracy: 0.4072 - val_loss: 2.2813
Epoch 9/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 64s 181ms/step - accuracy: 0.3877 - los
s: 2.3239 - val_accuracy: 0.4180 - val_loss: 2.2126
Epoch 10/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 68s 192ms/step - accuracy: 0.4015 - los
s: 2.2490 - val_accuracy: 0.4282 - val_loss: 2.1865
Epoch 11/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 68s 193ms/step - accuracy: 0.4154 - los
s: 2.1843 - val_accuracy: 0.4282 - val_loss: 2.1733
Epoch 12/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 69s 196ms/step - accuracy: 0.4265 - los
s: 2.1265 - val_accuracy: 0.4294 - val_loss: 2.1705
Epoch 13/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 77s 220ms/step - accuracy: 0.4383 - los
s: 2.0707 - val_accuracy: 0.4398 - val_loss: 2.1257
Epoch 14/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 460s 1s/step - accuracy: 0.4508 - loss:
2.0243 - val_accuracy: 0.4510 - val_loss: 2.1096
Epoch 15/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 121s 343ms/step - accuracy: 0.4607 - lo
ss: 1.9751 - val_accuracy: 0.4530 - val_loss: 2.0903
Epoch 16/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 70s 200ms/step - accuracy: 0.4667 - los
s: 1.9323 - val_accuracy: 0.4552 - val_loss: 2.0768
Epoch 17/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 75s 214ms/step - accuracy: 0.4767 - los
s: 1.8925 - val_accuracy: 0.4508 - val_loss: 2.1063
Epoch 18/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 65s 186ms/step - accuracy: 0.4829 - los
s: 1.8646 - val_accuracy: 0.4540 - val_loss: 2.1037
Epoch 19/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 64s 181ms/step - accuracy: 0.4893 - los
s: 1.8301 - val_accuracy: 0.4506 - val_loss: 2.1067
Epoch 20/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 65s 184ms/step - accuracy: 0.4983 - los
s: 1.7966 - val_accuracy: 0.4492 - val_loss: 2.1073
Epoch 21/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 67s 190ms/step - accuracy: 0.5056 - los
s: 1.7619 - val_accuracy: 0.4600 - val_loss: 2.0755
```

```
Epoch 22/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 64s 181ms/step - accuracy: 0.5133 - los
s: 1.7380 - val_accuracy: 0.4512 - val_loss: 2.0987
Epoch 23/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 69s 195ms/step - accuracy: 0.5179 - los
s: 1.7099 - val_accuracy: 0.4656 - val_loss: 2.0583
Epoch 24/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 67s 190ms/step - accuracy: 0.5232 - los
s: 1.6859 - val_accuracy: 0.4616 - val_loss: 2.0953
Epoch 25/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 84s 239ms/step - accuracy: 0.5268 - los
s: 1.6659 - val_accuracy: 0.4554 - val_loss: 2.0942
Epoch 26/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 86s 243ms/step - accuracy: 0.5377 - los
s: 1.6325 - val_accuracy: 0.4626 - val_loss: 2.1109
Epoch 27/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 87s 247ms/step - accuracy: 0.5394 - los
s: 1.6258 - val_accuracy: 0.4618 - val_loss: 2.0751
Epoch 28/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 86s 244ms/step - accuracy: 0.5389 - los
s: 1.6150 - val_accuracy: 0.4632 - val_loss: 2.0937
Epoch 29/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 80s 227ms/step - accuracy: 0.5455 - los
s: 1.5848 - val_accuracy: 0.4566 - val_loss: 2.1099
Epoch 30/30
352/352 ━━━━━━━━━━━━━━━━━━━━ 77s 218ms/step - accuracy: 0.5491 - los
s: 1.5696 - val_accuracy: 0.4678 - val_loss: 2.1086
```

In [29]:

```python
# Print model summary and trainable parameters
cnn.summary()

trainable_params = sum(p.numpy().size for p in cnn.trainable_weight
print(f"\nTotal trainable parameters: {trainable_params:,}")

# Evaluate on test set
test_loss, test_acc = cnn.evaluate(x_test_norm, y_test)
print(f"\nCNN Test accuracy: {test_acc:.4f}")
```

Model: "sequential_1"

Layer (type)	Output Shape	
conv2d_9 (Conv2D)	(None, 32, 32, 32)	
conv2d_10 (Conv2D)	(None, 32, 32, 32)	
max_pooling2d_4 (MaxPooling2D)	(None, 16, 16, 32)	
dropout_3 (Dropout)	(None, 16, 16, 32)	
conv2d_11 (Conv2D)	(None, 16, 16, 64)	
conv2d_12 (Conv2D)	(None, 16, 16, 64)	
max_pooling2d_5 (MaxPooling2D)	(None, 8, 8, 64)	
dropout_4 (Dropout)	(None, 8, 8, 64)	
flatten_2 (Flatten)	(None, 4096)	
dense_3 (Dense)	(None, 256)	
dropout_5 (Dropout)	(None, 256)	
dense_4 (Dense)	(None, 100)	

Total params: 3,420,302 (13.05 MB)

Trainable params: 1,140,100 (4.35 MB)

Non-trainable params: 0 (0.00 B)

Optimizer params: 2,280,202 (8.70 MB)

```
Total trainable parameters: 1,140,100
313/313 ━━━━━━━━━━━━━━━━━━━━ 9s 28ms/step - accuracy: 0.4657 - loss:
2.0611

CNN Test accuracy: 0.4657
```

In [ ]:

```
# Plot training curves
fig, (ax1, ax2) = plt.subplots(1, 2, figsize=(FIG_W * 1.6, 4), cons

ax1.plot(cnn_history.history["loss"],     label="Train", color=PAL_
ax1.plot(cnn_history.history["val_loss"], label="Val",   color=PAL_
ax1.set_xlabel("Epoch")
ax1.set_ylabel("Loss")
ax1.set_title("Loss")
ax1.legend(frameon=False)
clean_ax(ax1)

ax2.plot(cnn_history.history["accuracy"],     label="Train", color=
ax2.plot(cnn_history.history["val_accuracy"], label="Val",   color=
ax2.set_xlabel("Epoch")
ax2.set_ylabel("Accuracy")
ax2.set_title("Accuracy")
ax2.legend(frameon=False)
clean_ax(ax2)
```

```
fig_caption(fig, 4, "CNN training curves for loss and accuracy over
```



Figure 4: CNN training curves for loss and accuracy over 30 epochs

A convolutional neural network was built following the architecture pattern from L12. The network consists of two convolutional blocks, each containing two Conv2D layers with ReLU activations followed by MaxPooling2D, for a total of four convolutional layers. Dropout (0.25) is applied after each block to reduce overfitting (L09). The feature maps are then flattened and passed through a fully connected dense layer (256 units, ReLU) with stronger dropout (0.5) before the final softmax output layer over all 100 CIFAR-100 classes.

The model was compiled with the Adam optimizer and sparse categorical cross-entropy loss, which is appropriate for integer-encoded multi-class labels. Training ran for 30 epochs on the normalized spatial images from Part 1.1, using the same 90/10 validation split for monitoring.

CNNs exploit spatial structure through local connectivity and weight sharing (L12), learning hierarchical features that flat distance-based methods like KNN cannot capture. This should give it a significant advantage over the KNN classifiers from Part 1.3.

In [ ]:
```
# Final comparison: all three classification methods
cnn_val_acc  = cnn_history.history["val_accuracy"][-1]
cnn_test_acc = test_acc

results_all = pd.DataFrame({
    "Method":        ["KNN Pixel (3072-dim)", "KNN Latent (256-dim)
    "Val Accuracy":  [pixel_val_acc,  latent_val_acc,  cnn_val_acc]
    "Test Accuracy": [pixel_test_acc, latent_test_acc, cnn_test_acc
})

# Styled table with caption above
styled = table_style(
    results_all.style.format({"Val Accuracy": "{:.4f}", "Test Accur
    2, "Classification Accuracy Across All Methods"
)
display(styled)

# Grouped bar chart
fig, ax = plt.subplots(figsize=(FIG_W, 4), constrained_layout=True)
```

```
x_pos = range(len(results_all))
width = 0.35
ax.bar([p - width/2 for p in x_pos], results_all["Val Accuracy"],
       label="Validation", color=PAL_10[7], alpha=0.85)
ax.bar([p + width/2 for p in x_pos], results_all["Test Accuracy"],
       label="Test", color=PAL_10[4], alpha=0.85)
ax.set_xticks(list(x_pos))
ax.set_xticklabels(results_all["Method"])
ax.set_ylabel("Accuracy")
ax.legend(frameon=False)
ax.set_ylim(0, max(results_all[["Val Accuracy", "Test Accuracy"]].m
clean_ax(ax)
fig_caption(fig, 5, "Classification accuracy comparison across all
```

Table 2: Classification Accuracy Across All Methods

	Method	Val Accuracy	Test Accuracy
0	KNN Pixel (3072-dim)	0.1516	0.1477
1	KNN Latent (256-dim)	0.2034	0.1994
2	CNN	0.4678	0.4657



Figure 5: Classification accuracy comparison across all methods

1.5 Results and Analysis

KNN on raw pixel features serves as the baseline, achieving 15.16% validation and 14.77% test accuracy. This is well above the 1% random chance for 100 classes, but the high dimensionality (3,072 dims) makes pixel similarity a poor proxy for semantic similarity.

Switching to the autoencoder's 256-dimensional latent features improved accuracy to 20.34% validation and 19.94% test, a roughly 5 percentage point gain. The encoder appears to retain enough structural information while discarding noise, making the compressed representations more suitable for distance-based comparison.

The CNN outperformed both by a wide margin, reaching 46.78% validation and 46.57% test accuracy. The training curves show steady improvement over 30 epochs, though a growing gap between training and validation accuracy in later epochs points to mild overfitting. Data augmentation or batch normalization could help close this gap.

Validation and test accuracy align closely across all three methods, suggesting stable generalization with no evaluation leakage. The jump from pixel KNN to latent KNN to CNN tracks what we expected: better feature representations and end-to-end optimization lead to stronger classification on a 100-class image task.