REQUIREMENT ANALYSIS

Customer Journey Map – Script-Controlled ACL

Journey of a user and an administrator while restricting record access based on a field value in ServiceNow. | Team ID: SWTID-2026-6390 | Date: 03 October 2026 | Maximum Marks: 4 Marks

SCENARIO Set up and test role-based and field-controlled record access	1. SETUP Create the test users and access roles	2. BUILD Create the table, fields and records	3. SECURE Configure the READ ACL and field condition	4. REQUEST User asks to open or use a record	5. OPERATE Create, write and delete by role	6. VERIFY Check each user against expected access
STEPS What happens in this journey?	Create EEE User and a user with no bb roles. Create roles bb1, bb2, bb3 and bb4.	Create the Institution Details table (u_institution_details). Add the fields and sample records for ECE, EEE and CSE.	Create the READ ACL with role bb1, condition Branch = EEE and the advanced script.	Impersonate the EEE User, open the Institution Details list and try to view records.	bb1 = Read, bb2 = Create, bb3 = Write, bb4 = Delete. Create one ACL for each operation.	Test the user without bb1, the EEE User with different role combinations, and the administrator.
INTERACTIONS What does the person use?	User Administration: Users and Roles lists, role assignment	System Definition: Tables, table columns, records list	System Security: Access Control (ACL) form, role, condition and script	Impersonate user, Institution Details list	Create ACL, Write ACL and Delete ACL forms	Impersonation, list view, New / Edit / Delete options
GOALS & MOTIVATIONS What does the person want?	Have the test users and roles ready for ACL testing.	Have the correct table structure with different Branch values to test.	Allow only EEE records for bb1 and keep full access for the administrator.	Find out whether access is allowed for each type of user.	Control create, edit and delete separately by role.	Confirm that every role combination gives the expected result.
POSITIVE MOMENTS What should work well?	Users and roles are created correctly.	Fields and Branch choices are available.	The READ ACL matches the planned configuration.	The EEE User and the administrator see what is expected.	Access grows as bb2, bb3 and bb4 are added.	Test results match the expected results.
NEGATIVE MOMENTS What could cause problems?	A wrong role assignment spoils the testing.	Missing fields or records affect the tests.	A wrong role, condition or script changes who gets access.	A user without permission may get an unexpected result.	A missing role blocks the operation.	Incomplete testing leaves the result unclear.
AREAS OF OPPORTUNITY How can it be improved?	Check the role assignments before testing.	Use the exact field names and Branch choices.	Keep the script logic: admin allowed, bb1 allowed, others denied.	Test each user type one at a time.	Test each ACL separately.	Take a screenshot for each test case.

ACCESS LOGIC: Read = bb1 + Branch = EEE + advanced script | Create = bb2 | Write = bb3 | Delete = bb4 | Administrator = full access