REQUIREMENT ANALYSIS

Solution Requirements (Functional & Non-functional)

Date	03 October 2026
Team ID	SWTID-2026-6390
Project Name	Script-Controlled ACL – Restrict Record Access Based on Field Value
Maximum Marks	4 Marks

Functional Requirements

These are the things the system must do for the Script-Controlled ACL project.

FR No.	Functional Requirement (Epic)	Sub Requirement (Story / Sub-Task)
FR-1	Creation of Users and Roles	Create the test user EEE User, create the roles bb1, bb2, bb3 and bb4, and assign the roles to EEE User for testing.
FR-2	Tables Creation	Create the custom table Institution Details (u_institution_details) with the fields Student Roll Number, Student Name, Faculty Name, Branch, Email, Phone Number and Description. Branch has the choices ECE, EEE and CSE.
FR-3	Access Control List – Read	Create an active, advanced record-level READ ACL on u_institution_details. It requires role bb1, uses the condition Branch is EEE, and uses a script that allows the administrator and bb1 and denies all others.
FR-4	Access Control List – Create	Create an active record-level CREATE ACL on u_institution_details that requires role bb2. No extra data condition is used.
FR-5	Access Control List – Write	Create an active record-level WRITE ACL on u_institution_details that requires role bb3. No extra data condition is used.
FR-6	Access Control List – Delete	Create an active record-level DELETE ACL on u_institution_details that requires role bb4. No extra data condition is used.

Non-functional Requirements

These describe how well the system should work. Where the project has not set a target, this is stated clearly instead of inventing one.

NFR No.	Non-functional Requirement	Description
NFR-1	Usability	Users and administrators work through the normal ServiceNow menus, lists and forms. No custom interface is built.
NFR-2	Security	Access to records is controlled by roles and, for READ, by the Branch = EEE condition and the script. The administrator keeps full access.
NFR-3	Reliability	The ACLs should give the same result every time for the same user and role. This is checked by testing users with and without the required roles, and the administrator.
NFR-4	Performance	No response-time or load target is set for this project, and performance testing is not part of it.
NFR-5	Availability	No uptime or availability target is set. The project runs on a ServiceNow instance.

NFR No.	Non-functional Requirement	Description
NFR-6	Scalability	No scaling target is set. The same ACL pattern could later be used for more branches, roles or tables.