Status	Finished
Started	Saturday, 24 October 2026, 10:21 PM
Completed	Saturday, 24 October 2026, 10:24 PM
Duration	3 mins 19 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the default mode in which the open() function opens a file?

- a. Read ✓
- b. Binary
- c. Append
- d. Write

The correct answer is: Read

Question **2**

Correct

Mark 1.00 out of 1.00

What does the mode attribute of a file object indicate?

- a. The size of the file
- b. The name of the file
- c. The current position of the file cursor
- d. The access mode in which the file was opened ✓

The correct answer is: The access mode in which the file was opened

Question **3**

Correct

Mark 1.00 out of 1.00

Default EOL character of text file in python is ,

a. \t

b. space

c. \n ✓

d. ,

The correct answer is:
\n

Question **4**

Correct

Mark 1.00 out of 1.00

Which of the following is data file?

a. none of the given choices

b. Text file

c. Binary file

d. Both text and binary file ✓

The correct answer is: Both text and binary file

Question **5**

Correct

Mark 1.00 out of 1.00

What will be the output of the following code if the file "example.txt" contains "Python Programming"?

```
f = open("example.txt", "r")
print(f.read(6))
f.close()
```

a. Python ✓

b. Python Programming

c. An error is raised

d. Program

The correct answer is: Python

Question **6**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

a. read()
b. readlist()
c. readlines() ✓
d. readline()

The correct answer is: readlines()

Question **7**

Incorrect

Mark 0.00 out of 1.00

Which method is used to sets the position of a file pointer

a. fseek() ✗
b. ftell()
c. seek()
d. tell()

The correct answer is: seek()

Question **8**

Correct

Mark 1.00 out of 1.00

Select the incorrect file access mode

a. wb+
b. rw+ ✓
c. ab+
d. r

The correct answer is: rw+

Question **9**

Correct

Mark 1.00 out of 1.00

Which function is used to open a file in Python?

a. openfile()
b. open_file()
c. file()
d. open() ✓

The correct answer is: open()

Question **10**

Correct

Mark 1.00 out of 1.00

The readlines() method returns _____

a. str
b. a list of lines ✓
c. a list of integers
d. a list of single characters

The correct answer is:
a list of lines

Question **11**

Correct

Mark 1.00 out of 1.00

Which of the following methods is used to read a single line from a file?

a. read()
b. readline() ✓
c. readline(size)
d. readlines()

The correct answer is: readline()

Question **12**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

a. A new file is created
b. An empty file object is returned
c. An error is raised ✓
d. The operation is ignored

The correct answer is: An error is raised

Question **13**

Correct

Mark 1.00 out of 1.00

What is the difference between r+ and w+ modes in file handling?

a. r+ is for read and append, w+ is for read and write
b. r+ is for read and write, w+ is for append only
c. r+ is for binary read and write, w+ is for text read and write
d. r+ is for read and write without truncating, w+ is for read and write with truncating ✓

The correct answer is: r+ is for read and write without truncating, w+ is for read and write with truncating

Question **14**

Correct

Mark 1.00 out of 1.00

What does the following code do?

```
fo = open("foo.txt", "w")
```

a. Appends to an existing file
b. Opens an existing file in read mode
c. Opens a file in binary mode
d. Creates a new file for writing ✓

The correct answer is: Creates a new file for writing

Question **15**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

a. infile = open(file = “a.txt”, “r”)

b. infile = open(file, “a.txt”, “r”)

c. infile = open(file = “a.txt”, “r”)

d. infile = open(“a.txt”, “r”) ✓

The correct answer is:
infile = open(“a.txt”, “r”)