Malware Analysis Using Recorded Future Triage

Anneliese Little & Teaundra Thompson

WannaCry

- WannaCry was a severe ransomware attack from May of 2017
- The attack was specifically for computers running on Windows
- It encrypted several important files and demanded a large sum of money in bitcoin, otherwise the information would be released
- Microsoft became aware of the attack 12 months before it occurred and released a patch to protect computers running Windows
- Even still, 200,000 computers across 156 countries were infected
- The virus was stopped by 22 -year-old self-taught cybersecurity expert, Marcus Hutchins, who discovered a "kill switch" in the virus



Systex

- Trojan loader written in c++
- Backdoor made to run on Windows machines
- Primary goal is to download and run secondary payloads such as RATs.
- Connects to C2 server to download payloads to be executed.



Mrs. Major

- Designed for Windows, disrupts normal computer functions and potentially compromises system integrity
- Initiates a series of actions that alter user experience, like modifying system settings, displaying unexpected images or messages, and creating a sense of unease
- Not necessarily destructive, but can cause system instability and user discomfort
- The modifications it makes on devices can serve as gateways for more serious attacks
- Received via unsolicited emails, compromised websites, or bundled with seemingly legitimate software




XWorm

- Designed to sneak into systems, steal everything it can, and give attackers full control
- Its primary purpose is to steal sensitive information, like login credentials, financial data, and personal files
- It can do many things, like log keystrokes, capture screenshots, access webcams, and download and execute other malware like ransomware
- Extremely dangerous, one infection can lead to the entire network being compromised
- It is distributed via phishing, like emails with attachments that can look like invoices, shipping notifications, and other legitimate business documents
- The RAT disguises itself as a legitimate system file and modifies the system registry so it runs every time the system starts
- Uses hollowing (injecting the code into a process) and disabling security software to make itself as undetectable as possible



Vidar

- Designed to exfiltrate sensitive data like passwords, credit card information, and cryptocurrency wallet information
- Usually used as a precursor to larger attacks, like ransomware attacks
- It often operates under aliases and adapts its behavior to remain as discreet as possible, making it a huge threat
- Distributed using phishing emails, malvertising, and exploit kits
- It exhibits persistence by modifying registry keys
- Avoids detection using sandbox-evasion techniques



Mozi

- Peer-to-peer botnet that targets Internet of Things (IoT) devices
- It exploits weak telnet passwords and known vulnerabilities
- Launches Distributed Denial-of-Service (DDoS) attacks, execute payloads, or steal information
- Derived from source code of other IoT malware families like Mirai, Gafgyt, and IoT Reaper
- Infects as many IoT devices as possible to form a massive zombie army
- A worm that spreads aggressively, scanning through the internet for open telnet ports, then brute forces using a list of weak passwords
- Uses Distributed Hash Table protocol to create P2P network, making it harder to track



Sources

https://pmc.ncbi.nlm.nih.gov/articles/PMC5461132/
https://www.england.nhs.uk/long-read/case-study-wannacry-attack/
https://www.malwarebytes.com/blog/detections/trojan-loader
https://www.trendmicro.com/vinfo/us/threat-encyclopedia/malware/backdoor.win32.systex.b
https://www.cyclonis.com/remove-mrsmajor-malware/
https://www.huntress.com/threat-library/malware/xworm
https://www.huntress.com/threat-library/malware/vidar
https://www.huntress.com/threat-library/malware/mozi-iot-botnet