

**Selig Master Mechanic NC Aero DZ**

Version 2.0

Revision Date 07/10/2015

Print Date 08/17/2016

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : Selig Master Mechanic NC Aero DZ

Material number : 000000000000915701

**Manufacturer or supplier's details**

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW  
Atlanta, GA 30318

Telephone : 404-352-1680

**Emergency telephone numbers****For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	Compressed gas
Colour	clear, colourless, yellow
Odour	like fruit

**GHS Classification**Flammable aerosols : Category 1  
Gases under pressure : Compressed gas  
Eye irritation : Category 2A  
Skin sensitisation : Category 1**GHS Label element**

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.Precautionary statements : **Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.

**Selig Master Mechanic NC Aero DZ**

Version 2.0

Revision Date 07/10/2015

Print Date 08/17/2016

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear eye protection/ face protection.  
P280 Wear protective gloves.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P363 Wash contaminated clothing before reuse.

**Storage:**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

Dispose of contents/container in accordance with local regulation.

**Potential Health Effects****Carcinogenicity:****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**ACGIH**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous components**

Chemical Name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 5 - < 10
Distillates (petroleum), straight-run middle	64741-44-2	>= 5 - < 10
carbon dioxide	124-38-9	>= 1 - < 5
(2-methoxymethylethoxy)propanol (Mixture of isomers)	34590-94-8	>= 1 - < 5
Linseed oil	8001-26-1	>= 1 - < 5

**Selig Master Mechanic NC Aero DZ**

Version 2.0

Revision Date 07/10/2015

Print Date 08/17/2016

---

**SECTION 4. FIRST AID MEASURES**

- |                         |   |
|-------------------------|---|
| General advice          | : Move out of dangerous area.<br>Show this safety data sheet to the doctor in attendance.<br>Do not leave the victim unattended.  |
| If inhaled              | : If unconscious place in recovery position and seek medical advice.<br>If symptoms persist, call a physician.  |
| In case of skin contact | : If skin irritation persists, call a physician.<br>Wash off immediately with plenty of water for at least 15 minutes.<br>If on clothes, remove clothes.  |
| In case of eye contact  | : Remove contact lenses.<br>Protect unharmed eye.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist.<br>If in eyes, rinse with water for 15 minutes.                                     |
| If swallowed            | : Keep respiratory tract clear.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician.<br>DO NOT induce vomiting unless directed to do so by a physician or poison control center. |

---

**SECTION 5. FIREFIGHTING MEASURES**

- |   |  |
|---|--|
| Suitable extinguishing media                  | : Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical<br>Water spray jet   |
| Unsuitable extinguishing media                | : High volume water jet  |
| Specific hazards during firefighting          | : Do not allow run-off from fire fighting to enter drains or water courses.  |
| Hazardous combustion products                 | : Carbon dioxide (CO <sub>2</sub> )<br>Carbon monoxide<br>Smoke  |
| Specific extinguishing methods                | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  |
| Further information                           | : For safety reasons in case of fire, cans should be stored separately in closed containments.<br>Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary.   |

**Selig Master Mechanic NC Aero DZ**

Version 2.0

Revision Date 07/10/2015

Print Date 08/17/2016

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- |   |   |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.<br>Ensure adequate ventilation.<br>Remove all sources of ignition.<br>Evacuate personnel to safe areas.<br>Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions   | : Prevent product from entering drains.<br>Prevent further leakage or spillage if safe to do so.<br>If the product contaminates rivers and lakes or drains inform respective authorities.   |
| Methods and materials for containment and cleaning up               | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).<br>Sweep up or vacuum up spillage and collect in suitable container for disposal.  |

---

**SECTION 7. HANDLING AND STORAGE**

- |                             |  |
|-----------------------------|--|
| Advice on safe handling     | : Avoid exposure - obtain special instructions before use.<br>Avoid contact with skin and eyes.<br>For personal protection see section 8.<br>Smoking, eating and drinking should be prohibited in the application area.<br>Take precautionary measures against static discharges.<br>Provide sufficient air exchange and/or exhaust in work rooms.<br>Open drum carefully as content may be under pressure.<br>Dispose of rinse water in accordance with local and national regulations.<br>Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.<br>Always replace cap after use.<br>Do not breathe vapours or spray mist. |
| Conditions for safe storage | : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.<br>No smoking.<br>Observe label precautions.<br>Keep in a dry, cool and well-ventilated place.<br>Electrical installations / working materials must comply with the technological safety standards.   |
| Materials to avoid          | : Oxidizing agents<br>Do not freeze.   |

---

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Selig Master Mechanic NC Aero DZ

Version 2.0

Revision Date 07/10/2015

Print Date 08/17/2016

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH
carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
		ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m <sup>3</sup>	OSHA P0
		STEL	30,000 ppm 54,000 mg/m <sup>3</sup>	OSHA P0
(2-methoxymethylethoxy)propano I (Mixture of isomers)	34590-94-8	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		ST	150 ppm 900 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 600 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 600 mg/m <sup>3</sup>	OSHA Z-1
		TWA	100 ppm 600 mg/m <sup>3</sup>	OSHA P0
		STEL	150 ppm 900 mg/m <sup>3</sup>	OSHA P0

## Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.  
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Selig Master Mechanic NC Aero DZ**

Version 2.0

Revision Date 07/10/2015

Print Date 08/17/2016

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Compressed gas

Colour : clear, colourless, yellow

Odour : like fruit

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : Not applicable

Boiling point : > 230 °C

Flash point :  
Not applicable

Evaporation rate : not determined

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.81 g/cm<sup>3</sup>

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : > 20 kJ/g

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous : No decomposition if stored and applied as directed.

**Selig Master Mechanic NC Aero DZ**

Version 2.0

Revision Date 07/10/2015

Print Date 08/17/2016

reactions

Vapours may form explosive mixture with air.

Conditions to avoid

: Extremes of temperature and direct sunlight.

Heat, flames and sparks.

Incompatible materials

: Oxidizing agents

Hazardous decomposition products

: Carbon oxides

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute oral toxicity

: Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity

: Acute toxicity estimate : > 10 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity

: Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity

: LD50 Rat: &gt; 5,000 mg/kg

Acute inhalation toxicity

: LC50 Rat: > 5 mg/l  
Exposure time: 4 h

Acute dermal toxicity

: LD50 Rabbit: &gt; 5,000 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation****Product:**

Remarks: Severe eye irritation

**Respiratory or skin sensitisation****Product:**

Remarks: Causes sensitisation.

**Selig Master Mechanic NC Aero DZ**

Version 2.0

Revision Date 07/10/2015

Print Date 08/17/2016

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**Distillates (petroleum), hydrotreated heavy naphthenic:****Distillates (petroleum), straight-run middle:****carbon dioxide:****(2-methoxymethylethoxy)propanol (Mixture of isomers):****Linseed oil:****STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product:**

Remarks: No data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Product:**Partition coefficient: n- : Remarks: No data available  
octanol/water**Components:****(2-methoxymethylethoxy)propanol (Mixture of isomers) :**Partition coefficient: n- : Pow: 0.0043  
octanol/water**Mobility in soil**

No data available

**Other adverse effects**



**Selig Master Mechanic NC Aero DZ**

Version 2.0

Revision Date 07/10/2015

Print Date 08/17/2016

No data available

**Product:**

Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information	: No data available
-----------------------------------	---------------------

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY
---

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity
---

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity
--

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity
--

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity
--

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act**

**Selig Master Mechanic NC Aero DZ**

Version 2.0

Revision Date 07/10/2015

Print Date 08/17/2016

**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Sudden Release of Pressure Hazard  
Acute Health Hazard  
Fire Hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop 65** This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

<b>TSCA</b>	On TSCA Inventory
<b>DSL</b>	This product contains one or several components that are not on the Canadian DSL nor NDSL.
<b>AICS</b>	Not in compliance with the inventory
<b>NZIoC</b>	Not in compliance with the inventory
<b>PICCS</b>	Not in compliance with the inventory
<b>IECSC</b>	Not in compliance with the inventory

**Inventory Acronym and Validity Area Legend:**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

---

**SECTION 16. OTHER INFORMATION**

## Selig Master Mechanic NC Aero DZ


Version 2.0

Revision Date 07/10/2015

Print Date 08/17/2016

## Further information

## NFPA:



## HMIS III:

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

## OSHA GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.  
May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statements

: **Prevention:** Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear eye protection/ face protection. Wear protective gloves.  
**Response:** IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Wash contaminated clothing before reuse.  
**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	2.0
Revision Date:	07/10/2015
Print Date:	08/17/2016

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®,

**Selig Master Mechanic NC Aero DZ**

Version 2.0

Revision Date 07/10/2015

Print Date 08/17/2016

Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.