

## Low Energy Timer

AN0026 - Application Note

### Introduction

This application note gives an overview of the Low Energy Timer (LETIMER) and demonstrates how to use its features to generate pulses, PWM and other waveforms while remaining in EM2 to achieve high energy efficiency.

This application note includes:

- This PDF document
- Source files (zip)
  - Example C-code
  - Multiple IDE projects


# 1 Introduction

The unique LETIMER<sup>™</sup>, the Low Energy Timer, is a 16-bit timer that is available in energy mode EM2 in addition to EM1 and EM0. Because of this, it can be used for timing and output generation when most of the device is powered down, allowing simple tasks to be performed while the power consumption of the system is kept at an absolute minimum. The LETIMER runs from the LFACLK which can be clocked by the LFXO, LFRCO or HFCORECLK<sub>LE</sub>/2. If clocked by the HFCORECLK<sub>LE</sub>/2 the LETIMER and other peripherals running from the LFACLK will not be available in EM2.

The LETIMER can be used to output a variety of waveforms with minimal software intervention. The waveforms include PWM, pulses with the duration of one LFACLK<sub>LETIMER</sub> period and variable frequency waveforms. The LETIMER is also connected to the Real Time Counter (RTC), and can be configured to start counting on compare matches from the RTC.

An overview of the LETIMER module is shown in Figure 1.1 (p. 2). The LETIMER is a 16-bit down-counter with two compare registers, LETIMERn\_COMP0 and LETIMERn\_COMP1. The LETIMERn\_COMP0 register can optionally act as a top value for the counter. The repeat counter LETIMERn\_REP0 allows the timer to count a specified number of times before it stops. Both the LETIMERn\_COMP0 and LETIMERn\_REP0 registers can be double buffered by the LETIMERn\_COMP1 and LETIMERn\_REP1 registers to allow continuous operation. The timer can generate a single pin output, or two linked outputs.

**Figure 1.1. LETIMER Overview**



## 2 LETIMER Features

### 2.1 Compare Registers

The LETIMER has two compare match registers, LETIMERn\_COMP0 and LETIMERn\_COMP1. Each of these compare registers are capable of generating an interrupt when the counter value LETIMERn\_CNT becomes equal to their value. When LETIMERn\_CNT becomes equal to the value of LETIMERn\_COMP0, the interrupt flag COMP0 in LETIMERn\_IF is set, and when LETIMERn\_CNT becomes equal to the value of LETIMERn\_COMP1, the interrupt flag COMP1 in LETIMERn\_IF is set.

The compare values can be set using the `LETIMER_CompareSet(LETIMER_TypeDef *letimer, unsigned int comp, uint32_t value)` from the `emlib`.

### 2.2 Top Value

If COMP0TOP in LETIMERn\_CTRL is set, the value of LETIMERn\_COMP0 acts as the top value of the timer, and LETIMERn\_COMP0 is loaded into LETIMERn\_CNT on timer underflow. Otherwise the timer wraps around to 0xFFFF. The underflow interrupt flag UF in LETIMERn\_IF is set when the timer reaches zero.

If BUFTOP in LETIMERn\_CTRL is set, the value of LETIMERn\_COMP0 is buffered by LETIMERn\_COMP1. In this mode, the value of LETIMERn\_COMP1 is loaded into LETIMERn\_COMP0 every time LETIMERn\_REP0 is about to decrement to 0.

### 2.3 Repeat Modes

By default, the timer wraps around to the top value or 0xFFFF on each underflow, and continues counting. The repeat counters can be used to get more control of the operation of the timer, including defining the number of times the counter should wrap around. There are four repeat modes available which are detailed in Table 2.1 (p. 3).

**Table 2.1. LETIMER Repeat Modes**

REPMODE	Mode	Description
00	Free	The timer runs until it is stopped
01	One-shot	The timer runs as long as LETIMERn_REP0 != 0. LETIMERn_REP0 is decremented at each timer underflow.
10	Buffered	The timer runs as long as LETIMERn_REP0 != 0. LETIMERn_REP0 is decremented on each timer underflow. If LETIMERn_REP1 has been written, it is loaded into LETIMERn_REP0 when LETIMERn_REP0 is about to be decremented to 0.
11	Double	The timer runs as long as LETIMERn_REP0 != 0 or LETIMERn_REP1 != 0. Both LETIMERn_REP0 and LETIMERn_REP1 are decremented at each timer underflow.

The interrupt flags REP0 and REP1 in LETIMERn\_IF are set whenever LETIMERn\_REP0 or LETIMERn\_REP1 are decremented to 0 respectively. REP0 is also set when the value of LETIMERn\_REP1 is loaded into LETIMERn\_REP0 in buffered mode.

The function `LETIMER_RepeatSet(LETIMER_TypeDef *letimer, unsigned int rep, uint32_t value)` from the `emlib` can be used to set the values of the repeat registers.

### 2.3.1 Free Mode

In the free running mode, the LETIMER acts as a regular timer, and the repeat counter is disabled. The LETIMER can be started by writing the START bit in `LETIMERn_CMD` and runs until it is stopped using the STOP bit in the same register.

### 2.3.2 One-shot Mode

The one-shot repeat mode is the most basic repeat mode. In this mode, the repeat register `LETIMERn_REP0` is decremented every time the timer underflows, and the timer stops when `LETIMERn_REP0` goes from 1 to 0. In this mode, the timer counts down `LETIMERn_REP0` times, i.e. the timer underflows `LETIMERn_REP0` times. `LETIMERn_REP0` can be written while the timer is running to allow the timer to run for longer periods at a time without stopping.

### 2.3.3 Buffered Mode

The Buffered repeat mode allows buffered timer operation. When started, the timer runs `LETIMERn_REP0` number of times. If `LETIMERn_REP1` has been written since the last time it was used and it is nonzero, `LETIMERn_REP1` is then loaded into `LETIMERn_REP0`, and counting continues the new number of times. The timer keeps going as long as `LETIMERn_REP1` is updated with a nonzero value before `LETIMERn_REP0` is finished counting down. If the timer is started when both `LETIMERn_CNT` and `LETIMERn_REP0` are zero but `LETIMERn_REP1` is non-zero, `LETIMERn_REP1` is loaded into `LETIMERn_REP0`, and the counter counts the loaded number of times.

### 2.3.4 Double Mode

The Double repeat mode works much like the one-shot repeat mode with the difference that the LETIMER counts as long as either `LETIMERn_REP0` or `LETIMERn_REP1` is larger than 0.

## 2.4 Clock Source

The LETIMER clock source and its prescaler value are defined in the Clock Management Unit (CMU). The `LFACLKLETIMERn` has a frequency given by Equation 2.1 (p. 4) where the exponent `LETIMERn` is a 4 bit value in the `CMU_LFAPRESC0` register.

#### LETIMER Clock Frequency

$$f_{\text{LFACLK\_LETIMERn}} = 32.768 / 2^{\text{LETIMERn}} \quad (2.1)$$

To use this module, the LE interface clock must be enabled in `CMU_HFCORECLKEN0`, in addition to the module clock. Clock enabling and prescaling is covered in AN0004 Clock Management Unit.

## 2.5 RTC Trigger

The LETIMER can be configured to start on compare match events from the Real Time Counter (RTC). If `RTCC0TEN` in `LETIMERn_CTRL` is set, the LETIMER will start on a compare match on RTC compare channel 0. In the same way, `RTCC1TEN` in `LETIMERn_CTRL` enables the LETIMER to start on a compare match with RTC compare channel 1.

## 2.6 Underflow Output Action

For each of the LETIMER outputs an underflow output action can be set. The configured output action is performed every time the counter underflows while the respective repeat register is nonzero. In PWM

mode, the output is similarly only changed on COMP1 match if the repeat register is nonzero. The different output actions are shown in Table 2.2 (p. 5)

**Table 2.2. LETIMER Underflow Output Actions**

UF0A0/UF0A1	Mode	Description
00	Idle	The output is held at its idle value
01	Toggle	The output is toggled on LETIMERn_CNT underflow if LETIMERn_REPx is nonzero
10	Pulse	The output is held active for one clock cycle on LETIMERn_CNT underflow if LETIMERn_REPx is nonzero. It then returns to its idle value
11	PWM	The output is set idle on LETIMERn_CNT underflow and active on compare match with LETIMERn_COMP1 if LETIMERn_REPx is nonzero.

The LETIMER outputs must be routed to pins using the LETIMERn\_ROUTE register. The selected pins must be enabled as output in the GPIO module. Pin configuration is covered in AN0012 GPIO

## 2.7 Interrupts

There are 5 interrupts available in the LETIMER. One interrupt for when each of the Repeat Counters (REP0 and REP1) reaches zero, one when the LETIMER counter matches the value of each compare register (COMP0 and COMP1) and one when the LETIMER underflows.

These interrupts can be enabled, disabled and cleared using the following functions from the emlib:

- `LETIMER_IntEnable(LETIMER_TypeDef *letimer, uint32_t flags)` enables interrupts
- `LETIMER_IntDisable(LETIMER_TypeDef *letimer, uint32_t flags)` disables interrupts
- `LETIMER_IntClear(LETIMER_TypeDef *letimer, uint32_t flags)` clears interrupts

## 2.8 Register Access and Synchronization

Since the LETIMER is a Low Energy Peripheral and runs off a low frequency clock which is asynchronous to the HFCORECLK some register, writes need to be synchronized from the high frequency domain to the low frequency domain. **The changes will not take effect until the synchronization is done and it takes 3 low frequency clock cycles to synchronize between the two domains.**

After writing to a register that requires synchronization the correspondent flag in the LETIMERn\_SYNCBUSY register will be set while the synchronization is in progress. Writing to the same register before the synchronization is complete may result in undefined behavior and therefore a wait cycle must be performed to ensure the register was synchronized. This can be done using the `LETIMER_Sync(LETIMER_TypeDef *letimer, uint32_t mask)` function from the emlib. **All emlib LETIMER functions check for synchronizations before writing the registers.**

## 3 Configuration

The LETIMER can be easily and quickly configured using the `LETIMER_Init(LETIMER_TypeDef *letimer, const LETIMER_Init_TypeDef *init)` function from the emlib. This function allows the configuration of the following parameters:

- Start counting when the initialization is complete
- Counter running during debug
- Start counting on RTC COMP0 match
- Start counting on RTC COMP1 match
- Use COMP0 register as TOP value
- Load COMP1 to COMP0 when REP reaches 0
- Idle value for output 0
- Idle value for output 1
- Underflow output 0 action
- Underflow output 1 action
- Repeat mode

## 4 Software Examples

This application note contains two software examples demonstrating the LETIMER features. On project `letimer_pwm_pulse` the LETIMER runs in free mode and outputs a variable duty-cycle PWM signal on output 0 and pulses on output 1. On `letimer_rtc_pulses` project the LETIMER is triggered by the RTC and runs in One-shot mode with pulses output. The projects are intended for both the EFM32 Starter Kits (STK) and Development Kit (DK).

### 4.1 PWM and Pulses Output

On `letimer_pwm_pulse` project the LETIMER is configured to run in Free mode with PWM on output 1 (pin PD6, P5.9 on the DK protoboard) and pulses on output 0 (pin PD7, P5.10 on the DK protoboard). The value of COMP0 is used as TOP value for the counter and is loaded after each underflow. Using underflow interrupts the value of COMP1 is decremented throughout the program execution resulting in a variable PWM duty-cycle.

The PWM frequency and duty-cycle can be obtained using the formulas below.

#### **PWM Frequency Equation**

$$f_{\text{PWM}} = 32768 / \text{TOP} \quad (4.1)$$


#### **PWM Duty-cycle Equation**

$$\text{DS}_{\text{PWM}} = \text{COMP1} / \text{COMP0} \times 100 \quad (4.2)$$

The purpose of this example is to demonstrate how the LETIMER can be used to output PWM and/or pulses with little CPU intervention and keeping the energy consumption to a minimum

### 4.2 RTC Triggered Counter

The `letimer_rtc_pulses` project demonstrates how the RTC can be used to trigger the LETIMER. The LETIMER is configured to start counting on RTC COMP0 match with pulses on output 0 (no action on output 1) and One-shot repeat mode. Figure 4.1 (p. 8) illustrates the program flow.

**Figure 4.1. RTC Trigger**

The RTC generates a compare match after 5 seconds ( $\text{RTC\_COMP0} = 5$ ) of program execution which will trigger the LETIMER to start counting. The LETIMER will count-down while  $\text{LETIMERn\_REP0} \neq 0$  generating a pulse on each underflow. For this project  $\text{LETIMER\_REP0}$  has the value of 5 so there will be 5 pulses generated on pin PD6 (P5.9 on the DK protoboard).

#### Note

The RTC continues counting after the compare match. If it wraps around the top value and generates a new compare match the LETIMER will not be triggered because  $\text{LETIMERn\_REP0} = 0$ .



## 5 Revision History

### 5.1 Revision 1.06

2013-09-03

New cover layout

### 5.2 Revision 1.05

2013-05-08

Added software projects for ARM-GCC and Atollic TrueStudio.

### 5.3 Revision 1.04

2012-11-12

Adapted software projects to new kit-driver and bsp structure.

Added projects for Tiny and Giant Gecko STKs.

### 5.4 Revision 1.03

2012-08-13

Added projects for Tiny and Giant Gecko STKs.

### 5.5 Revision 1.02

2012-04-20

Adapted software projects to new peripheral library naming and CMSIS\_V3.

### 5.6 Revision 1.01

2011-10-21

Updated IDE project paths with new kits directory.

### 5.7 Revision 1.00

2010-12-17

Initial revision.

# A Disclaimer and Trademarks

## A.1 Disclaimer

*Silicon Laboratories intends to provide customers with the latest, accurate, and in-depth documentation of all peripherals and modules available for system and software implementers using or intending to use the Silicon Laboratories products. Characterization data, available modules and peripherals, memory sizes and memory addresses refer to each specific device, and "Typical" parameters provided can and do vary in different applications. Application examples described herein are for illustrative purposes only. Silicon Laboratories reserves the right to make changes without further notice and limitation to product information, specifications, and descriptions herein, and does not give warranties as to the accuracy or completeness of the included information. Silicon Laboratories shall have no liability for the consequences of use of the information supplied herein. This document does not imply or express copyright licenses granted hereunder to design or fabricate any integrated circuits. The products must not be used within any Life Support System without the specific written consent of Silicon Laboratories. A "Life Support System" is any product or system intended to support or sustain life and/or health, which, if it fails, can be reasonably expected to result in significant personal injury or death. Silicon Laboratories products are generally not intended for military applications. Silicon Laboratories products shall under no circumstances be used in weapons of mass destruction including (but not limited to) nuclear, biological or chemical weapons, or missiles capable of delivering such weapons.*

## A.2 Trademark Information

Silicon Laboratories Inc., Silicon Laboratories, the Silicon Labs logo, Energy Micro, EFM, EFM32, EFR, logo and combinations thereof, and others are the registered trademarks or trademarks of Silicon Laboratories Inc. ARM, CORTEX, Cortex-M3 and THUMB are trademarks or registered trademarks of ARM Holdings. Keil is a registered trademark of ARM Limited. All other products or brand names mentioned herein are trademarks of their respective holders.

## B Contact Information

**Silicon Laboratories Inc.**

400 West Cesar Chavez

Austin, TX 78701

Please visit the Silicon Labs Technical Support web page:

<http://www.silabs.com/support/pages/contacttechnicalsupport.aspx>

and register to submit a technical support request.

## Table of Contents

1. Introduction .....	2
2. LETIMER Features .....	3
2.1. Compare Registers .....	3
2.2. Top Value .....	3
2.3. Repeat Modes .....	3
2.4. Clock Source .....	4
2.5. RTC Trigger .....	4
2.6. Underflow Output Action .....	4
2.7. Interrupts .....	5
2.8. Register Access and Synchronization .....	5
3. Configuration .....	6
4. Software Examples .....	7
4.1. PWM and Pulses Output .....	7
4.2. RTC Triggered Counter .....	7
5. Revision History .....	9
5.1. Revision 1.06 .....	9
5.2. Revision 1.05 .....	9
5.3. Revision 1.04 .....	9
5.4. Revision 1.03 .....	9
5.5. Revision 1.02 .....	9
5.6. Revision 1.01 .....	9
5.7. Revision 1.00 .....	9
A. Disclaimer and Trademarks .....	10
A.1. Disclaimer .....	10
A.2. Trademark Information .....	10
B. Contact Information .....	11
B.1. ....	11

List of Figures

1.1. LETIMER Overview ..... 2

4.1. RTC Trigger ..... 8

List of Tables

2.1. LETIMER Repeat Modes ..... 3

2.2. LETIMER Underflow Output Actions ..... 5

List of Equations

2.1. LETIMER Clock Frequency ..... 4

4.1. PWM Frequency Equation ..... 7

4.2. PWM Duty-cycle Equation ..... 7

# silabs.com

