

Unit 2

DATA PREPROCESSING

Data Manipulation

1. Handling Missing Data

```
8] 0s ▶ import pandas as pd
import numpy as np
# Sample data with missing entries
data = {
    'Name': ['Alice', 'Bob', 'Charlie', 'David'],
    'Age': [25, np.nan, 30, 22],
    'Salary': [50000, 60000, np.nan, 45000]
}
df = pd.DataFrame(data)
# 1. Check for missing values
print("Missing count:\n", df.isnull().sum())
# 2. Fill missing Age with the column median
df['Age'] = df['Age'].fillna(df['Age'].median())
# 3. Drop rows where Salary is missing
df = df.dropna(subset=['Salary'])
print("\nCleaned DataFrame:\n", df)
```

```
... Missing count:
      Name      0
      Age      1
      Salary    1
dtype: int64

Cleaned DataFrame:
      Name  Age  Salary
0  Alice  25.0  50000.0
1   Bob   25.0  60000.0
3  David  22.0  45000.0
```

2. Filtering Rows Based on Multiple Conditions

```
1s ▶ import pandas as pd
data = {
    'Employee': ['Amy', 'John', 'Raj', 'Kevin', 'Sora'],
    'Department': ['HR', 'IT', 'IT', 'Sales', 'IT'],
    'Experience': [3, 7, 1, 5, 6]
}
df = pd.DataFrame(data)
# Filter for employees in IT with more than 5 years of experience
filtered_df = df[(df['Department'] == 'IT') & (df['Experience'] > 5)]
print(filtered_df)
```

```
...   Employee Department  Experience
1      John          IT            7
4      Sora          IT            6
```

3. Aggregating and Grouping Data

```
import pandas as pd
data = {
    'Store': ['North', 'South', 'North', 'West', 'South', 'West'],
    'Sales': [1200, 1500, 900, 1100, 1700, 1300],
    'Employees': [5, 7, 5, 4, 8, 4]
}
df = pd.DataFrame(data)
# Group by Store and calculate total sales and average employees
summary = df.groupby('Store').agg({
    'Sales': 'sum',
    'Employees': 'mean'
}).reset_index()
print(summary)
```

```
...   Store  Sales  Employees
0  North   2100         5.0
1  South   3200         7.5
2  West   2400         4.0
```

4. Python Program Using describe()

```
import pandas as pd
# Create a sample dictionary with numeric and categorical data
data = {
    'Age': [25, 30, 35, 40, 45],
    'Salary': [50000, 60000, 75000, 90000, 110000],
    'Department': ['HR', 'IT', 'IT', 'Marketing', 'HR']
}
# Convert the dictionary into a Pandas DataFrame
df = pd.DataFrame(data)
# 1. Default describe() - Summary of numeric columns
print("--- Numeric Summary ---")
print(df.describe())
# 2. Categorical describe() - Summary of text/object columns
print("\n--- Categorical Summary ---")
print(df.describe(include='object'))
```

```
... --- Numeric Summary ---
      Age      Salary
count  5.000000  5.000000
mean   35.000000  77000.000000
std     7.905694  23874.672773
min    25.000000  50000.000000
25%    30.000000  60000.000000
50%    35.000000  75000.000000
75%    40.000000  90000.000000
max    45.000000  110000.000000

--- Categorical Summary ---
      Department
count          5
unique         3
```

5. head() and tail() in Python

```
import pandas as pd
# Creating a sample dataset
data = {

    'Name': ['Alice', 'Bob', 'Charlie', 'David', 'Eva', 'Frank', 'Grace'],
    'Score': [85, 92, 78, 95, 88, 72, 91]
}
df = pd.DataFrame(data)
# 1. Get the top 5 rows (default behavior)
print(df.head())
# 2. Get the top 2 rows
print(df.head(2))
# 3. Get the bottom 3 rows
print(df.tail(3))
```

```
...      Name  Score
0    Alice     85
1     Bob     92
2  Charlie     78
3   David     95
4     Eva     88
      Name  Score
0  Alice     85
1    Bob     92
      Name  Score
4     Eva     88
5  Frank     72
6  Grace     91
```