

Program 2 : Develop a Multi Stage Dockerfile for Container Orchestration

Step 1 : Create the Project Directory.

1. Create the main folder for your project.
mkdir Program-2
2. Move into the new directory.
cd Program-2

```
1rv24mc101_shreya@shreya-Lenovo-IdeaPad-S145-15IWL:~/program1$ cd ..
1rv24mc101_shreya@shreya-Lenovo-IdeaPad-S145-15IWL:~$ mkdir program2
1rv24mc101_shreya@shreya-Lenovo-IdeaPad-S145-15IWL:~$ cd program2
1rv24mc101_shreya@shreya-Lenovo-IdeaPad-S145-15IWL:~/program2$ mkdir src
1rv24mc101_shreya@shreya-Lenovo-IdeaPad-S145-15IWL:~/program2$ nano src/index.js
1rv24mc101_shreya@shreya-Lenovo-IdeaPad-S145-15IWL:~/program2$ nano package.json
1rv24mc101_shreya@shreya-Lenovo-IdeaPad-S145-15IWL:~/program2$ nano Dockerfile
1rv24mc101_shreya@shreya-Lenovo-IdeaPad-S145-15IWL:~/program2$ █
```

Step 2: Create the Source Code

1. Create the src folder.
mkdir src
2. Create the index.js file inside src.
[index.js](#)

```
GNU nano 7.2 src/index.js
const express = require('express');
const app = express();
const PORT = 3000;
app.get('/', (req, res) => {
    res.send('Hello from Multi-stage Docker!');
});
app.listen(PORT, () => {
    console.log(`Server running on port ${PORT}`);
});
```

Step 3 : Create a package.json

```
>nano package.json
> npm init -y
```

```
GNU nano 7.2 package.json
{
  "name": "program-2",
  "version": "1.0.0",
  "description": "A simple Node.js app with multi-stage dockerfile",
  "main": "dist/index.js",
  "scripts": {
    "start": "node dist/index.js",
    "build": "mkdir -p dist && cp -r src/* dist/"
  },
  "author": "Deepika K",
  "license": "MIT",
  "dependencies": {
    "express": "4.18.2"
  }
}
```

Step 4 : Create a Dockerfile

> nano Dockerfile

```
GNU nano 7.2 Dockerfile
# Stage 1: Build Stage
# We use a full Node.js image and name this stage 'builder'
FROM node:18-alpine AS builder
# Set the working directory inside the container
WORKDIR /app
# Copy package files first to leverage Docker's layer cache
COPY package.json package-lock.json ./
# Install all dependencies (including devDependencies, if any)
RUN npm install
# Copy the rest of the application source code
COPY . .
# Run the build script defined in package.json
# This will create the /app/dist folder inside this stage
RUN npm run build
# ---
# Stage 2: Production Stage
# We start from a fresh, lightweight alpine image
FROM node:18-alpine
# Set the working directory
WORKDIR /app
# Copy ONLY the necessary files from the 'builder' stage
COPY --from=builder /app/package.json ./
COPY --from=builder /app/package-lock.json ./
COPY --from=builder /app/dist ./dist
COPY --from=builder /app/node_modules ./node_modules
# Expose the port the application runs on
EXPOSE 3000

^G Help      ^O Write Out  ^W Where Is   ^K Cut        ^T Execute    ^C Location   M-U Und
^X Exit      ^R Read File  ^_ Replace    ^U Paste      ^J Justify    ^_ Go To Line M-E Red
```

Step 5 : Install node modules with the following commands

> npm install

Step 6 : Execute the Docker build command

> docker build -t program2 .

up to date, audited 70 packages in 2s

14 packages are looking for funding
run 'npm fund' for details

found 0 vulnerabilities

1rv24mc101_shreya@shreya-Lenovo-IdeaPad-S145-15IWL:~/program2\$ docker build -t program2 .

```
[+] Building 17.7s (15/15) FINISHED                                docker:default
=> [internal] load build definition from Dockerfile                  0.2s
=> => transferring dockerfile: 1.08kB                               0.0s
=> [internal] load metadata for docker.io/library/node:18-alpine    4.8s
=> [internal] load .dockerignore                                     0.3s
=> => transferring context: 2B                                         0.0s
=> [builder 1/6] FROM docker.io/library/node:18-alpine@sha256:8d6421d663b4c28fd3ebc498332f249011d118945588d0a35cb9bc4b8c 0.0s
=> [internal] load build context                                     0.5s
=> => transferring context: 2.31MB                                     0.2s
=> CACHED [builder 2/6] WORKDIR /app                                0.0s
=> CACHED [builder 3/6] COPY package.json package-lock.json ./      0.0s
=> CACHED [builder 4/6] RUN npm install                             0.0s
=> [builder 5/6] COPY . .                                           4.1s
=> [builder 6/6] RUN npm run build                                   4.4s
=> CACHED [stage-1 3/6] COPY --from=builder /app/package.json ./    0.0s
=> CACHED [stage-1 4/6] COPY --from=builder /app/package-lock.json ./ 0.0s
=> [stage-1 5/6] COPY --from=builder /app/dist ./dist               0.4s
=> [stage-1 6/6] COPY --from=builder /app/node_modules ./node_modules 0.9s
=> exporting to image                                              0.7s
=> => exporting layers                                              0.5s
=> => writing image sha256:91e149c316e49eaafde78d3c4bbca36ff1a80a47dfcca2ae1ca8ae1784dc5922 0.0s
=> => naming to docker.io/library/program2                         0.0s
1rv24mc101_shreya@shreya-Lenovo-IdeaPad-S145-15IWL:~/program2$
```

Step 7 : Run the Docker run command

```
> docker run -it -p 3000:3000 program2
```

```
1rv24mc101_shreya@shreya-Lenovo-IdeaPad-S145-15IWL:~/program2$ docker run -it -p 3000:3000 program2
Server running on port 3000
█
```

Step 8 : Verifying the details on the browser with the text -> "Hello from multi stage Docker"



http://localhost:3000

Hello from Multi-stage Docker!