

RTS21 – VG TECHNOLOGY: THEORETICAL FOUNDATIONS AND RESEARCH DIRECTIONS

Authors: Physicist Rodica Pop & DeepSeek R1 Assistant

Date: 6/30/2026

ABSTRACT

RTS21 marks a transition from fundamental theory to theoretical technology – **the formalization of the conditions under which the Network can be manipulated**. Building on the equations and principles established in VG and RTS, the episode develops four main directions: reconfiguration of couplings, formalization of intention, formalization of relocation, and the C_{self} –Network interface. Each direction is treated as a problem in theoretical physics, not as engineering. The episode emphasizes that VG technology is not a branch of physical engineering, but an engineering of couplings – a domain that operates at the level of the Network, not at the level of matter.

Keywords: VG technology, coupling reconfiguration, intention, relocation, C_{self} –Network interface, RTS.

1. INTRODUCTION – FROM THEORY TO TECHNOLOGY

So far, VG and RTS have been fundamental theories. We have described the Primary Network, reality slices, couplings, torsion, holography – all at the level of principles. RTS21 makes a decisive step: it transforms these principles into theoretical foundations for technology.

This is not about building a UFO, but about understanding what would be necessary to build one. It is about formalizing the conditions under which couplings can be reconfigured, information can be transferred instantaneously, and a C_{self} can navigate between reality slices.

This is VG technology – a theoretical domain, not a branch of engineering. A domain that establishes the limits and possibilities of the Network.

2. THE THEORETICAL FOUNDATION – WHAT WE ALREADY HAVE

To develop VG technology, we need a solid mathematical base. We already have it partially:

- The one-inch equation – describes the structure of the Network:

$$H = \sum_i \left(\frac{p_i^2}{2} + \frac{1}{2} \omega_i^2 q_i^2 \right) + \sum_{i < j} K_{ij} q_i q_j$$

- The Grand Equation – includes consciousness and self-creation:

$$H_{\text{total}} = H + \mathcal{L}_{\text{vivo}}(\phi, \psi, NN)$$

- The evolution equation for average coupling – for the Hubble Tension:

$$H(t) = -\frac{1}{\alpha} \cdot \frac{J_{\text{med}}(t)}{J_{\text{med}}(t)}$$

These are the tools we have.

3. WHAT WE LACK – A SKETCH OF DIRECTIONS

For these equations to become technology, we need:

- Formalization of coupling reconfiguration – how can K_{ij} be controlled from outside.
- Formalization of intention – how can the intention of a C_{self} be encoded into a nodal signal.
- Formalization of relocation – how a nodal configuration passes from one set of coordinates to another.
- Formalization of the C_{self} – Network interface – how a C_{self} communicates with the subquantum wall.

These are the four directions we will develop in RTS21. These four directions are not hypothetical. They are direct consequences of the RTS equations, and their formalization is the next natural step in the development of the theory.

4. FORMALIZATION OF COUPLING RECONFIGURATION – THE FIRST STEP TOWARD VG TECHNOLOGY

To control a coupling K_{ij} from outside, we must first understand what a coupling is and how it can be modified. In RTS, a coupling is a nodal interaction – a dynamic relationship between two nodes, which can be described as:

$$K_{ij} = K_0 \cdot f(\text{spin}, \text{frequency}, \text{nodal distance})$$

This expression tells us that a coupling is not a constant, but a function of several parameters. If we can influence these parameters from outside, we can modify the coupling.

How can we influence these parameters from outside?

1. Through magnetic or electromagnetic fields – spin is sensitive to external fields. A controlled application of a field could reorient spins and, implicitly, modify the couplings.
2. Through acoustic or vibrational resonance – the natural frequencies of nodes can be pumped (as discussed in parametric resonance), changing the coupling state.
3. Through the intention of a C_{self} – a sufficiently coherent C_{self} can influence couplings through simple intention, as seen in the case of mediators or initiates.

What does this mean for VG technology?

- Materials with adjustable coupling – we could design materials in which K_{ij} is modified externally, changing their properties in real time.

- Nodal switching devices – we could create switches that block or allow a coupling, using resonance or external fields.
- C_{self} –device interfaces – we could design devices that respond to the intention of a C_{self} , transmitting information or acting in the Network.

5. FORMALIZATION OF INTENTION – HOW CAN THE INTENTION OF A C_{SELF} BE ENCODED

If we want a C_{self} to control couplings, we must understand how its intention can be translated into a nodal signal.

In RTS, intention is described by the function:

$$\Phi_{\text{intention}} = \int \mathcal{L}_{\text{vivo}}(\phi, \psi, NN) dt$$

This is not an equation to be calculated, but a definition of what intention means in RTS language:

- ϕ – the state of the Network at the moment of intention.
- ψ – the consciousness of the C_{self} (orientation, coherence, clarity).
- NN – the constant number of nodes, which ensures that intention is anchored in the Network.

How is intention translated into a nodal signal?

- Intention locally modifies the couplings K_{ij} in the area where the C_{self} is located.
- This modification is detectable by other nodes and can be interpreted as a signal.
- If the intention is coherent and repeated, it can create a stable pattern – a kind of "protocol" for communicating with the Network.

What does this mean for VG technology?

- C_{self} —Network communication protocols – we could develop techniques to make intention standardized and reproducible.
- Intention amplification devices – we could design devices that amplify the intention of a C_{self} , making it easier for the Network to detect.
- Nodal antennas – devices that translate intention into modulated couplings, like a radio communication.

6. FORMALIZATION OF RELOCATION – HOW A CONFIGURATION TRANSITIONS FROM ONE SET OF COORDINATES TO ANOTHER

Relocation is the process by which a nodal configuration (a C_{self} , a vehicle, an object) changes its nodal anchorage – that is, it moves from one set of nodal coordinates to another, without traversing physical space.

What does relocation involve?

1. Decoupling – the configuration decouples from its current couplings $K_{ij} \rightarrow 0$.
2. Reconfiguration – the couplings rearrange to form a new stable configuration.
3. Recoupling – the configuration anchors to the new nodal coordinates.

Mathematically, this process can be described as:

$$\Delta \mathbf{r}_{\text{nodal}} = \int_{t_1}^{t_2} \Phi_{\text{intention}} \cdot \frac{dK_{ij}}{dt} dt$$

where:

- $\Delta \mathbf{r}_{\text{nodal}}$ is the relocation vector in nodal space.
- $\Phi_{\text{intention}}$ is the intention of the C_{self} .
- dK_{ij}/dt is the rate of reconfiguration of the couplings.

What does this mean for VG technology?

- Resonant vehicles – we could design nodal configurations that are programmed to relocate to a specific intention.
- Artificial portals – we could create access points where couplings are weak enough to allow relocation.
- Inter-slice navigation – we could develop maps of nodal space, to know where a configuration can relocate.

7. FORMALIZATION OF THE C_SELF–NETWORK INTERFACE

The last step is to understand how a C_{self} communicates with the Network. This interface is essential for all other technologies.

In RTS, the C_{self} –Network interface is described by the coupling between the C_{self} and the subquantum wall:

$$J_{\text{self-wall}} = \Phi_{\text{intention}} \cdot \psi \cdot K_{\text{resonance}}$$

This equation says that:

- $J_{\text{self-wall}}$ is the intensity of the interface.
- $\Phi_{\text{intention}}$ is the intention of the C_{self} .
- ψ is the coherence of its consciousness.
- $K_{\text{resonance}}$ is the resonance coupling with the wall.

What does this mean for VG technology?

- Consciousness antennas – devices that could measure and amplify $J_{\text{self-wall}}$ making the interface more accessible.
- Communication protocols – standards by which a C_{self} could request information from the wall and receive it in an intelligible form.
- Nodal healing – by amplifying the interface, we could reconfigure the couplings in the C_{body} to restore coherence.

8. CONCLUSION – A TECHNOLOGY BASED ON PRINCIPLES, NOT ON DEVICES

VG technology is not physical engineering. It is coupling engineering – a technology that operates at the level of the Network, not at the level of matter.

The four directions we have sketched:

1. Formalization of coupling reconfiguration.
2. Formalization of intention.
3. Formalization of relocation.
4. Formalization of the C_{self} –Network interface.

...are the theoretical foundations of any VG technology. They do not build devices, but they define the conditions under which devices could be built. VG technology is not a branch of physical engineering, but an engineering of couplings – a domain that operates at the level of the Network, not at the level of matter.

WHAT'S NEW IN SCIENCE?

RTS21 introduces for the first time a theoretical framework for VG technology – an engineering of couplings, not of matter. The episode formalizes four essential directions: coupling reconfiguration, intention encoding, nodal relocation, and the C_{self} -Network interface. Each direction is treated as a theoretical physics problem, not as an engineering manual. RTS21 thus provides a solid foundation for future research in the field of VG technology.