

ECE220 Midterm 1 Review

Author: Members of HKN

Fall 2024

1 Memory-Mapped I/O

(a) What is the difference between a callee-saved and a caller-saved register?

(b) What is the difference between polling I/O vs. Interrupt-Driven I/O?

(c) Fill in the blanks of the following statements relating to Memory-Mapped I/O.

Certain device registers are _____ to certain _____ locations. However, the registers physically are _____ from the memory. Memory-mapped device registers are a common way to _____ computer systems with devices.

2 Traps and Subroutines

(a) Why would we need to have service routines (known as TRAPs)? Name three reasons.

(b) **Shifting** :(

Write a subroutine that performs a logical left shift of R1 by the value stored in R2, and reports the result in R1. You may assume that R2 contains a positive number. Only R6 and R1 can be modified/read from, and only R2 can be read from.

```

.ORG x3100
SHIFTL
; code starts here

```

```

; code ends here
RET
.END

```

(c) **Permute Quarters:**

A value stored in a 16-bit LC3 register can be divided into four equal parts of four bits each:

$$X = X_1 \ X_2 \ X_3 \ X_4$$

Write a subroutine, PERMUTE, that reorders R5 as follows:

$$R5 = X_1 \ X_3 \ X_2 \ X_4$$

Assume all registers are caller-saved. You should not use loops. You may assume the existence of a DIV subroutine, which divides as expected. There are also some labels for you to use. [Hint: the previous subroutine might be useful]

```

.ORG x3100
; assume code for entry point is omitted
;
;
;

```

```

PERMUTE
; write the code here

```

```

; code ends here
RET
; code omitted
;
.HALT ; labels below
CLEARX2X3 .FILL #0xF00F
FOUR .FILL #4
X2 .FILL 0x0F00
X3 .FILL 0x00F0
SAVER7 .FILL #0
.END

```

(d) **Trap Concepts**

Given the figures below, determine the memory address of the TRAP vector table that will be accessed and which TRAP service routine will be executed.

User Program ASM Code	
	;
	;
	TRAP 0xAA
	;
	;

Address	Value
0xAA	0x05C0
0x1AA	0x05D0
0x2AA	0x05E0
0x3AA	0x05F0
...	
0x05C0	Routine α
0x05D0	Routine ω
0x35C0	Routine κ
0x35D0	Routine π

Trap Vector Table Entry:

- a. 0xAA
- b. 0x1AA
- c. 0x2AA
- d. 0x3AA

Trap Routine Executed:

- a. α
- b. ω
- c. κ
- d. π

Of the following steps executed during a TRAP, in what order are they executed?

- a. Return to User Program
- b. Execute Trap Routine
- c. Access Trap Vector Table

- 1)
- 2)
- 3)

3 Stack Operations

(a) Given the following input sequence of numbers: “24609846117”, write a sequence of pushes and pops that produces this output: “64098116472”.

(b) Two Parts:

i. Write the expression $((4 * 2) + 1) / 3 + 5$ in postfix notation.

ii. Write the following postfix expressions in mathematical notation and indicate what they evaluate to (if they are not valid, write “not valid”)

* 6721*-5/*

* 83+632-+1*+-

* 2233*2+5-+8/-

* 89+6-44

(c) **MP2 Postfix Calculator:** This sequence is input to the console: $445+3/8*-=$ Draw the stack (and where the stack pointer points to) after:

i. 5 has been input

ii. + has been input

iii. * has been input

iv. = has been input

Assume that the stack pointer points to the address **one above the most recent-pushed entry**. Remember that a POP does NOT remove an item from memory but simply changes the stack pointer!

4 C Programming

(a) What will be the output of the following C Program?

```
1 int main() {
2     int i;
3     for (i = 3; i < 13; i ++ )
4     {
5         if (i % 3 == 1)
6         {
7             printf("Bong\n");
8         }
9         if (i % 2 == 0)
10        {
11            printf("Ding\n");
12            continue;
13        }
14        printf("Odd\n");
15    }
16    return 0;
17 }
18
19
```

(b) What is the return value of this program?

```
1 int foo(int x, int y);
2
3 int main()
4 {
5     int x = 3;
6     int y = 4;
7
8     x = y + foo(x,y);
9     y = x - foo(x,y);
10
11     return x + y;
12
13
14
15 }
16
17 int foo(int x, int y)
18 {
19     int a = x + y;
20     int b = x - y;
21     a += x--;
22     y ++;
23     a += (y + 1);
24     return b + a + --x;
25
26
27 }
28
29
```

5 Conceptual Questions

(a) What is the order of access for a stack abstract data type?

(b) Define overflow and underflow.

(c) True or False. Please explain your answer.

- i. Interrupts are more efficient than polling.
- ii. There are up to 8 possible TRAP service routines.
- iii. TRAPs shield programmers from system specific details.
- iv. PSR and PC are pushed to the User stack before executing an interrupt service routine.
- v. An item is deleted after being pushed off the stack.
- vi. TRAP service routines are provided as part of the system code.