Engine Types	1600	1600 S	1600 S-90
Rear  Seats  Number  Front  Rear	Engine hood is hinged at front. Held open by catch engaging and disengaging automatically. Opened from inside car.  2/2 2 adjustable individual seats, backs can be lowered for reclining two occasional seats. The back rest hinges forward to serve as luggage rack.		
Instrument panel	Speedometer with total mileage recorder and trip mileage recorder, illuminated Tachometer fitted with high beam indicator light and direction indicator pilot light, illuminated Combination instrument comprising remote-reading oil thermometer, fuel gauge, generator indicator light, and oil pressure warning light, illuminated Windshield wiper knob, ignition/starting switch, light, hand throttle knob, socket for inspection lamp, cigar lighter, ash tray, glove compartment with lock, grab handle Direction indicator and low beam headlight switch on steering column. Steering wheel with horn and button for headlight signal-ling		
Internal trimming and fittings Floor Tunnel Front side panels Doors and side walls Dome Heating	covered with rubber mat front covered with rubber, rear with carpeting covered with carpeting padded fitted with plastic lining hotair heating with remote control, 2 defroster nozzles for the windshield and 2 outlets for hot air in the side members under the doors		
Make	Golde approx. 260 (10.23) approx. 780 (30.7)		
Miscellaneous  Bumpers	at front and rear, ead in thief-proof location under the front hood under the front hood	h with two overriders n under the front hood	
Dimensions and Weights	MAIN.		
Wheelbase, mm (in.) Track, front, mm (in.) Track, rear, mm (in.) Length, mm (in.) Width, mm (in.) Height (empty), mm (in.) Overhang, front, mm (in.) Overhang, rear, mm (in.) Ground clearance, mm (in.) Bulk clearance, mm (in.) Weight, empty, acc. to DIN,kg (lbs.)	(51.5) 865 (34.05) 1055 (41.5) 150 (5.9) 140 (5.51)	330 (52.4); Hardtop 1315 ardtop 900 (1985); Road	