Engine Type	1600 C	1600 SC
:		44 A 44
Windows Windshield Door Windows	Single piece, constant radius Crank-down windows, quarter-panel wind wings in Coupe	
Side Windows	and Cabriolet/Hardtop Opening outward, with arresting latch Single piece, contoured shape	
Glass Type	Windshield of laminated safety glass, rear and side windows of tempered safety glass	
Windshield Wipers	Electric, 2 wiper arms moving parellel to each other	
Compartment Lids Front	Hinged at rear with automatically locking and releasing hold-open locks, theft-proof from outside, lid lock release under dashboard, lid secured by snap-bolt and safety latch	
Rear		ent lid opening at rear, hinges with au- ng and releasing hold-open locks, lock ver's seat
Seats		
Seating CapacityFrontRear	,	2/2 adjustable bucket seats dation seats with folding backrests which
Instrument Panel	Speedometer with indicators for total mileage and trip mileage, illuminated dial Tachometer with built-in control lamps for high-beam indicator, parking light and blinkers, illuminated dial Combination instrument containing fuel gauge, oil temperature gauge, generator control light, oil pressure control light, and parking brake control light, illuminated dial Windshield wiper switch (progressively variable), ignition/starter switch, light switch, cigar lighter (socket can be used as an electrical outlet), ventilation control, locking glove compartment, ashtray, and hand grip; Combination switch on steering post, controlling directional signals, high/low headlamp beams, and light-signal (head-lamp flicker) Steering wheel with horn button	
Interior Fittings Floor	Covered with rubber mat Forward part covered with rubber, rear with fabric Covered with fabric Upholstered Lined with plastic material Hot air heating with remote control, 2 defroster outlets for the windshield, 2 defroster jets for rear window, 2 hot air outlets on floor level below door posts Fresh air for heating is drawn through slits in engine compartment lid and for cold air ventilation through inlet below windshield; outlets are the defrosters and openings on floor level below door posts	
Sliding Sun Roof Type Aperture Length Aperture Width	Golde (electrically operated) approx. 260 mm (10.2 in.) approx. 780 mm (30.7 in.)	