

FULLSTACK DEVELOPMENT – DAY 5 SUMMARY

TODAY COVERED TOPICS:

- ❖ TYPE CASTING
- ❖ TYPES OF TYPECASTING
- ❖ TYPE CASTING WITH CHARACTERS
- ❖ OPERATORS
- ❖ USER INPUT

➤ TYPE CASTING:

Type casting is used to convert one data type into another data type.

➤ TYPES OF TYPE CASTING:

1. Widening Casting:

Widening is also called as Implicit Typecasting. It used to convert small data type into large data type in automatically.

Example:

```
public class Widening {  
    public static void main ( String [] args){  
        int num =10;  
        double d=num;  
        System.out.println(d);  
    }  
}
```

2. Narrowing Casting:

Narrowing is also called explicit typecasting.it used to convert large datatype into small datatype in manually.

Example:

```
public class Narrowing{  
    public static void main(String [] args){  
        double d = 53.4;  
        int num=(int) d;  
    }  
}
```

➤ TYPE CASTING WITH CHARACTERS

Character used to store internally as Unicode numbers.

```
Char c = 'A';  
int ascii =c;  
System.out.println(ascii);
```

➤ OPERATORS:

Operators is a symbol used to perform operation in variables or values.

TYPES OF OPERATORS:

- Arithmetic Operators

- Assignment Operators
- Relational Operators
- Logical Operators
- Unary Operators
- Ternary Operators
- Bitwise Operators

✓ **Arithmetic Operator:**

```
public class Arithmetic{
    public static void main (String [] args){
        int a= 5 , b=6;
        System.out.println("Addition:"+( a+b));
        System.out.println("Subtraction:"+( a-b));
        System.out.println("Multiple"+( a*b));
        System.out.println("Divition:"+( a%b));
    }
}
```

✓ **Assignment Operator:**

```
public class Assignment {
    public static void main (String [] args){
        int a=5;
        a+=5;
        a-=4;
        a*=2;
        a/=4;
        System.out.println("Result:"+a);
    }
}
```

✓ **Relational Operator:**

```
public class Relational {
    public static void main (String [] args){
        int a=5,b=10;
        System.out.println(a==b);
        System.out.println(a!=b);
        System.out.println(a>b);
        System.out.println(a<b);
        System.out.println(a>=b);
    }
}
```

✓ **Logical Operators :**

```
public class Relational {
    public static void main (String [] args){
```

```

int a=5,b=10;
System.out.println(a<b&& b>3);
System.out.println(a>b || a==5);
System.out.println(!a==5));
}
}

```

✓ **Unary Operator:**

```

public class Unary {
    public static void main (String [] args){
        int a=5;
        System.out.println("a++:" + (a++));
        System.out.println("++a:" + (++a));
        System.out.println("a--:" + (a--));
        System.out.println("--a:" + (--a));
        System.out.println("Final a :"+a);
    }
}

```

✓ **Ternary Operator:**

Syntax:

Variable=(condition)? valueIfTrue : valueIfFalse;

```

public class Ternary {
    public static void main (String [] args){
        int age =20;
        String result = (age>=20)? "Eligible " : Not Eligible;
        System.out.println(result);
    }
}

```

➤ **USER INPUT:**

User Input is a user give input to the programmer . it use scanner class.

```

import java. util. Scanner;
public class UserInput {
    public static void main (String [] args){
        Scanner sc=new Scanner(System.in);
        System.out.println("Enter your name:");
        String name = sc.nextLine();
        System.out.println("Enter your age:");
        Int age = sc.nextInt();
        System.out.println("Hello:"+name+"!Your age"+age + "years old.");
    }
}

```