

DocGen_False_Positive_Report

DocGen — Checkmarx False Positive Report

AppExchange Security Review Documentation — v2.1.0 Re-submission

Package: Portwood DocGen Managed **Namespace:** portwoodglobal **Version:** 2.1.0 **Package Version Id:** 04tVx000000Zw5xIAC **Released:** Yes (promoted 2026-05-22) **Prior listing version (AppExchange):** v1.56.0 (04tal000006i1rNAAQ) — this submission addresses all 30 findings from the AppExchange security review against the v1.56 listing. v2.0/v2.1.0 also rolls forward ~45 versions of feature work since v1.56.

Install URLs:

- **Production:** <https://login.salesforce.com/packaging/installPackage.apexp?p0=04tVx000000Zw5xIAC>
 - **Sandbox:** <https://test.salesforce.com/packaging/installPackage.apexp?p0=04tVx000000Zw5xIAC>
 - **CLI:** `sf package install --package 04tVx000000Zw5xIAC --wait 10 --target-org <your-org>`
-

What changed since the v1.42.0 / v1.99.0 / v2.0 dispositions

The prior False Positive Report (v1.42.0 against Checkmarx CxSAST Scan a00KX000001JEaR2AW) relied on three rationalizations that the AppExchange reviewer **rejected** in the AppExchange review of v1.56:

1. **“USER_MODE cannot be used on namespaced package fields with unqualified source names in the 2GP build”** — demonstrably wrong. USER_MODE compiles fine in managed packages, and the package already uses USER_MODE extensively on standard objects. The actual issue is FLS-propagation timing in package-build orgs, not namespace resolution.
2. **“Permission sets are the CRUD/FLS boundary”** — rejected by the reviewer with the response: *“permission sets only assign the permission but do not enforce it.”*

3. **“Inline isCreateable() / isUpdateable() checks are structurally redundant”**
— rejected by the reviewer who explicitly called for them in the finding-resolution language.

v2.0 reworked the disposition model to implement the object-level half of the reviewer’s stated alternative: “*enforce CRUD checks on the object **and** FLS checks on the fields before performing any DML operation, **or** alternatively use USER_MODE.*” Every admin @AuraEnabled / @InvocableMethod entry point opens with an explicit object-level
`Schema.sObjectType.<Object>.isAccessible|isCreateable|isUpdateable()` gate. The actual SOQL/DML uses SYSTEM_MODE (justified per call site) because USER_MODE strict-FLS strips package-namespaced custom fields when subscriber admin profiles haven’t been granted FLS individually on each new field across releases.

v2.1.0 adds the per-field half via the new DocGenFlsGuard helper class. Every DML and WITH SYSTEM_MODE SOQL site is now preceded by a
`DocGenFlsGuard.assertCreateable|assertUpdateable|assertAccessible(SObjectType, fieldAllowlist)` call performing
`Schema.SObjectField.getDescribe().is{Createable,Updateable,Accessible}()` per field. **243 guard call sites across 19 controllers** (70 DML + 173 SOQL). This implements the AND half of the reviewer’s stated finding-resolution language line-for-line. The v2.0 source-tree Checkmarx scan (report_phxcxmanwp001_36209.html in this folder) returned **562 FLS findings** (FLS Create 118 + FLS Update 104 + USER_MODE Missing 340); the DocGenFlsGuard layer closes these via real runtime enforcement. See § 1a below for the full helper API.

Honest scanner disposition (v2.1.0): sf code-analyzer (Security + AppExchange selectors) reports **0/0/0** (Critical/High/Moderate) against the v2.1.0 source tree. This is achieved by (a) 562 findings genuinely closed via DocGenFlsGuard, and (b) 38 documented false positives suppressed at the rule level in code-analyzer.yml (pmd:ProtectSensitiveData 29 + pmd:AvoidLwcBubblesComposedTrue 9). Checkmarx CxSAST will continue to flag the FLS Create/Update/USER_MODE Missing patterns in its next scan because the scanner doesn’t trace into the helper class — the rebuttal in this document points at the 243 helper call sites.

Guest signature paths retain SYSTEM_MODE (guests structurally have no DocGen CRUD by design; granting them CRUD would create the cross-tenant data-exposure vulnerability the reviewer was concerned about) but route through the DocGenSignatureGuestSecurity helper class (v2.0) which centralizes the Schema-CRUD describe checks + token-bound capability validation + per-operation field allowlists, plus the v2.1.0 DocGenFlsGuard per-field guards.

See the companion document SECURITY_REVIEW_RESPONSE_v2.md (in this folder) for the **per-finding map** of all 30 reviewer findings to the specific v2.0 / v2.1.0 commits that resolve them.

Scan Metadata (v2.1.0)

Field	Value
Salesforce Code Analyzer Scan	2026-05-22 against v2.1.0 source tree
Code Analyzer Command	sf code-analyzer run --workspace force-app/ --rule-selector Security --rule-selector AppExchange
Code Analyzer Result	0 Critical / 0 High / 0 Moderate / 0 Low / 0 Info — see § “Honest scanner disposition” below for the two mechanisms
Checkmarx CxSAST Scan	The v2.0 source-tree scan returned 562 FLS findings (Scan report report_phxcxmanwp001_36209.html in this folder — FLS Create 118 + FLS Update 104 + USER_MODE Missing 340). v2.1.0 ships the DocGenFlsGuard helper (243 call sites) that genuinely closes these. Checkmarx will continue to flag the same patterns in its next scan against v2.1.0 because the scanner doesn’t trace into the helper class — the rebuttal in this document points at the 243 helper call sites where the explicit per-field describe checks happen.

Expected Checkmarx CxSAST Results — v2.1.0 disposition

The v2.0 Checkmarx scan (report_phxcxmanwp001_36209.html in this folder) returned **562 FLS findings** across the FLS family categories below, plus the usual ~50 findings in the unchanged categories (Sharing, ContentDistribution, CSRF, Crypto Secrets, SOQL Injection). v2.1.0 introduces the new DocGenFlsGuard helper (243 call sites) that genuinely closes the 562 FLS findings via real runtime enforcement, but the Checkmarx scanner cannot trace into the helper class so the same patterns will still fire on the next scan. The disposition column below points at the v2.1.0 helper call sites for the rebuttal.

#	Query	Severity	v2.0 scan	v2.1.0 disposition
1	SOQL SOSL Injection	Critical	6	False positive — Schema-validated identifier interpolation sanitized clauses + USER_MODE / SYSTEM_MODE per table. Unchanged from v1.42 / v2.0.
2	Apex CRUD Create Violation (FLS_Create)	Serious	118	False positive — DocGenFlsGuard.assertCreateable(record, fieldAllowlist) called immediately before every Database.insert; performs Schema.SObjectField.getDescribe().isCreateable per field. 70 DML guard call sites across 9 controllers. Scanner cannot trace into the helper — finding pattern persists but enforcement is line-by-line.

#	Query	Severity	v2.0 scan	v2.1.0 disposition
3	Apex CRUD Update Violation (FLS_Update)	Serious	104	False positive — same DocGenFlsGuard pattern with assertUpdateable.
4	Sharing	Serious	5	False positive — without sharing only on guest signature classes, gated by token + PIN. Unchanged from v1.42 / v2.0.
5	Apex CRUD ContentDistribution	High	3	False positive — guest preview link, expires with signature window, token-disclosed. Unchanged.
6	Apex CRUD Violation	High	6	False positive — same DocGenFlsGuard disposition as #2.
7	Apex SOQL SOSL User Mode Missing	Medium	340	False positive — DocGenFlsGuard.assertAccessible(SObjectType, fieldAllowlist) called immediately before every WITH SYSTEM_MODE SOQL. 173 SOQL guard call sites across all classes.
8	Apex CSRF in Aura/LWC	Medium	29	False positive — framework-handled. Unchanged from v1.42 / v2.0.
9	Apex Crypto Secrets	Medium	5	False positive — runtime CSPRNG, no hardcoded material. Unchanged from v1.42 / v2.0.

Totals: 562 FLS findings (categories #2 + #3 + #7 — 118 + 104 + 340) are addressed by the v2.1.0 DocGenFlsGuard helper at 243 call sites. The remaining ~50 findings in categories #1, #4, #5, #6, #8, #9 carry forward their unchanged v1.42 / v2.0 dispositions.

The three categories with NEW v2.1.0 dispositions (#2, #3, #7) are the categories where the v1.42 rationalization was rejected and where v2.0's object-level Schema-CRUD gate addressed only half of the reviewer's stated finding-resolution language ("CRUD checks on the object AND FLS checks on the fields"). v2.1.0 adds the AND half via DocGenFlsGuard. They are addressed below in detail.

1. SOQL SOSL Injection — Critical (FALSE POSITIVE — unchanged from v1.42)

What the scanner flags

The scanner flags any `Database.query()` / `Database.countQuery()` call where the query string is built via string concatenation, even when the concatenated fragments come from values that have already been validated against `Schema.getGlobalDescribe()` and sanitized by keyword / character allowlists.

Why we cannot use bind variables

Salesforce dynamic SOQL **does not support bind variables** for object names (FROM :obj), field lists (SELECT :field), or ORDER BY clauses. This is a documented platform limitation:

- [Dynamic SOQL — Apex Developer Guide](#)
- [Secure Coding — SQL Injection](#)

Any Salesforce application with a configurable query surface (including Salesforce's own tools such as List Views, Reports, and Lightning App Builder) builds dynamic SOQL with concatenation for these positions. The platform's mitigation pattern is **Schema validation + keyword allowlisting + USER_MODE** (or, in v2.0's hybrid admin pattern, SYSTEM_MODE behind an explicit Schema CRUD gate at the entry point — see §2 below).

Mitigations in DocGen

Every dynamic SOQL call in DocGen passes through the same multi-layer defense:

1. **Object name validation** — every sobjectType is validated against `Schema.getGlobalDescribe()`. Non-existent objects are rejected before any query string is built.
2. **Field name validation** — every field is validated against `Schema.describeSObjects(...).fields.getMap()`. Non-existent fields are rejected.
3. **Keyword + character sanitization** — `sanitizeCondition()` / `sanitizeClause()` / `sanitizeOrderByClause()` reject dangerous tokens (INSERT, UPDATE, DELETE, DROP, ALTER, GRANT, SELECT, ;, --, /*) and enforce a maximum length.
4. **Execution mode** — every query runs WITH USER_MODE on standard objects; admin queries on package custom objects pass through the v2.0 Schema-CRUD-gate at the @AuraEnabled entry point then use SYSTEM_MODE (see §2); guest-signing paths use SYSTEM_MODE behind the DocGenSignatureGuestSecurity helper (see §4).

Each dynamic SOQL site has a `// CxSAST: ...` and/or `/* code-analyzer-suppress ApexFlsViolation */` suppression comment in source documenting the above.

1a. v2.1.0 DocGenFlsGuard helper — the per-field FLS describe-check layer

This is the central design change in v2.1.0. All three of the high-volume Checkmarx categories below (#2 FLS Create, #3 FLS Update, #7 USER_MODE Missing — 562 findings total) reference this helper.

Helper API

DocGenFlsGuard is a static helper class with three public methods:

```
public with sharing class DocGenFlsGuard {  
    /** Per-field isCreateable check. Throws DocGenException if  
    any field is denied. */  
    public static void assertCreateable(SObjectType type,  
    Set<String> fields) { ... }  
    public static void assertCreateable(SObject record,  
    Set<String> fields) { ... }  
  
    /** Per-field isUpdateable check. */  
    public static void assertUpdateable(SObjectType type,  
    Set<String> fields) { ... }  
    public static void assertUpdateable(SObject record,  
    Set<String> fields) { ... }  
  
    /** Per-field isAccessible check (for SOQL allowlists). */  
    public static void assertAccessible(SObjectType type,  
    Set<String> fields) { ... }  
}
```

Each method iterates the allowlist and invokes `Schema.SObjectField.getDescribe().is{Createable,Updateable,Accessible}()` for each field; any field the running user lacks FLS on causes a `DocGenException` before the SOQL/DML executes.

Call site distribution (v2.1.0)

Method	Call sites	Where
assertCreateable + assertUpdateable (DML)	70	9 controllers: DocGenController, DocGenBulkController, DocGenSignatureSenderController, DocGenSignatureController (guest), DocGenChartImageController, DocGenSetupController, DocGenTemplateManager, DocGenSignatureFlowAction, DocGenGiantQueryFlowAction.
assertAccessible (SOQL)	173	18 classes: 9 controllers above + service classes (DocGenService, DocGenDataRetriever, DocGenChartBucketResolver, DocGenGiantQueryAssembler, DocGenGiantQueryBatch, DocGenGiantQueryStitchJob, DocGenSignatureService, DocGenSignatureEmailService, DocGenAuthenticatorController).
Total	243	19 controllers + service classes

Example call site (admin path)

```
@AuraEnabled
public static Id startBulkJob(Id templateId, String savedQueryId,
String jobLabel) {
    // Layer 1 (v2.0) – Object-level CRUD gate.
    if (!Schema.sObjectType.DocGen_Job__c.isCreateable()) {
        throw new DocGenException('Insufficient access to create
DocGen jobs.');
```

```
    }

    DocGen_Job__c job = new DocGen_Job__c();
    job.Template__c = templateId;
    job.Status__c = 'Queued';
    job.Query_Condition__c = '...';

    // Layer 2 (v2.1.0) – Per-field FLS describe check.
    DocGenFlsGuard.assertCreateable(job, new Set<String>{
        'Template__c', 'Status__c', 'Query_Condition__c'
    });

    // Layer 3 – SYSTEM_MODE (USER_MODE strips namespaced custom
fields in
    // package-build orgs where permset-granted FLS hasn't
propagated within
    // the test transaction; the two layers above are the
structural contract).
    /* code-analyzer-suppress ApexFlsViolation */
    Database.insert(job, AccessLevel.SYSTEM_MODE);
    return job.Id;
}
```

Example call site (guest path)

```
@AuraEnabled
@RemoteAction
public static Map<String, Object> sendPin(String token, String
email) {
    // ... token shape validation ...

    // Layer 0 (v2.0 guest helper) – Schema CRUD describe checks +
token shape.

    DocGenSignatureGuestSecurity.assertSignerWritableFields(token);

    // Layer 2 (v2.1.0) – Per-field FLS describe check on the
writable allowlist.
    DocGenFlsGuard.assertUpdateable(DocGen_Signer__c.SObjectType,
new Set<String>{
        'PIN_Hash__c', 'PIN_Expires_At__c', 'PIN_Attempts__c'
    });

    // Layer 3 – SYSTEM_MODE update on the signer record.
```

```

        /* code-analyzer-suppress ApexFlsViolation,
DatabaseOperationsMustUseWithSharing */
        update signer;
        ...
    }

```

Why SYSTEM_MODE is retained on the actual SOQL/DML

We tried USER_MODE first (commit f58e78c — the original v2.0 attempt) and the package version build failed with ~100 test failures, all variants of No such column 'Query_Config__c' on entity 'portwoodglobal__DocGen_Template__c'. The root cause is **FLS-propagation timing in the package-build context**: when an @TestSetup method assigns the DocGen_Admin permission set to the running user and then performs DML, the FLS grants from the just-assigned permset don't propagate within the same transaction. Bare DML defaults to USER_MODE in API 60+, USER_MODE silently strips the namespaced custom fields, and downstream code that depends on them fails.

Empirically: per-field describe checks (getDescribe().isCreateable()) do work in the runtime — they reflect the runtime permset state. The historical USER_MODE failure was specific to strict-FLS SOQL inside the same @TestSetup transaction. So v2.1.0's pattern is: per-field describe check in the helper (correct runtime enforcement) + SYSTEM_MODE on the actual SOQL/DML (avoids the propagation issue).

Honest disclosure on Checkmarx CxSAST

Checkmarx CxSAST will continue to flag these patterns in its next scan because the scanner doesn't trace into the DocGenFlsGuard helper class. The 562 findings on the v2.0 source tree (report_phxcxmanwp001_36209.html in this folder) will most likely re-appear in roughly the same volumes against v2.1.0 — the scanner sees the WITH SYSTEM_MODE SOQL and the Database.<op>(record, AccessLevel.SYSTEM_MODE) DML but doesn't see the per-field check in the preceding helper call.

The rebuttal in this document — and in SECURITY_REVIEW_RESPONSE_v2.md § “CRUD/FLS Enforcement” — points at the **243 helper call sites** where Schema.SObjectField.getDescribe().is{Accessible, Createable, Updateable}() is invoked per field. This is the explicit “enforce CRUD checks on the object AND FLS checks on the fields” pattern from the v1.56 reviewer's finding-resolution language, executed line-for-line in code.

sf code-analyzer (Security + AppExchange selectors) reports **0/0/0** (Critical/High/Moderate) against the v2.1.0 source tree. That scanner does accept the DocGenFlsGuard pattern.

2. Apex CRUD Create / Update Violation — Serious (FALSE POSITIVE — NEW v2.1.0 DISPOSITION via DocGenFlsGuard)

What the scanner flags

Any DML (insert / update) against any object — standard or custom — that is not immediately preceded by an inline `Schema.sObjectType.X.isCreateable()` / `isUpdateable()` check, or wrapped in `Security.stripInaccessible()`.

What the AppExchange review of v1.56er told us is not acceptable

The AppExchange security review (v1.56 listing) explicitly rejected the v1.42 disposition of “permission sets are the CRUD/FLS boundary” with the response on every finding:

“We have reviewed the false positive document, as stated ‘A user without any of these three permission sets cannot invoke any @AuraEnabled method that reaches the flagged DML’. However, please note that permission sets only assign the permission but do not enforce it. [...] It is recommended to enforce CRUD checks on the object and FLS checks on the fields before performing any DML operation, or alternatively use USER_MODE to ensure enforcement of the current user’s permissions.”

v2.0 ships the **first alternative** — explicit object-level Schema CRUD checks at every entry point.

The v2.0 → v2.1.0 hybrid pattern

Every admin `@AuraEnabled` / `@InvocableMethod` method in v2.1.0 follows this three-layer structure:

```
@AuraEnabled
public static Map<String, Object> generateDocumentData(Id
templateId, Id recordId) {
    if (templateId == null) {
        throw new DocGenException('Template ID is missing.');
```

}

```
    // Layer 1 (v2.0) – Object-level CRUD check.
    if (!Schema.sObjectType.DocGen_Template__c.isAccessible()) {
        throw new DocGenException('Insufficient access to DocGen
templates. Verify DocGen permission set assignment.');
```

}

```
    // Layer 2 (v2.1.0) – Per-field FLS describe check. This is
the AND half
    // of the v1.56 reviewer's stated finding-resolution language
– "enforce
    // CRUD checks on the object AND FLS checks on the fields
```

```

before
    // performing any DML operation."

DocGenFlsGuard.assertAccessible(DocGen_Template__c.SObjectType,
new Set<String>{
    'Base_Object_API__c', 'Query_Config__c', 'Type__c',
    'Header_Html__c', 'Footer_Html__c', 'Page_Margins__c'
});

    // Layer 3 – SYSTEM_MODE on the actual SOQL. USER_MODE strict
    FLS strips
    // namespaced custom fields when permset FLS hasn't propagated
    within
    // the test transaction. The two layers above are the
    structural
    // enforcement contract.
    /* code-analyzer-suppress ApexFlsViolation */
    List<DocGen_Template__c> templates = [
        SELECT Base_Object_API__c, Query_Config__c, Type__c, ...
        FROM DocGen_Template__c
        WHERE Id = :templateId
        WITH SYSTEM_MODE
        LIMIT 1
    ];
    ...
}

```

The Schema-CRUD-gate (Layer 1) is the documented enforcement signal the AppExchange sfge:ApexFlsViolation rule pattern-matches on. The DocGenFlsGuard per-field check (Layer 2) implements the “AND FLS checks on the fields” half of the reviewer’s finding-resolution language line-for-line. sf code-analyzer reports **0/0/0** (Critical/High/Moderate) against the v2.1.0 source tree.

Why we still use SYSTEM_MODE on the actual SOQL/DML

See § 1a above for the full rationale. Brief recap: per-field describe checks (Layer 2) work correctly at runtime; SYSTEM_MODE on the SOQL/DML (Layer 3) is retained because USER_MODE strict-FLS strips namespaced custom fields in the package-build test transaction where permset-granted FLS hasn’t propagated yet.

Standard objects (ContentVersion, ContentDocumentLink, User, OrgWideEmailAddress, etc.) do not have this issue — they use **USER_MODE** throughout because they don’t have namespaced FLS to begin with, and DocGenFlsGuard is not called for them.

Distribution by class (v2.1.0)

Class	DocGenFlsGuard DML sites	DocGenFlsGuard SOQL sites	Notes
DocGenController	~22	~40	Admin-path entry @AuraEnabled op level Schema-CRU

Class	DocGenFlsGuard DML sites	DocGenFlsGuard SOQL sites	Notes
			field DocGenFlsGuard SYSTEM_MODE
DocGenBulkController	7	14	Admin-path bulk g Same three-layer p
DocGenSignatureSenderController	~12	~22	Admin-path signat Three-layer pattern
DocGenChartImageController	2	4	Admin-path chart Three-layer pattern
DocGenSetupController	3	8	First-run setup wiz layer pattern + FeatureManagemen check.
DocGenSignatureFlowAction	2	6	Flow invocable. T pattern.
DocGenGiantQueryFlowAction	3	8	Flow invocable. T pattern.
DocGenTemplateManager	2	5	Internal helper inv generateDocumen layer pattern.
DocGenSignatureController (guest)	~17	~30	Guest-path signing DocGenSignature (v2.0) + DocGenF (v2.1.0) at every e §4.
DocGenAuthenticatorController (guest)	0	4	Public document v only. DocGenFlsGuard. at each SOQL site
Service classes (DocGenService, DocGenDataRetriever, DocGenChartBucketResolver, DocGenGiantQuery*, DocGenSignatureService, DocGenSignatureEmailService)	0 (DML in async/ triggered context)	~32	DocGenFlsGuard. at each SOQL site package-namespac object data.
Total	~70	~173	243 call sites across controllers + serv

Each DocGenFlsGuard call has an inline comment explaining the field allowlist and the structural contract (object-level gate above; per-field describe check on this line; SYSTEM_MODE on the next SOQL/DML).

3. Sharing — Serious (FALSE POSITIVE — unchanged from v1.42)

What the scanner flags

Classes declared without `sharing`. The scanner recommends that every Apex class use with `sharing`.

Classes flagged (v2.0)

Class	Sharing	Reason
DocGenSignatureController	without sharing	Guest-facing signing entry point. Token + PIN gated. DocGenSignatureGuestSecurity helper enforces checks.
DocGenAuthenticatorController	without sharing	Public document verifier (capability is holding the hash / request Id). DocGenSignatureGuestSecurity.assertAudit enforces describe-check.
DocGenSignatureService	without sharing	Shared helpers for token-gated signature paths + the event triggered queueable that runs as Automated F

Why without sharing is correct here

Reference: [Using the with sharing Keyword](#)

These classes run in **guest user context** on a public Salesforce Site that hosts the DocGenSignature.page Visualforce page (or, for the verifier, anyone on the public internet holding a SHA-256 hash). The guest user owns no records and has no sharing grants — running with `sharing` would make it impossible to locate the signer record the signing link refers to, breaking the entire flow.

The standard Salesforce pattern for public-facing sites is:

1. Grant the guest user access to the code via a minimally scoped permission set (DocGen_Guest_Signature).
2. Run the code without `sharing` so the specific records referenced by an unauthenticated URL can be located.
3. Gate access with an out-of-band secret (here: a 64-character SHA-256 token + a 6-digit email PIN).

DocGen v2.0 implements this pattern rigorously and adds the new DocGenSignatureGuestSecurity helper to centralize the describe-check and field-allowlist contract:

- Every entry method calls `DocGenSignatureGuestSecurity.assertSignerReadable|assertSignerWritableFields|assertRequestWritableFields|assertPlacementWritableFields|assertAuditCreateable|assertAuditReadable(token)` before any SOQL or DML. The helper calls `Schema.sObjectType.<Object>.isAccessible|isCreateable|isUpdateable()` (admin path passes immediately) and

validates the 64-char SHA-256 hex token shape (guest path enforces capability before any record lookup).

- **Single-use tokens.** After successful signing the signer record transitions to a terminal status and subsequent token presentations fail validation.
- **48-hour expiry.** Tightened from 30 days in v1.4.
- **Email-PIN second factor.** 6-digit code, SHA-256 hashed at rest, 10-minute expiry, 3-attempt lockout.
- **Scope-limited guest permission set.** DocGen_Guest_Signature grants read on the signature objects only — no access to templates, jobs, query configs, or unrelated record data.

All **admin-path** controllers (DocGenController, DocGenBulkController, DocGenSignatureSenderController, DocGenSetupController, DocGenChartImageController, DocGenTemplateManager) are declared with sharing. The scanner findings apply only to the guest-facing signature classes where without sharing is mandatory.

4. Apex SOQL SOSL USER_MODE Missing — Medium (FALSE POSITIVE — v2.1.0 DocGenFlsGuard disposition)

What the scanner flags

Any SOQL query that does not include WITH USER_MODE. The v2.0 source scan returned **340 findings** in this category.

Why we keep SYSTEM_MODE on package-internal queries

The v1.42 disposition claimed “USER_MODE fails compile on namespaced package fields.” That was wrong — USER_MODE compiles fine in managed packages, and the package now uses USER_MODE extensively on standard-object queries.

The **actual** reason we retain SYSTEM_MODE on package-internal queries in v2.0/ v2.1.0 is documented in §1a and §2 above — USER_MODE strict-FLS strips package-namespaced custom fields when the permission-set-granted FLS hasn’t propagated within the same transaction (the package-build scratch org reproduces this failure mode reliably). Switching to USER_MODE on these queries broke ~100 tests in the v2.0 attempt-1 package build.

The v2.1.0 mitigation is the three-layer pattern from §2:

- **Layer 1 — Schema.sObjectType.<Object>.isAccessible()** gate at every @AuraEnabled entry point (v2.0).
- **Layer 2 — DocGenFlsGuard.assertAccessible(SObjectType, fieldAllowList)** call immediately before every WITH SYSTEM_MODE SOQL (v2.1.0 — NEW). Performs Schema.SObjectField.getDescribe().isAccessible() per field; throws if any field is denied. **173 SOQL guard call sites across 18 classes.**

- **Layer 3 — WITH SYSTEM_MODE SOQL** for the actual operation, with `/* code-analyzer-suppress ApexFlsViolation */` and inline justification.

`sf code-analyzer` accepts this pattern — **0/0/0** (Critical/High/Moderate) on the v2.1.0 scan. Checkmarx CxSAST will continue to flag the 340 `USER_MODE` Missing patterns because it doesn't trace into the `DocGenFlsGuard` helper; the rebuttal is the 173 helper call sites.

Permission-set boundary

Access to the `SYSTEM_MODE` queries is controlled by the same permission-set model that gates the `@AuraEnabled` entry points themselves:

Permission Set	Target objects	Entry-point scope
DocGen_Admin	All DocGen objects	Command Hub, template CRUD, bulk jobs, signatures, settings, chart engine.
DocGen_User	Templates (read), Jobs (read own), signers (write for own requests)	Record-page generation via <code>docGenRunner</code> .
DocGen_Guest_Runner	Templates (read), guest-context document rendering	Experience Cloud guest-context document rendering.
DocGen_Guest_Signature	Signer records (read via token), signature audit (insert)	<code>DocGenSignature.page</code> only, token + PIN gated on every call, <code>DocGenSignatureGuestSecurity</code> helper at every step.

A user without any DocGen permission set cannot reach a single line of the flagged code — no tab, no component, no `@AuraEnabled` endpoint is reachable. **And** v2.0 adds the explicit Schema-CRUD-gate that the reviewer's finding language calls out as the acceptable alternative.

5. Apex CRUD ContentDistribution — High (FALSE POSITIVE — unchanged from v1.42)

What the scanner flags

DML (insert) on ContentDistribution records without `isCreateable()` / `isUpdateable()` / `stripInaccessible()` checks.

Why these are false positives

ContentDistribution records are created so the signer's browser (guest user, no Salesforce login) can render the document preview before signing. The requirements are:

1. **Must be created in guest context** — a signer without a Salesforce session needs to render images from the preview. This requires a ContentDistribution with a public link.
2. **Security.stripInaccessible() cannot be used** — on a guest user, `stripInaccessible()` strips the exact fields that make the distribution work (`PreferencesLinkLatestVersion`, `PreferencesAllowOriginalDownload`, `PreferencesPasswordRequired`), producing a broken distribution.
3. **Expiry is controlled**. Each distribution has `PreferencesExpires = true` and `ExpiryDate` set to the signing window — preview links auto-expire with the signature request.
4. **Access is token-gated**. The public distribution link is only disclosed on `DocGenSignature.page` after token + PIN validation, and from the admin-side preview after the Schema-CRUD gate.

v2.0 admin-side ContentDistribution inserts now go through `Database.insert(dist, AccessLevel.USER_MODE)` (standard object — `USER_MODE` works) inside a try/catch that handles transient failures. Each suppression site has a `// CxSAST: ...` comment explaining the guest-context requirement.

6. Apex CRUD Violation — High (FALSE POSITIVE — v2.1.0 DocGenFlsGuard disposition)

These are additional DML sites on package-internal objects (creation of `DocGen_Signature_Request__c`, `DocGen_Signer__c`, `DocGen_Signature_Audit__c`, `DocGen_Signature_Placement__c`, and updates to `DocGen_Job__c`).

The v2.1.0 disposition is the same three-layer pattern as §2:

- **Admin DML**: Object-level Schema-CRUD gate (`isCreateable | isUpdateable | isDeletable`) at the `@AuraEnabled` entry point (v2.0) + `DocGenFlsGuard.assertCreateable/assertUpdateable(record, fieldAllowlist)` per-field describe check (v2.1.0) +

Database.<op>(record, AccessLevel.SYSTEM_MODE) for the actual DML. SYSTEM_MODE retained for the reason in §2.

- **Guest DML:** DocGenSignatureGuestSecurity.assert<scope>(token) helper call at the entry point (v2.0 — validates SHA-256 hex token shape + describes object access) + DocGenFlsGuard.assertCreateable/assertUpdateable per-field describe check (v2.1.0) + SYSTEM_MODE DML. The helper documents the field allowlist for each operation at the call site.

Each DML site has a code comment matching the structural contract at the call.

7. Apex CSRF in Aura/LWC — Medium (FALSE POSITIVE — unchanged from v1.42)

What the scanner flags

Any @AuraEnabled method that performs DML. The scanner treats @AuraEnabled entry points as CSRF-exposed if they modify data.

Why every finding is a false positive

Reference: [Secure Code — Request Forgery](#)

The Salesforce Aura/LWC framework includes **automatic CSRF protection** for every @AuraEnabled method call:

- Every request from a Lightning component includes a Salesforce-managed anti-CSRF token.
- The token is validated server-side by the Aura/LWC framework before the @AuraEnabled method is invoked.
- This protection is provided by the platform, not by the package.

In addition:

- **No DML occurs on page load.** Every DML-performing @AuraEnabled method is called only in response to an explicit user action (button click) inside an authenticated Lightning session.
- **with sharing on every admin-path controller.**
- **No plain HTTP endpoints** — DocGen does not expose REST/SOAP API classes, Aura controllers accessible from Apex REST, or custom VF action methods that could be targeted by cross-site forms.

This is a known category of false positives for LWC-based managed packages. The Salesforce AppExchange security review team recognizes this pattern and accepts “framework-handled CSRF” as the disposition.

8. Apex Crypto Secrets — Medium (FALSE POSITIVE — unchanged from v1.42)

What the scanner flags

The scanner flags calls to `Crypto.generateAesKey(...)` and `Crypto.generateDigest('SHA-256', ...)` as potential “hardcoded crypto secret” findings.

Why every finding is a false positive

Reference: [Storing Sensitive Data — Secure Coding Guide](#)

None of these calls contain hardcoded material. They **generate** random cryptographic material at runtime using Salesforce’s built-in CSPRNG:

Usage	API	Purpose
Signing token (per signer, per request)	<code>Crypto.generateAesKey(256) → SHA-256 hash</code>	64-char hex token stored on <code>DocGen_Signer__c</code> .
PIN generation	<code>Crypto.getRandomInteger()</code>	6-digit email verification code.
PIN storage	<code>Crypto.generateDigest('SHA-256', ...)</code>	SHA-256 hash — plaintext PIN is never persisted.
Document integrity	<code>Crypto.generateDigest('SHA-256', ...)</code>	SHA-256 hash of the finalized PDF for verification.

There are **no hardcoded keys, passwords, IVs, salts, or tokens** anywhere in the codebase. Every cryptographic value is generated fresh at runtime, and PIN plaintext is hashed on the same line it is produced and never written to the database.

9. Proof of Compliance — v2.0 / v2.1.0 Three-Layer Pattern Matrix

Scanner Expectation	Platform Reality	DocGen v2.1.0 Mitigation
Use SOQL bind variables everywhere	Bind variables not supported for object names, field names, or ORDER BY.	Schema validation + keyword sanitization table.
Use <code>stripInaccessible()</code> on all DML	Strips namespaced fields in managed 2GP build context, corrupting package data.	Object-level Schema CRUD gate (v2.1.0) + SYSTEM_MODE DML filter.
Use WITH USER_MODE on all SOQL		Hybrid: USER_MODE on standard queries + SYSTEM_MODE on package object queries.

Scanner Expectation	Platform Reality	DocGen v2.1.0 Mitigation
	Strict-FLS strips namespaced fields when permset FLS hasn't propagated within transaction.	
Use with sharing on every class	Guest-site signing flow requires locating records the guest user does not own.	without sharing only on signature (v2.0) enforces describe checks + field describe check at each guest
Add manual CSRF tokens to all mutating endpoints	Aura/LWC framework adds them automatically; package code cannot intercept the request.	Framework-handled; no custom R
Remove calls to <code>Crypto.generateAesKey / generateDigest</code>	These are the only sanctioned Salesforce primitives for secure random material and hashing.	Runtime-only material; nothing ha
Add inline <code>isCreateable() / isUpdateable()</code> checks	Object-level DONE in v2.0 — at every admin <code>@AuraEnabled</code> entry point and via <code>DocGenSignatureGuestSecurity</code> on every guest entry point. Per-field DONE in v2.1.0 via <code>DocGenFlsGuard</code> — 243 call sites.	Three-layer pattern: object-level <code>Schema.SObjectField.getDescribe()</code> via <code>DocGenFlsGuard</code> (v2.1.0) — halves of the v1.56 reviewer's stat object AND FLS checks on the fie

10. Defenses DocGen Adds Beyond the Scanner's Recommendations

The following defensive controls are **not** required by Checkmarx or `sf code-analyzer` but are shipped in v2.1.0:

- **Schema allowlist validation** on every dynamic object and field name, backed by `Schema.getGlobalDescribe()`.
- **Keyword sanitization** on every user-supplied WHERE / ORDER BY clause: rejects INSERT, UPDATE, DELETE, DROP, ALTER, GRANT, SELECT, ;, --, /*, and enforces a max length.
- **DocGenSignatureGuestSecurity helper class** (v2.0) — centralizes the guest-context Schema-CRUD-gate + token capability validation + per-operation field allowlist documentation at every guest entry point. Class-level javadoc documents the full guest security model.
- **DocGenFlsGuard helper class (NEW in v2.1.0)** — performs explicit per-field `Schema.SObjectField.getDescribe().is{Createable,Updateable,Accessible}()` checks (`assertCreateable/assertUpdateable/assertAccessible`). Called immediately before every package-namespaced DML and WITH SYSTEM_MODE SOQL. **243 call sites across 19 controllers** (70 DML + 173 SOQL). Closes the 562 Checkmarx FLS findings (FLS Create 118 + FLS Update 104 + USER_MODE Missing 340) via real runtime enforcement. Class-level javadoc documents the per-field describe-check pattern. See § 1a above for the full helper API and call-site distribution.
- **Object-level Schema-CRUD-gate** (v2.0) at every admin `@AuraEnabled` and `@InvocableMethod` entry point. Throws `DocGenException('Insufficient access...')` for users without the required DocGen permission set.

- **Single-use cryptographic tokens** with 48-hour expiry (tightened from 30 days in v1.4).
- **Email-PIN second factor** with hashed storage, 10-minute expiry, and 3-attempt lockout.
- **Zero-heap PDF image pipeline** — record-referenced images are emitted as relative Shepherd URLs resolved inside the Salesforce trust boundary. No external URL can be embedded in a template and no CV bytes leave the org.
- **Client-side DOCX assembly without external libraries.**
docGenZipWriter.js is implemented from scratch in-package. There are no third-party JS dependencies, no CDN fetches, no eval, and no Function constructor usage.
- **Document integrity verification — multi-signer fix in v2.0.** Every signed PDF has its SHA-256 hash stored on an immutable DocGen_Signature_Audit__c record per signer; the verifier (LWC + Visualforce) now returns **all** signers for a multi-signer document (prior LIMIT 1 bug only showed the first signer).
- **Field history tracking** on every audit field.
- **Clickjacking remediation (v2.0).** All style="position: absolute|fixed" inline attributes on exposed LWCs replaced with the SLDS slds-is-absolute utility class. Five bundles touched.
- **Salesforce Code Analyzer** (Security + AppExchange rule selectors) runs clean: **0 Critical / 0 High / 0 Moderate / 0 Low / 0 Info** against the v2.1.0 source tree. Achieved by 562 findings genuinely closed via DocGenFlsGuard + 38 documented false positives suppressed at the rule level in code-analyzer.yml (pmd:ProtectSensitiveData + pmd:AvoidLwcBubblesComposedTrue). Checkmarx will continue to flag the FLS Create/Update/USER_MODE Missing patterns because it doesn't trace into the helper — the rebuttal is the 243 helper call sites.
- **1,449 Apex tests** with 76% org-wide coverage.
- **11 end-to-end anonymous Apex scripts** run on every release (scripts/e2e-01-*.apex through scripts/e2e-08-*.apex plus four e2e-07-syntax*.apex variants), covering permissions, template CRUD, PDF generation, DOCX generation, bulk generation, signatures, four merge-tag syntax suites, and cleanup.

11. Contact

- **Publisher:** Portwood Global Solutions
 - **Security contact:** dave@portwood.dev
 - **Disclosure policy:** SECURITY.md in the source repository
 - **Release validation checklist:** CLAUDE.md — “Release Validation Checklist”
 - **Per-finding re-submission map:** SECURITY_REVIEW_RESPONSE_v2.md in this folder
-

Portwood Global Solutions — <https://portwood.dev>