



Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

# 图表示学习

Zhou Shen

School of Computer Science, Wuhan University

November 1, 2021



# Outline

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

1 Word2Vec

2 DeepWalk

3 Node2Vec

4 Struc2Vec

5 LINE

6 SDNE

7 Experiment



# Word2Vec

## 统计语言模型

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment



# Word2Vec

## One-Hot Encoding

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

### ***1-of-N Encoding***

apple = [ 1 0 0 0 0 ]

bag = [ 0 1 0 0 0 ]

cat = [ 0 0 1 0 0 ]

dog = [ 0 0 0 1 0 ]

elephant = [ 0 0 0 0 1 ]



# Word2Vec

## One-Word Context

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment




Figure 1: A simple CBOW model with only one word in the context

$$\mathbf{h} = \mathbf{W}^T \mathbf{x} = \mathbf{W}_{(k, \cdot)}^T := \mathbf{v}_{w_I}^T, u_j = \mathbf{v}'_{w_j} h \quad (1)$$

$$p(w_j | w_I) = y_j = \frac{\exp(u_j)}{\sum_{j'=1}^V \exp(u_{j'})} \quad (2)$$



# Word2Vec

## Objective Function

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

$$\begin{aligned}\max p(w_O \mid w_I) &= \max y_{j^*} \\ &= \max \log y_{j^*} \\ &= u_{j^*} - \log \sum_{j'=1}^V \exp(u_{j'}) := -E\end{aligned}\tag{3}$$

常用变形

$$\min E = -u_{j^*} + \log \sum_{j'=1}^V \exp(u_{j'})$$



# Word2Vec

## CBOW

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment




Figure 2: Continuous bag-of-words model

$$\mathbf{h} = \frac{1}{C}(\mathbf{v}_{w_1} + \mathbf{v}_{w_2} + \cdots + \mathbf{v}_{w_C})^T$$

$$E = -\log p(w_O | w_{I,1}, \cdots, w_{I,C})$$

$$= -u_{j^*} + \log \sum_{j'=1}^V \exp(u_{j'})$$



# Word2Vec

## Skip-Gram

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment




Figure 3: The skip-gram model.

$$\begin{aligned}
 E &= -\log p(w_{O,1}, w_{O,2}, \dots, w_{O,C} \mid w_I) \\
 &= -\log \prod_{c=1}^C \frac{\exp(u_{c,j_c^*})}{\sum_{j'=1}^V \exp(u_{j'})} \\
 &= -\sum_{c=1}^C u_{j_c^*} + C \cdot \log \sum_{j'=1}^V \exp(u_{j'})
 \end{aligned}$$





# Word2Vec

## Hierarchical Softmax

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk


Node2Vec

Struc2Vec

LINE

SDNE

Experiment



$$p(w = w_O) = \prod_{j=1}^{L(w)-1} \sigma \left( [n(w, j+1) = \text{ch}(n(w, j))] \cdot \mathbf{v}'_{n(w, j)} {}^T \mathbf{h} \right)$$



# Word2Vec

## Negative Sample

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

### 1. 词频计算

$$weight(w_i) = \frac{count(w_i)^{0.75}}{\sum_j^V count(w_j)^{0.75}}$$

### 2. 目标函数

$$E = -\log \sigma(\mathbf{v}'_{w_o} \mathbf{h}) - \sum_{w_j \in \mathcal{W}_{\text{neg}}} \log \sigma(-\mathbf{v}'_{w_j} \mathbf{h})$$



# DeepWalk

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec


LINE

SDNE

Experiment



(a) Input: Karate Graph



(b) Output: Representation

## Definition

**Problem Definition** Let  $G = (V, E)$ , where  $V$  are the members of the network, and  $E$  be its edges. Our goal is to learn  $X_E \in \mathcal{R}^{|V| \times d}$ , where  $d$  is number of latent dimensions.



# DeepWalk

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk


Node2Vec

Struc2Vec


LINE

SDNE

Experiment



(a) YouTube Social Graph



(b) Wikipedia Article Text

## Connection

The power-law distribution of vertices appearing in the short random walks follows a power-law, much like the distribution of words in natural language.



# DeepWalk

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

- 1 give a sequence of random walk from vertice  $i$

$$\mathcal{W}_i^n = \{v_1, v_2, v_3, \dots, v_n\} \quad (4)$$

- 2 maximize the likelihood

$$\Pr(v_i \mid (\Phi(v_1), \Phi(v_2), \dots, \Phi(v_{i-1}))) \quad (5)$$

## Mapping Function $\Phi$

$\Phi : v \in V \mapsto \mathcal{R}^{|V| \times d}$  where  $d$  is the number of dimensions



# DeepWalk

## Disadvantages and Optimizations

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec


Struc2Vec

LINE


SDNE

Experiment


- As the walk length grows, computing this objective function becomes unfeasible.
- Restricts the order in which vertices appear



(a) Random walk generation.



(b) Representation mapping.



(c) Hierarchical Softmax.



# DeepWalk

## Algorithm

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

---

**Algorithm 1** DEEPWALK( $G, w, d, \gamma, t$ )

---

**Input:** graph  $G(V, E)$

    window size  $w$

    embedding size  $d$

    walks per vertex  $\gamma$

    walk length  $t$

**Output:** matrix of vertex representations  $\Phi \in \mathbb{R}^{|V| \times d}$

1: Initialization: Sample  $\Phi$  from  $\mathcal{U}^{|V| \times d}$

2: Build a binary Tree  $T$  from  $V$

3: **for**  $i = 0$  to  $\gamma$  **do**

4:    $\mathcal{O} = \text{Shuffle}(V)$

5:   **for each**  $v_i \in \mathcal{O}$  **do**

6:      $\mathcal{W}_{v_i} = \text{RandomWalk}(G, v_i, t)$

7:      $\text{SkipGram}(\Phi, \mathcal{W}_{v_i}, w)$

8:   **end for**

9: **end for**

---

## Corollary

$$\underset{\Phi}{\text{minimize}} - \log \Pr(\{v_{i-w}, \dots, v_{i-1}, v_{i+1}, \dots, v_{i+w}\} \mid \Phi(v_i))$$



# Node2Vec

## Classic Search Strategies

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk


Node2Vec

Struc2Vec

LINE

SDNE

Experiment



1. The neighborhoods sampled by BFS lead to embeddings that correspond closely to structural equivalence.
2. DFS can freely explore network neighborhoods which is important in discovering homophilous communities.





# Node2Vec

Search Bias  $\alpha$

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk


Node2Vec

Struc2Vec

LINE

SDNE

Experiment



$$\alpha_{pq}(t, x) = \begin{cases} \frac{1}{p} & \text{if } d_{tx} = 0 \\ 1 & \text{if } d_{tx} = 1 \\ \frac{1}{q} & \text{if } d_{tx} = 2 \end{cases}$$



# Node2Vec

## Algorithm

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

---

**Algorithm 1** The *node2vec* algorithm.

---

**LearnFeatures** (Graph  $G = (V, E, W)$ , Dimensions  $d$ , Walks per

node  $r$ , Walk length  $l$ , Context size  $k$ , Return  $p$ , In-out  $q$ )

$\pi = \text{PreprocessModifiedWeights}(G, p, q)$

$G' = (V, E, \pi)$

Initialize *walks* to Empty

**for** *iter* = 1 **to**  $r$  **do**

**for all** nodes  $u \in V$  **do**

$walk = \text{node2vecWalk}(G', u, l)$

        Append *walk* to *walks*

$f = \text{StochasticGradientDescent}(k, d, \text{walks})$

**return**  $f$

---

**node2vecWalk** (Graph  $G' = (V, E, \pi)$ , Start node  $u$ , Length  $l$ )

Initialize *walk* to  $[u]$

**for** *walk\_iter* = 1 **to**  $l$  **do**

$curr = \text{walk}[-1]$

$V_{curr} = \text{GetNeighbors}(curr, G')$

$s = \text{AliasSample}(V_{curr}, \pi)$

    Append  $s$  to *walk*

**return** *walk*

---

## Corollary

$$\max_f \sum_{u \in V} \left[ \sum_{n_i \in N_S(u)} f(n_i) \cdot f(u) - \log Z_u \right]$$



# Struc2Vec

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk


Node2Vec

Struc2Vec

LINE

SDNE

Experiment



**Figure 1: An example of two nodes ( $u$  and  $v$ ) that are structurally similar (degrees 5 and 4, connected to 3 and 2 triangles, connected to the rest of the network by two nodes), but very far apart in the network.**

## Limitation

Structurally similar nodes will never share the same context if their distance (hop count) is larger than the Skip-Gram window.



# Struc2Vec

## Structural Similarity

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

$$f_k(u, v) = f_{k-1}(u, v) + g(s(R_k(u)), s(R_k(v))) \quad (6)$$
$$k \geq 0 \text{ and } |R_k(u)|, |R_k(v)| > 0$$

### 符号解释

$f_k(u, v)$  structural distance when consider k-hop neighborhoods

$R_k(u)$  the ring of nodes at distance k

$s(S)$  the ordered degree sequence

$g(a, b)$  DTW Function



# Struc2Vec

## Example

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk


Node2Vec

Struc2Vec

LINE

SDNE

Experiment



## Example

$$R_1(1) = \{2, 3, 4, 6, 7\}$$

$$R_2(1) = \{5, 8, 9\}$$

$$s(R_1(1)) = \{1, 1, 1, 2, 3\}$$

$$s(R_2(1)) = \{1, 1, 1\}$$



## Dynamic Time Warping

利用动态规划的思想来计算两条不等长序列的相似度

动态转移方程如下：

$$g(i, j) = \min\{g(i-1, j), g(i, j-1), g(i-1, j-1)\} + d(i, j)$$

$$d(a, b) = \frac{\max(a, b)}{\min(a, b)} - 1$$



# LINE

## Overview

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment




Figure 1: A toy example of information network. Edges can be undirected, directed, and/or weighted. Vertex 6 and 7 should be placed closely in the low-dimensional space as they are connected through a strong tie. Vertex 5 and 6 should also be placed closely as they share similar neighbors.



# LINE

## First-Order Proximity

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

The Joint Probability between  $v_i$  and  $v_j$ :

$$p_1(v_i, v_j) = \frac{1}{1 + \exp(-\vec{u}_i^T \cdot \vec{u}_j)}$$

Empirical Probability  $\hat{p}_1(i, j) = \frac{w_{ij}}{W}$

$$O_1 = d(\hat{p}_1(\cdot, \cdot), p_1(\cdot, \cdot))$$

where  $d(\cdot, \cdot)$  is the distance between two distributions.

### Objective Function

$$\min O_1 = - \sum_{(i,j) \in E} w_{ij} \log p_1(v_i, v_j)$$





# LINE

## Second-Order Proximity

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

The Probability of Context  $v_j$  generated by vertex  $v_i$  as:

$$p_2(v_j | v_i) = \frac{\exp(\vec{u}_j^T \cdot \vec{u}_i)}{\sum_{k=1}^{|V|} \exp(\vec{u}_k^T \cdot \vec{u}_i)}$$

Empirical Probability  $\hat{p}_1(v_j | v_i) = \frac{w_{ij}}{d_i}$

### Objective Function

$$O_2 = - \sum_{(i,j) \in E} w_{ij} \log p_2(v_j | v_i)$$



# LINE

## Optimization

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

### 1. Negative Sample

$$\log \sigma(\vec{u}_j'^T \cdot \vec{u}_i) + \sum_{i=1}^K E_{v_n \sim P_n(v)} [\log \sigma(-\vec{u}_n^T \cdot \vec{u}_i)]$$

where  $\sigma(x) = \frac{1}{1+\exp(-x)}$  is the sigmoid function.

### 2. Edge Sample - Alias Sample




# SDNE

## Overview

Graph  
Embedding

S. Zhou

Word2Vec  
DeepWalk  
Node2Vec  
Struc2Vec  
LINE  
SDNE  
Experiment





# SDNE

## First-Order Proximity

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

### Encoder and Decoder

$$\mathbf{y}_i^{(1)} = \sigma \left( W^{(1)} \mathbf{x}_i + \mathbf{b}^{(1)} \right)$$

$$\mathbf{y}_i^{(k)} = \sigma \left( W^{(k)} \mathbf{y}_i^{(k-1)} + \mathbf{b}^{(k)} \right), k = 2, \dots, K$$

### First-Order Proximity Loss Function

$$\begin{aligned} \mathcal{L}_{1st} &= \sum_{i,j=1}^n s_{i,j} \left\| \mathbf{y}_i^{(K)} - \mathbf{y}_j^{(K)} \right\|_2^2 \\ &= \sum_{i,j=1}^n s_{i,j} \left\| \mathbf{y}_i - \mathbf{y}_j \right\|_2^2 \end{aligned}$$



# SDNE

## Second-Order Proximity

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

The autoencoder goal is to minimize:

$$\mathcal{L} = \sum_{i=1}^n \|\hat{\mathbf{x}}_i - \mathbf{x}_i\|_2^2$$

Structural Similarity  $x_i = s_i$

$$\begin{aligned}\mathcal{L}_{2nd} &= \sum_{i=1}^n \|(\hat{\mathbf{x}}_i - \mathbf{x}_i) \odot \mathbf{b}_i\|_2^2 \\ &= \|(\hat{X} - X) \odot B\|_F^2\end{aligned}$$



# SDNE

## Objective Function

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

正则化部分

$$\mathcal{L}_{reg} = \frac{1}{2} \sum_{k=1}^K \left( \|W^{(k)}\|_F^2 + \|\hat{W}^{(k)}\|_F^2 \right)$$

损失函数

$$\begin{aligned} \mathcal{L}_{mix} &= \mathcal{L}_{2nd} + \alpha \mathcal{L}_{1st} + \nu \mathcal{L}_{reg} \\ &= \|(\hat{X} - X) \odot B\|_F^2 + \alpha \sum_{i,j=1}^n s_{i,j} \|\mathbf{y}_i - \mathbf{y}_j\|_2^2 + \nu \mathcal{L}_{reg} \end{aligned}$$



# 复现结果

Graph  
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Experiment

Dataset	Method	LabelNode	macro-F1	参考值
Wiki	Node2Vec	50%	51.10	50.52
	SDNE	50%	49.70	49.80
BlogCatalog	DeepWalk	50%	21.80	21.10
	Node2Vec	50%	23.50	23.00
Wikipedia	LINE	50%	11.40	11.64
Brazil-Flight	Struc2Vec	50%	67.94	68.30