



Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

图表示学习

Zhou Shen

School of Computer Science, Wuhan University

October 23, 2021



Outline

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

1 Word2Vec

2 DeepWalk

3 Node2Vec

4 Struc2Vec

5 LINE

6 SDNE



Word2Vec

One-Hot Encoding

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

1-of-N Encoding

apple = [1 0 0 0 0]

bag = [0 1 0 0 0]

cat = [0 0 1 0 0]

dog = [0 0 0 1 0]

elephant = [0 0 0 0 1]



Word2Vec

One-Word Context

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE




Figure 1: A simple CBOW model with only one word in the context

$$\mathbf{h} = \mathbf{W}^T \mathbf{x} = \mathbf{W}_{(k, \cdot)}^T := \mathbf{v}_{w_I}^T, u_j = \mathbf{v}'_{w_j} h \quad (1)$$

$$p(w_j | w_I) = y_j = \frac{\exp(u_j)}{\sum_{j'=1}^V \exp(u_{j'})} \quad (2)$$



Word2Vec

Objective Function

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

$$\begin{aligned}\max p(w_O \mid w_I) &= \max y_{j^*} \\ &= \max \log y_{j^*} \\ &= u_{j^*} - \log \sum_{j'=1}^V \exp(u_{j'}) := -E\end{aligned}\tag{3}$$

常用变形

$$\min E = -u_{j^*} + \log \sum_{j'=1}^V \exp(u_{j'})$$



Word2Vec

CBOW

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE




Figure 2: Continuous bag-of-words model

$$\mathbf{h} = \frac{1}{C}(\mathbf{v}_{w_1} + \mathbf{v}_{w_2} + \dots + \mathbf{v}_{w_C})^T$$

$$E = -\log p(w_O | w_{I,1}, \dots, w_{I,C})$$

$$= -u_{j^*} + \log \sum_{j'=1}^V \exp(u_{j'})$$



Word2Vec

Skip-Gram

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE




Figure 3: The skip-gram model.

$$\begin{aligned}
 E &= -\log p(w_{O,1}, w_{O,2}, \dots, w_{O,C} \mid w_I) \\
 &= -\log \prod_{c=1}^C \frac{\exp(u_{c,j_c^*})}{\sum_{j'=1}^V \exp(u_{j'})} \\
 &= -\sum_{c=1}^C u_{j_c^*} + C \cdot \log \sum_{j'=1}^V \exp(u_{j'})
 \end{aligned}$$



Word2Vec

Hierarchical Softmax

Graph
Embedding

S. Zhou

Word2Vec


DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE



$$p(w = w_O) = \prod_{j=1}^{L(w)-1} \sigma \left([n(w, j+1) = \text{ch}(n(w, j))] \cdot \mathbf{v}'_{n(w, j)} {}^T \mathbf{h} \right)$$



Word2Vec

Negative Sample

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

1. 词频计算

$$weight(w_i) = \frac{count(w_i)^{0.75}}{\sum_j^V count(w_j)^{0.75}}$$

2. 目标函数

$$E = -\log \sigma(\mathbf{v}'_{w_o} \mathbf{h}) - \sum_{w_j \in \mathcal{W}_{\text{neg}}} \log \sigma(-\mathbf{v}'_{w_j} \mathbf{h})$$



DeepWalk

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec


Struc2Vec

LINE

SDNE



(a) Input: Karate Graph



(b) Output: Representation

Definition

Problem Definition Let $G = (V, E)$, where V are the members of the network, and E be its edges. Our goal is to learn $X_E \in \mathcal{R}^{|V| \times d}$, where d is number of latent dimensions.



DeepWalk

Graph
Embedding

S. Zhou

Word2Vec


DeepWalk

Node2Vec


Struc2Vec

LINE

SDNE



(a) YouTube Social Graph



(b) Wikipedia Article Text

Connection

The power-law distribution of vertices appearing in the short random walks follows a power-law, much like the distribution of words in natural language.



DeepWalk

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

- 1 give a sequence of random walk from vertice i

$$\mathcal{W}_i^n = \{v_1, v_2, v_3, \dots, v_n\} \quad (4)$$

- 2 maximize the likelihood

$$\Pr(v_i \mid (\Phi(v_1), \Phi(v_2), \dots, \Phi(v_{i-1}))) \quad (5)$$

Mapping Function Φ

$\Phi : v \in V \mapsto \mathcal{R}^{|V| \times d}$ where d is the number of dimensions



DeepWalk

Disadvantages and Optimizations

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk


Node2Vec

Struc2Vec


LINE

SDNE


- As the walk length grows, computing this objective function becomes unfeasible.
- Restricts the order in which vertices appear



(a) Random walk generation.



(b) Representation mapping.



(c) Hierarchical Softmax.



DeepWalk

Algorithm

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Algorithm 1 DEEPWALK(G, w, d, γ, t)

Input: graph $G(V, E)$

 window size w

 embedding size d

 walks per vertex γ

 walk length t

Output: matrix of vertex representations $\Phi \in \mathbb{R}^{|V| \times d}$

1: Initialization: Sample Φ from $\mathcal{U}^{|V| \times d}$

2: Build a binary Tree T from V

3: **for** $i = 0$ to γ **do**

4: $\mathcal{O} = \text{Shuffle}(V)$

5: **for each** $v_i \in \mathcal{O}$ **do**

6: $\mathcal{W}_{v_i} = \text{RandomWalk}(G, v_i, t)$

7: $\text{SkipGram}(\Phi, \mathcal{W}_{v_i}, w)$

8: **end for**

9: **end for**

Corollary

$$\underset{\Phi}{\text{minimize}} -\log \Pr(\{v_{i-w}, \dots, v_{i-1}, v_{i+1}, \dots, v_{i+w}\} \mid \Phi(v_i))$$



DeepWalk

复现结果

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

	Label Node%	10	20	30	40	50	60	70	80	90
micro-F1	原文结果	36.00	38.20	39.60	40.30	41.00	41.30	41.50	41.50	42.00
	复现结果	36.00	38.73	39.75	40.70	41.27	41.98	42.18	41.99	42.65
macro-F1	原文结果	21.30	23.80	25.30	26.30	27.30	27.60	27.90	28.20	28.90
	复现结果	20.90	23.78	25.33	26.31	27.09	27.84	28.16	28.25	28.78



Node2Vec

Classic Search Strategies

Graph
Embedding

S. Zhou

Word2Vec


DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE



1. The neighborhoods sampled by BFS lead to embeddings that correspond closely to structural equivalence.
2. DFS can freely explore network neighborhoods which is important in discovering homophilous communities.



Node2Vec

Search Bias α

Graph
Embedding

S. Zhou

Word2Vec


DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE



$$\alpha_{pq}(t, x) = \begin{cases} \frac{1}{p} & \text{if } d_{tx} = 0 \\ 1 & \text{if } d_{tx} = 1 \\ \frac{1}{q} & \text{if } d_{tx} = 2 \end{cases}$$



Node2Vec

Algorithm

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Algorithm 1 The *node2vec* algorithm.

LearnFeatures (Graph $G = (V, E, W)$, Dimensions d , Walks per

node r , Walk length l , Context size k , Return p , In-out q)

$\pi = \text{PreprocessModifiedWeights}(G, p, q)$

$G' = (V, E, \pi)$

Initialize *walks* to Empty

for *iter* = 1 **to** r **do**

for all nodes $u \in V$ **do**

$walk = \text{node2vecWalk}(G', u, l)$

 Append *walk* to *walks*

$f = \text{StochasticGradientDescent}(k, d, \text{walks})$

return f

node2vecWalk (Graph $G' = (V, E, \pi)$, Start node u , Length l)

Initialize *walk* to $[u]$

for *walk_iter* = 1 **to** l **do**

$curr = \text{walk}[-1]$

$V_{curr} = \text{GetNeighbors}(curr, G')$

$s = \text{AliasSample}(V_{curr}, \pi)$

 Append s to *walk*

return *walk*

Corollary

$$\max_f \sum_{u \in V} \left[\sum_{n_i \in N_S(u)} f(n_i) \cdot f(u) - \log Z_u \right]$$



Struc2Vec

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE




Figure 1: An example of two nodes (u and v) that are structurally similar (degrees 5 and 4, connected to 3 and 2 triangles, connected to the rest of the network by two nodes), but very far apart in the network.

Limitation

Structurally similar nodes will never share the same context if their distance (hop count) is larger than the Skip-Gram window.



Struc2Vec

Structural Similarity

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

$$f_k(u, v) = f_{k-1}(u, v) + g(s(R_k(u)), s(R_k(v))) \quad (6)$$
$$k \geq 0 \text{ and } |R_k(u)|, |R_k(v)| > 0$$

符号解释

$f_k(u, v)$ structural distance when consider k-hop neighborhoods

$R_k(u)$ the ring of nodes at distance k

$s(S)$ the ordered degree sequence

$g(a, b)$ DTW Function



Struc2Vec

Example

Graph
Embedding

S. Zhou

Word2Vec


DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE



Example

$$R_1(1) = \{2, 3, 4, 6, 7\}$$

$$R_2(1) = \{5, 8, 9\}$$

$$s(R_1(1)) = \{1, 1, 1, 2, 3\}$$

$$s(R_2(1)) = \{1, 1, 1\}$$



Dynamic Time Warping

利用动态规划的思想来计算两条不等长序列的相似度

动态转移方程如下：

$$g(i, j) = \min\{g(i-1, j), g(i, j-1), g(i-1, j-1)\} + d(i, j)$$

$$d(a, b) = \frac{\max(a, b)}{\min(a, b)} - 1$$



LINE

Overview

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE




Figure 1: A toy example of information network. Edges can be undirected, directed, and/or weighted. Vertex 6 and 7 should be placed closely in the low-dimensional space as they are connected through a strong tie. Vertex 5 and 6 should also be placed closely as they share similar neighbors.



LINE

First-Order Proximity

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

The Joint Probability between v_i and v_j :

$$p_1(v_i, v_j) = \frac{1}{1 + \exp(-\vec{u}_i^T \cdot \vec{u}_j)}$$

Empirical Probability $\hat{p}_1(i, j) = \frac{w_{ij}}{W}$

$$O_1 = d(\hat{p}_1(\cdot, \cdot), p_1(\cdot, \cdot))$$

where $d(\cdot, \cdot)$ is the distance between two distributions.

Objective Function

$$\min O_1 = - \sum_{(i,j) \in E} w_{ij} \log p_1(v_i, v_j)$$



LINE

Second-Order Proximity

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

The Probability of Context v_j generated by vertex v_i as:

$$p_2(v_j | v_i) = \frac{\exp(\vec{u}_j^T \cdot \vec{u}_i)}{\sum_{k=1}^{|V|} \exp(\vec{u}_k^T \cdot \vec{u}_i)}$$

Empirical Probability $\hat{p}_1(v_j | v_i) = \frac{w_{ij}}{d_i}$

Objective Function

$$O_2 = - \sum_{(i,j) \in E} w_{ij} \log p_2(v_j | v_i)$$



LINE

Optimization

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

1. Negative Sample

$$\log \sigma(\vec{u}_j'^T \cdot \vec{u}_i) + \sum_{i=1}^K E_{v_n \sim P_n(v)} [\log \sigma(-\vec{u}_n^T \cdot \vec{u}_i)]$$

where $\sigma(x) = \frac{1}{1+\exp(-x)}$ is the sigmoid function.

2. Edge Sample - Alias Sample



SDNE

Overview

Graph
Embedding

S. Zhou

Word2Vec


DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE





SDNE

First-Order Proximity

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

Encoder and Decoder

$$\mathbf{y}_i^{(1)} = \sigma \left(W^{(1)} \mathbf{x}_i + \mathbf{b}^{(1)} \right)$$

$$\mathbf{y}_i^{(k)} = \sigma \left(W^{(k)} \mathbf{y}_i^{(k-1)} + \mathbf{b}^{(k)} \right), k = 2, \dots, K$$

First-Order Proximity Loss Function

$$\begin{aligned} \mathcal{L}_{1st} &= \sum_{i,j=1}^n s_{i,j} \left\| \mathbf{y}_i^{(K)} - \mathbf{y}_j^{(K)} \right\|_2^2 \\ &= \sum_{i,j=1}^n s_{i,j} \left\| \mathbf{y}_i - \mathbf{y}_j \right\|_2^2 \end{aligned}$$



SDNE

Second-Order Proximity

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

The autoencoder goal is to minimize:

$$\mathcal{L} = \sum_{i=1}^n \|\hat{\mathbf{x}}_i - \mathbf{x}_i\|_2^2$$

Structural Similarity $x_i = s_i$

$$\begin{aligned}\mathcal{L}_{2nd} &= \sum_{i=1}^n \|(\hat{\mathbf{x}}_i - \mathbf{x}_i) \odot \mathbf{b}_i\|_2^2 \\ &= \|(\hat{X} - X) \odot B\|_F^2\end{aligned}$$



SDNE

Objective Function

Graph
Embedding

S. Zhou

Word2Vec

DeepWalk

Node2Vec

Struc2Vec

LINE

SDNE

正则化部分

$$\mathcal{L}_{reg} = \frac{1}{2} \sum_{k=1}^K \left(\|W^{(k)}\|_F^2 + \|\hat{W}^{(k)}\|_F^2 \right)$$

损失函数

$$\begin{aligned} \mathcal{L}_{mix} &= \mathcal{L}_{2nd} + \alpha \mathcal{L}_{1st} + \nu \mathcal{L}_{reg} \\ &= \|(\hat{X} - X) \odot B\|_F^2 + \alpha \sum_{i,j=1}^n s_{i,j} \|\mathbf{y}_i - \mathbf{y}_j\|_2^2 + \nu \mathcal{L}_{reg} \end{aligned}$$