

# Java Week 3 (1)

Review of key language constructs, introduction to OO and Inheritance

Dr Chris Roadknight

# Pass by reference and pass by value

- The following code changes the location of a stored value
  - `changeReference`
- And changes the value itself without changing the locations
  - `changeValue`
- Note. We cheat a bit to display a memory 'location'. If we print an object with no suffix it prints the originating class name and a Hash of some location

```

1 class People {
2     public int age;
3     People(int passedAge) { age = passedAge; }
4     //People(int age) {this.age = age;} // a different way to assign
5 }
6
7 public class TestApp4 {
8     static void changeReference(People p) { //method
9         System.out.println("(1)address of p: " + p + " value of p.age: " + p.age);
10        People newP = new People(p.age); //instance of a new object in new location
11        p = newP; //replace the old object with the new one
12        System.out.println("(2)address of p: " + p + " value of p.age: " + p.age);
13    }
14    static void changeValue(People p) { //method
15        System.out.println("(3)address of p: " + p + " value of p.age: " + p.age);
16        p.age += 8; //change the age argument
17        System.out.println("(4)address of p: " + p + " value of p.age: " + p.age);
18    }
19    public static void main(String[] args) {
20        People p = new People(25); //passes the value 25
21        changeValue(p);
22        changeReference(p);
23    }
24 }

```

```

C:\Users\z2018044\Documents\JavaLab2>java TestApp4
(3)address of p: People@15db9742 value of p.age: 25
(4)address of p: People@15db9742 value of p.age: 33
(1)address of p: People@15db9742 value of p.age: 33
(2)address of p: People@6d06d69c value of p.age: 33

```

# Constructors vs methods

- Constructors **initialise** objects when they are created.
- **Methods perform operations on objects that already exist.**
- Constructors are called **implicitly** when the **new** keyword creates an object.
- **Methods can be called directly on an existing object.**
- Constructors must be named with the **same** name as the class name.
- **Methods must be called something different to the class name**
- Constructors can't return anything (because the object itself is the thing being returned).
- **Methods must be configured return something, although it can be void**

# Method overloading vs constructor overloading

```
class Overload {  
    void display() {                //these are methods  
        System.out.println("you passed nothing");  
    }  
    void display(int x) {  
        System.out.println("you passed " +x);  
    }  
}
```

```
class Overload{  
    int data;                //these are constructors  
    Overload(int x) { //object is created with one passed value  
        data = x;  
    }  
    Overload(int x, int y) {  
        data = x+y; //object is created with 2 passed values  
    }  
}
```

# Static keyword summary

- Used to reduce JVM memory usage (very important in Java)
  - (aside.. JVM, memory, virtual memory, OS etc)
- Makes code safer (variables change in a specified way)
- If a variable is declared `static` then changing it in any object changes it for all objects
  - Saves a lot of memory in some situation. (eg. agent based systems)
- Static methods are methods which don't require an object of its class to be created before it can be called. Belongs to the class
- Static methods can't use the `this` keyword as there is no instance for `this` to refer to.

# Object Oriented Programming

- Aids decision making when designing an application
- 4 major concepts
- **Inheritance, Encapsulation, Abstraction and Polymorphism**
- Why use it:
  - Allows multiple developers to work on the same project more efficiently
  - Modular, Extensible, Reusable
- Why not use it:
  - Creating efficient Classes can be hard (hence we use `Dog` and `Car` so much)
  - Unforeseen interactions (emergent behavior!)
  - Performance issues and requires more code

# Inheritance

- Allows for hierarchical program structures
- Means we can make a general class with common traits
- New classes can inherit these traits but also add class specific traits
- Class that is **inherited** is the superclass
- Class that **inherits** is the subclass
- Subclass inherits all the variables and methods of the superclass
- Changes in superclass effect subclasses
- Subclasses code can change the 'intention' of the superclass code
  - Immutable parameters classes can be copied and changed\*



# Inheritance

- A class can inherit all the methods and variables of another class (a "superclass").
- Use the keyword `extends`

```
class Superclass {...}
```

```
class Subclass extends Superclass { .....
```

- The subclass extends the superclass by adding behavior and data to the behavior and data provided by the superclass

# The Object class is the root superclass

- Every class is a subclass of Java's `Object` class..unless overridden
- Therefore every class includes the following methods:
  - `toString()`
  - `Equals(Object x)`
  - `HashCode()`
  - `getClass()`
- Every class (other than object) is a subclass
- Note-So If `p` is an object, java automatically converts "`p=`" + `p`  
To "`p=`" + `p.toString()`

# Example

```
class OneDimPoint { //Superclass
    int x = 3;
    int getX() { return x; }
}
class TwoDimPoint extends OneDimPoint { //Subclass
    int y = 4;
    int getY() { return y; }
}
class TestInherit {
    public static void main(String[] args) {
        TwoDimPoint pt = new twoDimPoint();
        /*this object has x and y, even though the
        subclass has no getX method*/
        System.out.println(pt.getX() + "," + pt.getY());
    }
}
```

# Inheritance key points

- Each superclass can have many subclasses but in Java (as opposed to C++) each class can have **at most** one superclass.
- A subclass cannot access the private members of its superclass.
- A subclass constructor can call a superclass constructor by use of `super( )`, before doing anything else.
- If you do not call a superclass constructor, the no-argument constructor is automatically called.

# Superclass constructors ((over)simple example)

```

1  class People //superclass
2  {
3      People()
4      {System.out.println("People Constructor");}
5  }
6  class Student extends People //subclass
7  {
8      Student()
9      {
10         super(); //call super class constructor
11         System.out.println("Student Constructor");
12     }
13 }
14
15 class TestSPerson
16 {
17     public static void main(String[] args)
18     {
19         Student s = new Student();
20     }
21 }

```

Note: super() not needed as no values are passed

```

C:\Users\z2018044\Documents\JavaLab2>java TestSPerson
People Constructor
Student Constructor

```

# Subclass Constructors 1 (no super used)

```
1  class OneDimPoint {
2      int x;
3      OneDimPoint() { x = 3; } //super constructor
4      int getX() { return x; }
5  }
6  class TwoDimPoint extends OneDimPoint {
7      int y;
8      TwoDimPoint() { y = 4; } // automatically calls
9                          // OneDimPoint() first
10     int getY() { return y; }
11 }
12 class TestTwoDimPoint {
13     public static void main(String[] args) {
14         TwoDimPoint line = new TwoDimPoint();
15         System.out.println(line.x + " " + line.y);
16     }
17 }
```

C:\Users\z2018044\Documents\JavaLab2>java TestTwoDimPoi  
3 4

# Subclass Constructors (super used)

```
1  class OneDimPointS {
2      int x;
3      OneDimPointS(int startX) { x = startX; }
4      int getX() { return x; }
5  }
6  class TwoDimPointS extends OneDimPointS {
7      int y;
8      TwoDimPointS(int startX, int startY) {
9          super(startX); // explicitly calls constructor
10         y = startY;
11     }
12     int getY() { return y; }
13 }
14
15 class TestTwoDimPointS {
16     public static void main(String[] args) {
17         TwoDimPointS line = new TwoDimPointS(5,6);
18         System.out.println(line.x + " " + line.y);
19     }
20 }
```

```
C:\Users\z2018044\Documents\JavaLab2>java TestTwoDimPointS
5 6
```

# Overriding

- If a class inherits a method from its superclass, it has an option to override it (provided that it is not marked `final`)
- If methods are rewritten with the same name they replace the original method at compile time
- Also needs the same argument list and return type
- A method declared `final` or `static` cannot be overridden.
- Constructors cannot be overridden



# Example Overriding

```
1  class Vehicle {
2      public void move() {
3          System.out.println("All vehicles move");
4      }
5  }
6  class Boat extends Vehicle {
7      public void move() {
8          System.out.println("Boats float");
9      }
10 }
11 public class TestBoat {
12     public static void main(String args[]) {
13         Vehicle a = new Vehicle(); // Vehicle reference and object
14         Vehicle b = new Boat();    // Vehicle reference but Boat object
15         a.move(); // runs the method in Vehicle class
16         b.move(); // runs the method in Boat class
17     }
18 }
```

C:\Users\z2018044\Documents\JavaLab2>java TestBoat  
All vehicles move  
Boats float

# ..but this is restrictive, cannot add new methods

```

1  class Vehicle {
2      public void move() {
3          System.out.println("All vehicles move");
4      }
5  }
6  class Boat extends Vehicle {
7      public void move() {
8          System.out.println("Boats float");
9      }
10     public void hasRudder() {
11         System.out.println("Boats have a rudder");
12     }
13 }
14 public class TestBoat {
15     public static void main(String args[]) {
16         Vehicle a = new Vehicle(); // Vehicle reference and object
17         Vehicle b = new Boat();    // Vehicle reference but Boat object
18         a.move(); // runs the method in Vehicle class
19         b.move(); // runs the method in Boat class
20         b.hasRudder();
21     }
22 }

```

```

C:\Users\z2018044\Documents\JavaLab2>javac TestBoat.java
TestBoat.java:20: error: cannot find symbol
        b.hasRudder();
        ^
    symbol:   method hasRudder()
    location: variable b of type Vehicle
1 error

```

# Solution

```
1 class Vehicle {
2     public void move() {
3         System.out.println("All vehicles move");
4     }
5 }
6 class Boat extends Vehicle {
7     public void move() {
8         System.out.println("Boats float");
9     }
10    public void hasRudder() {
11        System.out.println("Boats have a rudder");
12    }
13 }
14 public class TestBoat {
15     public static void main(String args[]) {
16         Vehicle a = new Vehicle(); // Vehicle reference and object
17         Boat b = new Boat();        // Boat reference and Boat object
18         a.move(); // runs the method in Vehicle class
19         b.move(); // runs the method in Boat class
20         b.hasRudder();
21     }
22 }
```

```
C:\Users\z2018044\Documents\JavaLab2>java TestBoat
All vehicles move
Boats float
Boats have a rudder
```

