



Computer Engineering Department

Artificial Intelligence

Mohammad Hossein Rohban, Ph.D.

Spring 2023

Courtesy: Most of slides are adopted from CS 285 Berkeley.

The Goal of Reinforcement Learning

$$J(\theta) = E \left[\sum_t r(\mathbf{s}_t, \mathbf{a}_t) \right]$$


$$s_1 \sim p(s_1)$$

$$a_t \sim \pi(. | s_t)$$

$$s_{t+1} \sim p(. | s_t, a_t)$$

Trajectory Probability

$$\underbrace{p_{\theta}(\mathbf{s}_1, \mathbf{a}_1, \dots, \mathbf{s}_T, \mathbf{a}_T)}_{p_{\theta}(\tau)} = p(\mathbf{s}_1) \prod_{t=1}^T \pi_{\theta}(\mathbf{a}_t | \mathbf{s}_t) p(\mathbf{s}_{t+1} | \mathbf{s}_t, \mathbf{a}_t)$$



The Goal of Reinforcement Learning

- The RL objective

$$J(\theta) = E_{\tau \sim p_{\theta}(\tau)} \left[\sum_t r(\mathbf{s}_t, \mathbf{a}_t) \right]$$

$$p_{\theta}(\tau) = \underbrace{p(\mathbf{s}_1)} \prod_{t=1}^T \underbrace{\pi_{\theta}(\mathbf{a}_t | \mathbf{s}_t)} \underbrace{p(\mathbf{s}_{t+1} | \mathbf{s}_t, \mathbf{a}_t)}$$

- The goal of policy gradient:

$$\theta^* = \arg \max_{\theta} E_{\tau \sim p_{\theta}(\tau)} \left[\sum_t r(\mathbf{s}_t, \mathbf{a}_t) \right]$$


Evaluating the Objective

$$\theta^* = \arg \max_{\theta} \underbrace{E_{\tau \sim p_{\theta}(\tau)} \left[\sum_t r(\mathbf{s}_t, \mathbf{a}_t) \right]}_{J(\theta)}$$

Monte Carlo estimation for objective function:

$$J(\theta) = E_{\tau \sim p_{\theta}(\tau)} \left[\sum_t r(\mathbf{s}_t, \mathbf{a}_t) \right] \approx \frac{1}{N} \sum_i \sum_t r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t})$$

sum over samples from π_{θ}



Direct Policy Differentiation

$$\theta^* = \arg \max_{\theta} \underbrace{E_{\tau \sim p_{\theta}(\tau)} \left[\sum_t r(\mathbf{s}_t, \mathbf{a}_t) \right]}_{J(\theta)}$$

$$J(\theta) = E_{\tau \sim p_{\theta}(\tau)} \left[\underbrace{r(\tau)}_{\sum_{t=1}^T r(\mathbf{s}_t, \mathbf{a}_t)} \right] = \int p_{\theta}(\tau) r(\tau) d\tau$$

$$\nabla_{\theta} J(\theta) = \int \underbrace{\nabla_{\theta} p_{\theta}(\tau)}_{p_{\theta}(\tau) \nabla_{\theta} \log p_{\theta}(\tau)} r(\tau) d\tau = \int p_{\theta}(\tau) \nabla_{\theta} \log p_{\theta}(\tau) r(\tau) d\tau = E_{\tau \sim p_{\theta}(\tau)} [\nabla_{\theta} \log p_{\theta}(\tau) r(\tau)]$$

a convenient identity

$$\underbrace{p_{\theta}(\tau) \nabla_{\theta} \log p_{\theta}(\tau)}_{p_{\theta}(\tau) \nabla_{\theta} \log p_{\theta}(\tau)} = p_{\theta}(\tau) \frac{\nabla_{\theta} p_{\theta}(\tau)}{p_{\theta}(\tau)} = \underbrace{\nabla_{\theta} p_{\theta}(\tau)}$$

Direct Policy Differentiation

$$\theta^* = \arg \max_{\theta} J(\theta)$$

$$J(\theta) = E_{\tau \sim p_{\theta}(\tau)}[r(\tau)]$$

$$\nabla_{\theta} J(\theta) = E_{\tau \sim p_{\theta}(\tau)}[\nabla_{\theta} \log p_{\theta}(\tau) r(\tau)]$$

$$\nabla_{\theta} \left[\log p(\mathbf{s}_1) + \sum_{t=1}^T \log \pi_{\theta}(\mathbf{a}_t | \mathbf{s}_t) + \log p(\mathbf{s}_{t+1} | \mathbf{s}_t, \mathbf{a}_t) \right]$$

$$\nabla_{\theta} J(\theta) = E_{\tau \sim p_{\theta}(\tau)} \left[\left(\sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_t | \mathbf{s}_t) \right) \left(\sum_{t=1}^T r(\mathbf{s}_t, \mathbf{a}_t) \right) \right]$$

log of both sides

$$\underbrace{p_{\theta}(\mathbf{s}_1, \mathbf{a}_1, \dots, \mathbf{s}_T, \mathbf{a}_T)}_{p_{\theta}(\tau)} = p(\mathbf{s}_1) \prod_{t=1}^T \pi_{\theta}(\mathbf{a}_t | \mathbf{s}_t) p(\mathbf{s}_{t+1} | \mathbf{s}_t, \mathbf{a}_t)$$

$$\log p_{\theta}(\tau) = \log p(\mathbf{s}_1) + \sum_{t=1}^T \log \pi_{\theta}(\mathbf{a}_t | \mathbf{s}_t) + \log p(\mathbf{s}_{t+1} | \mathbf{s}_t, \mathbf{a}_t)$$



Evaluating the Policy Gradient

$$\text{recall: } J(\theta) = E_{\tau \sim p_{\theta}(\tau)} \left[\sum_t r(\mathbf{s}_t, \mathbf{a}_t) \right] \approx \frac{1}{N} \sum_i \sum_t r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t})$$

$$\nabla_{\theta} J(\theta) = E_{\tau \sim p_{\theta}(\tau)} \left[\left(\sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_t | \mathbf{s}_t) \right) \left(\sum_{t=1}^T r(\mathbf{s}_t, \mathbf{a}_t) \right) \right]$$


$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \left(\sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \right) \left(\sum_{t=1}^T r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) \right)$$


$$\theta \leftarrow \theta + \alpha \nabla_{\theta} J(\theta)$$



REINFORCE Algorithm

REINFORCE algorithm:

- 
1. sample $\{\tau^i\}$ from $\pi_\theta(\mathbf{a}_t|\mathbf{s}_t)$ (run the policy)
 2. $\nabla_\theta J(\theta) \approx \sum_i (\sum_t \nabla_\theta \log \pi_\theta(\mathbf{a}_t^i|\mathbf{s}_t^i)) (\sum_t r(\mathbf{s}_t^i, \mathbf{a}_t^i))$
 3. $\theta \leftarrow \theta + \alpha \nabla_\theta J(\theta)$




Policy Gradient Intuition

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \left(\sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \right) \left(\sum_{t=1}^T r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) \right)$$

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \underbrace{\nabla_{\theta} \log \pi_{\theta}(\tau_i)}_{\sum_{t=1}^T \nabla_{\theta} \log_{\theta} \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t})} r(\tau_i)$$

maximum likelihood: $\nabla_{\theta} J_{\text{ML}}(\theta) \approx \frac{1}{N} \sum_{i=1}^N \nabla_{\theta} \log \pi_{\theta}(\tau_i)$

- Good stuff is made more likely
- Bad stuff is made less likely
- Simply formalizes the notion of “trial and error”!



Bias and Variance of Policy Gradient

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \nabla_{\theta} \log \pi_{\theta}(\tau_i) \boxed{r(\tau_i)}$$

The main source
of high variance



- Unbiased estimation:

$$E \left[\frac{1}{N} \sum_{i=1}^N \nabla_{\theta} \log \pi_{\theta}(\tau_i) r(\tau_i) \right] = \nabla_{\theta} J(\theta)$$

- But suffers from **high variance**!

Reducing Variance

- Causality trick
- Discount factor
- Baseline
- Actor-critic
- Optimization techniques:
 - Natural gradient
 - Trust region

Reducing Variance: Causality


$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \left(\sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \right) \left(\sum_{t=1}^T r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) \right)$$

Causality: policy at time t' cannot affect reward at time t when $t < t'$

$$\frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \left(\sum_{\substack{t'=1 \\ \text{red circle}}}^T r(\mathbf{a}_{i,t'}, \mathbf{s}_{i,t'}) \right)$$

$$\frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \left(\sum_{\substack{t'=t \\ \text{red circle}}}^T r(\mathbf{a}_{i,t'}, \mathbf{s}_{i,t'}) \right)$$

“reward to go” $\hat{Q}_{i,t}$




Reducing Variance: Baselines

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \nabla_{\theta} \log p_{\theta}(\tau) [r(\tau) - b]$$

$$b = \frac{1}{N} \sum_{i=1}^N r(\tau)$$

a convenient identity

$$p_{\theta}(\tau) \nabla_{\theta} \log p_{\theta}(\tau) = \nabla_{\theta} p_{\theta}(\tau)$$




$$E[\nabla_{\theta} \log p_{\theta}(\tau) b] = \int p_{\theta}(\tau) \nabla_{\theta} \log p_{\theta}(\tau) b d\tau = \int \nabla_{\theta} p_{\theta}(\tau) b d\tau = b \nabla_{\theta} \int p_{\theta}(\tau) d\tau = b \nabla_{\theta} 1 = 0$$

subtracting a baseline is *unbiased* in expectation!

average reward is *not* the best baseline, but it's pretty good!


Reducing Variance: Baselines

Faster convergence:




Policy Gradients so Far

REINFORCE algorithm:

- 
1. sample $\{\tau^i\}$ from $\pi_\theta(\mathbf{a}_t|\mathbf{s}_t)$ (run the policy)
 2. $\nabla_\theta J(\theta) \approx \sum_i \left(\sum_{t=1}^T \nabla_\theta \log \pi_\theta(\mathbf{a}_t^i|\mathbf{s}_t^i) \left(\sum_{t'=t}^T r(\mathbf{s}_{t'}^i, \mathbf{a}_{t'}^i) \right) \right)$
 3. $\theta \leftarrow \theta + \alpha \nabla_\theta J(\theta)$

$$\nabla_\theta J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_\theta \log \pi_\theta(\mathbf{a}_{i,t}|\mathbf{s}_{i,t}) \underbrace{\hat{Q}_{i,t}^\pi}_{\text{"reward to go"}}$$

“reward to go”



Improving Estimation of Reward to Go

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \underbrace{\left(\sum_{t'=1}^T r(\mathbf{s}_{i,t'}, \mathbf{a}_{i,t'}) \right)}$$


$\hat{Q}_{i,t}$: estimate of expected reward if we take action $\mathbf{a}_{i,t}$ in state $\mathbf{s}_{i,t}$

How to make a better estimate?

$Q(\mathbf{s}_t, \mathbf{a}_t) = \sum_{t'=t}^T E_{\pi_{\theta}} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]$: true *expected* reward-to-go

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_{\theta} \log \pi_{\theta}(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) \underline{Q(\mathbf{s}_{i,t}, \mathbf{a}_{i,t})}$$

much lower variance!




Improving Estimation of Reward to Go

Further improvement: Adding a baseline!

$Q(\mathbf{s}_t, \mathbf{a}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]$: true *expected* reward-to-go

$$\nabla_\theta J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_\theta \log \pi_\theta(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) (Q(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) - b_t)$$

$$b_t = \frac{1}{N} \sum_i Q(\mathbf{s}_{i,t}, \mathbf{a}_{i,t})$$



Improving Estimation of Reward to Go


Further improvement: Adding a baseline!

$Q(\mathbf{s}_t, \mathbf{a}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]$: true *expected* reward-to-go

$$\nabla_\theta J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_\theta \log \pi_\theta(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) (Q(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) - V(\mathbf{s}_{i,t}))$$

$$b_t = \frac{1}{N} \sum_i Q(\mathbf{s}_{i,t}, \mathbf{a}_{i,t})$$

$$\downarrow$$
$$V(\mathbf{s}_t) = E_{\mathbf{a}_t \sim \pi_\theta(\mathbf{a}_t | \mathbf{s}_t)} [Q(\mathbf{s}_t, \mathbf{a}_t)]$$



Advantage Value

$Q^\pi(\mathbf{s}_t, \mathbf{a}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]$: total reward from taking \mathbf{a}_t in \mathbf{s}_t

$V^\pi(\mathbf{s}_t) = E_{\mathbf{a}_t \sim \pi_\theta(\mathbf{a}_t | \mathbf{s}_t)} [Q^\pi(\mathbf{s}_t, \mathbf{a}_t)]$: total reward from \mathbf{s}_t

$A^\pi(\mathbf{s}_t, \mathbf{a}_t) = Q^\pi(\mathbf{s}_t, \mathbf{a}_t) - V^\pi(\mathbf{s}_t)$: how much better \mathbf{a}_t is

$$\nabla_\theta J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_\theta \log \pi_\theta(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) A^\pi(\mathbf{s}_{i,t}, \mathbf{a}_{i,t})$$



the better this estimate, the lower the variance

Advantage Value Approximation

$$Q^\pi(\mathbf{s}_t, \mathbf{a}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]$$

$$V^\pi(\mathbf{s}_t) = E_{\mathbf{a}_t \sim \pi_\theta(\mathbf{a}_t | \mathbf{s}_t)} [Q^\pi(\mathbf{s}_t, \mathbf{a}_t)]$$


$$A^\pi(\mathbf{s}_t, \mathbf{a}_t) = Q^\pi(\mathbf{s}_t, \mathbf{a}_t) - V^\pi(\mathbf{s}_t)$$

$$\nabla_\theta J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t=1}^T \nabla_\theta \log \pi_\theta(\mathbf{a}_{i,t} | \mathbf{s}_{i,t}) A^\pi(\mathbf{s}_{i,t}, \mathbf{a}_{i,t})$$

$$Q^\pi(\mathbf{s}_t, \mathbf{a}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]$$

$$= r(\mathbf{s}_t, \mathbf{a}_t) + \underbrace{\sum_{t'=t+1}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t, \mathbf{a}_t]}$$

$$\approx V^\pi(\mathbf{s}_{t+1})$$




Advantage Value Approximation

$$Q^\pi(\mathbf{s}_t, \mathbf{a}_t) \approx r(\mathbf{s}_t, \mathbf{a}_t) + V^\pi(\mathbf{s}_{t+1})$$

$$A^\pi(\mathbf{s}_t, \mathbf{a}_t) \approx r(\mathbf{s}_t, \mathbf{a}_t) + V^\pi(\mathbf{s}_{t+1}) - V^\pi(\mathbf{s}_t)$$

let's just fit $V^\pi(\mathbf{s})$!



Policy Evaluation

$$V^\pi(\mathbf{s}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t]$$

$$J(\theta) = E_{\mathbf{s}_1 \sim p(\mathbf{s}_1)} [V^\pi(\mathbf{s}_1)]$$


how can we perform policy evaluation?

Monte Carlo policy evaluation (this is what policy gradient does)

$$V^\pi(\mathbf{s}_t) \approx \sum_{t'=t}^T r(\mathbf{s}_{t'}, \mathbf{a}_{t'})$$

$$V^\pi(\mathbf{s}_t) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t'=t}^T r(\mathbf{s}_{t'}, \mathbf{a}_{t'})$$

(requires us to reset the simulator)



Policy Evaluation

Monte Carlo estimation with function approximator:



$$V^\pi(\mathbf{s}_t) \approx \sum_{t'=t}^T r(\mathbf{s}_{t'}, \mathbf{a}_{t'})$$

not as good as this: $V^\pi(\mathbf{s}_t) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t'=t}^T r(\mathbf{s}_{t'}, \mathbf{a}_{t'})$

but still pretty good!

training data: $\left\{ \left(\mathbf{s}_{i,t}, \underbrace{\sum_{t'=t}^T r(\mathbf{s}_{i,t'}, \mathbf{a}_{i,t'})}_{y_{i,t}} \right) \right\}$

supervised regression: $\mathcal{L}(\phi) = \frac{1}{2} \sum_i \left\| \hat{V}_\phi^\pi(\mathbf{s}_i) - y_i \right\|^2$



Policy Evaluation

How to make a better estimate?

$$\text{ideal target: } y_{i,t} = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_{i,t}] \approx r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) + V^\pi(\mathbf{s}_{i,t+1}) \approx r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) + \underbrace{\hat{V}_\phi^\pi(\mathbf{s}_{i,t+1})}$$

$$\text{Monte Carlo target: } y_{i,t} = \sum_{t'=t}^T r(\mathbf{s}_{i,t'}, \mathbf{a}_{i,t'})$$

directly use previous fitted value function!

Policy Evaluation

Bootstrap Estimation with Function Approximator

ideal target: $y_{i,t} = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_{i,t}] \approx r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) + \hat{V}_\phi^\pi(\mathbf{s}_{i,t+1})$


training data: $\left\{ \left(\mathbf{s}_{i,t}, \underbrace{r(\mathbf{s}_{i,t}, \mathbf{a}_{i,t}) + \hat{V}_\phi^\pi(\mathbf{s}_{i,t+1})}_{y_{i,t}} \right) \right\}$

supervised regression: $\mathcal{L}(\phi) = \frac{1}{2} \sum_i \left\| \hat{V}_\phi^\pi(\mathbf{s}_i) - y_i \right\|^2$

Batch Actor-Critic Algorithm

batch actor-critic algorithm:

1. sample $\{\mathbf{s}_i, \mathbf{a}_i\}$ from $\pi_\theta(\mathbf{a}|\mathbf{s})$ (run it on the robot)
2. fit $\hat{V}_\phi^\pi(\mathbf{s})$ to sampled reward sums
3. evaluate $\hat{A}^\pi(\mathbf{s}_i, \mathbf{a}_i) = r(\mathbf{s}_i, \mathbf{a}_i) + \hat{V}_\phi^\pi(\mathbf{s}'_i) - \hat{V}_\phi^\pi(\mathbf{s}_i)$
4. $\nabla_\theta J(\theta) \approx \sum_i \nabla_\theta \log \pi_\theta(\mathbf{a}_i|\mathbf{s}_i) \hat{A}^\pi(\mathbf{s}_i, \mathbf{a}_i)$
5. $\theta \leftarrow \theta + \alpha \nabla_\theta J(\theta)$



$$V^\pi(\mathbf{s}_t) = \sum_{t'=t}^T E_{\pi_\theta} [r(\mathbf{s}_{t'}, \mathbf{a}_{t'}) | \mathbf{s}_t]$$

