

Important notice: Powermax products must be tested by the user for compliance with the equipment and production treatment applied by the user. Powermax is not liable for any injury, direct or consequential, arising from the use of, or inability to use Powermax products. The maximum obligation of Powermax is to replace any product supplied by Powermax, which has been proven to be defective.

Technical Data: TEXIMAX CP-e 80P (green, gray)

TEXIMAX CP-e 80P is the highest quality transfer paper for Screen printing on textile with plastisol inks with the excellent dimensional stability. Suitable for multi color transfers.

TEXIMAX CP-e 80P is designed for cold peel transfers.

Basic weight of paper 80g./sm.

Screen printing:

Printing side: Light green side

Ink types: Wide range of plastisol inks can be used with or without powdered adhesives (polyester, polyamide, polyurethane).

We recommend opening the packaging and cutting sheets on working dimension a few hours before final using in reason to optimize the stability of the paper.

Storage: Teximax CP-e 80P must be stored at room temperature in dry condition environment with no exposure to moisture.

Pre-conditioning for screen printing: TEXIMAX CP-e 80P is necessary pre-heating, before screen printing, through drier on recommended temperature 140°C-150°C for 45 seconds.

Final appearance after transferring on textil - MATTE.

Recommended processing-time: within one year from the date of production.

Transfer process:

Application temperatures: 170° to 205°C

Dwell time 10–15 seconds

Pressure: Medium (35 to 45 psi)

Packaging: 250 Sheets 100 x 70 cm

500 Sheets 50 x 70 cm

Other sizes are available on customer request.

Producer: Powermax d.o.o. Backa Palanka
Vuka Karadzica str. 15
21400 Backa Palanka
Serbia

Tel. +38121753533; +38121754066
Mob.+381603377946

