

# HYPERSPECTRAL IMAGING

## CONTENTS

- Hyperspectral Imagery
- Issues
- General Framework
- Feature Reduction
- Examples

# Hyperspectral Imagery

3

- Simultaneous acquisition of hundreds of spectral wavelengths for each image pixel.
- Bands are **continuous**, regularly spaced.
- Spectral resolution  $\sim 10\text{nm}$ .


# Why Hyperspectral Imagery

4

- Possibility of more **accurate** discrimination among materials of interest.
- Higher spectral resolution, thus giving the opportunity to **push further** the information extraction capability.
- Inter class and **intra class** delineation.
- Lots of application in **diverse fields**.

# Hyperspectral Imagery

5






191 Band HYDICE  
image of Washington  
DC Mall





220 Band AVIRIS image  
Indian Pine Test Site

<https://engineering.purdue.edu/~biehl/MultiSpec/hyperspectral.html>




7



# Issues

10

- Huge quantity of data to store.
- Computationally intensive.
- Exhibit redundant information.
- **Curse of Dimensionality**: With a limited training set, beyond a certain limit, the classification accuracy actually decreases as the number of features increases.



Fu *et al.* (1969);  
Richards (2013)

11

## Small Training Sample Size

12

- GML
  - Effectiveness: reliable estimation of mean vector and covariance matrix for each class
  - Sufficient training sample for each class
- $N$  dimensional spectral space
  - Mean vector:  $N$  elements
  - Covariance matrix:  $N(N+1)/2$  elements

## Clustering High Dimensional Data

13

- **Problem 1**: Visualization and tabularization of data becomes extremely difficult.

Kriegel *et al.* (2009)


# Clustering High Dimensional Data

# Curse of Dimensionality

14

- **Problem 1:** Visualization and tabularization of data becomes extremely difficult.
- **Problem 2:** Discrimination between nearest and farthest point in high dimension becomes poor (Beyer *et al.* 1999).

15



Kriegel *et al.* (2009)

Parsons, Haque and Liu (2004)


# Clustering High Dimensional Data

# Example

16

- **Problem 1:** Visualization and tabularization of data becomes extremely difficult.
- **Problem 2:** Discrimination between nearest and farthest point in high dimension becomes poor (Beyer *et al.* 1999).
- **Problem 3:** Subset of some bands may be relevant to one cluster and subset of some other bands may be relevant to other cluster, and so on.

17



Parsons, Haque and Liu (2004)


400 data points  
4 clusters of 100 data points each  
Normally distributed,  $\mu = 0.5$  and  $-0.5$  in dim  $a$  and  $0.5$  in dim  $b$ , and  $\sigma = 0.2$ , dim  $c$   $\mu = 0$  and  $\sigma = 1$   
Other two clusters in dim  $b$  and  $c$  (same manner)

Kriegel *et al.* (2009)

# Clustering High Dimensional Data

19


- **Problem 1:** Visualization and tabularization of data becomes extremely difficult.
- **Problem 2:** Discrimination between nearest and farthest point in high dimension becomes poor (Beyer *et al.* 1999).
- **Problem 3:** Appropriate subset of bands to describe the similarity of pixel belonging to the same group and possibly different subsets of bands for different groups of pixel.
- **Problem 4:** Correlation among bands.



Parsons, Haque and Liu (2004)

Kriegel *et al.* (2009)


18



Color coded visualization of correlation matrix. Red color indicates high correlation and blue color indicates low correlation.

## General Framework

21



## Feature Reduction

## Feature Selection

- Original feature space: not necessarily most effective.
- Not designed for any particular problem.
- Redundant information: contiguous bands highly correlated.
- Classification cost increases with the number of features.
- Small training sample size issue.

- Subset of spectral bands
- Advantages
  - Data Transmission
  - Interpretability of the results
  - Extrapolation of results
- Limitations
  - Information loss: features are completely discarded
  - Computationally intensive



## Feature Extraction

- Redistribution of information: higher dimensional to lower dimensional space without loss of significant amount of information
- Advantages
  - Can use all the available features
- Limitations
  - Transformed features losses physical meaning
  - Large number of features are noisy/irrelevant

25

## Classification

Examples



## Clustering Evaluation

$$\Omega = \begin{bmatrix} 1 & 1 & 1 & 2 \\ 2 & 2 & 2 & 1 \end{bmatrix}; \mathbb{C} = \begin{bmatrix} 1 & 1 & 1 & 1 \\ 2 & 2 & 2 & 2 \end{bmatrix}$$

$$\text{purity} = 0.7500$$

$$\text{NMI} = 0.1888$$

Purity<sup>1</sup>

Normalized Mutual Information<sup>1,2</sup> (NMI)

$$\text{purity}(\Omega, \mathbb{C}) = \frac{1}{N} \sum_k \max_j |\omega_k \cap c_j|$$

$$\text{NMI}(\Omega, \mathbb{C}) = \frac{MI(\Omega, \mathbb{C})}{\max(H(\Omega), H(\mathbb{C}))}$$

$$MI(\Omega, \mathbb{C}) = \sum_k \sum_j p(\omega_k \cap c_j) \log_2 \frac{p(\omega_k \cap c_j)}{p(\omega_k) p(c_j)}$$

$$H(\Omega) = -\sum_k p(\omega_k) \log_2 p(\omega_k)$$

$\Omega = \{\omega_1, \omega_2, \dots, \omega_k\}$  is the set of clusters

$\mathbb{C} = \{c_1, c_2, \dots, c_j\}$  is the set of classes

obtained from reference image

$N$  is total number of pixel samples

Purity

Normalized Mutual Information (NMI)

$$\text{purity}(\Omega, \mathbb{C}) = \frac{1}{N} \sum_k \max_j |\omega_k \cap c_j|$$

$$\text{NMI}(\Omega, \mathbb{C}) = \frac{MI(\Omega, \mathbb{C})}{\max(H(\Omega), H(\mathbb{C}))}$$

$$MI(\Omega, \mathbb{C}) = \sum_k \sum_j p(\omega_k \cap c_j) \log_2 \frac{p(\omega_k \cap c_j)}{p(\omega_k) p(c_j)}$$

$$H(\Omega) = -\sum_k p(\omega_k) \log_2 p(\omega_k)$$

$\Omega = \{\omega_1, \omega_2, \dots, \omega_k\}$  is the set of clusters

$\mathbb{C} = \{c_1, c_2, \dots, c_j\}$  is the set of classes

obtained from reference image

$N$  is total number of pixel samples

<sup>1</sup> <http://nlp.stanford.edu/IR-book/html/htmledition/evaluation-of-clustering-1.html>


<sup>2</sup> Cai, D., X. He, and J. Han. 2005. "Document Clustering Using Locality Preserving Indexing." *IEEE Transactions on Knowledge and Data Engineering*, 17 (12): 1624-1637.



30

## Application of clustering in Supervised Classification


31




## Classification Strategy II

## Classification Strategy III

32



33







PaviaU (TCC)



Strategy I



Strategy II



Strategy III



	Strategy I	Strategy II	Strategy III
Overall Kappa (%)	57.98	73.67	82.80

- Asphalt
- Meadows
- Gravel
- Trees
- Painted metal sheets
- Bare Soil
- Bitumen
- Self-Blocking Bricks
- Shadows

Thank You